PENETRATION TESTING REPORT

FOOTPRINTING, OSINT & NETWORK SCANNING PHASES

W2-PM-FINAL | CYBERSECURITY | NETWORKWALKS

Pentester Name (Cybersecurity Professional)	Tsepo Maroibaki
Program/Batch	B084-Networkwalks
Date	10 November 2026
Modules completed	W2-PM1 (Multiple Kali Tools) W2-PM3 (Maltego) W2-PM4 (theHarvester) W2-PM5 (Zenmap Scanning)
Client/Target	1. Networkwalks (written permission secured) 2. Public search-engine data (passive OSINT, theHarvester) 3. My own local LAN network
Permission secured from client?	Yes
Phases covered	**Phase 1:** Reconnaissance & Footprinting (PM1, PM3, PM4) **Phase 2:** Scanning & Network Discovery (PM5) **Phase 3-5:** In Progress

1. Liability Disclaimer

All activities in this report were carried out only against systems for which I held written authorisation, against assets I own personally, or, in the passive OSINT case, against data that is already public. The material is provided strictly for education and research. It must not be used to violate any law. The instructor, the authors and Networkwalks accept no responsibility for how this knowledge is applied; each person answers for their own actions. Misuse can lead to criminal prosecution, substantial fines, loss of employment and a permanent criminal record, and in most jurisdictions unauthorised access is an offence even when no damage results.

2. Introduction

This report documents the Week 2 practical work of my Cybersecurity & Ethical Hacking internship (Batch 84) at Networkwalks. It spans four modules: multi-tool footprinting of the `networkwalks.com` domain with six Kali Linux utilities (W2-PM1), link analysis of the same domain in Maltego (W2-PM3), passive harvesting of hostnames and e-mail addresses with theHarvester (W2-PM4), and host discovery on my own local network with Zenmap (W2-PM5).

Taken together, the modules follow the way an attacker typically progresses: first collecting registration, DNS and technology data without touching the target in any meaningful way, then correlating it into a relationship graph, and finally mapping which hosts are alive on a network segment. Footprinting and OSINT were performed from a Kali Linux workstation (`pentest-serv01`); Maltego Graph Desktop 4.14.0 was used for the link analysis, and Zenmap was used for the LAN scan.

For each step the report lists the exact command or transform, the observed output, screenshot evidence (Section 9) and a short note on why the result matters from an attacker's perspective. Findings are observations only; none was exploited or validated as a vulnerability.

3. Tools Used

The table below lists every tool used and the role it played.

Tool	Purpose
Kali Linux / Windows	Operating systems used to run the reconnaissance and scanning tools.
WHOIS	Retrieve domain registration data: registrar, dates, status flags, name servers.
WhatWeb	Fingerprint the web stack: server, CMS, plugins, JavaScript libraries, exposed e-mail.
nslookup	Resolve the domain to its IP address through a public DNS resolver.
curl -i	Capture HTTP response headers and redirect behaviour.
wafw00f	Detect and identify a Web Application Firewall in front of the site.
dnsrecon	Enumerate DNS records (SOA, NS, MX, A, TXT/SPF, SRV) and DNS server banners.
Maltego Graph 4.14.0	Link analysis: pivot from the domain to e-mail addresses, DNS names, MX and web entities.
theHarvester 4.11.1	Passive OSINT: collect hostnames, IPs, e-mail addresses and names from public search engines.
Zenmap (Nmap GUI)	Ping scan of the local subnet to list live hosts, IP/MAC addresses and topology.
Windows CMD (`ipconfig`)	Identify the local IP address and subnet before scanning.

4. Activities Performed

4.1 Footprinting & Reconnaissance (W2-PM1)

Six Kali Linux tools were run against `networkwalks.com` on 9 November 2026. Each one exposes a different layer of the target: registration, web technology, network location, HTTP behaviour, perimeter defences and DNS.

4.1.1 WHOIS – domain registration

Command

```
whois networkwalks.com
```

Observation

- Registrar: **GoDaddy.com, LLC** (IANA ID 146). Created **2019-11-06**, last updated 2025-11-12, registry expiry **2027-11-06**.
- Status flags: `clientTransferProhibited`, `clientUpdateProhibited`, `clientRenewProhibited`, `clientDeleteProhibited`. The domain is registrar-locked.
- Registrant and technical contacts are masked by **Domains By Proxy, LLC** (privacy service, Tempe, Arizona).
- Name servers: `NS6135.HOSTGATOR.COM` and `NS6136.HOSTGATOR.COM` at the registry. The registrar-side record additionally lists `NS29.DOMAINCONTROL.COM` and `NS30.DOMAINCONTROL.COM`. DNSSEC: **unsigned**.

Relevance

The lock flags and WHOIS privacy are good practice. The hosting provider (HostGator) is revealed through the name servers, and the extra GoDaddy name servers are an inconsistency worth verifying, since stale delegations can be abused if the zone is ever removed from one provider.

4.1.2 WhatWeb – web technology fingerprinting

Command

```
whatweb networkwalks.com
```

Observation

- HTTP request answered with **301 Moved Permanently** to HTTPS; the HTTPS page returned **200 OK**.
- Server: **Apache**. CMS: **WordPress 7.1.4**, with the plugin **WordPress Download Manager 3.3.76** disclosed in the generator meta tag.
- Front-end: jQuery **3.7.1**, Bootstrap, Google Tag Manager, HTML5, Open Graph tags; page title “Networkwalks Academy”.
- IP address **192.232.216.135** (United States). Public contact address **info@networkwalks.com**. Cookie `__wpdm_client` set with the HttpOnly flag.

Relevance

Exact CMS and plugin versions let an attacker match the stack against vulnerability databases without sending a single exploit. Each disclosed component is a candidate for later, authorised vulnerability assessment.

4.1.3 Nslookup – name resolution

Command

```
nslookup networkwalks.com
```

Observation

Querying Google’s resolver (`8.8.8.8#53`) returned a non-authoritative answer: **192.232.216.135**. This matches the address found by WhatWeb and the A/MX records found later by dnsrecon.

Relevance

The site resolves directly to a hosting-provider address rather than a CDN or reverse-proxy range, so the origin server is exposed to direct contact.

4.1.4 Curl – HTTP response headers

Command

```
curl -i networkwalks.com
```

Observation

- `HTTP/1.1 301 Moved Permanently` to `https://networkwalks.com/`; `Server: Apache`.
- `X-Redirect-By: WordPress - Really Simple Security` reveals that the Really Simple Security plugin performs the HTTPS redirect.
- `X-Endurance-Cache-Level: 0` and `X-nginx-cache: WordPress` point to the hosting provider’s caching layer; `Set-Cookie: __wpdm_client` is issued even on the redirect.
- Present: `Permissions-Policy` and `Referrer-Policy: no-referrer-when-downgrade`. Not seen in this response: `Strict-Transport-Security`, `X-Content-Type-Options`, `X-Frame-Options` / CSP.

Relevance

Custom headers act as a second fingerprint source that confirms the plugin and hosting stack. The 301 response was the only one captured, so the final HTTPS response should be checked separately before concluding that the security headers are missing.

Note: `-i` prints the headers followed by the response, using a normal GET request. This differs from `-I`, which sends a HEAD request.

4.1.5 Wafw00f – WAF detection

Command

```
wafw00f networkwalks.com
```

Observation

wafw00f v2.4.2 needed only **2 requests** to conclude that the site is protected by **ModSecurity (SpiderLabs)**.

Relevance

A WAF is a positive control, but knowing its vendor lets an attacker tailor payload encoding and evasion techniques to that specific rule set.

4.1.6 DNSRecon – DNS enumeration

Command

```
dnsrecon -d networkwalks.com
```

Observation

- SOA and NS: `ns6135.hostgator.com` (50.87.144.87) and `ns6136.hostgator.com` (192.232.216.131). Both servers disclose their version banner: **BIND 9.16.23-RH**.
- A and MX: `networkwalks.com` and `mail.networkwalks.com` both resolve to **192.232.216.135**, so web and mail are on the same host.
- SPF: `v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all` (soft fail). A `google-site-verification` TXT record is also published.
- Eight SRV records for `_autodiscover._tcp` point to `cpanelemaildiscovery.cpanel.net` (184.94.203.x / 184.94.204.x, port 443), indicating a **cPanel**-managed hosting account.
- The DNSSEC query returned no answer, consistent with the WHOIS flag `DNSSEC: unsigned`.

Relevance

DNS output gives a map of mail and name-server infrastructure, the hosting control panel in use and the sender policy for e-mail. Version banners on authoritative servers, the unsigned zone and a soft-fail SPF policy are all hardening opportunities.

4.2 Link Analysis with Maltego (W2-PM3)

In Maltego Graph (Desktop) 4.14.0 I created a new graph, placed a **Domain** entity for `networkwalks.com` from the Entity Palette and ran a chain of Utilities transforms to expand it. Each transform consumed credits from the account's allowance (200 in total), which was tracked in the Transform Output window.

Transform	Result	Credits
To Emails @domain [Search Engine]	Returned 2 entities in about 30 s: **info@networkwalks.com** and a related web page entity ("How to login & study your courses").	10 used (190 left)
To Email Addresses [PGP] (on the domain, then on the e-mail)	Completed in about 2.4 s each; no additional addresses were added to the graph.	21–22 used cumulatively
To DNS Name [SecurityTrails]	Returned **13 entities** in 2.7 s: `cpcalendars`, `cpcontacts`, `autoconfig`, `www`, `whm`, `webdisk`, `cpanel`, `ftp`, `localhost`, `mail`, `autodiscover`, `webmail` and the apex domain.	52 used (148 left)
To DNS Name – MX (mail server)	Returned 1 entity: **mail.networkwalks.com** (MX).	No change
To Website [Quick lookup]	Returned 1 website entity for `www.networkwalks.com` (about 2 min 17 s).	No change

The resulting graph (Figures 9–11) links the domain to its public e-mail address, to twelve subdomains and to its MX host. The subdomain list follows the standard cPanel pattern, which corroborates the SRV records and `cpanelemaildiscovery.cpanel.net` seen in dnsrecon. Several of the names (`cpanel`, `whm`, `webmail`, `ftp`,

`webdisk`) represent management or service portals. `localhost.networkwalks.com` is a typical cPanel default record that normally points to the loopback address; its actual value was not checked in this exercise.

The practical value of Maltego here was correlation: one seed entity became a connected map of people-facing contacts, infrastructure and services in a few minutes, and the visual graph made it easy to spot that all of these assets belong to one hosting environment.

4.3 Passive OSINT with theHarvester (W2-PM4)

Command

```
theHarvester -d microsoft.com -l 1000 -b baidu
```

theHarvester 4.11.1 loaded its `proxies.yaml` configuration, queried the **Baidu** search engine for up to 1,000 results (`-l 1000`) and parsed the results for hosts, IPs, e-mail addresses and people.

Observation

- IPs: none found. E-mail addresses: none found. People: none found.
- **6 hosts** found: `account.microsoft.com`, `admin.exchange.microsoft.com`, `developer.microsoft.com`, `dynamicspartners.transform.microsoft.com`, `prod.support.services.microsoft.com`, `support.microsoft.com`.

Scope and ethics

This was a passive technique: the requests went only to the Baidu search engine, and no packets were sent to the target's own infrastructure. A widely known public domain was used purely as a demonstration of the tool's output format.

Relevance

Even one search engine produced hostnames whose labels reveal function and environment (`admin.exchange`, `prod.support.services`). Names such as these help an attacker choose follow-up targets. Coverage with a single source is limited; combining several sources (for example certificate-transparency or DNS-aggregator back-ends such as `crtsh`, `hackertarget` or `rapiddns`) would give a much more complete host list.

4.4 Network Scanning with Zenmap (W2-PM5)

The second activity moved from public data to active discovery on a network I own. The objective was to find my local address and subnet, enumerate live hosts with their IP and MAC addresses, and export a topology diagram.

I first ran `ipconfig` in Windows CMD to read my IPv4 address and subnet mask, which gave the LAN range **10.0.1.0/24** (256 addresses). In Zenmap I entered that range as the target and selected the **Ping Scan** profile. Zenmap built the equivalent command shown below (Nmap 7.99):

```
nmap -sn 10.0.1.0/24
```

A ping scan performs host discovery only and does not probe ports. On a directly connected Ethernet segment Nmap uses ARP requests, which is why each responding host is listed with its MAC address and the vendor derived from its OUI.

The scan started at 09:07 and finished at 09:08 on 10 November 2026. Its summary reports **256 hosts scanned, 50 up and 206 down**, with no ports examined, as expected for a ping scan. I reviewed the addresses and MAC/vendor data in the output and Hosts views, then opened the **Topology** view, enabled the legend and saved the diagram as a PDF, as required by the practical.

Having 50 responding devices on a single segment shows how much a basic discovery scan reveals: workstations, servers, printers, network equipment and any IoT or personal devices all appear with equal visibility. Each address is a potential attack surface and must be matched to a known, owned asset.

One detail stands out in the MAC column: 9 of the 16 addresses visible in the screenshot have the locally administered bit set (for example `F6:15:75`, `82:05:3C`, `9A:37:81`, `26:83:44`). This is the pattern produced by randomised or private MAC addresses on modern phones and tablets, so those hosts cannot be attributed to a

vendor and cannot be tracked reliably by MAC alone. Asset inventory on such a network therefore needs additional identifiers, such as DHCP hostnames or 802.1X identities.

4.5 Consolidated Target Profile – networkwalks.com

The outputs of W2-PM1 and W2-PM3 were merged into a single profile.

Attribute	Value
Domain / Registrar	networkwalks.com / GoDaddy.com, LLC (created 2019-11-06, expires 2027-11-06, privacy-protected, registrar-locked)
Authoritative DNS	ns6135.hostgator.com (50.87.144.87), ns6136.hostgator.com (192.232.216.131); BIND 9.16.23-RH; DNSSEC unsigned
Web / Mail host	192.232.216.135 (A and MX record on the same server)
Web stack	Apache; WordPress 7.1.4; WordPress Download Manager 3.3.76; jQuery 3.7.1; Google Tag Manager; Really Simple Security
Hosting control panel	cPanel/WHM (inferred from subdomains and `cpanelemaildiscovery.cpanel.net` SRV records)
Perimeter	ModSecurity (SpiderLabs) WAF; HTTP to HTTPS 301 redirect
E-mail policy	SPF with soft fail (`~all`), includes `websitewelcome.com`; DKIM/DMARC not assessed
Public contact	info@networkwalks.com
Exposed hostnames	cpanel, whm, webmail, webdisk, ftp, cpcalendars, cpcontacts, autodiscover, autoconfig, mail, www, localhost

5. Risk Analysis / Impact

From the footprinting, OSINT and scanning results I identified the following potential risks. They are observations, not confirmed vulnerabilities.

#	Risk / Finding	Evidence / Observation	Potential Impact	Risk Level
1	CMS, plugin and library versions disclosed	WhatWeb: WordPress 7.1.4, WP Download Manager 3.3.76, jQuery 3.7.1, Apache	Attackers can match exact versions to known vulnerabilities and prioritise targets	● **Medium**
2	Management portals discoverable	Maltego/SecurityTrails: cpanel, whm, webmail, ftp, webdisk subdomains	Larger attack surface for credential stuffing, brute force and phishing against admin interfaces	● **Medium**
3	DNS server version disclosure	dnsrecon: BIND 9.16.23-RH on both name servers	Aids fingerprinting of DNS infrastructure (a Red Hat build may carry back-ported fixes, so the banner alone does not prove a flaw)	● **Medium**
4	DNSSEC not enabled	WHOIS: DNSSEC unsigned; dnsrecon: no DNSSEC answer	Responses cannot be cryptographically validated, which leaves resolvers more exposed to spoofing or cache poisoning	● **Low**
5	Soft-fail SPF and unverified DMARC	SPF ends in `~all`; includes a shared hosting provider	Spoofed e-mail from the domain may still be delivered, which supports phishing against students and staff	● **Medium**
6	Server IP and hosting provider identifiable	nslookup/dnsrecon: 192.232.216.135; HostGator name servers	Shows the network location of the service and allows direct contact with the origin server	● **Low**

#	Risk / Finding	Evidence / Observation	Potential Impact	Risk Level
7	HTTP header information leakage	curl: X-Redirect-By (plugin name), X-Endurance-Cache-Level, X-nginx-cache; HSTS and other security headers not seen on the 301 response	Confirms the plugin and hosting stack; missing headers reduce browser-side protection (final HTTPS response still to be checked)	● **Low**
8	WAF vendor identifiable	wafw00f: ModSecurity (SpiderLabs) in 2 requests	Lets an attacker tailor evasion techniques to the known rule set	● **Low**
9	Public e-mail address harvestable	WhatWeb and Maltego: info@networkwalks.com	Target for phishing and spam	● **Low**
10	Registrar and registry name servers differ	WHOIS: HostGator at the registry, plus domaincontrol.com at the registrar	Stale or inconsistent delegation can cause outages or be abused if left unmanaged	● **Low**
11	Hostnames leak through search engines	theHarvester: 6 hosts including admin.exchange and prod.support.services	Hostnames that reveal function and environment help choose follow-up targets	● **Low**
12	Large number of live LAN hosts	Zenmap ping scan of 10.0.1.0/24: 50 of 256 addresses live; several randomised (locally administered) MAC addresses	Unknown or unauthorised devices can hide among them without an up-to-date asset inventory	● **Medium**

Risk level key: ● Critical ● Medium ● Low

Positive controls observed: a ModSecurity WAF is active, the domain is registrar-locked with WHOIS privacy, HTTP is redirected to HTTPS, and `Permissions-Policy` and `Referrer-Policy` headers are sent.

These modules involved information gathering and host discovery only. No exploitation or vulnerability validation was performed. A version string, IP address or DNS record does not by itself make a system vulnerable; confirming any weakness would need further authorised testing.

6. Recommendations

Based on the observations above, I recommend the following improvements.

1. **Reduce technology fingerprinting**
   Remove the generator meta tag and version query strings, set `ServerTokens Prod` and `ServerSignature Off` on Apache, and drop unneeded headers such as `X-Redirect-By` and `X-Endurance-Cache-Level` where the host allows.
2. **Keep the CMS and plugins patched**
   Update WordPress core, WordPress Download Manager and other plugins promptly, remove unused plugins, and review each against current security advisories.
3. **Harden HTTP security headers**
   Confirm the HTTPS response sends `Strict-Transport-Security`, `X-Content-Type-Options`, `X-Frame-Options` or CSP `frame-ancestors`, and a strict `Referrer-Policy`.
4. **Restrict management interfaces**
   Limit cPanel, WHM, FTP and webmail access by IP allow-list or VPN, enforce multi-factor authentication, enable brute-force protection (cPHulk or fail2ban), prefer SFTP over FTP, and delete unused DNS records such as `localhost`, `webdisk`, `cpcalendars` and `cpcontacts`.
5. **Improve DNS hygiene**
   Ask the DNS provider to hide the BIND version banner, enable DNSSEC where the provider supports it, and reconcile the name servers listed at the registry and the registrar.

6. **Strengthen e-mail authentication**
   Publish DKIM and a DMARC policy (start with `p=none` for monitoring, then move to `quarantine` or `reject`), and tighten SPF from `~all` to `-all` once all legitimate senders are covered.
7. **Protect public contact addresses**
   Use role-based or alias addresses, filter inbound phishing, and train staff and students to recognise it.
8. **Keep the WAF enabled and tuned**
   Keep ModSecurity active with an up-to-date rule set, review its logs, and do not rely on it as the only layer of defence.
9. **Manage the domain lifecycle**
   Keep registrar locks and WHOIS privacy on, and enable auto-renew ahead of the 2027-11-06 expiry.
10. **Maintain a LAN asset inventory**
    Run periodic internal discovery scans, compare the results with an authorised asset list, investigate every unknown device, and document the network topology.
11. **Strengthen network access control**
    Consider 802.1X or MAC-based access control and VLAN segmentation so that unknown devices cannot join the main segment.
12. **Test only with authorisation**
    Perform reconnaissance and scanning solely against systems and networks where written permission exists.

7. Conclusion

During Week 2 of the Cybersecurity & Ethical Hacking internship I completed four practicals covering footprinting, link analysis, passive OSINT and network discovery.

In W2-PM1, six Kali tools each exposed a different layer of `networkwalks.com`: WHOIS showed registration and hosting details, WhatWeb and curl exposed the web stack, nslookup and dnsrecon mapped the IP, name-server and mail infrastructure, and wafw00f identified the ModSecurity WAF. In W2-PM3, Maltego tied those results together into one graph linking the domain to its e-mail address, its cPanel-style subdomains and its mail host. In W2-PM4, theHarvester showed that public search-engine data alone can reveal hostnames without any direct contact with the target. In W2-PM5, Zenmap's ping scan found 50 live hosts on my LAN together with their IP and MAC addresses, and produced a topology diagram.

The main lesson is that a great deal can be learned about an organisation before any exploitation is attempted, using only public records, DNS data and network responses. Defenders therefore need to know what their own footprint looks like. I also learned that findings must be reported clearly: what was done, what was seen, why it matters, what risk it carries and how it can be reduced.

Finally, all reconnaissance and scanning must stay within an authorised scope. These activities were performed in an educational lab environment with the permissions described on the cover page.

8. Evidence Collected

Screenshots are numbered in the order of the activities in Section 4.




Figure 1. *WHOIS (1/3): registrar, dates, status flags and name servers for networkwalks.com.*

```
for lawful purposes and that under no circumstances will you use this Data
to: (1) allow, enable, or otherwise support the transmission of mass
unsolicited, commercial advertising or solicitations via e-mail, telephone,
or facsimile; or (2) enable high volume, automated, electronic processes
that apply to VeriSign (or its computer systems). The compilation,
repackaging, dissemination or other use of this Data is expressly
prohibited without the prior written consent of VeriSign. You agree not to
use electronic processes that are automated and high-volume to access or
query the Whois database except as reasonably necessary to register
domain names or modify existing registrations. VeriSign reserves the right
to restrict your access to the Whois database in its sole discretion to ensure
operational stability.  VeriSign may restrict or terminate your access to the
Whois database for failure to abide by these terms of use. VeriSign
reserves the right to modify these terms at any time.

The Registry database contains ONLY .COM, .NET, .EDU domains and
Registrars.
Domain Name: networkwalks.com
Registry Domain ID: 2452319255_DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.godaddy.com
Registrar URL: https://www.godaddy.com
Updated Date: 2025-11-12T05:08:41Z
Creation Date: 2019-11-06T17:51:46Z
Registrar Registration Expiration Date: 2027-11-06T17:51:46Z
Registrar: GoDaddy.com, LLC
Registrar IANA ID: 146
Registrar Abuse Contact Email: abuse@godaddy.com
Registrar Abuse Contact Phone: +1.4806242505
Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited
Domain Status: clientRenewProhibited https://icann.org/epp#clientRenewProhibited
Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
Registry Registrant ID: Not Available From Registry
Registrant Name: Registration Private
Registrant Organization: Domains By Proxy, LLC
Registrant Street: DomainsByProxy.com
Registrant Street: 100 S. Mill Ave, Suite 1600
Registrant City: Tempe
Registrant State/Province: Arizona
Registrant Postal Code: 85281
Registrant Country: US
Registrant Phone: +1.4806242599
Registrant Phone Ext:
```

Figure 2. *WHOIS (2/3): registry data with registrant privacy (Domains By Proxy) and registrar-side details.*

```
Registry Tech ID: Not Available From Registry
Tech Name: Registration Private
Tech Organization: Domains By Proxy, LLC
Tech Street: DomainsByProxy.com
Tech Street: 100 S. Mill Ave, Suite 1600
Tech City: Tempe
Tech State/Province: Arizona
Tech Postal Code: 85281
Tech Country: US
Tech Phone: +1.4806242599
Tech Phone Ext:
Tech Fax:
Tech Fax Ext:
Tech Email: https://www.godaddy.com/whois/results.aspx?domain=networkwalks.com&action=contactDomainOwner
Name Server: NS6135.HOSTGATOR.COM
Name Server: NS6136.HOSTGATOR.COM
Name Server: NS29.DOMAINCONTROL.COM
Name Server: NS30.DOMAINCONTROL.COM
DNSSEC: unsigned
URL of the ICANN WHOIS Data Problem Reporting System: http://wdprs.internic.net/
>>> Last update of WHOIS database: 2026-11-09T13:34:25Z <<<
For more information on Whois status codes, please visit https://icann.org/epp

TERMS OF USE: The data contained in this registrar's Whois database, while believed by the
registrar to be reliable, is provided "as is" with no guarantee or warranties regarding its
accuracy. This information is provided for the sole purpose of assisting you in obtaining
information about domain name registration records. Any use of this data for any other purpose
is expressly forbidden without the prior written permission of this registrar. By submitting
an inquiry, you agree to these terms and limitations of warranty. In particular, you agree not
to use this data to allow, enable, or otherwise support the dissemination or collection of this
data, in part or in its entirety, for any purpose, such as transmission by e-mail, telephone,
postal mail, facsimile or other means of mass unsolicited, commercial advertising or solicitations
of any kind, including spam. You further agree not to use this data to enable high volume, automated
or robotic electronic processes designed to collect or compile this data for any purpose, including
mining this data for your own personal or commercial purposes. Failure to comply with these terms
may result in termination of access to the Whois database. These terms may be subject to modification
at any time without notice.

**NOTICE** This WHOIS server is being retired. Please use our RDAP service instead.
```

Figure 3. *WHOIS (3/3): technical contact, name servers (including domaincontrol.com) and DNSSEC status.*

```
└─$ whatweb networkwalks.com
http://networkwalks.com [301 Moved Permanently] Apache, Cookies[__wpdm_client], Country[UNITED STATES][US], HTTPServer[Apache], HttpOnly[__wpdm_client], IP[
192.232.216.135], RedirectLocation[https://networkwalks.com/], UncommonHeaders[permissions-policy,x-redirect-by,upgrade,referrer-policy,x-endurance-cache-le
vel,x-nginx-cache]
https://networkwalks.com [200 OK] Apache, Bootstrap[7.1.4], Cookies[__wpdm_client], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, Google-
Tag-Manager, HTML5, HTTPServer[Apache], HttpOnly[__wpdm_client], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1.4,WordPress Download Manage
r 3.3.76], Open-Graph-Protocol[website], Script[4684NR-IPIB&amp;pidnVar2=505118amp;prtVar2=78amp;scvVar2=12,application/json,application/ld+json,module,spec
ulationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-
cache], WordPress[7.1.4]
https://networkwalks.com/ [200 OK] Apache, Bootstrap[7.1.4], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, Google-Tag-Manager, HTML5, HTT
PServer[Apache], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1.4,WordPress Download Manager 3.3.76], Open-Graph-Protocol[website], Script[
4684NR-IPIB&amp;pidnVar2=50511&amp;prtVar2=7&amp;scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalk
s Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1.4]
```

Figure 4. *WhatWeb: WordPress 7.1.4, WP Download Manager 3.3.76, jQuery 3.7.1, Apache, e-mail and IP.*

```
└─$ nslookup networkwalks.com
Server:         8.8.8.8
Address:        8.8.8.8#53

Non-authoritative answer:
Name:   networkwalks.com
Address: 192.232.216.135
```

Figure 5. *Nslookup: networkwalks.com resolves to 192.232.216.135 via 8.8.8.8.*

```
└─$ curl -I networkwalks.com
HTTP/1.1 301 Moved Permanently
Date: Mon, 09 Nov 2026 14:24:49 GMT
Server: Apache
Permissions-Policy: private-state-token-redemption=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.clou
dflare.com" "https://hcaptcha.com"), private-state-token-issuance=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://
challenges.cloudflare.com" "https://hcaptcha.com")
Expires: Mon, 09 Nov 2026 15:24:49 GMT
Cache-Control: max-age=3600
X-Redirect-By: WordPress - Really Simple Security
Set-Cookie: __wpdm_client=83643b004be5816e303176da8651f0c4; path=/; domain=networkwalks.com; HttpOnly
Upgrade: h2,h2c
Connection: Upgrade
Location: https://networkwalks.com/
Referrer-Policy: no-referrer-when-downgrade
X-Endurance-Cache-Level: 0
X-nginx-cache: WordPress
Content-Length: 0
Content-Type: text/html; charset=UTF-8
```

Figure 6. *Curl: HTTP 301 redirect with X-Redirect-By, Permissions-Policy and cache headers.*

```
└─$ wafw00f networkwalks.com

                ?                 ,.   (   .      )       .      "
      __          ??            ("     )  )'     ,'        )  . (`      ``
 (___()'`;    ???             .; )   ' (( (" )    ;(,     ((  (  ;)   "   )")
 /,___ /`                     _".,  ,._ '_.,)_(..,( . )_  _' )_') (. _..( ' )
 \\    \\                   |____|____|____|____|____|____|____|____|____|

                           ~ WAFW00F : v2.4.2 ~
                 ~ Sniffing Web Application Firewalls since 2009 ~

[*] Checking https://networkwalks.com
[+] The site https://networkwalks.com is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2
```

Figure 7. *Wafw00f: site detected behind ModSecurity (SpiderLabs) after 2 requests.*

```
└─$ dnsrecon -d networkwalks.com
2026-11-09T16:37:35.021283+0200 INFO Starting enumeration for domain: networkwalks.com
2026-11-09T16:37:35.021814+0200 INFO std: Performing General Enumeration against: networkwalks.com...
2026-11-09T16:37:35.777563+0200 ERROR No answer for DNSSEC query for networkwalks.com
2026-11-09T16:37:36.342505+0200 INFO     SOA ns6135.hostgator.com 50.87.144.87
2026-11-09T16:37:36.809065+0200 INFO     NS ns6135.hostgator.com 50.87.144.87
2026-11-09T16:37:37.479106+0200 INFO     Bind Version for 50.87.144.87 "9.16.23-RH"
2026-11-09T16:37:37.479408+0200 INFO     NS ns6136.hostgator.com 192.232.216.131
2026-11-09T16:37:38.142360+0200 INFO     Bind Version for 192.232.216.131 "9.16.23-RH"
2026-11-09T16:37:38.662582+0200 INFO     MX mail.networkwalks.com 192.232.216.135
2026-11-09T16:37:39.054554+0200 INFO     A networkwalks.com 192.232.216.135
2026-11-09T16:37:39.770701+0200 INFO     TXT networkwalks.com v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all
2026-11-09T16:37:39.771040+0200 INFO     TXT networkwalks.com google-site-verification=rr04eRmqHoWY3XemnizDNVK4q75X-Ij-mjgEeg-UsYI
2026-11-09T16:37:40.070638+0200 INFO Enumerating SRV Records
2026-11-09T16:37:42.818261+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.203.14 443
2026-11-09T16:37:42.818608+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.204.14 443
2026-11-09T16:37:42.818679+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.203.9 443
2026-11-09T16:37:42.818722+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.203.15 443
2026-11-09T16:37:42.818761+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.204.11 443
2026-11-09T16:37:42.818795+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.204.9 443
2026-11-09T16:37:42.818824+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.204.15 443
2026-11-09T16:37:42.818852+0200 INFO     SRV _autodiscover._tcp.networkwalks.com cpanelemaildiscovery.cpanel.net 184.94.203.11 443
2026-11-09T16:37:42.820122+0200 INFO 8 Records Found
2026-11-09T16:37:42.820618+0200 INFO Completed enumeration for domain: networkwalks.com
```

Figure 8. *DNSRecon: SOA/NS with BIND 9.16.23-RH, MX/A, SPF/TXT and eight SRV records.*




Figure 9. *Maltego: seed domain, info@networkwalks.com and related web page (To Emails @domain).*




Figure 10. *Maltego: 13 DNS names returned by the SecurityTrails transform (52 credits used, 148 left).*




Figure 11. *Maltego: completed graph with MX host and website entity.*




Figure 12. *theHarvester 4.11.1: `-d microsoft.com -l 1000 -b baidu`, 6 hosts found.*




Figure 13. *Zenmap (W2-PM5): Ping scan of 10.0.1.0/24 (nmap -sn), Nmap 7.99, 50 hosts up, 206 down, 256 scanned.*