



Department of Computer Engineering

Faculty of Engineering

Kasetsart University

HW# NoSQL & MongoDB

In this homework, you should create an evidence of your work such as picture with description in PDF and submit the Github link of your homework. Make sure that your Github link is public.

- 1) You're creating a database to contain a set of sensor measurements from a two-dimensional grid. Each measurement is a time-sequence of readings, and each reading contains ten labeled values. Should you use the relational model or MongoDB? Please justify your answer

- 2) For each of the following applications
 - a. IoT
 - b. E-commerce
 - c. Gaming
 - d. Finance

Propose an appropriate Relational Model or MongoDB database schema. For each application, clearly justify your choice of database.

3) Create MongoDB database with following information.

- 1) ({ "name": "Ramesh", "subject": "maths", "marks": 87 })
- 2) ({ "name": "Ramesh", "subject": "english", "marks": 59 })
- 3) ({ "name": "Ramesh", "subject": "science", "marks": 77 })
- 4) ({ "name": "Rav", "subject": "maths", "marks": 62 })
- 5) ({ "name": "Rav", "subject": "english", "marks": 83 })
- 6) ({ "name": "Rav", "subject": "science", "marks": 71 })
- 7) ({ "name": "Alison", "subject": "maths", "marks": 84 })
- 8) ({ "name": "Alison", "subject": "english", "marks": 82 })
- 9) ({ "name": "Alison", "subject": "science", "marks": 86 })
- 10) ({ "name": "Steve", "subject": "maths", "marks": 81 })
- 11) ({ "name": "Steve", "subject": "english", "marks": 89 })
- 12) ({ "name": "Steve", "subject": "science", "marks": 77 })
- 13) ({ "name": "Jan", "subject": "english", "marks": 0, "reason": "absent" })

Give MongoDB statements (with results) for the following queries

- Find the total marks for each student across all subjects.
- Find the maximum marks scored in each subject.
- Find the minimum marks scored by each student.
- Find the top two subjects based on average marks.

- 1) You're creating a database to contain a set of sensor measurements from a two-dimensional grid. Each measurement is a time-sequence of readings, and each reading contains ten labeled values. Should you use the relational model or MongoDB? Please justify your answer

ANS: I prefer relational model because information that question gave me have a well design structure which is each measurement is a time sequence of reading and contain ten labeled values.

- 2) For each of the following applications

- a. IoT
- b. E-commerce
- c. Gaming
- d. Finance

Propose an appropriate Relational Model or MongoDB database schema. For each application, clearly justify your choice of database.

A. MongoDB

```
{
  "sensor_id": ObjectID,
  "location": STR,
  "timestamp": ISODate,
  "sensor_reading": {
    "reading1": value1,
    "reading2": value2,
    "reading3": value3
  }
}
```

B. relational model

Products (product_id, name, description, price, stock)
Customers (customer_id, name, email, password)
Orders (order_id, customer_id, order_date, status, total)
Order_Items (order_id, product_id, quantity)

C. MongoDB

```
{
  "user_id": ObjectID,
  "game_id": ObjectID,
  "timestamp": ISODate,
  "position": {
    "data": {
      "x": int,
      "y": int,
      "z": int
    }
  }
}
```

D. Relation model

Customers (customer_id, name, email, password, phone, address)
Accounts (account_id, customer_id, account_type, balance)
Transactions (transaction_id, account_id, transaction_date, transaction_type, amount)

3.

- Find the total marks for each student across all subjects.

```
marks> db.marks.aggregate([
...   {$group: {_id: "$name", total_marks: {$sum: "$marks"}}}
... ])
[
  { _id: 'Rav', total_marks: 216 },
  { _id: 'Alison', total_marks: 252 },
  { _id: 'Steve', total_marks: 247 },
  { _id: 'Ramesh', total_marks: 223 },
  { _id: 'Jan', total_marks: 0 }
]
```

- Find the maximum marks scored in each subject.

```
marks> db.marks.aggregate([
...   {$group: {_id: "$subject", max_marks: {$max: "$marks"}}}
... ])
[
  { _id: 'maths', max_marks: 87 },
  { _id: 'english', max_marks: 89 },
  { _id: 'science', max_marks: 86 }
]
```

- Find the minimum marks scored by each student.

```
marks> db.marks.aggregate([
...   {$group: {_id: "$name", min_marks: {$min: "$marks"}}}
... ])
[
  { _id: 'Rav', min_marks: 62 },
  { _id: 'Alison', min_marks: 82 },
  { _id: 'Jan', min_marks: 0 },
  { _id: 'Ramesh', min_marks: 59 },
  { _id: 'Steve', min_marks: 77 }
]
```

- Find the top two subjects based on average marks.

```
marks> db.marks.aggregate([
...   {$group: {_id: "$subject", avg_marks: {$avg: "$marks"}}},
...   {$sort: {avg_marks: -1}},
...   {$limit: 2}
... ])
[
  { _id: 'maths', avg_marks: 78.5 },
  { _id: 'science', avg_marks: 77.75 }
]
```