

Chapter 5 Workshop

Table of contents

Summarising data	3
Exercise 5.1	4
Exercise 5.2	4
Exercise 5.3	4
Exercise 5.4	5
Tidying data	6
Exercise 5.5	7
Combining datasets	8
Specifying join keys	10
Exercise 5.6	12
Exercise 5.7	12
case_when()	13
Exercise 5.8	14
Dataset Toxaemia	15
Exercise 5.9	15
Exercise 5.10	18
Data diamonds	21
Exercise 5.11	21

Summarising data

```
library(tidyverse)
my.tv.data <- read_csv(
  "../data/tv.csv",
  col_types = "nfcc"
)
```

The argument `col_types = "nfcc"` stands for {numeric, factor, character, character}, to match the order of the columns.

```
my.tv.data
```

```
# A tibble: 46 x 5
#   ...1 TELETIME SEX SCHOOL STANDARD
#   <dbl> <fct>    <chr> <chr>    <dbl>
1     1 1482     1     1         4
2     2 2018     1     1         4
3     3 1849     1     1         4
4     4 857      1     1         4
5     5 2027     2     1         4
6     6 2368     2     1         4
7     7 1783     2     1         4
8     8 1769     2     1         4
9     9 2534     1     1         3
10    10 2366     1     1         3
# i 36 more rows
```

We often do a summary of a numerical variable for a given categorical variable. For example, we like to see obtain the summary statistics of TV viewing times for various schools. The commands

```
by(my.tv.data$TELETIME, my.tv.data$SCHOOL, summary)
```

We employed the `by()` command above and instead, we may also use `tapply()` `aggregate()` functions:

```
tapply(my.data$TELETIME, my.data$SCHOOL, summary)
aggregate(my.data$TELETIME, list(my.data$SCHOOL), summary)
```

A tabulated summary of categorical data is obtained using the `table()` command. You can also use the tidyverse employing functions like `filter`, `group_by`, and `summarise`.

```
rangitikei <- read.csv(
  "../data/rangitikei.csv",
  header=TRUE,
  row.names = 1
)

wind <- rangitikei |> pull(wind)
river <- rangitikei |> pull(river)

table(wind, river)
```

Exercise 5.1

Describe the table generated above. What does it tell you?

Exercise 5.2

Generate a table that summarizes the mean number of vehicles at each level of wind and temperature. What does this table tell you about the data?

```
# your code goes here
```

Exercise 5.3

Now repeat this for the average people observed. What does this tell you about the data?

```
# your code goes here
```

Exercise 5.4

Given the two tables you produced describe patterns of people and vehicles at Rangitikei rivers.

Tidying data

Most real analyses will require at least a little tidying. You'll begin by figuring out what the underlying variables and observations are. Sometimes this is easy; other times you'll need to consult with the people who originally generated the data. Next, you'll pivot your data into a tidy form, with variables in the columns and observations in the rows.

The `billboard` dataset records the billboard rank of songs in the year 2000:

```
billboard

# A tibble: 317 x 79
  artist      track date.entered  wk1  wk2  wk3  wk4  wk5  wk6  wk7  wk8
  <chr>      <chr> <date>    <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
1 2 Pac      Baby~ 2000-02-26    87   82   72   77   87   94   99   NA
2 2Ge+her    The ~ 2000-09-02    91   87   92   NA   NA   NA   NA   NA
3 3 Doors D~ Kryp~ 2000-04-08    81   70   68   67   66   57   54   53
4 3 Doors D~ Loser 2000-10-21    76   76   72   69   67   65   55   59
5 504 Boyz   Wobb~ 2000-04-15    57   34   25   17   17   31   36   49
6 98~0      Give~ 2000-08-19    51   39   34   26   26   19    2    2
7 A*Teens    Danc~ 2000-07-08    97   97   96   95  100   NA   NA   NA
8 Aaliyah    I Do~ 2000-01-29    84   62   51   41   38   35   35   38
9 Aaliyah    Try ~ 2000-03-18    59   53   38   28   21   18   16   14
10 Adams, Yo~ Open~ 2000-08-26    76   76   74   69   68   67   61   58
# i 307 more rows
# i 68 more variables: wk9 <dbl>, wk10 <dbl>, wk11 <dbl>, wk12 <dbl>,
# wk13 <dbl>, wk14 <dbl>, wk15 <dbl>, wk16 <dbl>, wk17 <dbl>, wk18 <dbl>,
# wk19 <dbl>, wk20 <dbl>, wk21 <dbl>, wk22 <dbl>, wk23 <dbl>, wk24 <dbl>,
# wk25 <dbl>, wk26 <dbl>, wk27 <dbl>, wk28 <dbl>, wk29 <dbl>, wk30 <dbl>,
# wk31 <dbl>, wk32 <dbl>, wk33 <dbl>, wk34 <dbl>, wk35 <dbl>, wk36 <dbl>,
# wk37 <dbl>, wk38 <dbl>, wk39 <dbl>, wk40 <dbl>, wk41 <dbl>, wk42 <dbl>, ...
```

In this dataset, each observation is a song. The first three columns (`artist`, `track` and `date.entered`) are variables that describe the song. Then we have 76 columns (`wk1`-`wk76`) that describe the rank of the song in each week. Here, the column names are one variable (the week) and the cell values are another (the rank).

Exercise 5.5

Use `pivot_longer()` to tidy this data

```
# your code goes here
```

Combining datasets

Two tables can be connected through a pair of keys, within each table.

Every join involves a pair of keys: a primary key and a foreign key. A primary key is a variable or set of variables that uniquely identifies each observation. When more than one variable is needed, the key is called a compound key.

There are four types of joins, we will illustrate them using a simple example:

First lets make some data:

```
df1 <- tibble(x = c(1, 2), y = 2:1)
df2 <- tibble(x = c(3, 1), a = 10, b = "a")
```

Now join the two datasets using the different join functions:

```
df1 %>% inner_join(df2)
```

```
# A tibble: 1 x 4
      x     y     a b
  <dbl> <int> <dbl> <chr>
1     1     2    10 a
```

```
df1 %>% left_join(df2)
```

```
# A tibble: 2 x 4
      x     y     a b
  <dbl> <int> <dbl> <chr>
1     1     2    10 a
2     2     1     NA <NA>
```

```
df1 %>% right_join(df2)
```



```
# A tibble: 2 x 4
      x     y     a b
  <dbl> <int> <dbl> <chr>
1     1     2    10 a
2     3    NA    10 a
```

```
df2 %>% left_join(df1)
```

```
# A tibble: 2 x 4
      x     a b     y
  <dbl> <dbl> <chr> <int>
1     3    10 a    NA
2     1    10 a     2
```

```
df1 %>% full_join(df2)
```

```
# A tibble: 3 x 4
      x     y     a b
  <dbl> <int> <dbl> <chr>
1     1     2    10 a
2     2     1    NA <NA>
3     3    NA    10 a
```

What are the differences between the join functions?

Specifying join keys

By default, `left_join()` will use all variables that appear in both data frames as the join key, but it doesn't always work.

For example let's look at some airline data:

```
library(nycflights13) # data package

flights2 <- flights |>
  select(year, time_hour, origin, dest, tailnum, carrier)
flights2
```

A tibble: 336,776 x 6

	year	time_hour	origin	dest	tailnum	carrier
	<int>	<dtm>	<chr>	<chr>	<chr>	<chr>
1	2013	2013-01-01 05:00:00	EWB	IAH	N14228	UA
2	2013	2013-01-01 05:00:00	LGA	IAH	N24211	UA
3	2013	2013-01-01 05:00:00	JFK	MIA	N619AA	AA
4	2013	2013-01-01 05:00:00	JFK	BQN	N804JB	B6
5	2013	2013-01-01 06:00:00	LGA	ATL	N668DN	DL
6	2013	2013-01-01 05:00:00	EWB	ORD	N39463	UA
7	2013	2013-01-01 06:00:00	EWB	FLL	N516JB	B6
8	2013	2013-01-01 06:00:00	LGA	IAD	N829AS	EV
9	2013	2013-01-01 06:00:00	JFK	MCO	N593JB	B6
10	2013	2013-01-01 06:00:00	LGA	ORD	N3ALAA	AA

i 336,766 more rows

```
planes
```

A tibble: 3,322 x 9

	tailnum	year	type	manufacturer	model	engines	seats	speed	engine
	<chr>	<int>	<chr>	<chr>	<chr>	<int>	<int>	<int>	<chr>
1	N10156	2004	Fixed wing multi~	EMBRAER	EMB~	2	55	NA	Turbo~
2	N102UW	1998	Fixed wing multi~	AIRBUS	INDU~	2	182	NA	Turbo~

```

3 N103US 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
4 N104UW 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
5 N10575 2002 Fixed wing multi~ EMBRAER EMB~ 2 55 NA Turbo~
6 N105UW 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
7 N107US 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
8 N108UW 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
9 N109UW 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
10 N110UW 1999 Fixed wing multi~ AIRBUS INDU~ A320~ 2 182 NA Turbo~
# i 3,312 more rows

```

We are going to try to going flight data to data about types of planes

```

flights2 |>
  left_join(planes)

# A tibble: 336,776 x 13
   year time_hour      origin dest tailnum carrier type manufacturer
  <int> <dtm>      <chr>  <chr> <chr>  <chr>  <chr>  <chr>
1  2013 2013-01-01 05:00:00 EWR   IAH   N14228 UA      <NA>  <NA>
2  2013 2013-01-01 05:00:00 LGA   IAH   N24211 UA      <NA>  <NA>
3  2013 2013-01-01 05:00:00 JFK   MIA   N619AA AA      <NA>  <NA>
4  2013 2013-01-01 05:00:00 JFK   BQN   N804JB B6      <NA>  <NA>
5  2013 2013-01-01 06:00:00 LGA   ATL   N668DN DL      <NA>  <NA>
6  2013 2013-01-01 05:00:00 EWR   ORD   N39463 UA      <NA>  <NA>
7  2013 2013-01-01 06:00:00 EWR   FLL   N516JB B6      <NA>  <NA>
8  2013 2013-01-01 06:00:00 LGA   IAD   N829AS EV      <NA>  <NA>
9  2013 2013-01-01 06:00:00 JFK   MCO   N593JB B6      <NA>  <NA>
10 2013 2013-01-01 06:00:00 LGA   ORD   N3ALAA AA      <NA>  <NA>
# i 336,766 more rows
# i 5 more variables: model <chr>, engines <int>, seats <int>, speed <int>,
#   engine <chr>

```

We get a lot of missing matches because our join is trying to use tailnum and year as a compound key. Both flights and planes have a year column but they mean different things: `flights$year` is the year the flight occurred and `planes$year` is the year the plane was built.

Since these represent different types of data and we might want to keep both, we can be explicit about how to join the two data tables:

```

flights2 |>
  left_join(planes, join_by(tailnum))

```

```
# A tibble: 336,776 x 14
```

```
  year.x time_hour      origin dest  tailnum carrier year.y type
  <int> <dtm>      <chr>  <chr> <chr>    <chr>    <int> <chr>
1   2013 2013-01-01 05:00:00 EWR    IAH    N14228  UA      1999 Fixed wing mu~
2   2013 2013-01-01 05:00:00 LGA    IAH    N24211  UA      1998 Fixed wing mu~
3   2013 2013-01-01 05:00:00 JFK    MIA    N619AA  AA      1990 Fixed wing mu~
4   2013 2013-01-01 05:00:00 JFK    BQN    N804JB  B6      2012 Fixed wing mu~
5   2013 2013-01-01 06:00:00 LGA    ATL    N668DN  DL      1991 Fixed wing mu~
6   2013 2013-01-01 05:00:00 EWR    ORD    N39463  UA      2012 Fixed wing mu~
7   2013 2013-01-01 06:00:00 EWR    FLL    N516JB  B6      2000 Fixed wing mu~
8   2013 2013-01-01 06:00:00 LGA    IAD    N829AS  EV      1998 Fixed wing mu~
9   2013 2013-01-01 06:00:00 JFK    MCO    N593JB  B6      2004 Fixed wing mu~
10  2013 2013-01-01 06:00:00 LGA    ORD    N3ALAA  AA      NA <NA>
# i 336,766 more rows
# i 6 more variables: manufacturer <chr>, model <chr>, engines <int>,
#   seats <int>, speed <int>, engine <chr>
```

Now by default there is a year.x and year.y coming from the flights and planes data respectively. You can change this using the `suffix` argument in `join` or by renaming the columns after the join.

Exercise 5.6

Imagine you've found the top 10 most popular destinations using this code:

```
top_dest <- flights2 |>
  count(dest, sort = TRUE) |>
  head(10)
```

How can you find all flights to those destinations?

```
# your code goes here
```

Exercise 5.7

What do the tail numbers that don't have a matching record in planes have in common? (Hint: one variable explains ~90% of the problems.)

```
# your code goes here
```

case_when()

Sometimes you want to add a new variable to your data based on existing variables.

dplyr's `case_when()` is inspired by SQL's CASE statement and provides a flexible way of performing different computations for different conditions. It has a special syntax that unfortunately looks like nothing else you'll use in the tidyverse. It takes pairs that look like `condition ~ output`. `condition` must be a logical vector; when it's TRUE, `output` will be used.

This can take the place of `if_else()` statements.

For example:

```
flights |>
  mutate(
    status = case_when( # make a new variable status based on the flights arrival delay
      is.na(arr_delay) ~ "cancelled",
      arr_delay < -30 ~ "very early",
      arr_delay < -15 ~ "early",
      abs(arr_delay) <= 15 ~ "on time",
      arr_delay < 60 ~ "late",
      arr_delay < Inf ~ "very late",
    ),
    .keep = "used"
  )
```

```
# A tibble: 336,776 x 2
```

	arr_delay	status
	<dbl>	<chr>
1	11	on time
2	20	late
3	33	late
4	-18	early
5	-25	early
6	12	on time
7	19	late
8	-14	on time
9	-8	on time

```
10          8 on time  
# i 336,766 more rows
```

Exercise 5.8

Write a `case_when()` statement that uses the `month` and `day` columns from `flights` to label a selection of important US holidays (e.g., New Years Day, 4th of July, Thanksgiving, and Christmas). First create a logical column that is either `TRUE` or `FALSE`, and then create a character column that either gives the name of the holiday or is `NA`.

```
# your code goes here
```

Dataset Toxaemia

This dataset is from the `vcdExtra` package. Two signs of *toxaemia*, an abnormal condition during pregnancy characterized by high blood pressure (hypertension) and high levels of protein in the urine. If untreated, both the mother and baby are at risk of complications or death. The dataset **Toxaemia** represents 13384 expectant mothers in Bradford, England in their first pregnancy, who were also classified according to social class and the number of cigarettes smoked per day.

The dataset is a 5 x 3 x 2 x 2 contingency table, with 60 observations on the following 5 variables:

class - Social class of mother, a factor with levels: 1, 2, 3, 4, 5

smoke - Cigarettes smoked per day during pregnancy, a factor with levels: 0, 1-19, 20+

hyper - Hypertension level, a factor with levels: Low, High

urea - Protein urea level, a factor with levels: Low, High

Freq - frequency in each cell, a numeric vector

Exercise 5.9

Obtain relevant graphical displays for this dataset.

Bar charts-

```
library(tidyverse)

library(vcdExtra)
data(Toxaemia)

Toxaemia |>
  ggplot() +
  aes(x=smoke, y=Freq, fill=hyper) +
  geom_bar(stat='identity')
```

```

Toxaemia |>
  ggplot() +
  aes(x=smoke, y=Freq, fill=hyper) +
  geom_bar(stat='identity',
           position = "dodge"
          )

Toxaemia |>
  ggplot() +
  aes(x=smoke, y=Freq, fill=hyper) +
  geom_bar(stat='identity',
           position = "dodge") +
  facet_grid(urea ~ ., scales = "free")

```

Mosaic type charts

```

tab.data <- xtabs(Freq ~ smoke + hyper + urea, data=Toxaemia)

plot(tab.data)

mosaic(tab.data, shade=TRUE, legend=TRUE)

assoc(tab.data, shade=TRUE)

strucplot(tab.data)

sieve(tab.data)

```

The full dataset is a 5 x 3 x 2 x 2 contingency table, with 60 observations on the following 5 variables. For this question we will focus on two categorical variables from this dataset, **hyper** and **urea**. This forms a 2 x 2 contingency table since these variables each have two levels.

```

# subset the data
tox_2 <- Toxaemia |>
  dplyr::select(hyper, urea, Freq)

# the tidyverse way
tox_display <- tox_2 |>
  pivot_wider(names_from = urea,

```



```

        values_from = Freq,
        values_fn = sum) |>
column_to_rownames( var = "hyper") # make values of hyper column row names

tox_display

```

```

      High  Low
High  665 2715
Low   589 9415

```

```
# xtabs()
```

Two signs of *toxaemia*, are high blood pressure (hypertension) and high levels of protein in the urine. We want to ask if in our sample of expectant mothers in Bradford, England, is high blood pressure related to high protein levels? If these two variables are associated this may indicate the presence of toxaemia in the sample, if they are independent toxaemia may not be present.

We can test this question using a Chi-squared test.

The null hypothesis of the chi-squared test is that the two variables are independent and the alternative hypothesis is that the two variables are not independent.

Our null hypothesis is that Hypertension level and the Protein urea level in expectant mothers in Bradford, England are independent.

Our alternative hypothesis that Hypertension level and the Protein urea level in expectant mothers in Bradford, England are *not* independent.

Set our $\alpha = 0.05$

```
chisq.test(tox_display)
```

Pearson's Chi-squared test with Yates' continuity correction

```

data:  tox_display
X-squared = 563.9, df = 1, p-value < 2.2e-16

```

Since our p-value is less than our alpha level we reject the null hypothesis and conclude that the two variables (hyper & urea) are not independent. We found evidence of an association between hypertension levels and protein in urine levels in our sample of expectant mothers in Bradford, England.

We can see the expected counts

```
chisq.test(tox_display)$expected
```

```
      High      Low  
High 316.6856 3063.314  
Low  937.3144 9066.686
```

```
# compared to our observed  
tox_display
```

```
      High  Low  
High  665 2715  
Low   589 9415
```

```
# total counts 13384
```

Exercise 5.10

The genetic information of an organism is stored in its Deoxyribonucleic acid (DNA). DNA is a double stranded helix made up of four different nucleotides. These nucleotides differ in which of the four bases Adenine (A), Guanine (G), Cytosine (C), or Thymine (T) they contain. Nucleotides combine to form amino acids which are the building blocks of proteins. Simply put, three nucleotides form an amino acid and the specific order of a combination dictates what amino acid is formed. A simple pattern that we may want to detect in a DNA sequence is that of the nucleotide at position $i+1$ based on the nucleotide at position i . The nucleotide positional data collected by a researcher in a particular case is given in the following table:

$i \backslash (i+1)$	A	C	G	T
A	622	316	328	536
C	428	262	204	306
G	354	294	174	266
T	396	330	382	648

Perform a test of association and then obtain the symmetric plot.

```
tabledata <- data.frame(  
  A = c(622, 428, 354, 396),  
  C = c(316, 262, 294, 330),
```

```
G = c(328, 204, 174, 382),
T = c(536, 306, 266, 648),
row.names = c("A", "C", "G", "T")
)
```

```
chisq.test(tabledata)$exp
```

	A	C	G	T
A	554.8409	370.5104	335.3705	541.2781
C	369.4834	246.7328	223.3322	360.4516
G	334.9983	223.7044	202.4879	326.8094
T	540.6774	361.0523	326.8094	527.4608

```
chisq.test(tabledata)
```

Pearson's Chi-squared test

```
data: tabledata
X-squared = 153.21, df = 9, p-value < 2.2e-16
```

```
chisq.test(tabledata, simulate.p.value = T)
```

Pearson's Chi-squared test with simulated p-value (based on 2000 replicates)

```
data: tabledata
X-squared = 153.21, df = NA, p-value = 0.0004998
```

```
# if there is an association we can examine patterns
library(MASS)
corresp(tabledata)
```

First canonical correlation(s): 0.1443355

Row scores:

	A	C	G	T
	-0.1921802	-0.8894387	-1.0334109	1.4453224

```

Column scores:
      A      C      G      T
-1.1304512 -0.6952989  0.8139424  1.1304056

```

```

plot(corresp(tabledata, nf=2))
abline(v=0)
abline(h=0)

```

```

#or
library(FactoMineR)
CA(tabledata)

```

****Results of the Correspondence Analysis (CA)****

The row variable has 4 categories; the column variable has 4 categories

The chi square of independence between the two variables is equal to 153.2146 (p-value = 1.9e-05)

*The results are available in the following objects:

	name	description
1	"\$eig"	"eigenvalues"
2	"\$col"	"results for the columns"
3	"\$col\$coord"	"coord. for the columns"
4	"\$col\$cos2"	"cos2 for the columns"
5	"\$col\$contrib"	"contributions of the columns"
6	"\$row"	"results for the rows"
7	"\$row\$coord"	"coord. for the rows"
8	"\$row\$cos2"	"cos2 for the rows"
9	"\$row\$contrib"	"contributions of the rows"
10	"\$call"	"summary called parameters"
11	"\$call\$marge.col"	"weights of the columns"
12	"\$call\$marge.row"	"weights of the rows"

Data diamonds

The `diamonds` dataset contains the prices and other attributes of almost 54,000 diamonds. Use `?diamonds` to see information for each variable.

```
data("diamonds")
names(diamonds)
```

```
[1] "carat"  "cut"     "color"   "clarity" "depth"   "table"   "price"
[8] "x"      "y"      "z"
```

```
## Some EDA plots
```

```
ggplot(diamonds, aes(color))+geom_bar() + facet_wrap(~cut)
```

```
ggplot(diamonds, aes(color))+geom_bar(aes(fill=cut))
```

```
ggplot(diamonds, aes(color))+geom_bar(aes(fill=cut))+ facet_wrap(~clarity)
```

Exercise 5.11

We are interested in whether there is an association between cut and color. Perform a test of association and then obtain the symmetric plot. Write your hypotheses, perform the test, make a decision based on the results of the test, and report a conclusion in context.

```
# your code goes here
```

- More R code examples are [here](#)