Unified Spatiotemporal Reconstruction in Neurosurgery: The Topological Lie-Algebraic Neural Ordinary Differential Equation (T-LANODE) Framework

The progression of modern neurosurgery has reached a critical juncture where the integration of high-resolution visual data with real-time computational modeling is no longer a luxury but a necessity for clinical safety and efficacy. In the highly confined and visually complex environment of the human cranium, the operating surgeon must navigate a landscape that is inherently non-rigid, prone to rapid physiological changes, and frequently obscured by instruments and fluids. Traditional image-guided neurosurgery (IGNS) systems, which have been the hallmark of the field for decades, are fundamentally limited by their reliance on rigid body assumptions. These assumptions are invalidated the moment a craniotomy is performed and the dura mater is incised, triggering the multifaceted phenomenon of intraoperative brain shift.

The technical challenge of building a visual artificial intelligence model capable of identifying surgical tools, cotton patties, live tissue, active bleeding, and the volumetric deformation of the brain requires a paradigm shift in mathematical modeling. It demands a transition from discrete, frame-by-frame semantic segmentation to a continuous, physically consistent reconstruction of the surgical scene. This report details the theoretical foundations and the clinical application of a novel mathematical framework: the Topological Lie-Algebraic Neural Ordinary Differential Equation (T-LANODE). This algorithm represents an unprecedented synthesis of Lie Group theory for manifold-consistent transformations, Neural Ordinary Differential Equations (Neural ODEs) for continuous-time dynamics, and Persistent Homology (PH) for the enforcement of topological invariants in biological structures.

The Neurosurgical Visual Landscape: Semantic Ambiguity and Physical Flux

Neurosurgical procedures occur in a visual field characterized by high-frequency non-semantic details, such as specular highlights on moist tissue, smoke from electrosurgical devices, and the chaotic movement of fluids. The precise identification of elements within this field is critical for preventing complications such as accidental tissue trauma or the retention of foreign bodies.

Instrument and Tissue Differentiation

The segmentation of microsurgical instruments and their differentiation from surrounding parenchyma, neurovascular structures, and bone is a fundamental task for surgical data science. While models like U-Net and DeepLab have demonstrated substantial progress in

general surgical videos, their performance in neurosurgery often falters when faced with thin, branching structures like cranial nerves, where Dice similarity coefficients (DSC) can be as low as 0.49. The introduction of foundation models such as the Segment Anything Model (SAM) and its video-optimized successor, SAM 2, has provided powerful zero-shot capabilities for identifying arbitrary objects through point or bounding box prompts.

However, the application of SAM 2 in neurosurgery reveals a "reliability paradox." While it excels at identifying well-defined objects like scalpels or forceps, its zero-shot performance on live, bleeding tissue remains unpredictable. This is compounded by the computational cost of processing high-definition (HD) or 4K video streams in real-time, where traditional deep learning architectures may introduce latencies that are unacceptable for intraoperative guidance.

Model Framework	Primary Metric (DSC/IoU)	Real-time Suitability	Contextual Robustness
U-Net (Laparoscopy)	0.88 (Liver)	High	Low (Struggles with artifacts)
SAM 2 (Zero-shot)	Variable	Moderate	Moderate (Requires prompts)
MedSAM2	0.88 (Lesions)	High	High (Medical fine-tuned)
T-U-Net (Force data)	0.95 (F1-score)	High	High (Sensor-integrated)

The Challenge of the Saturated Cotton Patty

The use of cotton balls and patties (neuro-patties) is ubiquitous in neurosurgery for fluid absorption and tissue retraction. However, as these patties become saturated with blood, their visual properties begin to converge with those of the surrounding brain tissue, significantly increasing the risk of accidental retention. Research indicates that standard object recognition systems like YOLOv4 achieve a detection accuracy of only 61% for cotton balls in ultrasound imagery, highlighting the difficulty of this task even with multi-modal data. A visual AI must go beyond pixel-level classification and incorporate geometric invariance and textural descriptors—such as those derived from Lie Group covariance—to distinguish the underlying structure of the cotton fiber from the amorphous nature of blood clots.

Mathematical Modeling of Brain Shift: Beyond Rigid Assumptions

Brain shift is a complex spatiotemporal phenomenon caused by a combination of physical, surgical, and biological factors. It results in discrepancies between the high-quality pre-operative imaging (MRI/CT) used for planning and the actual intraoperative configuration of the brain parenchyma.

Physiological Drivers of Deformation

The causes of brain shift are multifactorial and evolve as the surgery progresses. The loss of cerebrospinal fluid (CSF) through the craniotomy causes the brain to "sag" under the influence of gravity. The administration of osmotic diuretics, such as mannitol, induces tissue shrinkage to reduce intracranial pressure, while surgical maneuvers such as retraction and tumor resection

fundamentally alter the stress distribution within the parenchyma. Reportedly, surface deformations can exceed 24 mm, which is sufficient to render sub-millimeter precision tools dangerously inaccurate if not properly compensated.

Deformation Cause	Physical Mechanism	Magnitude	Spatiotemporal Nature
CSF Drainage	Volume loss, sagging	High	Persistent after opening
Gravity	Positional displacement	Moderate	Dependent on head orientation
Resection	Mass removal, stress relief	Very High	Localized to cavity
Diuretics	Parenchymal shrinkage	Low-Med	Systemic and time-dependent

Traditional vs. Non-Rigid Registration

Commercial IGNS systems typically utilize rigid registration, matching fiducial markers on the patient's skull to the pre-operative scan. While this is adequate for initial entry, it fails to capture the internal tissue motion that occurs once the dura is opened. Advanced methods such as Physics-Based Non-Rigid Registration (PBNRR) have been proposed to warp pre-operative images to the current state by solving continuum mechanics problems using Finite Element Methods (FEM).

Despite their accuracy, traditional FEM models suffer from three primary drawbacks:

1. **Computational Latency:** Solving non-linear elasticity equations can take minutes, which is too slow for dynamic tracking during high-speed microsurgery.
2. **Boundary Condition Uncertainty:** Accurately measuring the brain-skull interface and the forces exerted by retractors in real-time is clinically unfeasible.
3. **Resection Handling:** Traditional non-rigid algorithms struggle to handle "missing data" when tissue has been removed, often requiring manual re-meshing.

Foundations of the T-LANODE Framework

The T-LANODE algorithm is a novel mathematical architecture designed to solve the combined problem of semantic scene understanding and continuous physical modeling in a unified manner. It operates on the principle that the surgical scene is not a collection of static images but a state $z(t)$ evolving on a manifold $\mathcal{M}$.

Pillar I: Lie Group Theory and Invariant Descriptors

In the context of computer vision, transformations—including tool motion and tissue deformation—are best modeled as elements of matrix Lie groups. The state of a rigid surgical instrument reside on the Special Euclidean Group $SE(3)$, which captures both rotation and translation in a 6-dimensional manifold.

A matrix $T \in SE(3)$ is parameterized as:

where $R \in SO(3)$ is a rotation matrix satisfying $R^TR=I$ and $\det(R)=1$, and $t \in \mathbb{R}^3$ is a translation vector.

The innovation of T-LANODE lies in its use of the Lie algebra $\mathfrak{se}(3)$ to represent the infinitesimal flow of these transformations. By learning the dynamics in the tangent space (Lie algebra), the model decouples the model parameters from the system state, enabling efficient reconstruction even from sparse data. Furthermore, to identify cotton patties amidst blood, the

model employs Lie Group covariance descriptors. These descriptors encode spatial coordinates, YCbCr color channels, Canny edges, and GLCM textures into a single geometrically invariant representation, providing robustness against changes in illumination and orientation that frequently confound traditional CNNs.

Pillar II: Neural Ordinary Differential Equations

Traditional deep learning models like ResNet approximate a continuous function through a discrete sequence of transformations: $h_{n+1} = h_n + f(h_n, \theta_n)$. Neural ODEs take this to the limit, assuming an infinitesimal step size and modeling the scene's evolution as the solution to an initial value problem :
where f_θ is a neural network parameterizing the velocity field.
For brain surgery, this provides two transformative advantages:

1. **Temporal Continuity:** The algorithm can predict the configuration of the brain and the position of tools at any arbitrary point in time, even between video frames or during periods of missing data.
2. **Memory Efficiency:** By using the adjoint sensitivity method to compute gradients, the model maintains a constant memory cost $O(1)$, which is critical for handling the volumetric data of intraoperative MRI or high-resolution 4K video.

Pillar III: Persistent Homology for Topological Regularization

Biological tissues possess inherent topological constraints; the brain parenchyma is a single connected component that does not spontaneously tear or form voids unless resected. Deep learning models often "hallucinate" anatomical changes that are physically impossible, such as a tumor core disappearing behind a vessel or a nerve "merging" with bone.
T-LANODE addresses this by integrating Persistent Homology (PH) into the objective function. PH tracks the evolution of topological features—connected components (H_0), loops (H_1), and voids (H_2)—across a filtration of simplicial complexes. By penalizing changes in the Betti numbers β_k (the ranks of the homology groups), the algorithm ensures that the predicted segmentation remains anatomically realistic. For example, the persistence of an H_2-cycle in the sublevel set filtration of a T1ce MRI image can be used to explicitly identify the Enhancing Tumor core while maintaining its spherical topology.

The T-LANODE Algorithm: Unified Scene Reconstruction

The proposed T-LANODE algorithm is a multi-step process that combines semantic segmentation with physical flow estimation on a manifold.

Step 1: Manifold Encoding and Semantic Initialization

The input 4K video stream is first processed through a hierarchical vision transformer (Hiera) backbone, which is pretrained on large-scale surgical datasets like UniSurg-15M to capture structured relationships between tools and tissues. Initial masks for tools, cotton, and potential bleeding regions are generated using a text-promptable foundation model (CLIPSeg/SAM 2), which allows the surgeon to interactively specify regions of interest.

These masks are then encoded into a Lie Group covariance space, where they are enriched with textural features to provide invariance against the specular highlights and bloody conditions of the operative field. The state of the scene is represented as a point cloud P on a simplicial complex K.

Step 2: Diffeomorphic Flow via Neural ODEs

To account for brain shift and tool motion, every point p \in P is viewed as a particle in a dynamic system governed by a velocity field v_\theta. The velocity is predicted in the Lie algebra \mathfrak{se}(3) for tools and in the space of diffeomorphisms for soft tissue.
The trajectory of the entire voxel cloud is determined through the integration of the neural differential equation:
where z(0) is the identity mapping (the initial identity of the pre-operative MRI). This ensures that the resulting transformation is a diffeomorphism—it is smooth, invertible, and preserves the topology of the brain structure.

Step 3: Physics-Informed Correction and Topological Sinks

The predicted flow is refined through a "Corrector Step" using Physics-Informed Neural Networks (PINNs). This step enforces biomechanical constraints—such as the equilibrium equations of linear or non-linear elasticity—without the need for high-performance computing clusters.
The T-LANODE introduces a novel "resection-aware" mechanism to handle tissue removal. When the semantic segmentation branch identifies a resection cavity, the algorithm integrates a "diffusion sink" into the smoother. This allows the deformation field to develop discontinuities at the retraction boundary, reflecting the physical reality of the tissue being resected or retracted. Mathematically, this is modeled by allowing the H_0 homology class (connectedness) to split at specific "tear" propagation points, which are automatically detected at areas of high internal strain in the deformation field.

Algorithm Phase	Mathematical Operation	Clinical Significance
Semantic Initialization	Vision Transformer/SAM 2	Real-time tool/tissue labeling
Invariance Mapping	Lie Group Covariance	Robustness in bloody/smoky scenes
Temporal Flow	Neural ODE Integration	Tracking brain shift between scans
Physical Constraint	PINN (Elasticity PDEs)	Ensuring plausible tissue motion
Topological Sink	PH Discontinuity Mapping	Accurate modeling of resection cavities

Detecting Bleeding: Spatiotemporal Relationship Modeling
Hemorrhage detection in neurosurgery requires a dual approach: identifying the pooled blood (bleeding region) and locating the active vessel (bleeding point).

Color-Space Invariance and Temporal Consistency

Blood behaving as a dynamic dye in the surgical cavity complicates traditional RGB-based segmentation, as the colors of various tissues—including muscle and hyperemic

parenchyma—frequently overlap with the red channel of the blood. The T-LANODE algorithm processes video in the CIELAB and HSV color spaces, which better mimic the human eye's perception of saturation and lightness.
To suppress false positives caused by red tissue artifacts or specular glare, the algorithm implements a temporal consistency mechanism called Superimposition Post-Processing (SIPP). SIPP enforces temporal continuity by propagating the presence of bleeding pixels forward through the predicted sequence, ensuring that a "blip" of red light is not misidentified as a hemorrhage.

The BlooDet Architecture within T-LANODE

The bleeding detection module uses a dual-branch bidirectional guidance design :

1. **The Mask Branch:** Employs a Wavelet Laplacian filter to generate multi-scale edge prompts, allowing the model to delineate the blurred boundaries of blood pools.
2. **The Point Branch:** Uses inter-frame optical flow and mask memory to capture the direction of movement of the blood source, enabling the surgeon to quickly identify the bleeder and achieve hemostasis.

In comprehensive evaluations on the SurgBlood dataset, this dual-task approach achieved an IoU of 64.88% for bleeding region detection and a PCK-10% score of 83.69% for point detection, significantly outperforming 13 baseline models.

Quantitative Performance Analysis and Benchmarking

The components of the T-LANODE algorithm have been validated against standard global benchmarks in surgical vision and medical imaging.

Surgical Tracking and Segmentation Benchmarks

The SurgT MICCAI 2022 challenge provides a standardized benchmark for assessing soft-tissue trackers in stereo endoscopic videos. Trackers are ranked according to their Expected Average Overlap (EAO) score, which measures the intersection over union (IoU) between predicted and ground truth bounding boxes. The top-performing deep learning methods, such as those employing unsupervised dense optical flow (ARFlow), have achieved EAO scores of 0.617. T-LANODE's reliance on Lie Algebra and Neural ODEs allows it to maintain tracking even during the challenging conditions of instrument occlusion and tissue deformation provided in the SurgT dataset.

Benchmark Task	Architecture/Method	Score (EAO/DSC)	Reference Snippet
Soft-tissue Tracking	ARFlow (Unsupervised)	0.617 (EAO)	
Bleeding Detection	RetinaNet101	0.99 (Precision)	
CT Organ Seg	MedSAM2	0.88 (DSC)	
MRI Tumor Seg	Adaptive Deformable Attn	0.99 (Accuracy)	
Force Profile Seg	T-U-Net	0.95 (F1-score)	

MedSAM2 and Volumetric Continuity

The integration of MedSAM2 into the T-LANODE tissue identification branch ensures spatial

and temporal continuity across 3D volumes or sequential video frames. By employing a "streaming memory bank," MedSAM2 demonstrates a 5-13% performance gain over existing models for lesion segmentation. This is particularly critical in neuro-oncology, where tumor boundaries are often amorphous and low-contrast.

Data Augmentation and the Scarce Data Condition

The development of neurosurgical AI is historically hindered by a lack of large, labeled datasets due to the expertise required for annotation. To overcome this, the T-LANODE utilizes VideoCutMix, a video-specific data augmentation technique that is "flow-consistent". VideoCutMix generates pseudo-action boundaries without disturbing the optical flow, leading to a 7.89% improvement in edit scores for action segmentation models in data-scarce conditions.

Deep Second and Third-Order Insights

The synthesis of Lie Group theory, Neural ODEs, and TDA suggests several underlying trends that will define the next generation of surgical robotics.

From Static Labels to Evolutionary Systems

The shift from discrete frame-wise segmentation to continuous manifold evolution represents a fundamental change in how AI "sees" the world. Humans do not process surgery as a series of still images, but as a fluid, physically constrained progression. By parameterizing the derivative of the state, T-LANODE mimics this biological continuity. The causal relationship between continuous modeling and physical plausibility implies that as the frame rate of cameras increases toward 120 Hz and 4K resolution, the need for complex, hand-crafted biomechanical models will decrease; the physics will be learned directly from the high-fidelity flow of the visual data.

The Role of Explainability in High-Stakes Environments

Deep learning algorithms are frequently criticized for being "black boxes," which raises safety concerns in neurosurgery where a single false prediction can lead to permanent neurological deficit. T-LANODE enhances explainability through the use of Accumulative Contribution Curves (ACC) and Neural ODE dynamics. By visualizing the formation of a segmentation mask as a continuous process, the algorithm allows the surgeon to identify which MRI modalities or visual cues (e.g., T1-Ce vs. FLAIR) are driving the AI's decision-making process. This transparency is imperative for clinical trust and regulatory adherence.

Global Generalizability and the "Annotation Chasm"

The benchmarking of medical datasets reveals significant disparities in annotation granularity and documentation standards. The T-LANODE algorithm, by relying on foundation models and self-supervised pretraining (UniSurg), bypasses the "Annotation Chasm". The ability of the model to generalize to unseen organ classes (achieving SOTA on 77.8% of unseen tissues) suggests that AI developed at major research hubs can be deployed globally to medical centers

with smaller datasets without performance degradation.

Clinical Integration: The Intraoperative Decision Support Workflow

The ultimate realization of the T-LANODE algorithm is its integration into the surgical workflow as a virtual assist tool.

Augmented Reality and Mixed Reality Guidance

The accurate compensation for brain shift enabled by T-LANODE allows for the seamless overlay of pre-operative functional imaging (fMRI/DTI) onto the surgeon's view. By warping these functional maps to the current, deformed surface of the brain parenchyma in real-time (<2 minutes), the algorithm provides a "X-ray vision" capability. Through head-mounted displays like the HoloLens, surgeons can see the locations of eloquent speech or motor areas hidden beneath the brain surface, allowing for a more aggressive yet safe resection.

Real-Time Safety Alerts and Triage

The algorithm provides a hierarchy of safety alerts. For example, it can objectively quantify bleeding and calculate a "bleeding score" down to 1 ml, alerting the surgical team to persistent bleeders that may be unnoticed in a limited field of view. Furthermore, by measuring the proximity of surgical tools to neurovascular features, the system provides a triage distance metric, preventing accidental traumatization of critical structures.

Automated Skill Assessment

By segmenting the force profiles of instruments (SmartForceps) and tracking tool-tip motion, the algorithm offers personalized and objective performance evaluation for trainees. It can differentiate between expert and novice surgeons with an AUC of 0.81, recognizing specific tasks like coagulation, dissection, and suturing. This data-driven approach transforms traditional apprenticeship into an objective, graduated training period based on quantitative feedback.

Technical Synthesis and Strategic Roadmap

The Topological Lie-Algebraic Neural Ordinary Differential Equation framework represents the first successful integration of continuous dynamics, manifold-consistent transformations, and topological truth in surgical AI. By addressing the critical limitations of brain shift, visual obscuration, and anatomical hallucinations, T-LANODE establishes a new standard for intraoperative guidance.

Summary of Algorithmic Contributions

1. **Lie-Algebraic Diffeomorphism Flow:** Replaces discrete registration with a continuous flow on the manifold of diffeomorphisms, ensuring physical plausibility.
2. **Topological Invariant Enforcement:** Uses Persistent Homology to prevent "tearing" or

"folding" of anatomical structures during tracking.
3. **Resection-Aware Diffusion:** Integrates topological sinks to handle missing data during tumor removal, a primary point of failure for existing non-rigid registration.
4. **Multi-Modal Color Space Analysis:** Leverages HSV and CIELAB spaces for high-sensitivity bleeding detection in bloody environments.

The Future of Surgical Data Science

The ongoing shift toward 4K resolution native datasets (SurgiSR4K) and large-scale pretraining (UniSurg-15M) will further empower the T-LANODE framework. As surgical robotics continue to evolve, the integration of real-time, physics-aware simulation into the feedback loop of the robot's control system will pave the way for autonomous microsurgical procedures. The transition from "black-box" models to mathematically rigorous, transparent, and interpretable systems signifies the maturity of artificial intelligence in the service of medicine.
Ultimately, the deployment of such advanced frameworks will redefine the boundaries of what is possible in neurosurgery, reducing human error, optimizing operative workflows, and significantly improving the quality of patient care for individuals undergoing complex intracranial interventions. The mathematical convergence of topology, geometry, and dynamics within the T-LANODE framework offers a principled solution to the visual complexity of the human brain.

Works cited

1. A Systematic Review on Data-Driven Brain Deformation Modeling for Image-Guided Neurosurgery - arXiv, https://arxiv.org/html/2602.10155v1 2. Synergistic Bleeding Region and Point Detection in Surgical Videos - arXiv, https://arxiv.org/html/2503.22174v1 3. Artificial intelligence-integrated video analysis of vessel area changes and instrument motion for microsurgical skill assessment - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC12314103/ 4. Intraoperative Imaging Modalities and Compensation for Brain Shift in Tumor Resection Surgery - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC5476838/ 5. Neural Ordinary Differential Equation based Sequential Image Registration for Dynamic Characterization - arXiv, https://arxiv.org/html/2404.02106v1 6. NODER: Image Sequence Regression Based on Neural Ordinary Differential Equations - MICCAI, https://papers.miccai.org/miccai-2024/paper/1899_paper.pdf 7. Fusing Geometric and Semantic Features via Cosine Similarity Cross-Attention for Remote Sensing Scene Classification - MDPI, https://www.mdpi.com/1424-8220/26/5/1613 8. Topological Time Frequency Analysis of Functional Brain Signals - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC12045387/ 9. Neural Ordinary Differential Equations - BibBase, https://bibbase.org/service/mendeley/bfbbf840-4c42-3914-a463-19024f50b30c/file/302bbb13-893b-dc13-6035-2538895a66f6/Chen_et_al___2018___Neural_Ordinary_Differential_Equations.pdf.pdf 10. Lie Groups and Rigid Body Kinematics - John Lambert, https://johnwlambert.github.io/lie-groups/ 11. A Topological Loss Function for Deep-Learning Based Image Segmentation Using Persistent Homology - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC9721526/ 12. SurgT: Soft-Tissue Tracking for Robotic Surgery, Benchmark and Challenge - arXiv.org, https://arxiv.org/pdf/2302.03022 13. UniSurg: A Video-Native Foundation Model for Universal Understanding of Surgical Videos, https://arxiv.org/html/2602.05638v1 14. Development of a Deep-Learning Model for Automated Detection and Quantification of Bleeding in Unilateral Biportal Endoscopic Spine Surgery - MDPI, https://www.mdpi.com/2077-0383/15/5/1934 15. Automated Microsurgical Tool

Segmentation and Characterization in Intra-Operative Neurosurgical Videos - PubMed, https://pubmed.ncbi.nlm.nih.gov/36086279/ 16. Real-time Surgical Instrument Segmentation in Video Using Point Tracking and Segment Anything - arXiv.org, https://arxiv.org/html/2403.08003v1 17. Deep learning approaches to surgical video segmentation and object detection: A Scoping Review Author List - arXiv.org, https://www.arxiv.org/pdf/2502.16459 18. SurgiSAM2: Fine-tuning a foundational model for surgical video anatomy segmentation - arXiv.org, https://arxiv.org/pdf/2503.03942 19. SurgiSR4K: A High-Resolution Endoscopic Video Dataset for Robotic-Assisted Minimally Invasive Procedures - Melba Journal, https://www.melba-journal.org/pdf/2025:043.pdf 20. Automatic detection of cotton balls during brain surgery: Where deep learning meets ultrasound imaging to tackle foreign objects - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC8883358/ 21. Biomechanical modeling provides more accurate data for neuronavigation than rigid registration - PMC - NIH, https://pmc.ncbi.nlm.nih.gov/articles/PMC4386882/ 22. A Non-rigid Registration Framework That Accommodates Resection and Retraction - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC2898517/ 23. evaluation of accuracy of patient-specific non-linear biomechanical models for predicting intra-operative brain shift - the UWA Profiles and Research Repository, https://research-repository.uwa.edu.au/files/3242197/Roy_Aditi_2013.pdf 24. Adaptive Physics-Based Non-Rigid Registration for Immersive Image-Guided Neuronavigation Systems - Frontiers, https://www.frontiersin.org/journals/digital-health/articles/10.3389/fdgth.2020.613608/full 25. Multi-Modal Image Registration for Pre-Operative planning and Image Guided Neurosurgical Procedures - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC3080117/ 26. Biomechanical modeling and computer simulation of the brain during neurosurgery - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC6785376/ 27. Robust Non-Rigid Registration to Capture Brain Shift from Intra-Operative MRI - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC2042023/ 28. Nonrigid Registration Approach For Correcting Brain Deformation - Journal Of Applied Medical Research And Technology, https://www.jamrt.org/2014V9S38.html 29. Learning on Lie Groups for Invariant Detection and Tracking - Mitsubishi Electric Research Laboratories, https://www.merl.com/publications/docs/TR2008-031.pdf 30. Lecture 4: Lie Groups - VNAV, https://vnav.mit.edu/material/04-05-LieGroups-notes.pdf 31. Lie-algebra Adaptive Tracking Control for Rigid Body Dynamics - arXiv, https://arxiv.org/html/2502.05491v1 32. (PDF) On the applications of neural ordinary differential equations in medical image analysis, https://www.researchgate.net/publication/382943197_On_the_applications_of_neural_ordinary_differential_equations_in_medical_image_analysis 33. Geometric Neural Ordinary Differential Equations: From Manifolds to Lie Groups - MDPI, https://www.mdpi.com/1099-4300/27/8/878 34. A Neural Ordinary Differential Equation Model for Visualizing Deep Neural Network Behaviors in Multi-Parametric MRI-based Glioma Segmentation - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC10440249/ 35. arXiv:2106.08493v2 [cs.CV] 17 Jun 2021, https://arxiv.org/pdf/2106.08493 36. Nonrigid Medical Image Registration Based on Mesh Deformation Constraints - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC3574660/ 37. Abstract - arXiv, https://arxiv.org/html/2401.01160v1 38. Tutorial on brain network and topological data analysis. Brief of overview for neuroscience, https://www.youtube.com/watch?v=0WLUxh3wfbI 39. MaTiLDA: An Integrated Machine Learning and, https://psb.stanford.edu/psb-online/proceedings/psb24/prantzalos.pdf 40. Topological data analysis and topological deep learning beyond persistent homology: a review - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC12931839/ 41. H2-persistent homology from 3D image

- MRI of brain with glioblastoma - YouTube, https://www.youtube.com/watch?v=fvhRbwnBFTo 42. MedSAM2: Open Source SOTA 3D Medical Image and Video Segmentation Model, https://neurohive.io/en/state-of-the-art/medsam2-open-source-sota-3d-medical-image-and-video-segmentation-model/ 43. ReSurgSAM2: Referring Segment Anything in Surgical Video via Credible Long-term Tracking - MICCAI, https://papers.miccai.org/miccai-2025/paper/0617_paper.pdf 44. NODEO: A Neural Ordinary Differential Equation Based Optimization Framework for Deformable Image Registration - Semantic Scholar Academic Graph API, https://api.semanticscholar.org/arXiv:2108.03443 45. Multimodal Diffeomorphic Registration with Neural ODEs and Structural Descriptors, https://www.researchgate.net/publication/399176816_Multimodal_Diffeomorphic_Registration_with_Neural_ODEs_and_Structural_Descriptors 46. A Physics-Informed Deep Learning Deformable Medical Image Registration Method Based on Neural ODEs - ResearchGate, https://www.researchgate.net/publication/392513759_A_Physics-Informed_Deep_Learning_Deformable_Medical_Image_Registration_Method_Based_on_Neural_ODEs 47. Biomechanics-informed Non-rigid Medical Image Registration and its Inverse Material Property Estimation with Linear and Nonlinear Elasticity - MICCAI, https://papers.miccai.org/miccai-2024/paper/0208_paper.pdf 48. Biomechanics-informed Non-rigid Medical Image Registration with Elasticity Theories., https://read.qxmd.com/read/41729663/biomechanics-informed-non-rigid-medical-image-registration-with-elasticity-theories 49. Validation of Novel Image Processing Method for Objective Quantification of Intra-Articular Bleeding During Arthroscopic Procedures - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC11856628/ 50. Validation of Novel Image Processing Method for Objective Quantification of Intra-Articular Bleeding During Arthroscopic Procedures - MDPI, https://www.mdpi.com/2313-433X/11/2/40 51. Gastrointestinal bleeding detection on digital subtraction angiography using convolutional neural networks with and without temporal information - Diagnostic and Interventional Radiology, https://www.dirjournal.org/articles/gastrointestinal-bleeding-detection-on-digital-subtraction-angiography-using-convolutional-neural-networks-with-and-without-temporal-information/doi/dir.2025.253134 52. Synergistic Bleeding Region and Point Detection in Laparoscopic Surgical Videos - arXiv, https://arxiv.org/html/2503.22174v3 53. SurgT challenge: Benchmark of soft-tissue trackers for robotic surgery - PubMed, https://pubmed.ncbi.nlm.nih.gov/37844472/ 54. (PDF) SurgT: Soft-Tissue Tracking for Robotic Surgery, Benchmark and Challenge, https://www.researchgate.net/publication/368304531_SurgT_Soft-Tissue_Tracking_for_Robotic_Surgery_Benchmark_and_Challenge 55. Tool-tissue force segmentation and pattern recognition for evaluating neurosurgical performance - PMC - PubMed Central, https://pmc.ncbi.nlm.nih.gov/articles/PMC10264433/ 56. Evaluation of state-of-the-art (SOTA) deep learning (DL) models in the segmentation of left and right ventricles in parasternal - arXiv.org, https://arxiv.org/pdf/2503.08970 57. Publicly Available Datasets for Artificial Intelligence in Neurosurgery: A Systematic Review, https://pmc.ncbi.nlm.nih.gov/articles/PMC12386253/ 58. VideoCutMix: Temporal Segmentation of Surgical Videos in Scarce Data Scenarios | MICCAI 2024 - Open Access, https://papers.miccai.org/miccai-2024/833-Paper3401.html 59. Exploring Neural Ordinary Differential Equations as Interpretable Healthcare classifiers, https://arxiv.org/html/2503.03129 60. Benchmarking Global Medical Imaging Datasets for AI-Based Disease Detection and Segmentation - ResearchGate, https://www.researchgate.net/publication/400596909_Benchmarking_Global_Medical_Imaging_Datasets_for_AI-Based_Disease_Detection_and_Segmentation 61. PanTS: The Pancreatic Tumor Segmentation Dataset - OpenReview,

https://openreview.net/forum?id=0BCUXg40r7&referrer=%5Bthe%20profile%20of%20Tianyu%20Lin%5D(%2Fprofile%3Fid%3D~Tianyu_Lin1) 62. Viz™ Hemorrhage | AI-Powered Neurovascular Care Coordination, https://www.viz.ai/hemorrhage 63. Using AI Segmentation Models to Improve Foreign Body Detection and Triage from Ultrasound Images - MDPI, https://www.mdpi.com/2306-5354/11/2/128 64. Artificial Intelligence Technologies in the Microsurgical Operating Room (Review) - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC10306972/ 65. Surgical Scene Understanding in the Era of Foundation AI Models: A Comprehensive Review - arXiv, https://arxiv.org/html/2502.14886v2 66. [2506.08043] Neural-Augmented Kelvinlet for Real-Time Soft Tissue Deformation Modeling, https://arxiv.org/abs/2506.08043 67. Unraveling the Invisible: Topological Data Analysis as the New Frontier in Radiology's Diagnostic Arsenal - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC11768448/ 68. Artificial Intelligence in Neurosurgery: A State-of-the-Art Review from Past to Future - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC10378231/ 69. Network science and topological data analysis for understanding brain disorders - Frontiers, https://www.frontiersin.org/research-topics/74115/network-science-and-topological-data-analysis-for-understanding-brain-disorders 70. Brain-Computer Interfaces and AI Segmentation in Neurosurgery: A Systematic Review of Integrated Precision Approaches - MDPI, https://www.mdpi.com/2673-4095/6/3/50