Synchronisation: Reader-Writer Problem

Master M1 MOSIG, Grenoble University

2014

I. The Reader-Writer Problem

We consider a situation in which a shared resource is concurrently accessed by two types of entities: the readers and the writers. The readers access the resource without modifying it. The writers, can alter the resource. To keep the resource is in a consistent state, multiple readers may access it concurrently but writers should access it exclusively. In other terms, when a writer is using a resource, no reader or writer can access this ressource.

The reader-writer problem is a classical synchronization problem. This access scheme is typically used when working with files or memory.

In the following we will consider the following functions:

- init (reader_writer_t) is the initialization function
- begin_read(reader_writer_t) and end_read(reader_writer_t) are the functions used by each reader before and after reading
- begin_write(reader_writer_t) et end_write(reader_writer_t) are the funstions used by a writer before and after writing.

The structure reader_writer_t is to be defined. It must contain all the variables used by the synchronization primitives.

II. Implementing a thread-safe linked list

Your are asked to implement a **thread-safe linked list**. A **non** thread-safe linked list implementation is included in the archive¹ (linked_list.c, linked_list.h).

In the linked list the list_insert() and list_remove() are concidered to be writings, since it alter the linked list. list_exists() is concidered to be reading.

The provided implementation includes correct calls to the <code>begin_read()</code>, <code>end_read()</code>, <code>begin_write()</code> and <code>end_write()</code> primitives. Your work consists in implementing theses primitives so the linked list behave correctly when accessed by multiple threads.

http://membres-lig.imag.fr/negrevergne/ens/assignment_two.tar.gz

```
Thread nmbr 0, won.
Thread nmbr 1, won.
THREAD 0 TIME: +0s 0.046ms, TYPE : BEGIN WRITE
THREAD 0 TIME: +0s 0.047ms, TYPE : END WRITE
THREAD 0 TIME: +0s 0.047ms, TYPE : BEGIN READ
THREAD 0 TIME: +0s 0.047ms, TYPE : END READ
THREAD 1 TIME: +0s 0.062ms, TYPE : BEGIN WRITE
THREAD 1 TIME: +0s 0.065ms, TYPE : END WRITE
THREAD 1 TIME: +0s 0.065ms, TYPE : BEGIN READ
THREAD 1 TIME: +0s 0.066ms, TYPE : END READ
THREAD 1 TIME: +0s 0.066ms, TYPE : BEGIN WRITE
THREAD 1 TIME: +0s 0.066ms, TYPE : END WRITE
THREAD 1 TIME: +0s 0.066ms, TYPE : BEGIN READ
THREAD 1 TIME: +0s 0.066ms, TYPE : END READ
THREAD 1 TIME: +0s 0.067ms, TYPE : BEGIN WRITE
THREAD 1 TIME: +0s 0.067ms, TYPE : END WRITE
THREAD 1 TIME: +0s 0.067ms, TYPE : BEGIN READ
THREAD 1 TIME: +0s 0.067ms, TYPE : END READ
THREAD 1 TIME: +0s 0.067ms, TYPE : BEGIN WRITE
THREAD 1 TIME: +0s 0.068ms, TYPE : END WRITE
THREAD 1 TIME: +0s 0.068ms, TYPE : BEGIN READ
THREAD 1 TIME: +0s 0.068ms, TYPE : END READ
```

Figure 1: output of : linked_list_simple_test

The archive also contains a simple test file linked_list_simple_test.c. Read it carefully. Any successful test must return EXIT_SUCCESS.

Question II.1: Considering that no synchronization has been implemented yet, what result could you expect from this test. If you run the test, it won't actually fail, why? What do you conclude on the validity of this test?

The code of begin_read(), end_read(), begin_write() and end_write() contains calls to the tracing module (reader_writer_tracing.h, reader_writer_tracing.c). This module allow one to record events and to prints them afterward.

- Question II.2: Fig. 1 is a possible output of ./linked_list_simple_test 2. Using this output, how can you verify the consistency of the calls to begin_read(), end_read(), begin_write() and end_write().
- Question II.3: Write a naÔve implementation of begin_read(), end_read(), begin_write() and end_write() in a new file named reader_writer_1.c using only mutexes².
- **Question II.4:** Write a test program using the tracing module to check the consistency of the calls to begin_read(), end_read(), begin_write() and end_write().

²You must uncomment the corresponding line in the Makefile

Question II.5: What could be the definition of efficiency in this particular problem? In synchronization problems in general? How would you evaluate the efficiency of this solution according to your previous definition?

III. Improving concurrency

The previous solution does not meet the requirements in terms of concurrency since two readers cannot read the list simultaneously.

Question III.1: Implement new begin_read(), end_read(), begin_write() and end_write() functions in reader_writer_2.c to improve the concurrent capabilities of your thread-safe list. You may use conditions.

Question III.2: Write a test program that verify that readers can access the list concurrently. Note that this test will fail with your first implementation and pass with your second implementation.

IV. Improving fairness

Question IV.1: Introducing the events WAITS TO READ and WAITS TO WRITE for threads waiting in the functions begin_read() and begin_write(). Spot the fairness issue in Fig. 2.

Question IV.2: Discuss about the **fairness** of your previous solution.

Question IV.3: Build a fair solution for the reader writer problem in reader_writer_3.c. Write a corresponding test.

Hint: You must not mix the readers which arrived before a writer with the ones arriving after.

```
THREAD 0 TIME: +0s 0.068ms, TYPE: BEGIN READ
THREAD 1 TIME: +0s 0.069ms, TYPE: WAITS TO WRITE
THREAD 2 TIME: +0s 0.070ms, TYPE: BEGIN READ
THREAD 0 TIME: +0s 0.071ms, TYPE: END READ

THREAD 0 TIME: +0s 0.083ms, TYPE: BEGIN READ
THREAD 2 TIME: +0s 0.085ms, TYPE: END READ

THREAD 2 TIME: +0s 0.123ms, TYPE: BEGIN READ
THREAD 0 TIME: +0s 0.127ms, TYPE: END READ

THREAD 2 TIME: +0s 0.127ms, TYPE: END READ

THREAD 2 TIME: +0s 0.143ms, TYPE: BEGIN READ
THREAD 2 TIME: +0s 0.145ms, TYPE: END READ

THREAD 2 TIME: +0s 0.161ms, TYPE: END READ

THREAD 2 TIME: +0s 0.168ms, TYPE: END READ

THREAD 1 TIME: +0s 0.183ms, TYPE: END READ
THREAD 1 TIME: +0s 0.184ms, TYPE: BEGIN WRITE
THREAD 1 TIME: +0s 0.187ms, TYPE: END WRITE
```

Figure 2: problematic behavior