

Nanyang Technological University

Domain Expansion: Infinite Penalty(ˆ. .ˆ) ∫

Peeranat Kongkijpipat (autoastt), Nathan Juirnarongrit (saltyy), Kittiphat Pongarunotai (Marszpace)

2026-11-09

Contents

1 Contest 1
2 Mathematics 1
3 Data structures 1
4 Numerical 4
5 Number theory 8
6 Combinatorial 10
7 Graph 12
8 Geometry 17
9 Strings 21
10 Various 22

Contest (1)

macros.cpp 7 lines

```
#define rep(i, a, b) for(int i = a; i < (b); ++i)
#define all(x) begin(x), end(x)
#define sz(x) (int)(x).size()
#define pb push_back
typedef long long ll;
typedef pair<int, int> pii;
typedef vector<int> vi;
```

hash.sh 7 lines

```
#!/bin/bash
# Prints the first 6 chars of the md5 of a file (or stdin),
# ignoring whitespace and comments: to check typed code.
# Usage: chmod +x hash.sh; ./hash.sh [file.cpp]
[ -z "$1" -o -r "$1" ] || { echo "can't read $1"; exit 1; }
cpp -dD -P -fpreprocessed < "${1:-/dev/stdin}" |
  tr -d '[:space:]' | md5sum | cut -c-6
```

stress.sh 15 lines

```
# Stress test. Compile like the judge, plus -Wall and
# -D_GLIBCXX_ASSERTIONS (vector/string out-of-range aborts).
# ./A solution, ./gen S prints a small random test (seed S),
# ./A2 brute force (may be missing if ./checker exists),
# ./checker in out ans: optional, exit 0 = OK (ans = A2 output)
# Usage: bash stress.sh [iterations]
for ((i=1; i<=${1:-1000}; i++)); do
  ./gen $i > in
  timeout 5 ./A < in > out ||
    { echo "A crash/TLE, seed $i"; exit 1; }
  if [ -x A2 ]; then ./A2 < in > ans; else : > ans; fi
  if [ -x checker ]; then ./checker in out ans
  else diff -wB out ans >/dev/null; fi || {
    echo "WA, seed $i"; tail -n+1 in out ans; exit 1; }
done; echo OK
```

interactive.sh 24 lines

```
# Interactive tester. ./A solution; ./interactor in reads the
# test file "in", talks on stdin/stdout (flush every line!),
# verdict on stderr, exit != 0 on WA; ./gen S prints a test.
# Usage: bash interactive.sh in        one test
#        bash interactive.sh gen [N]   stress test
run() {
  timeout 5 ./interactor $1 > to < from 2> verdict & p=$!
  timeout 5 ./A < to > from; ar=$?  # keep this open order
# Transcript in "log": use these lines, not the 2 above
# : > log
# timeout 5 ./interactor $1 > >(tee -a log > to) < from \
#   2> verdict & p=$!
# timeout 5 ./A < to > >(tee -a log > from); ar=$?
  wait $p; ir=$?
  [ $ar -eq 0 -a $ir -eq 0 ] && return
  echo "A exit $ar (124 = timeout: flush?)," \
    "judge exit $ir: $(cat verdict)"; return 1
}
mkfifo to from; trap 'rm -f to from' EXIT
if [ "$1" = gen ]; then
  for ((i=1; i<=${2:-100}; i++)); do ./gen $i > in
    run in || { echo "seed $i"; exit 1; }
  done; echo OK
else run $1 && cat verdict; fi
```

Mathematics (2)

2.1 Trigonometry

$$\sin(v+w) = \sin v \cos w + \cos v \sin w$$
$$\cos(v+w) = \cos v \cos w - \sin v \sin w$$
$$\tan(v+w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$
$$\sin v + \sin w = 2 \sin \frac{v+w}{2} \cos \frac{v-w}{2}$$
$$\cos v + \cos w = 2 \cos \frac{v+w}{2} \cos \frac{v-w}{2}$$
$$(V+W)\tan(v-w)/2 = (V-W)\tan(v+w)/2$$

where V, W are lengths of sides opposite angles v, w.

$$a\cos x + b \sin x = r\cos(x-\phi)$$
$$a\sin x + b \cos x = r\sin(x+\phi)$$

where $r = \sqrt{a^2+b^2}, \phi = \text{atan2}(b, a)$.

2.2 Geometry

2.2.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a+b+c}{2}$

Area: $A = \sqrt{p(p-a)(p-b)(p-c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2+2c^2-a^2}$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc\left[1 - \left(\frac{a}{b+c}\right)^2\right]}$$

Law of sines: $\frac{\sin\alpha}{a} = \frac{\sin\beta}{b} = \frac{\sin\gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc\cos\alpha$

Law of tangents: $\frac{a+b}{a-b} = \frac{\tan\frac{\alpha+\beta}{2}}{\tan\frac{\alpha-\beta}{2}}$

2.2.2 Quadrilaterals

With side lengths a, b, c, d, diagonals e, f, diagonals angle θ, area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin\theta = F\tan\theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is $180°$, $ef = ac + bd$, and $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$.

2.2.3 Lattice polygons

Pick's theorem: a simple polygon with integer vertices has area $A = I + B/2 - 1$, where I, B count the interior and boundary lattice points. The segment from (x_1, y_1) to (x_2, y_2) contains $\gcd(|x_2 - x_1|, |y_2 - y_1|) + 1$ lattice points.

2.3 Useful Formulae

$$\frac{d}{dx}\arcsin x = \frac{1}{\sqrt{1-x^2}} \qquad \frac{d}{dx}\arccos x = -\frac{1}{\sqrt{1-x^2}}$$
$$\frac{d}{dx}\tan x = 1 + \tan^2 x \qquad \frac{d}{dx}\arctan x = \frac{1}{1+x^2}$$
$$\int \tan ax = -\frac{\ln|\cos ax|}{a} \qquad \int x\sin ax = \frac{\sin ax - ax\cos ax}{a^2}$$
$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2}\text{erf}(x) \qquad \int xe^{ax}dx = \frac{e^{ax}}{a^2}(ax-1)$$
$$1^4 + 2^4 + 3^4 + \cdots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$
$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \ldots, (-1 < x \le 1)$$
$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \ldots, (-1 \le x \le 1)$$

Data structures (3)

OrderStatisticTree.h 8f2f6d, 19 lines

Description: A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change `null_type`. **Time:** $\mathcal{O}(\log N)$

```
#pragma push_macro("int")
#undef int
#include <bits/extc++.h>
#pragma pop_macro("int")
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
  Tree<int> t, t2; t.insert(8);
  auto it = t.insert(10).first;
  assert(it == t.lower_bound(9));
  assert(t.order_of_key(10) == 1);
  assert(t.order_of_key(11) == 2);
  assert(*t.find_by_order(0) == 8);
  t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

HashMap.h

8a5c0c, 10 lines

Description: Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

```
#pragma push_macro("int")
#undef int
#include <bits/extc++.h>
#pragma pop_macro("int")
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
  const uint64_t C = ll(4e18 * acos(0)) | 71;
  ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{},{1<<16});
```

SegmentTree.h

0f4bdb, 19 lines

Description: Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit. **Time:** $\mathcal{O}(\log N)$

```
struct Tree {
  typedef int T;
  static constexpr T unit = INT_MIN;
  T f(T a, T b) { return max(a, b); } // (any associative fn)
  vector<T> s; int n;
  Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
  void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
      s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
  }
  T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
      if (b % 2) ra = f(ra, s[b++]);
      if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
  }
};
```

LazySegTreeBlock.h

d22e37, 18 lines

Description: The part of LazySeg you edit. Range chmin and range add, queries sum / max / count of max (segment tree beats). A tag is $x \mapsto \min(x, c) + a$: chmin v is $\{v,\ 0\}$, add v is $\{\texttt{INF},\ v\}$. S() is a leaf with value 0. To change it, L must stay closed under comp, and app must act on the aggregate like the tag acts on every element. ok(s, x) says whether x can be applied to the whole segment s without looking inside (else it recurses). **Add only:** ok returns 1, drop se, cnt. **Min query:** add mn, op takes min, app: mn = min(mn, x.c) + x.a. **Chmax instead of chmin:** store $-a_i$ (chmax v = chmin $-v$, add v = add $-v$), negate the answers. **Set, add, mul:** L = (a, b), $x \mapsto ax + b$, id = $\{1,\ 0\}$, set v = $\{0,\ v\}$, add = $\{1,\ v\}$, mul = $\{v,\ 0\}$, app = a * s + b * len (sum) or a * s + b (max, $a \geq 0$), comp(x, y) = {x.a * y.a, x.a * y.b + x.b}, ok returns 1. **Chmin, chmax, add, set with only max / min queries:** L = (a, lo, hi), $x \mapsto \min(\max(x + a, lo), hi)$, set v = $\{0,\ v,\ v\}$, comp(x, y): a = x.a + y.a, and lo, hi = y.lo, y.hi each shifted by x.a, then clamped to [x.lo, x.hi].

```
const ll INF = 1e18;
struct S { ll mx = 0, se = -INF, cnt = 1, sum = 0; };
struct L { ll c, a; };
S e() { return {-INF, -INF, 0, 0}; }
L id() { return {INF, 0}; }
S op(S a, S b) {
  if (a.mx < b.mx) swap(a, b);
  if (a.mx == b.mx) return {a.mx, max(a.se, b.se), a.cnt + b.
      cnt, a.sum + b.sum};
  return {a.mx, max(a.se, b.mx), a.cnt, a.sum + b.sum};
}
bool ok(S s, L x) { return x.c > s.se; }
S app(S s, L x, int len) {
  if (x.c < s.mx) s.sum -= (s.mx - x.c) * s.cnt, s.mx = x.c;
  s.sum += x.a * len; s.mx += x.a;
  if (s.se > -INF / 2) s.se += x.a;
  return s;
}
L comp(L x, L y) { return {min(y.c, x.c - y.a), x.a + y.a}; }
```

LazySegTree.h

f8c112, 42 lines

Description: Lazy segment tree over any monoid with lazy tags. Never edit this part, only the block before it (LazySegTreeBlock.h), which defines S, L, e, id, op, ok, app, comp. app(s, x, len) applies tag x to the value s of a segment of length len, comp(x, y) is the tag "y first, then x". Ranges are $[l, r)$. Beats with add is $O(\log^2 N)$ amortized. maxRight(l, f) is the largest r with f(query(l, r)) true, for monotone f with f(e()) true (descent in $O(\log N)$). **Time:** $\mathcal{O}(\log N)$

Usage: vector<S> v(n); LazySeg t(v); t.upd(l, r, {5, 0}); t.query(l, r).sum;
t.maxRight(l, [&](S s) { return s.mx < x; }); // first index >= l with value >= x

```
struct LazySeg {
  int n; vector<S> t; vector<L> z;
  LazySeg(vector<S> v) : n(sz(v)), t(4*n), z(4*n, id()) { build
      (v, 1, 0, n); }
  void build(vector<S>& v, int o, int lo, int hi) {
    if (hi - lo == 1) { t[o] = v[lo]; return; }
    int m = (lo + hi) / 2;
    build(v, 2*o, lo, m); build(v, 2*o+1, m, hi);
    t[o] = op(t[2*o], t[2*o+1]);
  }
  void ap(int o, int len, L x) { t[o] = app(t[o], x, len); z[o]
       = comp(x, z[o]); }
  void push(int o, int lo, int hi) {
    int m = (lo + hi) / 2;
    ap(2*o, m-lo, z[o]); ap(2*o+1, hi-m, z[o]); z[o] = id();
  }
  void upd(int l, int r, L x, int o=1, int lo=0, int hi=-1) {
    if (hi < 0) hi = n;
    if (r <= lo || hi <= l) return;
    if (l<=lo && hi<=r && ok(t[o], x)) return ap(o, hi-lo, x);
    push(o, lo, hi); int m = (lo + hi) / 2;
    upd(l, r, x, 2*o, lo, m); upd(l, r, x, 2*o+1, m, hi);
    t[o] = op(t[2*o], t[2*o+1]);
  }
  S query(int l, int r, int o = 1, int lo = 0, int hi = -1) {
    if (hi < 0) hi = n;
    if (r <= lo || hi <= l) return e();
    if (l <= lo && hi <= r) return t[o];
    push(o, lo, hi); int m = (lo + hi) / 2;
    return op(query(l,r,2*o,lo,m), query(l,r,2*o+1,m,hi));
  }
  template<class F> int maxRight(int l, F f) {
    S a = e();
    auto go = [&](auto&& go, int o, int lo, int hi) -> int {
      if (hi <= l) return hi;
      if (l<=lo && f(op(a, t[o]))) return a = op(a, t[o]), hi;
      if (hi - lo == 1) return lo;
      push(o, lo, hi); int m = (lo + hi) / 2;
      int r = go(go, 2*o, lo, m);
      return r < m ? r : go(go, 2*o+1, m, hi);
    };
    return go(go, 1, 0, n);
  }
};
```

PersistentSegmentTree.h

7845a1, 31 lines

Description: Persistent segment tree over positions $[0, n)$ holding sums. A version is identified by its root; version 0 is empty. upd adds x at position p and returns the new root. query(v, l, r) sums $[l, r)$ in version v. kth(a, b, k) is the k-th smallest (0-indexed) position in the multiset b − a (all counts ≥ 0), e.g. range k-th element with a_i added at position rank(a_i) per version. **Time:** $\mathcal{O}(\log N)$ per operation, $\mathcal{O}(\log N)$ memory per update

Usage: PST t(n); r[i+1] = t.upd(r[i], p, 1); t.kth(r[l], r[r], k);

```
struct PST {
  struct Nd { int l = 0, r = 0; ll s = 0; };
  vector<Nd> t{Nd()}; int n;
  PST(int n) : n(n) {}
  int upd(int v, int p, ll x, int lo = 0, int hi = -1) {
    if (hi < 0) hi = n;
    int c = sz(t), m = (lo + hi) / 2, ch;
    t.push_back(t[v]); t[c].s += x;
    if (hi - lo > 1) {
      if (p < m) ch = upd(t[v].l, p, x, lo, m), t[c].l = ch;
      else ch = upd(t[v].r, p, x, m, hi), t[c].r = ch;
    }
    return c;
  }
  ll query(int v, int l, int r, int lo = 0, int hi = -1) {
    if (hi < 0) hi = n;
    if (!v || r <= lo || hi <= l) return 0;
    if (l <= lo && hi <= r) return t[v].s;
    int m = (lo + hi) / 2;
    return query(t[v].l,l,r,lo,m) + query(t[v].r,l,r,m,hi);
  }
  int kth(int a, int b, ll k) {
    int lo = 0, hi = n;
    while (hi - lo > 1) {
      int m = (lo + hi) / 2; ll c = t[t[b].l].s - t[t[a].l].s;
      if (k < c) a = t[a].l, b = t[b].l, hi = m;
      else k -= c, a = t[a].r, b = t[b].r, lo = m;
    }
    return lo;
  }
};
```

UnionFindRollback.h

a88960, 23 lines

Description: Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback(). Optional parity: join(a, b, w) also demands that the parity par(a) ⊕ par(b) (distance mod 2 to the root) is w. If join returns false and par(a) ⊕ par(b) ≠ w, the demand is contradictory. **Time:** $\mathcal{O}(\log(N))$

Usage: int t = uf.time(); ...; uf.rollback(t);

```
struct RollbackUF {
  vi e, d; vector<pii> st;
  RollbackUF(int n) : e(n, -1), d(n) {}
  int size(int x) { return -e[find(x)]; }
  int find(int x) { return e[x] < 0 ? x : find(e[x]); }
  int par(int x) { return e[x] < 0 ? 0 : d[x] ^ par(e[x]); }
  int time() { return sz(st); }
  void rollback(int t) {
    for (int i = time(); i --> t;)
      e[st[i].first] = st[i].second;
    st.resize(t);
  }
  bool join(int a, int b, int w = 0) {
    int x = par(a) ^ par(b) ^ w;
    a = find(a), b = find(b);
    if (a == b) return false;
    if (e[a] > e[b]) swap(a, b);
    st.push_back({a, e[a]});
    st.push_back({b, e[b]});
    e[a] += e[b]; e[b] = a; d[b] = x;
```

```
    return true;
  }
};
```

DynCon.h

"UnionFindRollback.h" 53ca31, 24 lines

Description: Offline dynamic connectivity. `add(l, r, a, b)` makes edge a–b present during times $[l, r)$. `run(f)` calls `f(t)` for $t = 0, \ldots, T-1$ in order; during the call `uf` describes the graph at time t (components, sizes), and `bad` is the number of edges closing an odd cycle (the graph is bipartite iff `bad == 0`). For toggle queries, keep a `map<pii,int>` of start times and close open edges at T. **Time:** $\mathcal{O}((N + E \log T) \log N)$
Usage: `DynCon dc(n, T); dc.add(l, r, a, b);`
`dc.run([&](int t){ ... dc.uf.find(x) ... });`

```
struct DynCon {
  int T, bad = 0; RollbackUF uf; vector<vector<pii>> seg;
  DynCon(int n, int T) : T(T), uf(n), seg(4*T + 4) {}
  void add(int l, int r, int a, int b, int o = 1, int lo = 0,
       int hi = -1) {
    if (hi < 0) hi = T;
    if (r <= lo || hi <= l) return;
    if (l<=lo && hi<=r) { seg[o].push_back({a, b}); return; }
    int m = (lo + hi) / 2;
    add(l, r, a, b, 2*o, lo, m); add(l, r, a, b, 2*o+1, m, hi);
  }
  template<class F> void run(F&& f, int o = 1, int lo = 0, int
       hi = -1) {
    if (hi < 0) hi = T;
    if (lo >= hi) return;
    int t = uf.time(), b0 = bad;
    for (auto [a, b] : seg[o])
      if (!uf.join(a, b, 1) && uf.par(a) == uf.par(b)) bad++;
    if (hi - lo == 1) f(lo);
    else {
      int m = (lo + hi) / 2;
      run(f, 2*o, lo, m); run(f, 2*o+1, m, hi);
    }
    uf.rollback(t); bad = b0;
  }
};
```

Matrix.h

4da5a2, 26 lines

Description: Basic operations on square matrices.
Usage: `Matrix<int, 3> A;`
`A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};`
`array<int, 3> vec = {1,2,3};`
`vec = (A^N) * vec;`

```
template<class T, int N> struct Matrix {
  typedef Matrix M;
  array<array<T, N>, N> d{};
  M operator*(const M& m) const {
    M a;
    rep(i,0,N) rep(j,0,N)
      rep(k,0,N) a.d[i][k] += d[i][j] * m.d[j][k];
    return a;
  }
  array<T, N> operator*(const array<T, N>& vec) const {
    array<T, N> ret{};
    rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
    return ret;
  }
  M operator^(ll p) const {
    assert(p >= 0);
    M a, b(*this);
    rep(i,0,N) a.d[i][i] = 1;
    while (p) {
      if (p&1) a = a*b;
      b = b*b;
      p >>= 1;
    }
    return a;
  }
};
```

LineContainer.h

8ec1c7, 30 lines

Description: Container where you can add lines of the form kx+m, and query maximum values at points x. Useful for dynamic programming ("convex hull trick"). **Time:** $\mathcal{O}(\log N)$

```
struct Line {
  mutable ll k, m, p;
  bool operator<(const Line& o) const { return k < o.k; }
  bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
  // (for doubles, use inf = 1/.0, div(a,b) = a/b)
  static const ll inf = LLONG_MAX;
  ll div(ll a, ll b) { // floored division
    return a / b - ((a ^ b) < 0 && a % b); }
  bool isect(iterator x, iterator y) {
    if (y == end()) return x->p = inf, 0;
    if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
    else x->p = div(y->m - x->m, x->k - y->k);
    return x->p >= y->p;
  }
  void add(ll k, ll m) {
    auto z = insert({k, m, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
      isect(x, erase(y));
  }
  ll query(ll x) {
    assert(!empty());
    auto l = *lower_bound(x);
    return l.k * x + l.m;
  }
};
```

LiChao.h

8f3109, 30 lines

Description: Li Chao tree: minimum of lines $kx + m$ at integer points $x \in [0, n)$. `add` inserts a line everywhere, `addSeg` only for $x \in [a, b)$, in any order. For maximum, negate k, m and the answer. `query` returns `INF` if no line covers x. **Time:** $\mathcal{O}(\log N)$ per operation ($\mathcal{O}\left(\log^2 N\right)$ for `addSeg`)

```
struct LiChao {
  static const ll INF = 4e18;
  struct Ln { ll k=0, m=INF; ll at(ll x) { return k*x + m; } };
  int n; vector<Ln> t;
  LiChao(int n) : n(n), t(4*n) {}
  void ins(Ln ln, int o, int lo, int hi) {
    int mid = (lo + hi) / 2;
    bool l=ln.at(lo)<t[o].at(lo), m=ln.at(mid)<t[o].at(mid);
    if (m) swap(t[o], ln);
    if (hi - lo == 1) return;
    if (l != m) ins(ln,2*o+1,mid,hi); else ins(ln,2*o+2,mid,hi);
  }
  void addSeg(ll k, ll m, int a, int b, int o = 1, int lo = 0,
       int hi = -1) {
    if (hi < 0) hi = n;
    if (b <= lo || hi <= a) return;
    if (a <= lo && hi <= b) return ins({k, m}, o, lo, hi);
    int mid = (lo + hi) / 2;
    addSeg(k,m,a,b,2*o,lo,mid); addSeg(k,m,a,b,2*o+1,mid,hi);
  }
  void add(ll k, ll m) { addSeg(k, m, 0, n); }
  ll query(int x) {
    ll r = INF;
    for (int o = 1, lo = 0, hi = n; ; ) {
      r = min(r, t[o].at(x));
      if (hi - lo == 1) return r;
      int mid = (lo + hi) / 2;
      if (x < mid) o = 2*o, hi = mid; else o = 2*o+1, lo = mid;
    }
  }
};
```

Treap.h

08bcd4, 82 lines

Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data. Here each node keeps the sum of its subtree, with lazy range add and range reverse: `go(t, l, r, f)` runs `f` on the subtree holding positions $[l, r)$ (see the comment above it). **Time:** $\mathcal{O}(\log N)$

```
struct Node {
  Node *l = 0, *r = 0;
  ll val, sum, add = 0;
  int y, c = 1;
  bool rev = 0;
  Node(ll val) : val(val), sum(val), y(rand()) {}
  void recalc(), push();
  void app(ll a, bool f) { // add a to all values, reverse if f
    val += a, sum += a * c, add += a;
    if (f) rev ^= 1, swap(l, r);
  }
};

int cnt(Node* n) { return n ? n->c : 0; }
ll sm(Node* n) { return n ? n->sum : 0; }
void Node::recalc() {
  c = cnt(l) + cnt(r) + 1, sum = sm(l) + sm(r) + val;
}
void Node::push() {
  if (l) l->app(add, rev);
  if (r) r->app(add, rev);
  add = rev = 0;
}

template<class F> void each(Node* n, F f) {
  if (n) {
    n->push(); each(n->l, f); f(n->val); each(n->r, f);
  }
}

pair<Node*, Node*> split(Node* n, int k) {
  if (!n) return {};
  n->push();
  if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
    auto [L,R] = split(n->l, k);
    n->l = R;
    n->recalc();
    return {L, n};
  } else {
    auto [L,R] = split(n->r,k - cnt(n->l) - 1); // and just "k"
    n->r = L;
    n->recalc();
    return {n, R};
  }
}

Node* merge(Node* l, Node* r) {
  if (!l) return r;
  if (!r) return l;
  if (l->y > r->y) {
    l->push();
```

```
    l->r = merge(l->r, r);
    return l->recalc(), l;
  } else {
    r->push();
    r->l = merge(l, r->l);
    return r->recalc(), r;
  }
}

Node* ins(Node* t, Node* n, int pos) {
  auto [l,r] = split(t, pos);
  return merge(merge(l, n), r);
}

// Run f on the subtree of positions [l, r), e.g.
// go(t, l, r, [&](Node* n) { n->app(5, 0); }); // add 5
// app(0, 1) reverses, n->sum is the sum (f skipped if empty).
template<class F> void go(Node*& t, int l, int r, F f) {
  Node *a, *b, *c;
  tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
  if (b) f(b);
  t = merge(merge(a, b), c);
}

// Example application: move the range [l, r) to index k
void move(Node*& t, int l, int r, int k) {
  Node *a, *b, *c;
  tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
  if (k <= l) t = merge(ins(a, b, k), c);
  else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h

e62fac, 22 lines

Description: Computes partial sums a[0] + a[1] + ... + a[pos - 1], and updates single elements a[i], taking the difference between the old and new value. **Time:** Both operations are $\mathcal{O}(\log N)$.

```
struct FT {
  vector<ll> s;
  FT(int n) : s(n) {}
  void update(int pos, ll dif) { // a[pos] += dif
    for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
  }
  ll query(int pos) { // sum of values in [0, pos)
    ll res = 0;
    for (; pos > 0; pos &= pos - 1) res += s[pos-1];
    return res;
  }
  int lower_bound(ll sum) {// min pos st sum of [0, pos] >= sum
    // Returns n if no sum is >= sum, or -1 if empty sum is.
    if (sum <= 0) return -1;
    int pos = 0;
    for (int pw = 1 << 25; pw; pw >>= 1) {
      if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
        pos += pw, sum -= s[pos-1];
    }
    return pos;
  }
};
```

FenwickTree2d.h

"FenwickTree.h" 157f07, 22 lines

Description: Computes sums a[i,j] for all i<I, j<J, and increases single elements a[i,j]. Requires that the elements to be updated are known in advance (call fakeUpdate() before init()). **Time:** $\mathcal{O}\left(\log^2 N\right)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

```
struct FT2 {
  vector<vi> ys; vector<FT> ft;
  FT2(int limx) : ys(limx) {}
  void fakeUpdate(int x, int y) {
    for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
  }
  void init() {
    for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
  }
  int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
  void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
      ft[x].update(ind(x, y), dif);
  }
  ll query(int x, int y) {
    ll sum = 0;
    for (; x; x &= x - 1)
      sum += ft[x-1].query(ind(x-1, y));
    return sum;
  }
};
```

RMQ.h

510c32, 16 lines

Description: Range Minimum Queries on an array. Returns min(V[a], V[a + 1], ... V[b - 1]) in constant time. **Time:** $\mathcal{O}(|V| \log |V| + Q)$
Usage: `RMQ rmq(values);`
`rmq.query(inclusive, exclusive);`

```
template<class T>
struct RMQ {
  vector<vector<T>> jmp;
  RMQ(const vector<T>& V) : jmp(1, V) {
    for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
      jmp.emplace_back(sz(V) - pw * 2 + 1);
      rep(j,0,sz(jmp[k]))
        jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
    }
  }
  T query(int a, int b) {
    assert(a < b); // or return inf if a == b
    int dep = 31 - __builtin_clz(b - a);
    return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
  }
};
```

MoQueries.h

a12ef4, 49 lines

Description: Interval or tree path queries: visit the queries along an approximate TSP, adding/removing points at the ends. Values on tree edges: `step` adds/removes the edge (a, c) and the initial `add` goes (keep `in`). **Time:** $\mathcal{O}\left(N\sqrt{Q}\right)$

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vi mo(vector<pii> Q) {
  int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s;
#define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) {
    pii q = Q[qi];
    while (L > q.first) add(--L, 0);
    while (R < q.second) add(R++, 1);
    while (L < q.first) del(L++, 0);
    while (R > q.second) del(--R, 1);
    res[qi] = calc();
  }
  return res;
}

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
  int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
  add(0, 0), in[0] = 1;
  auto dfs = [&](int x, int p, int dep, auto& f) -> void {
    par[x] = p;
    L[x] = N;
    if (dep) I[x] = N++;
    for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
    if (!dep) I[x] = N++;
    R[x] = N;
  };
  dfs(root, -1, 0, dfs);
#define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) rep(end,0,2) {
    int &a = pos[end], b = Q[qi][end], i = 0;
#define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                  else { add(c, end); in[c] = 1; } a = c; }
    while (!(L[b] <= L[a] && R[a] <= R[b]))
      I[i++] = b, b = par[b];
    while (a != b) step(par[a]);
    while (i--) step(I[i]);
    if (end) res[qi] = calc();
  }
  return res;
}
```

Numerical (4)

4.1 Polynomials and recurrences

Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
  vector<double> a;
  double operator()(double x) const {
    double val = 0;
    for (int i = sz(a); i--;) (val *= x) += a[i];
    return val;
  }
  void diff() {
    rep(i,1,sz(a)) a[i-1] = i*a[i];
    a.pop_back();
  }
  void divroot(double x0) {
    double b = a.back(), c; a.back() = 0;
    for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
    a.pop_back();
  }
};
```

PolyInterpolate.h

08bf48, 13 lines

Description: Given n points (x[i], y[i]), computes an n-1-degree polynomial p that passes through them: $p(x) = a[0] * x^0 + ... + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \ldots n-1$. **Time:** $\mathcal{O}\left(n^2\right)$

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
  vd res(n), temp(n);
  rep(k,0,n-1) rep(i,k+1,n)
    y[i] = (y[i] - y[k]) / (x[i] - x[k]);
  double last = 0; temp[0] = 1;
  rep(k,0,n) rep(i,0,n) {
    res[i] += y[k] * temp[i];
    swap(last, temp[i]);
```

```
    temp[i] -= last * x[k];
  }
  return res;
}
```

LagrangeInterpolation.h

"../number-theory/ModPow.h" 4f0513, 18 lines

Description: Given $y_i = f(i)$ for $i = 0, \dots, n-1$, where f is a polynomial of degree $< n$, returns $f(x) \bmod p$ for any integer x (mod prime $> n$). Use for sums of powers: $\sum_{i \le x} i^k$ has degree $k+1$, so feed it $k+2$ prefix sums. **Time:** $\mathcal{O}(n)$

```
ll lagrange(const vector<ll>& y, ll x) {
  int n = sz(y);
  x = (x % mod + mod) % mod;
  if (x < n) return y[x];
  vector<ll> pre(n + 1, 1), suf(n + 1, 1), ifact(n, 1);
  rep(i,0,n) pre[i+1] = pre[i] * ((x - i + mod) % mod) % mod;
  for (int i = n; i--;) suf[i] = suf[i+1] * ((x - i + mod) %
       mod) % mod;
  ll f = 1;
  rep(i,1,n) f = f * i % mod;
  ifact[n-1] = modpow(f, mod - 2);
  for (int i = n-1; i--;) ifact[i] = ifact[i+1] * (i+1) % mod;
  ll ans = 0;
  rep(i,0,n) {
    ll t = y[i] * pre[i] % mod * suf[i+1] % mod * ifact[i] %
         mod * ifact[n-1-i] % mod;
    ans = (ans + ((n - 1 - i) & 1 ? mod - t : t)) % mod;
  }
  return ans;
}
```

BerlekampMassey.h

"../number-theory/ModPow.h" 96548b, 20 lines

Description: Recovers any n-order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\le n$. **Time:** $\mathcal{O}(N^2)$
Usage: `berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}`

```
vector<ll> berlekampMassey(vector<ll> s) {
  int n = sz(s), L = 0, m = 0;
  vector<ll> C(n), B(n), T;
  C[0] = B[0] = 1;

  ll b = 1;
  rep(i,0,n) { ++m;
    ll d = s[i] % mod;
    rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
    if (!d) continue;
    T = C; ll coef = d * modpow(b, mod-2) % mod;
    rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
    if (2 * L > i) continue;
    L = i + 1 - L; B = T; b = d; m = 0;
  }

  C.resize(L + 1); C.erase(C.begin());
  for (ll& x : C) x = (mod - x) % mod;
  return C;
}
```

LinearRecurrence.h

f4e444, 26 lines

Description: Generates the k'th term of an n-order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \ge n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp–Massey. **Time:** $\mathcal{O}(n^2 \log k)$
Usage: `linearRec({0, 1}, {1, 1}, k) // k'th Fibonacci number`

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
  int n = sz(tr);

  auto combine = [&](Poly a, Poly b) {
    Poly res(n * 2 + 1);
    rep(i,0,n+1) rep(j,0,n+1)
      res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
    for (int i = 2 * n; i > n; --i) rep(j,0,n)
      res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
    res.resize(n + 1);
    return res;
  };

  Poly pol(n + 1), e(pol);
  pol[0] = e[1] = 1;

  for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
  }

  ll res = 0;
  rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
  return res;
}
```

BostanMori.h

"NumberTheoreticTransform.h" 75eebc, 16 lines

Description: Generates the k'th term of an n-order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \ge n-1]$ and $tr[0 \dots n-1]$, modulo 998244353 (values in $[0, mod)$). Same interface as `linearRec`, much faster for large n. With $Q = 1 - \sum_j tr[j]x^{j+1}$ and $P = S \cdot Q \bmod x^n$ we want $[x^k]P/Q$; multiplying both by $Q(-x)$ makes the denominator even, so k halves. **Time:** $\mathcal{O}(n \log n \log k)$
Usage: `bostanMori({0, 1}, {1, 1}, k) // k'th Fibonacci number`

```
ll bostanMori(const vl& S, const vl& tr, ll k) {
  int n = sz(tr);
  if (!n) return 0;
  vl Q(n + 1, 1);
  rep(j,0,n) Q[j + 1] = (mod - tr[j]) % mod;
  vl P = conv(S, Q);
  P.resize(n);
  for (; k; k /= 2) {
    vl R = Q;
    for (int i = 1; i <= n; i += 2) R[i] = (mod - R[i]) % mod;
    vl U = conv(P, R), V = conv(Q, R);
    rep(i,0,n) P[i] = U[2 * i + k % 2];
    rep(i,0,n+1) Q[i] = V[2 * i];
  }
  return P[0];
}
```

4.2 Optimization

HillClimbing.h

8eeeaf, 14 lines

Description: Poor man's optimization for unimodal functions.

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
  pair<double, P> cur(f(start), start);
  for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
    rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
      P p = cur.second;
      p[0] += dx*jmp;
      p[1] += dy*jmp;
      cur = min(cur, make_pair(f(p), p));
    }
  }
  return cur;
}
```

Integrate.h

4756fc, 7 lines

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4, although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
  double h = (b - a) / 2 / n, v = f(a) + f(b);
  rep(i,1,n*2)
    v += f(a + i*h) * (i&1 ? 4 : 2);
  return v * h / 3;
}
```

4.3 Matrices

Determinant.h

bd5cec, 15 lines

Description: Calculates determinant of a matrix. Destroys the matrix. **Time:** $\mathcal{O}(N^3)$

```
double det(vector<vector<double>>& a) {
  int n = sz(a); double res = 1;
  rep(i,0,n) {
    int b = i;
    rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
    if (i != b) swap(a[i], a[b]), res *= -1;
    res *= a[i][i];
    if (res == 0) return 0;
    rep(j,i+1,n) {
      double v = a[j][i] / a[i][i];
      if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
    }
  }
  return res;
}
```

IntDeterminant.h

3313dc, 18 lines

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version. **Time:** $\mathcal{O}(N^3)$

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
  int n = sz(a); ll ans = 1;
  rep(i,0,n) {
    rep(j,i+1,n) {
      while (a[j][i] != 0) { // gcd step
        ll t = a[i][i] / a[j][i];
        if (t) rep(k,i,n)
          a[i][k] = (a[i][k] - a[j][k] * t) % mod;
        swap(a[i], a[j]);
        ans *= -1;
      }
    }
    ans = ans * a[i][i] % mod;
    if (!ans) return 0;
  }
  return (ans + mod) % mod;
}
```

SolveLinear.h

44c9ab, 38 lines

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost. **Time:** $\mathcal{O}(n^2 m)$

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
  int n = sz(A), m = sz(x), rank = 0, br, bc;
  if (n) assert(sz(A[0]) == m);
  vi col(m); iota(all(col), 0);
```

```
  rep(i,0,n) {
    double v, bv = 0;
    rep(r,i,n) rep(c,i,m)
      if ((v = fabs(A[r][c])) > bv)
        br = r, bc = c, bv = v;
    if (bv <= eps) {
      rep(j,i,n) if (fabs(b[j]) > eps) return -1;
      break;
    }
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) swap(A[j][i], A[j][bc]);
    bv = 1/A[i][i];
    rep(j,i+1,n) {
      double fac = A[j][i] * bv;
      b[j] -= fac * b[i];
      rep(k,i+1,m) A[j][k] -= fac*A[i][k];
    }
    rank++;
  }

  x.assign(m, 0);
  for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

SolveLinear2.h

"SolveLinear.h" 08e495, 7 lines

Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
  rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
  x[col[i]] = b[i] / A[i][i];
fail:; }
```

SolveLinearBinary.h

fa2d7a, 34 lines

Description: Solves $Ax = b$ over $\mathbb{F}_2$. If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b. **Time:** $\mathcal{O}\left(n^2 m\right)$

```
typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
  int n = sz(A), rank = 0, br;
  assert(m <= sz(x));
  vi col(m); iota(all(col), 0);
  rep(i,0,n) {
    for (br=i; br<n; ++br) if (A[br].any()) break;
    if (br == n) {
      rep(j,i,n) if(b[j]) return -1;
      break;
    }
    int bc = (int)A[br]._Find_next(i-1);
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) if (A[j][i] != A[j][bc]) {
      A[j].flip(i); A[j].flip(bc);
    }
    rep(j,i+1,n) if (A[j][i]) {
      b[j] ^= b[i];
      A[j] ^= A[i];
    }
    rank++;
  }

  x = bs();
  for (int i = rank; i--;) {
    if (!b[i]) continue;
    x[col[i]] = 1;
    rep(j,0,i) b[j] ^= A[j][i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

SolveLinearMod.h

"../number-theory/ModPow.h" 5008e8, 29 lines

Description: Solves $Ax = b$ over the field $\mathbb{Z}_{mod}$ (mod prime). Returns the rank, or -1 if there is no solution. Free variables are set to 0. Data in A and b is lost. Entries must be in $[0, mod)$. **Time:** $\mathcal{O}\left(nm \min(n,m)\right)$

```
typedef vector<ll> vl;
int solveLinearMod(vector<vl>& A, vl& b, vl& x) {
  int n = sz(A), m = sz(x), rank = 0;
  vi col(m); iota(all(col), 0);
  rep(i,0,n) {
    int br = -1, bc = 0;
    rep(r,i,n) rep(c,i,m) if (br<0 && A[r][c]) br = r, bc = c;
    if (br < 0) {
      rep(j,i,n) if (b[j]) return -1;
      break;
    }
    swap(A[i], A[br]); swap(b[i], b[br]); swap(col[i],col[bc]);
    rep(j,0,n) swap(A[j][i], A[j][bc]);
    ll iv = modpow(A[i][i], mod - 2);
    rep(j,i+1,n) {
      ll fac = A[j][i] * iv % mod;
      b[j] = (b[j] - fac * b[i] % mod + mod) % mod;
      rep(k,i+1,m) A[j][k] = (A[j][k] - fac * A[i][k] % mod +
          mod) % mod;
    }
    rank++;
  }
  x.assign(m, 0);
  for (int i = rank; i--;) {
    b[i] = b[i] * modpow(A[i][i], mod - 2) % mod;
    x[col[i]] = b[i];
    rep(j,0,i) b[j] = (b[j] - A[j][i]*b[i] % mod + mod) % mod;
  }
  return rank; // (multiple solutions if rank < m)
}
```

XorBasis.h

89ae6a, 28 lines

Description: Basis of the span of the inserted 64-bit numbers under xor. `insert` returns whether x was independent. `has(x)` tests $x \in$ span. `best(x)` is the maximum of $x \oplus s$ over the span ($x = 0$: maximum element). `kth(k)` is the k-th smallest element of the span (0-indexed, $k < 2^{\text{rk}}$); it makes the basis reduced, which is harmless. **Time:** $\mathcal{O}\left(64\right)$ per operation

```
typedef unsigned long long ull;
struct XorBasis {
  ull b[64] = {}; int rk = 0;
  bool insert(ull x) {
    for (int i = 64; i--;) if (x >> i & 1) {
      if (!b[i]) { b[i] = x; rk++; return 1; }
      x ^= b[i];
    }
    return 0;
  }
  bool has(ull x) {
    for (int i = 64; i--;) if (x >> i & 1) {
      if (!b[i]) return 0;
      x ^= b[i];
    }
    return 1;
  }
  ull best(ull x = 0) {
    for (int i = 64; i--;) x = max(x, x ^ b[i]);
    return x;
  }
  ull kth(ull k) {
    rep(i,0,64) rep(j,0,i) if (b[j] && (b[i] >> j & 1)) b[i] ^=
          b[j];
    ull r = 0; int t = 0;
    rep(i,0,64) if (b[i] && (k >> t++ & 1)) r ^= b[i];
    return r;
  }
};
```

MatrixInverse.h

ebfff6, 35 lines

Description: Invert matrix A. Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of A mod p, and k is doubled in each step. **Time:** $\mathcal{O}\left(n^3\right)$

```
int matInv(vector<vector<double>>& A) {
  int n = sz(A); vi col(n);
  vector<vector<double>> tmp(n, vector<double>(n));
  rep(i,0,n) tmp[i][i] = 1, col[i] = i;

  rep(i,0,n) {
    int r = i, c = i;
    rep(j,i,n) rep(k,i,n)
      if (fabs(A[j][k]) > fabs(A[r][c]))
        r = j, c = k;
    if (fabs(A[r][c]) < 1e-12) return i;
    A[i].swap(A[r]); tmp[i].swap(tmp[r]);
    rep(j,0,n)
      swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
    swap(col[i], col[c]);
    double v = A[i][i];
    rep(j,i+1,n) {
      double f = A[j][i] / v;
      A[j][i] = 0;
      rep(k,i+1,n) A[j][k] -= f*A[i][k];
      rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
    }
    rep(j,i+1,n) A[i][j] /= v;
    rep(j,0,n) tmp[i][j] /= v;
    A[i][i] = 1;
  }

  for (int i = n-1; i > 0; --i) rep(j,0,i) {
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
  }

  rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
  return n;
}
```

FastFourierTransform.h

00ced6, 35 lines

Description: `fft(a)` computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k, N a power of 2. `conv(a, b) = c` with $c[x] = \sum a[i]b[x-i]$. Complex or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16}, more if random); else NTT/FFTMod. **Time:** $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{22}$)

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vector<complex<long double>> R(2, 1);
  static vector<C> rt(2, 1);  // (^ 10% faster if double)
  for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
      a[i + j + k] = a[i + j] - z;
      a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
  if (a.empty() || b.empty()) return {};
  vd res(sz(a) + sz(b) - 1);
  int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
  vector<C> in(n), out(n);
  copy(all(a), begin(in));
  rep(i,0,sz(b)) in[i].imag(b[i]);
  fft(in);
  for (C& x : in) x *= x;
  rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
  fft(out);
  rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
  return res;
}
```

FastFourierTransformMod.h

"FastFourierTransform.h" 2bc998, 22 lines

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$. **Time:** $\mathcal{O}(N \log N)$, where $N = |A|+|B|$ (twice as slow as NTT or FFT)

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  vl res(sz(a) + sz(b) - 1);
  int B=32-__builtin_clz(sz(res)), n=1<<B, cut=(int)sqrt(M);
  vector<C> L(n), R(n), outs(n), outl(n);
  rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
  rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
  fft(L), fft(R);
  rep(i,0,n) {
    int j = -i & (n - 1);
    outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
    outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
  }
  fft(outl), fft(outs);
  rep(i,0,sz(res)) {
    ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
    ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
    res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
  }
  return res;
}
```

NumberTheoreticTransform.h

"../number-theory/ModPow.h" d54056, 35 lines

Description: `ntt(a)` computes $\hat{f}(k) = \sum_x a[x] g^{xk}$ for all k, $g = \text{root}^{(mod-1)/N}$, N a power of 2. `conv(a, b) = c` with $c[x] = \sum a[i]b[x-i]$, modulo primes $2^a b + 1$ with result size at most 2^a (any modulus: FFTMod). By hand: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs in [0, mod). **Time:** $\mathcal{O}(N \log N)$

```
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vl rt(2, 1);
  for (static int k = 2, s = 2; k < n; k *= 2, s++) {
    rt.resize(n);
    ll z[] = {1, modpow(root, mod >> s)};
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
      a[i + j + k] = ai - z + (z > ai ? mod : 0);
      ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
      n = 1 << B;
  ll inv = modpow(n, mod - 2);
  vl L(a), R(b), out(n);
  L.resize(n), R.resize(n);
  ntt(L), ntt(R);
  rep(i,0,n)
    out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
  ntt(out);
  return {out.begin(), out.begin() + s};
}
```

FastSubsetTransform.h

464cf3, 16 lines

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of a must be a power of two. **Time:** $\mathcal{O}(N \log N)$

```
void FST(vi& a, bool inv) {
  for (int n = sz(a), step = 1; step < n; step *= 2) {
    for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
      int &u = a[j], &v = a[j + step]; tie(u, v) =
        inv ? pii(v - u, u) : pii(v, u + v); // AND
        inv ? pii(v, u - v) : pii(u + v, u); // OR
        pii(u + v, u - v);                   // XOR
    }
  }
  if (inv) for (int& x : a) x /= sz(a); // XOR only
}
vi conv(vi a, vi b) {
  FST(a, 0); FST(b, 0);
  rep(i,0,sz(a)) a[i] *= b[i];
  FST(a, 1); return a;
}
```

PolyOps.h

"NumberTheoreticTransform.h" fe06e0, 68 lines

Description: Power series modulo x^n (coefficients in $[0, mod)$, NTT prime). `polyInv` needs $a_0 \neq 0$, `polyLog` needs $a_0 = 1$, `polyExp` needs $a_0 = 0$. All results have exactly n coefficients. `polyPow(a, k, n)` is $a^k \bmod x^n$ for any a (also with leading zeros) and k up to 10^{18}; `polySqrt` needs $a_0 = 1$; `polyDivMod(a, b)` returns (q, r) with $a = qb + r$, $\deg r < \deg b$, and needs `b.back() != 0`. **Time:** $\mathcal{O}(n \log n)$

Usage: `polyExp(polyLog(a, n), n) == a`

```
vl polyInv(vl a, int n) {
  vl b = {modpow(a[0], mod - 2)};
  for (int m = 1; m < n; m *= 2) {
    vl f(a.begin(), a.begin()+min(sz(a), 2*m)), c = conv(f, b);
    c.resize(2 * m);
    for (ll& x : c) x = (mod - x) % mod;
    c[0] = (c[0] + 2) % mod;
    b = conv(b, c); b.resize(2 * m);
  }
  b.resize(n); return b;
}
vl polyDer(vl a) {
  rep(i,1,sz(a)) a[i-1] = a[i] * i % mod;
  if (!a.empty()) a.pop_back();
  return a;
}
vl polyInt(vl a) {
  a.insert(a.begin(), 0);
  vl inv(sz(a), 1);
  rep(i,2,sz(a)) inv[i] = (mod - mod/i*inv[mod%i] % mod) % mod;
  rep(i,1,sz(a)) a[i] = a[i] * inv[i] % mod;
  return a;
}
vl polyLog(vl a, int n) {
  vl c = conv(polyDer(a), polyInv(a, n));
  c.resize(n - 1); return polyInt(c);
}
vl polyExp(vl a, int n) {
  vl b = {1};
  for (int m = 1; m < n; m *= 2) {
    vl l = polyLog(b, 2 * m), f(2 * m);
    rep(i,0,2*m) f[i] = ((i<sz(a) ? a[i] : 0)-l[i]+mod) % mod;
    f[0] = (f[0] + 1) % mod;
    b = conv(b, f); b.resize(2 * m);
  }
  b.resize(n); return b;
}
vl polyPow(vl a, ll k, int n) { // a^k mod x^n, k >= 0
  int z = 0;
  while (z < sz(a) && !a[z]) z++;
  vl r(n);
  if (!k) { r[0] = n > 0; return r; }
  if (z == sz(a) || z > (n - 1) / k) return r; // z * k >= n
  int m = n - (int)(z * k);
  ll c = a[z], ci = modpow(c, mod - 2);
  vl b(a.begin() + z, a.end());
  for (ll& x : b) x = x * ci % mod;
  b = polyLog(b, m); // a^k = c^k x^(zk) exp(k log b)
  for (ll& x : b) x = x * (k % mod) % mod;
  b = polyExp(b, m);
  ll ck = modpow(c, k);
  rep(i,0,m) r[z * k + i] = b[i] * ck % mod;
  return r;
}
vl polySqrt(vl a, int n) { // a[0] = 1
  return polyPow(a, (mod + 1) / 2, n);
}
pair<vl, vl> polyDivMod(vl a, vl b) {
```

```
  int n = sz(a), m = sz(b);
  if (n < m) return {{}, a};
  vl ra(a.rbegin(), a.rend()), rb(b.rbegin(), b.rend());
  vl q = conv(ra, polyInv(rb, n - m + 1)), r = b;
  q.resize(n - m + 1), reverse(all(q));
  r = conv(b, q);
  rep(i,0,m-1) r[i] = (a[i] - r[i] + mod) % mod;
  r.resize(m - 1);
  return {q, r};
}
```

Number theory (5)

5.1 Modular arithmetic

ModularArithmetic.h

286b7b, 52 lines

Description: Modular integers, `mint<mod>`: $+ - */$, the compound forms, `++`, `--`, unary minus, comparisons, input and output, `fpow(a, p)` and `inverse(a)` (Fermat: needs a prime *mod*). $mod < 2^{30}$ (e.g. $10^9 + 7$ or 998244353) so that the sum of two values fits an `int`; `(int)a` is the value in $[0, mod)$. **Time:** $\mathcal{O}(\log p)$ for `fpow`
Usage: `mi a = 5, b = 7; cout << a / b << ' ' << fpow(a, 100); vmi v(n);`

```
const int M = 1e9 + 7; // prime
template<int mod> struct mint {
  int v;
  explicit operator int() const { return v; }
  mint() : v(0) {}
  mint(ll x) : v((int)(x % mod)) { if (v < 0) v += mod; }
  bool operator==(mint o) const { return v == o.v; }
  friend bool operator!=(mint a, mint b) { return !(a == b); }
  friend bool operator<(mint a, mint b) { return a.v < b.v; }
  friend istream& operator>>(istream& is, mint& a) {
    ll x; is >> x; a = mint(x); return is;
  }
  friend ostream& operator<<(ostream& os, mint a) {
    return os << (int)a;
  }
  mint& operator+=(mint o) {
    if ((v += o.v) >= mod) v -= mod;
    return *this;
  }
  mint& operator-=(mint o) {
    if ((v -= o.v) < 0) v += mod;
    return *this;
  }
  mint& operator*=(mint o) {
    v = (int)((ll)v * o.v % mod);
    return *this;
  }
  mint& operator/=(mint o) { return *this *= inverse(o); }
  friend mint fpow(mint a, ll p) { // p >= 0
    mint r = 1;
    for (; p; p /= 2, a *= a) if (p & 1) r *= a;
    return r;
  }
  friend mint inverse(mint a) {
    assert(a.v); return fpow(a, mod - 2);
  }
  mint operator-() const { return mint(-v); }
  mint& operator++() { return *this += 1; }
  mint& operator--() { return *this -= 1; }
  mint operator++(signed) {
    mint r = *this; ++*this; return r;
  }
  mint operator--(signed) {
    mint r = *this; --*this; return r;
  }
  friend mint operator+(mint a, mint b) { return a += b; }
  friend mint operator-(mint a, mint b) { return a -= b; }
  friend mint operator*(mint a, mint b) { return a *= b; }
  friend mint operator/(mint a, mint b) { return a /= b; }
};
using mi = mint<M>;
using vmi = vector<mi>;
```

ModInverse.h

6f684f, 3 lines

Description: Pre-computation of modular inverses. Assumes LIM $\leq$ mod and that mod is a prime.

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

ModPow.h

b83e45, 8 lines

```
const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
  ll ans = 1;
  for (; e; b = b * b % mod, e /= 2)
    if (e & 1) ans = ans * b % mod;
  return ans;
}
```

ModLog.h

c040b8, 11 lines

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used to calculate the order of a. **Time:** $\mathcal{O}\left(\sqrt{m}\right)$

```
ll modLog(ll a, ll b, ll m) {
  ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
  unordered_map<ll, ll> A;
  while (j <= n && (e = f = e * a % m) != b % m)
    A[e * b % m] = j++;
  if (e == b % m) return j;
  if (__gcd(m, e) == __gcd(m, b))
    rep(i,2,n+2) if (A.count(e = e * f % m))
      return n * i - A[e];
  return -1;
}
```

ModSum.h

5c5bc5, 16 lines

Description: Sums of mod'ed arithmetic progressions.
`modsum(to, c, k, m)` $= \sum_{i=0}^{to-1} (ki + c)\%m$. `divsum` is similar but for floored division. **Time:** $\log(m)$, with a large constant.

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
  ull res = k / m * sumsq(to) + c / m * to;
  k %= m; c %= m;
  if (!k) return res;
  ull to2 = (to * k + c) / m;
  return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}

ll modsum(ull to, ll c, ll k, ll m) {
  c = ((c % m) + m) % m;
  k = ((k % m) + m) % m;
  return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

bbbd8f, 11 lines

Description: Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$. **Time:** $\mathcal{O}(1)$ for `modmul`, $\mathcal{O}(\log b)$ for `modpow`

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
  ll ret = a * b - M * ull(1.L / M * a * b);
  return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
  ull ans = 1;
  for (; e; b = modmul(b, b, mod), e /= 2)
    if (e & 1) ans = modmul(ans, b, mod);
  return ans;
}
```

ModSqrt.h

"ModPow.h" 19a793, 24 lines

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution). **Time:** $\mathcal{O}\left(\log^2 p\right)$ worst case, $\mathcal{O}(\log p)$ for most p

```
ll sqrt(ll a, ll p) {
  a %= p; if (a < 0) a += p;
  if (a == 0) return 0;
  assert(modpow(a, (p-1)/2, p) == 1); // else no solution
  if (p % 4 == 3) return modpow(a, (p+1)/4, p);
  // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
  ll s = p - 1, n = 2;
  int r = 0, m;
  while (s % 2 == 0)
    ++r, s /= 2;
  while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
  ll x = modpow(a, (s + 1) / 2, p);
  ll b = modpow(a, s, p), g = modpow(n, s, p);
  for (;; r = m) {
    ll t = b;
    for (m = 0; m < r && t != 1; ++m)
      t = t * t % p;
    if (m == 0) return x;
    ll gs = modpow(g, 1LL << (r - m - 1), p);
    g = gs * gs % p;
    x = x * gs % p;
    b = b * g % p;
  }
}
```

PrimitiveRoot.h

"ModMulLL.h" 6d4b61, 15 lines

Description: Smallest primitive root of the prime p ($p \leq 7 \cdot 10^{18}$, but $p - 1$ is factored by trial division, so $p \lesssim 10^{12}$; use `Factor` beyond). A primitive root g has order $p - 1$; e.g. 998244353 has $g = 3$, $10^9 + 7$ has $g = 5$. **Time:** $\mathcal{O}\left(\sqrt{p} + \log^2 p\right)$ expected

```
ull primitiveRoot(ull p) {
  if (p == 2) return 1;
  vector<ull> f;
  ull m = p - 1;
  for (ull d = 2; d * d <= m; d++) if (m % d == 0) {
    f.push_back(d);
    while (m % d == 0) m /= d;
  }
  if (m > 1) f.push_back(m);
  for (ull g = 2;; g++) {
    bool ok = 1;
    for (ull q : f) ok &= modpow(g, (p - 1) / q, p) != 1;
    if (ok) return g;
  }
}
```

5.2 Primality

FastEratosthenes.h

25a76b, 20 lines

Description: Prime sieve for generating all primes smaller than LIM. **Time:** LIM=1e9 $\approx$ 1.5s

```
const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
  const int S = (int)round(sqrt(LIM)), R = LIM / 2;
  vi pr = {2}, sieve(S+1); pr.reserve((int)(LIM/log(LIM)*1.1));
  vector<pii> cp;
  for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
    cp.push_back({i, i * i / 2});
    for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
  }
  for (int L = 1; L <= R; L += S) {
    array<bool, S> block{};
    for (auto &[p, idx] : cp)
      for (int i=idx; i < S+L; idx = (i+=p)) block[i-L] = 1;
    rep(i,0,min(S, R - L))
      if (!block[i]) pr.push_back((L + i) * 2 + 1);
  }
  for (int i : pr) isPrime[i] = 1;
  return pr;
}
```

MillerRabin.h

"ModMulLL.h" 60dcd1, 12 lines

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly. **Time:** 7 times the complexity of $a^b \mod c$.

```
bool isPrime(ull n) {
  if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
  ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
      s = __builtin_ctzll(n-1), d = n >> s;
  for (ull a : A) {   // ^ count trailing zeroes
    ull p = modpow(a%n, d, n), i = s;
    while (p != 1 && p != n - 1 && a % n && i--)
      p = modmul(p, p, n);
    if (p != n-1 && i != s) return 0;
  }
  return 1;
}
```

Factor.h

"ModMulLL.h", "MillerRabin.h" d8d98d, 18 lines

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}). **Time:** $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

```
ull pollard(ull n) {
  ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
  auto f = [&](ull x) { return modmul(x, x, n) + i; };
  while (t++ % 40 || __gcd(prd, n) == 1) {
    if (x == y) x = ++i, y = f(x);
    if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
    x = f(x), y = f(f(y));
  }
  return __gcd(prd, n);
}
vector<ull> factor(ull n) {
  if (n == 1) return {};
  if (isPrime(n)) return {n};
  ull x = pollard(n);
  auto l = factor(x), r = factor(n / x);
  l.insert(l.end(), all(r));
  return l;
}
```

5.3 Divisibility

euclid.h

33ba8f, 5 lines

Description: Finds two integers x and y, such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If a and b are coprime, then x is the inverse of $a \pmod b$.

```
ll euclid(ll a, ll b, ll &x, ll &y) {
  if (!b) return x = 1, y = 0, a;
  ll d = euclid(b, a % b, y, x);
  return y -= a/b * x, d;
}
```

CRT.h

"euclid.h" 04d93a, 7 lines

Description: Chinese Remainder Theorem.
crt(a, m, b, n) computes x such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \le x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.
Time: $\log(n)$

```
ll crt(ll a, ll m, ll b, ll n) {
  if (n > m) swap(a, b), swap(m, n);
  ll x, y, g = euclid(m, n, x, y);
  assert((a - b) % g == 0); // else no solution
  x = (b - a) % n * x % n / g * m + a;
  return x < 0 ? x + m*n/g : x;
}
```

ExLucas.h

"euclid.h" 22dc2e, 42 lines

Description: Binomial $\binom{n}{k} \mod m$ for any $m < 2^{31}$ (extended Lucas). Per prime power $q = p^a$: $n!$ with factors p removed (product of units mod q is -1, or $+1$ if $p = 2, a \ge 3$) and $v_p(n!)$ by Legendre; then CRT with $c \equiv [q]$. Requires $n \le mx$; tables have size $\min(q, mx+1)$. **Time:** $\mathcal{O}\left(\sqrt{m} + \omega(m) \cdot mx\right)$ build, $\mathcal{O}\left(\omega(m) \log n\right)$ per query.
Usage: BinomMod C(m, maxn); C(n, k);

```
struct BinomPP {
  ll p, q, c, a = 0; vector<ll> f;
  ll inv(ll b) { ll x, y; euclid(b, q, x, y); return (x % q + q
      ) % q; }
  BinomPP(ll p, ll q, ll mx, ll m) : p(p), q(q), f(min(q, mx +
      1), 1) {
    rep(i,1,sz(f)) f[i] = f[i-1] * (i % p ? i : 1) % q;
    c = m / q * inv(m / q % q) % m;
    for (ll t = q; t > 1; t /= p) a++;
  }
  ll nu(ll n) { ll e = 0; while (n /= p) e += n; return e; } //
       v_p(n!)
  ll fact(ll n) { // n! / p^nu(n) mod q
    ll r = 1;
    for (; n; n /= p) {
      if ((p != 2 || q <= 4) && n / q % 2) r = q - r;
      r = r * f[n % q] % q;
    }
    return r;
  }
  ll C(ll n, ll k) {
    ll e = nu(n) - nu(k) - nu(n - k), r;
    if (e >= a) return 0;
    for (r = fact(n) * inv(fact(k) * fact(n - k) % q) % q; e
        --;) r = r * p % q;
    return r;
  }
};

struct BinomMod {
  ll m; vector<BinomPP> v;
  BinomMod(ll m, ll mx) : m(m) {
    for (ll p = 2, x = m; x > 1; p++) {
      if (p * p > x) p = x;
      ll q = 1;
      while (x % p == 0) x /= p, q *= p;
      if (q > 1) v.emplace_back(p, q, mx, m);
    }
  }
  ll operator()(ll n, ll k) {
    if (k < 0 || k > n) return 0;
    ll r = 0;
    for (auto& b : v) r = (r + b.C(n, k) * b.c) % m;
    return r;
  }
};
```

5.3.1 Bézout's identity

For $a \neq 0$, $b \neq 0$, then $d = gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

$ax + by = c$ is solvable iff $g = \gcd(a, b) \mid c$: take $(x_0, y_0) = (x_g, y_g) \cdot c/g$ from euclid, then $x = x_0 + \frac{b}{g}t$, $y = y_0 - \frac{a}{g}t$. For $a, b > 0$, $x \in [L, R]$ means $t \in [\lceil (L - x_0)g/b \rceil, \lfloor (R - x_0)g/b \rfloor]$ and $y \in [L', R']$ means $t \in [\lceil (y_0 - R')g/a \rceil, \lfloor (y_0 - L')g/a \rfloor]$: intersect the ranges (careful with floor division of negatives). $x + y$ changes by $(b - a)/g$ per step of t, so it is minimal at an end of the range.

phiFunction.h

cf7d6d, 8 lines

Description: *Euler's* ϕ function is defined as $\phi(n) :=$ # of positive integers $\le n$ that are coprime with n. $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} ... p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1 - 1} ... (p_r - 1)p_r^{k_r - 1}$. $\phi(n) = n \cdot \prod_{p|n}(1 - 1/p)$.
$\sum_{d|n} \phi(d) = n$, $\sum_{1 \le k \le n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$
Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.
Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod p$ $\forall a$.

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
  rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
  for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
    for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

5.3.2 Garner's algorithm

CRT for pairwise coprime $m_0, \ldots, m_{k-1}$ (for two moduli see crt): write $x = x_0 + x_1 m_0 + x_2 m_0 m_1 + \cdots + x_{k-1} m_0 \cdots m_{k-2}$ with $0 \le x_i < m_i$. Then $x_i = \left(a_i - x_0 - x_1 m_0 - \cdots - x_{i-1} m_0 \cdots m_{i-2}\right)\left(m_0 \cdots m_{i-1}\right)^{-1} \mod m_i$, in $O(k^2)$ with the inverses $m_j^{-1} \mod m_i$ precomputed:

```
for i: t = a[i];
  for j < i: t = (t-x[j])
    * inv(m[j], m[i]) % m[i];
  x[i] = t;
```

Then $x \bmod M$ for any M by Horner (e.g. a convolution result mod M from three NTT primes):

```
r = x[k-1]; for i = k-2..0:
  r = (r*m[i] + x[i]) % M;
```

5.3.3 Exponents

Generalized Euler: $a^b \equiv a^{(b \bmod \phi(m))+\phi(m)} \pmod m$ for every a and every $b \geq \log_2 m$ (use it for a^{b^c} and power towers). Lifting the exponent: for an odd prime p with $p \mid x-y$ and $p \nmid xy$,
$v_p(x^n-y^n) = v_p(x-y)+v_p(n)$; if n is odd and $p \mid x+y$,
$v_p(x^n+y^n) = v_p(x+y)+v_p(n)$. For $p=2$ and odd x, y:
$v_2(x^n-y^n) = v_2(x-y)$ for odd n, and
$v_2(x-y)+v_2(x+y)+v_2(n)-1$ for even n (so $v_2(x-y)+v_2(n)$ if $4 \mid x-y$).

5.4 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2-n^2),\ \ b = k \cdot (2mn),\ \ c = k \cdot (m^2+n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

5.5 Primes

$p = 962592769$ is such that $2^{21} \mid p-1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a, except for $p=2, a>2$, and there are $\phi(\phi(p^a))$ many. For $p=2, a>2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

5.6 Floor blocks

$\lfloor n/i \rfloor$ takes $O(\sqrt{n})$ distinct values; the blocks $[l, r]$ with equal $\lfloor n/i \rfloor$ are:

```
for (l = 1; l <= n; l = r + 1) {
  r = n / (n / l); ... }
```

$\lfloor \lfloor n/a \rfloor / b \rfloor = \lfloor n/(ab) \rfloor$, and
$\sum_{i=1}^{n} \lfloor n/i \rfloor = 2\sum_{i \leq \lfloor \sqrt{n} \rfloor} \lfloor n/i \rfloor - \lfloor \sqrt{n} \rfloor^2$.

Lucy.h — 328402, 20 lines

Description: Prime counting and prime sums for all $v = \lfloor n/i \rfloor$ and all $v \leq \sqrt{n}$. `f(p)` is a completely multiplicative function at a prime (`1` counts, `p` sums, p^k power sums) and `g(v)` $= f(2) + \cdots + f(v)$ in closed form; the type of `g(v)` is the type of the result (use `ull` to sum modulo 2^{64}). `L(v)` is then $\sum_{p \leq v} f(p)$ for such a v. **Time:** $\mathcal{O}\left(n^{3/4}\right)$, about 0.4 s for $n = 10^{11}$

Usage: `Lucy L(n, [](ll) { return 1LL; }, [](ll v) { return v - 1; }); // L(n) = pi(n)`

```
template<class F, class G> struct Lucy {
  typedef decltype(declval<G>()(0LL)) T;
  ll n, s; vector<T> lo, hi;
  Lucy(ll n, F f, G g) : n(n), s((ll)sqrtl((long double)n)),
      lo(s + 2), hi(s + 2) {
    while (s * s > n) s--;
    while ((s + 1) * (s + 1) <= n) s++;
    rep(i,1,s+1) lo[i] = g(i), hi[i] = g(n / i);
    for (ll p = 2; p <= s; p++) if (lo[p] != lo[p - 1]) {
      T fp = f(p), pre = lo[p - 1];
      for (ll i = 1; i <= s && n / i >= p * p; i++) {
        ll d = i * p;
        hi[i] -= fp * ((d <= s ? hi[d] : lo[n / d]) - pre);
      }
      for (ll v = s; v >= p * p; v--)
        lo[v] -= fp * (lo[v / p] - pre);
    }
  }
  T operator()(ll v) { return v <= s ? lo[v] : hi[n / v]; }
};
```

DuSieve.h — a5bf54, 39 lines

Description: Prefix sums of ϕ (128 bit: $\Phi(10^{10}) \approx 3 \cdot 10^{19}$) and μ for all $v = \lfloor n/i \rfloor$ and all $v \leq B = n^{2/3}$, from a sieve up to B and $S_f(v) = H(v) - \sum_{d \geq 2} S_f(\lfloor v/d \rfloor)$ for $f * 1 = h$ (H the prefix sums of h: $v(v+1)/2$ for ϕ, 1 for μ). The same recurrence $S_f(v) = (H(v) - \sum_{d \geq 2} g(d) S_f(\lfloor v/d \rfloor))/g(1)$ handles any $f * g = h$ with known prefix sums of g and h. Memory is also $O(n^{2/3})$. **Time:** $\mathcal{O}\left(n^{2/3}\right)$, about 0.3 s for $n = 10^{10}$

Usage: `Du D(n); D.phi(n); D.mu(n); // also D.phi(n / 3)`

```
struct Du {
  typedef __int128 L;
  ll n, B; vector<ll> sp, sm, bm; vector<L> bp;
  Du(ll n) : n(n), B(max<ll>(10, (ll)cbrtl((long double)n) *
      (ll)cbrtl((long double)n))), sp(B + 1), sm(B + 1) {
    vi pr, phi(B + 1), mu(B + 1);
    phi[1] = mu[1] = 1;
    rep(i,2,B+1) {
      if (!phi[i])
        pr.push_back((int)i), phi[i] = (int)i - 1, mu[i] = -1;
      for (int p : pr) {
        if ((ll)i * p > B) break;
        if (i % p) {
          phi[i * p] = phi[i] * (p - 1), mu[i * p] = -mu[i];
        } else {
          phi[i * p] = phi[i] * p, mu[i * p] = 0;
          break;
        }
      }
    }
    rep(i,1,B+1) {
      sp[i] = sp[i-1] + phi[i], sm[i] = sm[i-1] + mu[i];
    }
    ll K = n / B;
    bp.resize(K + 1), bm.resize(K + 1);
    for (ll i = K; i >= 1; i--) {
      ll v = n / i, m = 1; L p = (L)v * (v + 1) / 2;
      for (ll l = 2, r; l <= v; l = r + 1) {
        r = v / (v / l);
        ll d = i * l; // v / l = n / d
        p -= (L)(r - l + 1) * (d <= K ? bp[d] : (L)sp[n / d]);
        m -= (r - l + 1) * (d <= K ? bm[d] : sm[n / d]);
      }
      bp[i] = p, bm[i] = m;
    }
  }
  L phi(ll v) { return v <= B ? (L)sp[v] : bp[n / v]; }
  ll mu(ll v) { return v <= B ? sm[v] : bm[n / v]; }
};
```

5.7 Estimates

$\sum_{d|n} d = O(n \log \log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

5.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

Other useful formulas/forms:

$\sum_{d|n} \mu(d) = [n = 1]$ (very useful)

$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n) g(d)$

$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

IntPerm.h — 558085, 18 lines

Description: Permutation of $0, \ldots, n-1 \leftrightarrow$ integer in $[0, n!)$: `permToInt` is the rank of the permutation in lexicographic order and `intToPerm(r, n)` is the `r`'th permutation (0-indexed), its exact inverse. Order preserving. Exact for $n \leq 20$. For a permutation whose size is not fixed, see `radixToPerm`. **Time:** $\mathcal{O}(n)$ and $\mathcal{O}\left(n^2\right)$

Usage: `intToPerm(0, 3) // {0, 1, 2}, intToPerm(5, 3) // {2, 1, 0}`

```
ll permToInt(vi& v) { // rank in lexicographic order
  ll use = 0, r = 0;
  int n = sz(v);
  rep(i,0,n) {
    int x = v[i];
    r = r * (n - i) + x
      - __builtin_popcountll(use & ((1LL << x) - 1));
    use |= 1LL << x;
  }
  return r;
}
vi intToPerm(ll r, int n) { // inverse: the r'th permutation
  vi c(n), s(n), v(n);
  iota(all(s), 0);
  for (int i = n; i--; r /= n - i) c[i] = (int)(r % (n - i));
  rep(i,0,n) v[i] = s[c[i]], s.erase(s.begin() + c[i]);
  return v;
}
```

6.1.2 Cycles

Let $g_S(n)$ be the number of n-permutations whose cycle lengths all belong to the set S. Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp\left(\sum_{n \in S} \frac{x^n}{n}\right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1)+D(n-2)) = nD(n-1)+(-1)^n = \left\lfloor \frac{n!}{e} \right\rceil$$

6.1.4 Burnside's lemma

Given a group G of symmetries and a set X, the number of elements of X *up to symmetry* equals

$$\frac{1}{|G|}\sum_{g\in G}|X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts "configurations" (of some sort) of length n, we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n}\sum_{k=0}^{n-1} f(\gcd(n,k)) = \frac{1}{n}\sum_{k|n} f(k)\phi(n/k).$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1,\ p(n) = \sum_{k\in\mathbb{Z}\setminus\{0\}} (-1)^{k+1} p(n-k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	∼2e5	∼2e8

6.2.2 Lucas' Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + ... + n_1 p + n_0$ and $m = m_k p^k + ... + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^{k} \binom{n_i}{m_i} \pmod p$.

Corollaries: $p \nmid \binom{n}{m} \iff m_i \le n_i\ \forall i$. In particular, $\binom{n}{m}$ is odd $\iff$ `(m & n) == m`. The number of $m \in [0,n]$ with $p \nmid \binom{n}{m}$ is $\prod_i (n_i+1)$ ($= 2^{\text{popcount}(n)}$ for $p = 2$).

6.2.3 Binomials

multinomial.h — a0a312, 5 lines

Description: Computes $\binom{k_1+\cdots+k_n}{k_1,k_2,\ldots,k_n} = \frac{(\sum k_i)!}{k_1!k_2!\ldots k_n!}$.

```
ll multinomial(vi& v) {
  ll c = 1, m = v.empty() ? 1 : v[0];
  rep(i,1,sz(v)) rep(j,0,v[i]) c = c * ++m / (j+1);
  return c;
}
```

6.2.4 Radix conversion

RadixConversion.h — e542fb, 44 lines

Description: Bijective base conversion: digits in $[0,a)$ to digits in $[0,b)$ ($2 \le a,b < 2^{31}$), most significant first. The k-th sequence in (length, lexicographic) order in base a maps to the k-th in base b (empty to empty), so `radixconv(radixconv(x, a, b), b, a) == x` with no length or leading zeros to store; the result has about $|x|\log_b a$ digits. `radixToPerm(x, a)` does the same onto all permutations of $0,\ldots,n-1$ (n comes from the data: 2000 bits give 296 elements), in (size, lexicographic) order; `permToRadix(p, a)` is its inverse ($O(|y|^2)$, y the result). Fixed size: `intToPerm`, or `radixToPerm` on the base $2^{31}-1$ digits of $r + 0! + \cdots + (n-1)!$ (one digit for $n \le 12$, two up to 20). **Time:** $\mathcal{O}(|x|\cdot|y|)$

```
// y = y * m + c in bijective mixed radix: digit i (least
// significant first) is in [1, r(i)]
template<class F> void mulAdd(vector<ll>& y, ll m, ll c, F r) {
  rep(i,0,sz(y)) {
    ll t = y[i] * m + c, R = r(i);
    y[i] = (t - 1) % R + 1, c = (t - 1) / R;
  }
  while (c) {
    ll R = r(sz(y));
    y.push_back((c - 1) % R + 1), c = (c - 1) / R;
  }
}
vi radixconv(const vi& x, int a, int b) {
  vector<ll> y; // bijective base b, least significant first
  for (int d : x) mulAdd(y, a, d + 1, [&](int) { return b; });
  vi r;
  for (int i = sz(y); i--;) r.push_back((int)(y[i] - 1));
  return r;
}
vi radixToPerm(const vi& x, int a) {
  vector<ll> y; // bijective factorial base
  for (int d : x)
    mulAdd(y, a, d + 1, [](int i) { return i + 1; });
  int n = sz(y);
  vi s(n), p(n);
  iota(all(s), 0);
  rep(i,0,n) {
    int c = (int)y[n - 1 - i] - 1;
    p[i] = s[c], s.erase(s.begin() + c);
  }
  return p;
}
vi permToRadix(const vi& p, int a) {
  int n = sz(p);
  vector<ll> z; // bijective base a
  rep(k,0,n) {
    int c = 0;
    rep(j,k+1,n) c += p[j] < p[k];
    mulAdd(z, n - k, c + 1, [&](int) { return a; });
  }
  vi x;
  for (int i = sz(z); i--;) x.push_back((int)z[i] - 1);
  return x;
}
```

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t-1}$ (FFT-able).
$B[0,\ldots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \ldots]$

Sums of powers:

$$\sum_{i=1}^{n} n^m = \frac{1}{m+1}\sum_{k=0}^{m}\binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^{\infty} f(i) = \int_m^\infty f(x)dx - \sum_{k=1}^{\infty}\frac{B_k}{k!}f^{(k-1)}(m)$$

$$\approx \int_m^\infty f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n,k) = c(n-1,k-1) + (n-1)c(n-1,k),\ c(0,0) = 1$$
$$\textstyle\sum_{k=0}^{n} c(n,k)x^k = x(x+1)\ldots(x+n-1)$$

$c(8,k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$
$c(n,2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \ldots$

6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \ge j$, k j:s s.t. $\pi(j) > j$.

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^{k}(-1)^j\binom{n+1}{j}(k+1-j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!}\sum_{j=0}^{k}(-1)^{k-j}\binom{k}{j}j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \ldots$. For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod p$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i: $n_1 n_2 \cdots n_k n^{k-2}$
with degrees d_i: $(n-2)!/((d_1-1)!\cdots(d_n-1)!)$

6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1,\ C_{n+1} = \frac{2(2n+1)}{n+2}C_n,\ C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \ldots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

6.4 Generating functions

6.4.1 Dictionary

OGF $A(x) = \sum_n a_n x^n$; EGF $\hat{A}(x) = \sum_n a_n x^n/n!$ (labeled objects), so $a_n = n!\,[x^n]\hat{A}$.

a_n	OGF	EGF
$a_n + b_n$	$A + B$	$\hat{A} + \hat{B}$
$\sum_i a_i b_{n-i}$	AB	
$\sum_i \binom{n}{i} a_i b_{n-i}$		$\hat{A}\hat{B}$
a_{n-1}	xA	$\int \hat{A}$
a_{n+1}	$(A - a_0)/x$	$\hat{A}'$
na_n	xA'	$x\hat{A}'$
$\sum_{i \le n} a_i$	$A/(1-x)$	

6.4.2 Common series

OGF: $\frac{1}{(1-x)^k} = \sum_n \binom{n+k-1}{k-1}x^n$, $\frac{x}{1-x-x^2} = \sum_n F_n x^n$, $\frac{1}{\sqrt{1-4x}} = \sum_n \binom{2n}{n}x^n$, Catalan $C = \frac{1-\sqrt{1-4x}}{2x} = 1 + xC^2$, partitions $\prod_{k\ge1}\frac{1}{1-x^k}$.

EGF: $\frac{1}{1-x}$ (permutations), $\frac{e^{-x}}{1-x}$ (derangements), e^{e^x-1} (Bell), $e^{x+x^2/2}$ (involutions), $\frac{(e^x-1)^k}{k!}$ $(S(n,k))$, $\frac{(-\ln(1-x))^k}{k!}$ $(c(n,k))$, $\frac{x}{e^x-1}$ (Bernoulli).

6.4.3 Counting structures

Labeled, F the EGF of one kind of structure $(F(0) = 0)$: sequence $\frac{1}{1-F}$, set e^F, cycle $\ln\frac{1}{1-F}$, one marked element xF', pair $F \cdot G$. E.g. permutations are sets of cycles $(e^{\ln\frac{1}{1-x}} = \frac{1}{1-x})$, set partitions are sets of non-empty sets, rooted trees $T = xe^T$ give n^{n-1}; all cycle lengths in S: $\exp\left(\sum_{k\in S} x^k/k\right)$.

Unlabeled, F the OGF with f_k objects of size k: sequence $\frac{1}{1-F}$; multiset $\prod_k (1-x^k)^{-f_k} = \exp\sum_{j\ge1} F(x^j)/j$ (Euler transform); set $\prod_k (1+x^k)^{f_k} = \exp\sum_{j\ge1}(-1)^{j+1}F(x^j)/j$; rooted trees $T = x\exp\sum_{j\ge1} T(x^j)/j$ $(1, 1, 2, 4, 9, 20, 48, \ldots)$.

6.4.4 Computing

P/Q with $Q(0) = 1$: $a_n = \sum_i c_i a_{n-i}$ for $Q = 1 - \sum_i c_i x^i$ (see `BostanMori`, `BerlekampMassey`); partial fractions give closed forms.

Lagrange inversion: if $f = x\varphi(f)$ with $\varphi(0) \neq 0$, then $[x^n]f^k = \frac{k}{n}[x^{n-k}]\varphi^n$ and $[x^n]H(f) = \frac{1}{n}[x^{n-1}]H'\varphi^n$.

$b = e^F$ with $F(0) = 0$: $nb_n = \sum_{k=1}^n k f_k b_{n-k}$ in $O(n^2)$; in $O(n \log n)$ with `polyExp` (also `polyLog`, `polyInv`).

Store EGF coefficients as $a_n/n!$ and a product is a plain `conv`; converting to the sequence a_n multiplies coefficient n by $n!$.

Graph (7)

7.1 Network flow

PushRelabel.h — 0ae1d4, 48 lines

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only. **Time:** $\mathcal{O}\left(V^2\sqrt{E}\right)$

```
struct PushRelabel {
  struct Edge {
    int dest, back;
    ll f, c;
  };
  vector<vector<Edge>> g;
  vector<ll> ec;
  vector<Edge*> cur;
  vector<vi> hs; vi H;
  PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}

  void addEdge(int s, int t, ll cap, ll rcap=0) {
    if (s == t) return;
    g[s].push_back({t, sz(g[t]), 0, cap});
    g[t].push_back({s, sz(g[s])-1, 0, rcap});
  }

  void addFlow(Edge& e, ll f) {
    Edge &back = g[e.dest][e.back];
    if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
    e.f += f; e.c -= f; ec[e.dest] += f;
    back.f -= f; back.c += f; ec[back.dest] -= f;
  }
  ll calc(int s, int t) {
    int v = sz(g); H[s] = v; ec[t] = 1;
    vi co(2*v); co[0] = v-1;
    rep(i,0,v) cur[i] = g[i].data();
    for (Edge& e : g[s]) addFlow(e, e.c);

    for (int hi = 0;;) {
      while (hs[hi].empty()) if (!hi--) return -ec[s];
      int u = hs[hi].back(); hs[hi].pop_back();
      while (ec[u] > 0)  // discharge u
        if (cur[u] == g[u].data() + sz(g[u])) {
          H[u] = 1e9;
          for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
            H[u] = H[e.dest]+1, cur[u] = &e;
          if (++co[H[u]], !--co[hi] && hi < v)
            rep(i,0,v) if (hi < H[i] && H[i] < v)
              --co[H[i]], H[i] = v + 1;
          hi = H[u];
        } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
          addFlow(*cur[u], min(ec[u], cur[u]->c));
        else ++cur[u];
    }
  }
  bool leftOfMinCut(int a) { return H[a] >= sz(g); }
};
```

MinCostMaxFlow.h — 85db88, 82 lines

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only. **Time:** $\mathcal{O}(FE\log(V))$ where F is max flow. $\mathcal{O}(VE)$ for setpi.

```
#pragma push_macro("int")
#undef int
#include <bits/extc++.h>
#pragma pop_macro("int")

const ll INF = numeric_limits<ll>::max() / 4;

struct MCMF {
  struct edge {
    int from, to, rev;
    ll cap, cost, flow;
  };
  int N;
  vector<vector<edge>> ed;
  vi seen;
  vector<ll> dist, pi;
  vector<edge*> par;

  MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}

  void addEdge(int from, int to, ll cap, ll cost) {
    if (from == to) return;
    ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
    ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
  }

  void path(int s) {
    fill(all(seen), 0);
    fill(all(dist), INF);
    dist[s] = 0; ll di;

    __gnu_pbds::priority_queue<pair<ll, int>> q;
    vector<decltype(q)::point_iterator> its(N);
    q.push({ 0, s });

    while (!q.empty()) {
      s = q.top().second; q.pop();
      seen[s] = 1; di = dist[s] + pi[s];
      for (edge& e : ed[s]) if (!seen[e.to]) {
        ll val = di - pi[e.to] + e.cost;
        if (e.cap - e.flow > 0 && val < dist[e.to]) {
          dist[e.to] = val;
          par[e.to] = &e;
          if (its[e.to] == q.end())
            its[e.to] = q.push({ -dist[e.to], e.to });
          else
            q.modify(its[e.to], { -dist[e.to], e.to });
        }
      }
    }
    rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
  }

  pair<ll, ll> maxflow(int s, int t) {
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
```

```
    ll fl = INF;
    for (edge* x = par[t]; x; x = par[x->from])
      fl = min(fl, x->cap - x->flow);

    totflow += fl;
    for (edge* x = par[t]; x; x = par[x->from]) {
      x->flow += fl;
      ed[x->to][x->rev].flow -= fl;
    }
  }
  rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
  return {totflow, totcost/2};
}

// If some costs can be negative, call this before maxflow:
void setpi(int s) { // (otherwise, leave this out)
  fill(all(pi), INF); pi[s] = 0;
  int it = N, ch = 1; ll v;
  while (ch-- && it--)
    rep(i,0,N) if (pi[i] != INF)
      for (edge& e : ed[i]) if (e.cap)
        if ((v = pi[i] + e.cost) < pi[e.to])
          pi[e.to] = v, ch = 1;
  assert(it >= 0); // negative cost cycle
}
};
```

Dinic.h

d7f0f1, 42 lines

Description: Flow algorithm with complexity $O(VE\log U)$ where $U = \max|\text{cap}|$. $O(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $O(\sqrt{V}E)$ for bipartite matching.

```
struct Dinic {
  struct Edge {
    int to, rev;
    ll c, oc;
    ll flow() { return max(oc - c, 0LL); } // if you need flows
  };
  vi lvl, ptr, q;
  vector<vector<Edge>> adj;
  Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
  void addEdge(int a, int b, ll c, ll rcap = 0) {
    adj[a].push_back({b, sz(adj[b]), c, c});
    adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
  }
  ll dfs(int v, int t, ll f) {
    if (v == t || !f) return f;
    for (int& i = ptr[v]; i < sz(adj[v]); i++) {
      Edge& e = adj[v][i];
      if (lvl[e.to] == lvl[v] + 1)
        if (ll p = dfs(e.to, t, min(f, e.c))) {
          e.c -= p, adj[e.to][e.rev].c += p;
          return p;
        }
    }
    return 0;
  }
  ll calc(int s, int t) {
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
      lvl = ptr = vi(sz(q));
      int qi = 0, qe = lvl[s] = 1;
      while (qi < qe && !lvl[t]) {
        int v = q[qi++];
        for (Edge e : adj[v])
          if (!lvl[e.to] && e.c >> (30 - L))
            q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
      }
      while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
  }
  bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s, only traversing edges with positive residual capacity.

GlobalMinCut.h

8b0e19, 21 lines

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix. **Time:** $\mathcal{O}\left(V^3\right)$

```
pair<int, vi> globalMinCut(vector<vi> mat) {
  pair<int, vi> best = {INT_MAX, {}};
  int n = sz(mat);
  vector<vi> co(n);
  rep(i,0,n) co[i] = {i};
  rep(ph,1,n) {
    vi w = mat[0];
    size_t s = 0, t = 0;
    rep(it,0,n-ph) { // O(V^2) -> O(E log V) with prio. queue
      w[t] = INT_MIN;
      s = t, t = max_element(all(w)) - w.begin();
      rep(i,0,n) w[i] += mat[t][i];
    }
    best = min(best, {w[t] - mat[t][t], co[t]});
    co[s].insert(co[s].end(), all(co[t]));
    rep(i,0,n) mat[s][i] += mat[t][i];
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
  }
  return best;
}
```

GomoryHu.h

"PushRelabel.h" 0418b3, 13 lines

Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path. **Time:** $\mathcal{O}\left(V\right)$ Flow Computations

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
  vector<Edge> tree;
  vi par(N);
  rep(i,1,N) {
    PushRelabel D(N); // Dinic also works
    for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
    tree.push_back({i, par[i], D.calc(i, par[i])});
    rep(j,i+1,N)
      if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
  }
  return tree;
}
```

7.2 Matching

HopcroftKarp.h

731cfb, 20 lines

Description: Bipartite matching. g: neighbours of each left vertex; r: all -1, size of the right side. Returns the matching size; $r[i]$ is the match of right vertex i, or -1. **Time:** $\mathcal{O}\left(E\sqrt{V}\right)$

```
int hopcroftKarp(vector<vi>& g, vi& r) {
  int n = sz(g), res = 0;
  vi l(n, -1), q(n), d(n);
  auto dfs = [&](auto f, int u) -> bool {
    int t = exchange(d[u], 0) + 1;
    for (int v : g[u])
      if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
        return l[u] = v, r[v] = u, 1;
    return 0;
  };
  for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
    rep(i,0,n) if (l[i] == -1) q[t++] = i, d[i] = 1;
    rep(i,0,t) for (int v : g[q[i]]) {
      if (r[v] == -1) f = 1;
      else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
    }
    if (!f) return res;
    rep(i,0,n) if (l[i] == -1) res += dfs(dfs, i);
  }
}
```

MinimumVertexCover.h

"HopcroftKarp.h" bfb654, 20 lines

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

```
vi cover(vector<vi>& g, int n, int m) {
  vi match(m, -1);
  int res = hopcroftKarp(g, match);
  vector<bool> lfound(n, true), seen(m);
  for (int it : match) if (it != -1) lfound[it] = false;
  vi q, cover;
  rep(i,0,n) if (lfound[i]) q.push_back(i);
  while (!q.empty()) {
    int i = q.back(); q.pop_back();
    lfound[i] = 1;
    for (int e : g[i]) if (!seen[e] && match[e] != -1) {
      seen[e] = true;
      q.push_back(match[e]);
    }
  }
  rep(i,0,n) if (!lfound[i]) cover.push_back(i);
  rep(i,0,m) if (seen[i]) cover.push_back(n+i);
  assert(sz(cover) == res);
  return cover;
}
```

WeightedMatching.h

8f41c7, 24 lines

Description: Min-cost bipartite matching that matches every left node, $N \leq M$. Takes cost[N][M] (cost[i][j]: L[i] with R[j]), returns (min cost, match) with L[i] matched to R[match[i]]. Negate costs for max cost. **Time:** $\mathcal{O}\left(N^2M\right)$

```
template<class T>
pair<T, vi> weightedMatching(vector<vector<T>> &C) {
  int i = sz(C), m = i ? sz(C[0]) : 0, c, s, r;
  vector<T> dist(m), pot(m);
  vi match(i), rev(m, -1), cols(m), prev(m);
  T d = 0, nd, cost = 0;
  while (i--) {
    rep(c,0,m) dist[c] = C[i][c], cols[c] = c, prev[c] = i;
    for (s = 0;;) {
      rep(j,s,m) {
        c = cols[j], nd = dist[c] - pot[c];
        if (j == s || d > nd) d = nd, swap(cols[s], cols[j]);
      }
      if ((r = rev[c = cols[s++]]) == -1) break;
      rep(j,0,m) if (dist[j] > (nd = C[r][j]-C[r][c]+dist[c]))
        dist[j] = nd, prev[j] = r;
    }
    cost += dist[c];
    while (s--) pot[cols[s]] = dist[cols[s]] - d;
    for (; r != i; swap(c, match[r]))
      r = rev[c] = prev[c];
```

```
  }
  return {cost, match};
}
```

GeneralMatching.h "../numerical/MatrixInverse-mod.h" cb1912, 40 lines

Description: Matching for general graphs. Fails with probability N/mod.
Time: $\mathcal{O}(N^3)$

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
  vector<vector<ll>> mat(N, vector<ll>(N)), A;
  for (pii pa : ed) {
    int a = pa.first, b = pa.second, r = rand() % mod;
    mat[a][b] = r, mat[b][a] = (mod - r) % mod;
  }

  int r = matInv(A = mat), M = 2*N - r, fi, fj;
  assert(r % 2 == 0);

  if (M != N) do {
    mat.resize(M, vector<ll>(M));
    rep(i,0,N) {
      mat[i].resize(M);
      rep(j,N,M) {
        int r = rand() % mod;
        mat[i][j] = r, mat[j][i] = (mod - r) % mod;
      }
    }
  } while (matInv(A = mat) != M);

  vi has(M, 1); vector<pii> ret;
  rep(it,0,M/2) {
    rep(i,0,M) if (has[i])
      rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
        fi = i; fj = j; goto done;
    } assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw,0,2) {
      ll a = modpow(A[fi][fj], mod-2);
      rep(i,0,M) if (has[i] && A[i][fj]) {
        ll b = A[i][fj] * a % mod;
        rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
      }
      swap(fi,fj);
    }
  }
  return ret;
}
```

7.3 DFS algorithms

SCC.h 76b5c9, 24 lines

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa. **Time:** $\mathcal{O}(E+V)$
Usage: `scc(graph, [&](vi& v) { ... })` visits all components in reverse topological order. `comp[i]` holds the component index of a node (a component only has edges to components with lower index). `ncomps` will contain the number of components.

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
  int low = val[j] = ++Time, x; z.push_back(j);
  for (auto e : g[j]) if (comp[e] < 0)
    low = min(low, val[e] ?: dfs(e,g,f));

  if (low == val[j]) {
    do {
      x = z.back(); z.pop_back();
      comp[x] = ncomps;
      cont.push_back(x);
    } while (x != j);
    f(cont); cont.clear();
    ncomps++;
  }
  return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
  int n = sz(g);
  val.assign(n, 0); comp.assign(n, -1);
  Time = ncomps = 0;
  rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

BiconnectedComponents.h c6b7c7, 32 lines

Description: Runs the callback on the edges of each biconnected component (any two of its nodes lie on a common cycle). A node can be in several components; an edge in none is a bridge. **Time:** $\mathcal{O}(E+V)$
Usage: `int eid = 0; ed.resize(N);`
`for each edge (a,b) {`
`ed[a].emplace_back(b, eid);`
`ed[b].emplace_back(a, eid++); }`
`bicomps([&](const vi& edgelist) {...});`

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
  int me = num[at] = ++Time, top = me;
  for (auto [y, e] : ed[at]) if (e != par) {
    if (num[y]) {
      top = min(top, num[y]);
      if (num[y] < me)
        st.push_back(e);
    } else {
      int si = sz(st);
      int up = dfs(y, e, f);
      top = min(top, up);
      if (up == me) {
        st.push_back(e);
        f(vi(st.begin() + si, st.end()));
        st.resize(si);
      }
      else if (up < me) st.push_back(e);
      else { /* e is a bridge */ }
    }
  }
  return top;
}

template<class F>
void bicomps(F f) {
  num.assign(sz(ed), 0);
  rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

BlockCutTree.h 2684bd, 25 lines

Description: Block-cut tree of an undirected graph (a forest if it is not connected). Nodes $0..n-1$ are the vertices; every biconnected component (a bridge is a component with 2 vertices) gets one more node, adjacent to its vertices. A vertex is a cut vertex iff it has more than one neighbour in the tree. Vertex w separates u and v iff it is a cut vertex on the tree path $u \dots v$.
Time: $\mathcal{O}(N+M)$

```
vector<vi> blockCut(vector<vi>& g) {
  int n = sz(g), T = 0;
  vi num(n), low(n), st;
  vector<vi> t(n);
  auto dfs = [&](auto&& self, int v, int p) -> void {
    num[v] = low[v] = ++T; st.push_back(v);
    for (int u : g[v]) if (u != p) {
      if (num[u]) low[v] = min(low[v], num[u]);
      else {
        self(self, u, v);
        low[v] = min(low[v], low[u]);
        if (low[u] >= num[v]) {
          int b = sz(t); t.emplace_back();
          for (int x = -1; x != u;) {
            x = st.back(); st.pop_back();
            t[b].push_back(x); t[x].push_back(b);
          }
          t[b].push_back(v); t[v].push_back(b);
        }
      }
    }
  };
  rep(v,0,n) if (!num[v]) dfs(dfs, v, -1);
  return t;
}
```

2sat.h 5f9706, 56 lines

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(!a||c)\&\&(d||!b)\&\&\dots$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (`~x`). **Time:** $\mathcal{O}(N+E)$, where N is the number of boolean variables, and E is the number of clauses.
Usage: `TwoSat ts(number of boolean variables);`
`ts.either(0, ~3); // Var 0 is true or var 3 is false`
`ts.setValue(2); // Var 2 is true`
`ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true`
`ts.solve(); // Returns true iff it is solvable`
`ts.values[0..N-1] holds the assigned values to the vars`

```
struct TwoSat {
  int N;
  vector<vi> gr;
  vi values; // 0 = false, 1 = true

  TwoSat(int n = 0) : N(n), gr(2*n) {}

  int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  }

  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  }
  void setValue(int x) { either(x, x); }

  void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }
```

```
  vi val, comp, z; int time = 0;
  int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
      low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
        values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
  }

  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
  }
};
```

EulerWalk.h

780b64, 15 lines

Description: Euler path/cycle, undirected or directed. Input: lists of (dest, global edge index); both directions of an undirected edge share the index. Returns the nodes of the walk (src at both ends for a cycle), or empty if there is none. Edge indices: add .second to s and ret. **Time:** $\mathcal{O}(V+E)$

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
  int n = sz(gr);
  vi D(n), its(n), eu(nedges), ret, s = {src};
  D[src]++; // to allow Euler paths, not just cycles
  while (!s.empty()) {
    int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
    if (it == end){ ret.push_back(x); s.pop_back(); continue; }
    tie(y, e) = gr[x][it++];
    if (!eu[e]) {
      D[x]--, D[y]++;
      eu[e] = 1; s.push_back(y);
    }}
  for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
  return {ret.rbegin(), ret.rend()};
}
```

7.4 Heuristics

MaximalCliques.h

b0d5b1, 12 lines

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique. **Time:** $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
  if (!P.any()) { if (!X.any()) f(R); return; }
  auto q = (P | X)._Find_first();
  auto cands = P & ~eds[q];
  rep(i,0,sz(eds)) if (cands[i]) {
    R[i] = 1;
    cliques(eds, f, P & eds[i], X & eds[i], R);
    R[i] = P[i] = 0; X[i] = 1;
  }
}
```

MaximumClique.h

e81d4b, 49 lines

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph. **Time:** Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

```
typedef vector<bitset<200>> vb;
struct Maxclique {
  double limit=0.025, pk=0;
  struct Vertex { int i, d=0; };
  typedef vector<Vertex> vv;
  vb e;
  vv V;
  vector<vi> C;
  vi qmax, q, S, old;
  void init(vv& r) {
    for (auto& v : r) v.d = 0;
    for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    sort(all(r), [](auto a, auto b) { return a.d > b.d; });
    int mxD = r[0].d;
    rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
  }
  void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
      if (sz(q) + R.back().d <= sz(qmax)) return;
      q.push_back(R.back().i);
      vv T;
      for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
      if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max<int>(sz(qmax)-sz(q)+1,1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
          int k = 1;
          auto f = [&](int i) { return e[v.i][i]; };
          while (any_of(all(C[k]), f)) k++;
          if (k > mxk) mxk = k, C[mxk + 1].clear();
          if (k < mnk) T[j++].i = v.i;
          C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k])
          T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
      } else if (sz(q) > sz(qmax)) qmax = q;
      q.pop_back(), R.pop_back();
    }
  }
  vi maxClique() { init(V), expand(V); return qmax; }
  Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
  }
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

7.5 Trees

BinaryLifting.h

bfce85, 25 lines

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself. **Time:** construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

```
vector<vi> treeJump(vi& P){
  int on = 1, d = 1;
  while(on < sz(P)) on *= 2, d++;
  vector<vi> jmp(d, P);
  rep(i,1,d) rep(j,0,sz(P))
    jmp[i][j] = jmp[i-1][jmp[i-1][j]];
  return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
  rep(i,0,sz(tbl))
    if(steps&(1<<i)) nod = tbl[i][nod];
  return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
  if (depth[a] < depth[b]) swap(a, b);
  a = jmp(tbl, a, depth[a] - depth[b]);
  if (a == b) return a;
  for (int i = sz(tbl); i--;) {
    int c = tbl[i][a], d = tbl[i][b];
    if (c != d) a = c, b = d;
  }
  return tbl[0][a];
}
```

LCA.h

"../data-structures/RMQ.h" 0f62fb, 21 lines

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected. **Time:** $\mathcal{O}(N \log N + Q)$

```
struct LCA {
  int T = 0;
  vi time, path, ret;
  RMQ<int> rmq;

  LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C,0,-1), ret)) {}
  void dfs(vector<vi>& C, int v, int par) {
    time[v] = T++;
    for (int y : C[v]) if (y != par) {
      path.push_back(v), ret.push_back(time[v]);
      dfs(C, y, v);
    }
  }

  int lca(int a, int b) {
    if (a == b) return a;
    tie(a, b) = minmax(time[a], time[b]);
    return path[rmq.query(a, b)];
  }
  //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

CompressTree.h

"LCA.h" 9775a0, 21 lines

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S|-1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself. **Time:** $\mathcal{O}(|S| \log |S|)$

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
  static vi rev; rev.resize(sz(lca.time));
  vi li = subset, &T = lca.time;
  auto cmp = [&](int a, int b) { return T[a] < T[b]; };
  sort(all(li), cmp);
  int m = sz(li)-1;
  rep(i,0,m) {
    int a = li[i], b = li[i+1];
    li.push_back(lca.lca(a, b));
  }
```

```
  sort(all(li), cmp);
  li.erase(unique(all(li)), li.end());
  rep(i,0,sz(li)) rev[li[i]] = i;
  vpi ret = {pii(0, li[0])};
  rep(i,0,sz(li)-1) {
    int a = li[i], b = li[i+1];
    ret.emplace_back(rev[lca.lca(a, b)], b);
  }
  return ret;
}
```

HLD.h

"../data-structures/LazySegTreeBlock.h", "../data-structures/LazySegTree.h"

3d7ef1, 46 lines

Description: Heavy-light decomposition: every path to the root has $O(\log n)$ light edges. Path and subtree updates and queries go to a `LazySeg` (edit its block for other operations): updates take its tag `L`, queries return its value `S`, all values start as `S()`. Takes the full adjacency list, root 0. `VALS_EDGES`: values on the edges instead of the nodes. **Time:** $\mathcal{O}\left((\log N)^2\right)$

```
template <bool VALS_EDGES> struct HLD {
  int N, tim = 0;
  vector<vi> adj;
  vi par, siz, rt, pos;
  LazySeg tree;
  HLD(vector<vi> adj_)
    : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1),
      rt(N),pos(N),tree(vector<S>(N)){ dfsSz(0); dfsHld(0); }
  void dfsSz(int v) {
    for (int& u : adj[v]) {
      adj[u].erase(find(all(adj[u]), v));
      par[u] = v;
      dfsSz(u);
      siz[v] += siz[u];
      if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
    }
  }
  void dfsHld(int v) {
    pos[v] = tim++;
    for (int u : adj[v]) {
      rt[u] = (u == adj[v][0] ? rt[v] : u);
      dfsHld(u);
    }
  }
  template <class B> void process(int u, int v, B op) {
    for (;; v = par[rt[v]]) {
      if (pos[u] > pos[v]) swap(u, v);
      if (rt[u] == rt[v]) break;
      op(pos[rt[v]], pos[v] + 1);
    }
    op(pos[u] + VALS_EDGES, pos[v] + 1);
  }
  void modifyPath(int u, int v, L x) {
    process(u, v, [&](int l, int r) { tree.upd(l, r, x); });
  }
  S queryPath(int u, int v) {
    S res = e();
    process(u, v, [&](int l, int r) {
        res = op(res, tree.query(l, r));
    });
    return res;
  }
  S querySubtree(int v) { // modifySubtree is similar
    return tree.query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
  }
};
```

CentroidDecomposition.h

a9f00e, 19 lines

Description: Centroid decomposition. `run(f)` calls `f(c)` once per centroid c; at that moment a DFS from c that skips `dead` vertices visits exactly the component of c (centroids of earlier calls are `dead`). `cpar` is the centroid tree (root has -1). Each vertex is in $O(\log N)$ components. **Time:** $\mathcal{O}(N \log N)$ plus the work done in `f`

Usage: `Centroid C(g); C.run([&](int c){ ... });`

```
struct Centroid {
  vector<vi> g; vi sub, cpar; vector<char> dead;
  Centroid(vector<vi> g) : g(g), sub(sz(g)), cpar(sz(g), -1),
       dead(sz(g)) {}
  int calc(int v, int p) {
    sub[v] = 1;
    for (int u : g[v]) if (u != p && !dead[u]) sub[v] += calc(u
        , v);
    return sub[v];
  }
  int find(int v, int p, int n) {
    for (int u : g[v]) if (u != p && !dead[u] && sub[u]*2 > n)
      return find(u, v, n);
    return v;
  }
  template<class F> void run(F&& f, int v = 0, int p = -1) {
    int c = find(v, -1, calc(v, -1));
    cpar[c] = p; f(c); dead[c] = 1;
    for (int u : g[c]) if (!dead[u]) run(f, u, c);
  }
};
```

DsuOnTree.h

933a26, 28 lines

Description: Answers a question about every subtree using one global structure. `add(v)` / `rem(v)` insert / remove vertex v (and only v) from it; `query(v)` is called when the structure holds exactly the vertices of the subtree of v. **Time:** $\mathcal{O}(N \log N)$ calls to add/rem

Usage: `DsuOnTree T(g, root);`
`T.run([&](int v){...}, [&](int v){...}, [&](int v){...});`

```
struct DsuOnTree {
  vector<vi> g; vi sub, big, tin, tout, ord; int tim = 0, root;
  DsuOnTree(vector<vi> g, int r = 0) : g(g), sub(sz(g)),
    big(sz(g), -1), tin(sz(g)), tout(sz(g)), ord(sz(g)),
    root(r) { init(r, -1); }
  void init(int v, int p) {
    sub[v] = 1; ord[tin[v] = tim++] = v;
    for (int u : g[v]) if (u != p) {
      init(u, v); sub[v] += sub[u];
      if (big[v] < 0 || sub[u] > sub[big[v]]) big[v] = u;
    }
    tout[v] = tim;
  }
  template<class A, class R, class Q>
  void go(int v, int p, bool keep, A& add, R& rem, Q& query) {
    for (int u : g[v]) if (u != p && u != big[v])
      go(u, v, 0, add, rem, query);
    if (big[v] >= 0) go(big[v], v, 1, add, rem, query);
    add(v);
    for (int u : g[v]) if (u != p && u != big[v])
      rep(i,tin[u],tout[u]) add(ord[i]);
    query(v);
    if (!keep) rep(i,tin[v],tout[v]) rem(ord[i]);
  }
  template<class A, class R, class Q> void run(A add, R rem, Q
       query) {
    go(root, -1, 1, add, rem, query);
  }
};
```

LinkCutTree.h

0fb462, 90 lines

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree. **Time:** All operations take amortized $\mathcal{O}(\log N)$.

```
struct Node { // Splay tree. Root's pp contains tree's parent.
  Node *p = 0, *pp = 0, *c[2];
  bool flip = 0;
  Node() { c[0] = c[1] = 0; fix(); }
  void fix() {
    if (c[0]) c[0]->p = this;
    if (c[1]) c[1]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
  }
  void pushFlip() {
    if (!flip) return;
    flip = 0; swap(c[0], c[1]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[1]) c[1]->flip ^= 1;
  }
  int up() { return p ? p->c[1] == this : -1; }
  void rot(int i, int b) {
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p = p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
      x->c[h] = y->c[h ^ 1];
      y->c[h ^ 1] = x;
    }
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
  }
  void splay() {
    for (pushFlip(); p; ) {
      if (p->p) p->p->pushFlip();
      p->pushFlip(); pushFlip();
      int c1 = up(), c2 = p->up();
      if (c2 == -1) p->rot(c1, 2);
      else p->p->rot(c2, c1 != c2);
    }
  }
  Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
  }
};

struct LinkCut {
  vector<Node> node;
  LinkCut(int N) : node(N) {}

  void link(int u, int v) { // add an edge (u, v)
    assert(!connected(u, v));
    makeRoot(&node[u]);
    node[u].pp = &node[v];
  }
  void cut(int u, int v) { // remove an edge (u, v)
    Node *x = &node[u], *top = &node[v];
    makeRoot(top); x->splay();
    assert(top == (x->pp ?: x->c[0]));
    if (x->pp) x->pp = 0;
    else {
      x->c[0] = top->p = 0;
      x->fix();
    }
  }
  bool connected(int u, int v) { // are u, v in the same tree?
```

```
    Node* nu = access(&node[u])->first();
    return nu == access(&node[v])->first();
  }
  void makeRoot(Node* u) {
    access(u);
    u->splay();
    if(u->c[0]) {
      u->c[0]->p = 0;
      u->c[0]->flip ^= 1;
      u->c[0]->pp = u;
      u->c[0] = 0;
      u->fix();
    }
  }
  Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
      pp->splay(); u->pp = 0;
      if (pp->c[1]) {
        pp->c[1]->p = 0; pp->c[1]->pp = pp; }
      pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
  }
};
```

DirectedMST.h "../data-structures/UnionFindRollback.h" 39e620, 60 lines

Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1. **Time:** $\mathcal{O}(E \log V)$

```
struct Edge { int a, b; ll w; };
struct Node {
  Edge key;
  Node *l, *r;
  ll delta;
  void prop() {
    key.w += delta;
    if (l) l->delta += delta;
    if (r) r->delta += delta;
    delta = 0;
  }
  Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
  if (!a || !b) return a ?: b;
  a->prop(), b->prop();
  if (a->key.w > b->key.w) swap(a, b);
  swap(a->l, (a->r = merge(b, a->r)));
  return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
  RollbackUF uf(n);
  vector<Node*> heap(n);
  for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
  ll res = 0;
  vi seen(n, -1), path(n), par(n);
  seen[r] = r;
  vector<Edge> Q(n), in(n, {-1,-1}), comp;
  deque<tuple<int, int, vector<Edge>>> cycs;
  rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
      if (!heap[u]) return {-1,{}};
      Edge e = heap[u]->top();
      heap[u]->delta -= e.w, pop(heap[u]);
      Q[qi] = e, path[qi++] = u, seen[u] = s;
      res += e.w, u = uf.find(e.a);
      if (seen[u] == s) {
        Node* cyc = 0;
        int end = qi, time = uf.time();
        do cyc = merge(cyc, heap[w = path[--qi]]);
        while (uf.join(u, w));
        u = uf.find(u), heap[u] = cyc, seen[u] = -1;
        cycs.push_front({u, time, {&Q[qi], &Q[end]}});
      }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
  }

  for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
  }
  rep(i,0,n) par[i] = in[i].a;
  return {res, par};
}
```

7.6 Math

7.6.1 Spanning trees, Euler circuits, disjoint paths

Laplacian $L = D - A$, where A_{ij} is the number of edges $i \to j$ (or $i - j$), D the degrees (loops ignored); weights multiply. Delete row and column r and take the determinant: undirected, this is the number of spanning trees (any r); for a digraph $D = D_{out}$ (edge $a \to b$: `L[a][a]++, L[a][b]--`) counts spanning trees with all edges directed *towards* r, and $D = D_{in}$ (`L[b][b]++, L[a][b]--`) those directed *away* from r.

BEST theorem: if every vertex has in-degree = out-degree and the graph is connected, the number of Euler circuits (cyclic sequences of edges) is $t_r \prod_v (\deg v - 1)!$, where t_r is the number of trees towards r (the same for every r); written as sequences starting at a given vertex s: times $\deg s$.

LGV lemma: in a DAG with sources $a_1, \ldots, a_k$, sinks $b_1, \ldots, b_k$ and M_{ij} the number (or weighted sum) of paths $a_i \to b_j$, $\det M = \sum \operatorname{sgn}(\sigma) \prod w$ over the systems of vertex-disjoint paths $a_i \to b_{\sigma(i)}$; if only $\sigma = \mathrm{id}$ can occur it counts them.

7.6.2 Flows with lower bounds

Edge $u \to v$ with bounds $[l, c]$: give it capacity $c - l$ and set $\mathrm{ex}[v] \mathrel{+}= l$, $\mathrm{ex}[u] \mathrel{-}= l$. A node bounded by $[A, B]$ is split into $v_{in} \to v_{out}$ with bounds $[A, B]$. Add $S^* \to v$ of capacity $\mathrm{ex}[v]$ if $\mathrm{ex}[v] > 0$, and $v \to T^*$ of capacity $-\mathrm{ex}[v]$ if $\mathrm{ex}[v] < 0$. A feasible flow exists iff the max flow $S^* \to T^*$ saturates all edges out of S^*. For an s–t flow also add $t \to s$ of capacity ∞; its flow F is the flow value. Then delete it: *max* flow is $F + \mathrm{maxflow}(s \to t)$ and *min* flow is $F - \mathrm{maxflow}(t \to s)$, both in the residual graph. Paths covering a DAG's vertices: bound every vertex by $[1, \infty]$, connect s to all sources and all sinks to t, take the min flow. Convex edge costs (e.g. x^2) in min-cost flow: use parallel unit edges with costs $1, 3, 5, \ldots$

7.6.3 Min cut models

Max-weight closure (choose items, each needs its prerequisites): $s \to i$ with capacity w_i if $w_i > 0$, $i \to t$ with $-w_i$ if $w_i < 0$, $i \to j$ with ∞ if i needs j; answer $= \sum_{w_i > 0} w_i -$ mincut (chosen items are on the s side). Bipartite graph: max matching = min vertex cover (König), max independent set = $V -$ matching. With weights, min weight vertex cover is the min cut of $s \to L$ (w), $L \to R$ (∞), $R \to t$ (w). DAG min path cover (vertex-disjoint) $= N -$ matching in the split graph (edge $u_{out} \to v_{in}$); paths may share vertices: use the transitive closure. Dilworth: max antichain = min chain cover (the latter with the transitive closure). Edge-disjoint paths: unit capacities; vertex-disjoint: split v into $v_{in} \to v_{out}$ of capacity 1. Two labels per item with pairwise penalties: s side / t side is the label; penalty edges between neighbours (needs submodular costs).

7.6.4 Segment tree graph

To add edges $v \to [l, r]$ cheaply, build a segment tree whose nodes are graph vertices, with edges parent $\to$ child (cost 0), and connect v to the $O(\log N)$ nodes covering $[l, r]$. For $[l, r] \to v$ use a second tree with the same leaves and edges child $\to$ parent. This gives $O(N + M \log N)$ edges for Dijkstra, SCC, topological sort or BFS.

7.6.5 Erdős–Gallai theorem

A simple graph with node degrees $d_1 \geq \cdots \geq d_n$ exists iff $d_1 + \cdots + d_n$ is even and for every $k = 1 \ldots n$,

$$\sum_{i=1}^{k} d_i \leq k(k-1) + \sum_{i=k+1}^{n} \min(d_i, k).$$

Geometry (8)

8.1 Geometric primitives

Point.h 47ec0a, 28 lines

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)


```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
  typedef Point P;
  T x, y;
  explicit Point(T x=0, T y=0) : x(x), y(y) {}
  bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
  bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
  P operator+(P p) const { return P(x+p.x, y+p.y); }
  P operator-(P p) const { return P(x-p.x, y-p.y); }
  P operator*(T d) const { return P(x*d, y*d); }
  P operator/(T d) const { return P(x/d, y/d); }
  T dot(P p) const { return x*p.x + y*p.y; }
  T cross(P p) const { return x*p.y - y*p.x; }
  T cross(P a, P b) const { return (a-*this).cross(b-*this); }
  T dist2() const { return x*x + y*y; }
  double dist() const { return sqrt((double)dist2()); }
  // angle to x-axis in interval [-pi, pi]
  double angle() const { return atan2(y, x); }
```

```
  P unit() const { return *this/dist(); } // makes dist()=1
  P perp() const { return P(-y, x); } // rotates +90 degrees
  P normal() const { return perp().unit(); }
  // returns point rotated 'a' radians ccw around the origin
  P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
  friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};
```

lineDistance.h "Point.h" 53630a, 4 lines

Description:

Signed distance from p to the line through a and b, positive on the left as seen from a towards b; a==b gives nan. T is double or long long; uses products of two coordinates (overflow).





```
template<class P>
double lineDist(P a, P b, P p) {
  return (double)(b-a).cross(p-a)/(b-a).dist();
}
```

SegmentDistance.h "Point.h" d5f39f, 6 lines

Description:

Returns the shortest distance between point p and the line segment from point s to e.




Usage: `Point<double> a, b(2,2), p(1,1);`
`bool onSegment = segDist(a,b,p) < 1e-10;`

```
typedef Point<double> P;
double segDist(P s, P e, P p) {
  if (s==e) return (p-s).dist();
  auto d = (e-s).dist2(), t = min(d,max(.0,(p-s).dot(e-s)));
  return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h "Point.h", "OnSegment.h" 9d57f2, 13 lines

Description:

Intersection of segments s1-e1 and s2-e2: one point, none (empty vector), or the two endpoints of the common segment if there are infinitely many. With Point<ll> the point is wrong if it is not integral. Uses products of three coordinates (overflow).




Usage: `vector<P> inter = segInter(s1,e1,s2,e2);`
`if (sz(inter)==1)`
`cout << "segments intersect at " << inter[0] << endl;`

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
  auto oa = c.cross(d, a), ob = c.cross(d, b),
       oc = a.cross(b, c), od = a.cross(b, d);
  // Checks if intersection is single non-endpoint point.
  if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
    return {(a * ob - b * oa) / (ob - oa)};
  set<P> s;
  if (onSegment(c, d, a)) s.insert(a);
  if (onSegment(c, d, b)) s.insert(b);
  if (onSegment(a, b, c)) s.insert(c);
  if (onSegment(a, b, d)) s.insert(d);
  return {all(s)};
}
```

lineIntersection.h "Point.h" a01f81, 8 lines

Description:

Intersection of the lines through s1,e1 and s2,e2: {1, point} if unique, {0, (0,0)} if parallel, {-1, (0,0)} if they are the same line. With Point<ll> the point is wrong if it is not integral. Uses products of three coordinates (overflow).



Usage: `auto res = lineInter(s1,e1,s2,e2);`
`if (res.first == 1)`
`cout << "intersection point at " << res.second << endl;`

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
  auto d = (e1 - s1).cross(e2 - s2);
  if (d == 0) // if parallel
    return {-(s1.cross(e1, s2) == 0), P(0, 0)};
  auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
  return {1, (s1 * p + e1 * q) / d};
}
```

sideOf.h "Point.h" ca4665, 9 lines

Description: 1/0/-1 if p is left of/on/right of the line from s towards e. With eps, 0 if p is within distance eps of the line. Uses products of coordinates (overflow).
Usage: `bool left = sideOf(p1,p2,q)==1;`

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(P s, P e, P p, double eps) {
  auto a = (e-s).cross(p-s);
  double l = (e-s).dist()*eps;
  return (a > l) - (a < -l);
}
```

OnSegment.h "Point.h" c597e8, 3 lines


Description: Returns true iff p lies on the line segment from s to e. Use `(segDist(s,e,p)<=epsilon)` instead when using Point<double>.

```
template<class P> bool onSegment(P s, P e, P p) {
  return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

linearTransformation.h "Point.h" 7871e9, 5 lines

Description:

Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.




```
typedef Point<double> P;
P linearTransformation(P p0, P p1, P q0, P q1, P r) {
  P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
  return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

LineProjectionReflection.h "Point.h" b5562d, 5 lines

Description: Projects point p onto line ab. Set refl=true to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

```
template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
  P v = b - a;
  return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
}
```

Angle.h 0f0602, 35 lines

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.
Usage: `vector<Angle> v = {w[0], w[0].t360() ...}; // sorted`
`int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }`
`// sweeps j such that (j-i) represents the number of positively oriented triangles with vertices at 0 and i`

```
struct Angle {
  int x, y;
  int t;
  Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
  Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
  int half() const {
    assert(x || y);
    return y < 0 || (y == 0 && x < 0);
  }
  Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
  Angle t180() const { return {-x, -y, t + half()}; }
  Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) {
  // add a.dist2() and b.dist2() to also compare distances
  return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
         make_tuple(b.t, b.half(), a.x * (ll)b.y);
}

// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
  if (b < a) swap(a, b);
  return (b < a.t180() ?
          make_pair(a, b) : make_pair(b, a.t360()));
}
Angle operator+(Angle a, Angle b) { // point a + vector b
  Angle r(a.x + b.x, a.y + b.y, a.t);
  if (a.t180() < r) r.t--;
  return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
  int tu = b.t - a.t; a.t = b.t;
  return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}
```

8.2 Circles

CircleIntersection.h "Point.h" 84d6d3, 11 lines

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
  if (a == b) { assert(r1 != r2); return false; }
  P vec = b - a;
  double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
         p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
  if (sum*sum < d2 || dif*dif > d2) return false;
  P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
  *out = {mid + per, mid - per};
  return true;
}
```

CircleTangents.h "Point.h" b0153d, 13 lines

Description: External tangents of two circles (internal ones if r2 is negated). Returns 0 tangents if one circle contains the other (internal case: also if they overlap; also if equal), 1 if they touch (.first = .second, perpendicular to the center line), else 2. .first and .second are the tangency points on circle 1 and 2. Tangents from a point: r2 = 0.

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
  P d = c2 - c1;
  double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
  if (d2 == 0 || h2 < 0)  return {};
  vector<pair<P, P>> out;
  for (double sign : {-1, 1}) {
    P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
    out.push_back({c1 + v * r1, c2 + v * r2});
  }
  if (h2 == 0) out.pop_back();
  return out;
}
```

CircleLine.h "Point.h" e0cfba, 9 lines

Description: Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>.

```
template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
  P ab = b - a, p = a + ab * (c-a).dot(ab) / ab.dist2();
  double s = a.cross(b, c), h2 = r*r - s*s / ab.dist2();
  if (h2 < 0) return {};
  if (h2 == 0) return {p};
  P h = ab.unit() * sqrt(h2);
  return {p - h, p + h};
}
```

CirclePolygonIntersection.h "../../content/geometry/Point.h" 19add1, 19 lines


Description: Returns the area of the intersection of a circle with a ccw polygon. **Time:** $\mathcal{O}(n)$

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
  auto tri = [&](P p, P q) {
    auto r2 = r * r / 2;
    P d = q - p;
    auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
    auto det = a * a - b;
    if (det <= 0) return arg(p, q) * r2;
    auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
    if (t < 0 || 1 <= s) return arg(p, q) * r2;
    P u = p + d * s, v = q + d * (t-1);
    return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
  };
  auto sum = 0.0;
  rep(i,0,sz(ps))
    sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
  return sum;
}
```

circumcircle.h "Point.h" 6cffc5, 9 lines

Description:

The circumcirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.




```
typedef Point<double> P;
double ccRadius(P A, P B, P C) {
  return (B-A).dist()*(C-B).dist()*(A-C).dist()/
      abs((B-A).cross(C-A))/2;
}
P ccCenter(P A, P B, P C) {
  P b = C-A, c = B-A;
  return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

MinimumEnclosingCircle.h "circumcircle.h" 09dd0a, 17 lines

Description: Computes the minimum circle that encloses a set of points. **Time:** expected $\mathcal{O}(n)$

```
pair<P, double> mec(vector<P> ps) {
  shuffle(all(ps), mt19937(time(0)));
  P o = ps[0];
  double r = 0, EPS = 1 + 1e-8;
  rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
    o = ps[i], r = 0;
    rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
      o = (ps[i] + ps[j]) / 2;
      r = (o - ps[i]).dist();
      rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
        o = ccCenter(ps[i], ps[j], ps[k]);
        r = (o - ps[i]).dist();
      }
    }
  }
  return {o, r};
}
```

8.3 Polygons

InsidePolygon.h "Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow. **Time:** $\mathcal{O}(n)$

Usage: `vector<P> v = {P{4,4}, P{1,2}, P{2,1}};`
`bool in = inPolygon(v, P{3, 3}, false);`

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
  int cnt = 0, n = sz(p);
  rep(i,0,n) {
    P q = p[(i + 1) % n];
    if (onSegment(p[i], q, a)) return !strict;
    //or: if (segDist(p[i], q, a) <= eps) return !strict;
    cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
  }
  return cnt;
}
```

PolygonArea.h "Point.h" f12300, 6 lines

Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

```
template<class T>
T polygonArea2(vector<Point<T>>& v) {
  T a = v.back().cross(v[0]);
  rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
  return a;
}
```

PolygonCenter.h "Point.h" 9706dc, 9 lines


Description: Returns the center of mass for a polygon. **Time:** $\mathcal{O}(n)$

```
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
  P res(0, 0); double A = 0;
  for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
    res = res + (v[i] + v[j]) * v[j].cross(v[i]);
    A += v[j].cross(v[i]);
  }
  return res / A / 3;
}
```

PolygonCut.h "Point.h" d07181, 13 lines

Description:

Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.



Usage: `vector<P> p = ...;`
`p = polygonCut(p, P(0,0), P(1,0));`

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
  vector<P> res;
  rep(i,0,sz(poly)) {
    P cur = poly[i], prev = i ? poly[i-1] : poly.back();
    auto a = s.cross(e, cur), b = s.cross(e, prev);
    if ((a < 0) != (b < 0))
      res.push_back(cur + (prev - cur) * (a / (a - b)));
    if (a < 0)
      res.push_back(cur);
  }
  return res;
}
```

HalfPlane.h "lineIntersection.h" 77549e, 29 lines

Description: Intersection of half-planes. Each half-plane is a pair (s, e): the points on the left of the directed line $s \to e$. Returns the vertices of the intersection in ccw order, or an empty vector if it is empty. Use `Point<double>`, and add a large bounding box (4 half-planes) if the intersection may be unbounded. Touching or degenerate results may come back either empty or with (almost) zero area. **Time:** $\mathcal{O}(n \log n)$

Usage: `vector<pair<P,P>> h = {{s1, e1}, {s2, e2}, ...};`

```
template<class P> vector<P> halfPlanes(vector<pair<P, P>> h) {
  typedef pair<P, P> H;
  const double eps = 1e-9;
  auto dir = [](H& l) { return l.second - l.first; };
  auto out = [&](H& l, P p) { return dir(l).cross(p - l.first)
      < -eps; };
  auto inter = [](H& a, H& b) {
    return lineInter(a.first, a.second, b.first, b.second).
        second; };
  sort(all(h), [&](H a, H b) { return dir(a).angle() < dir(b).
      angle(); });
  vector<H> q(sz(h));
  int a = 0, b = 0;
  for (H& l : h) {
    for (; b - a > 1 && out(l, inter(q[b-1], q[b-2])); b--);
    for (; b - a > 1 && out(l, inter(q[a], q[a+1])); a++);
    if (b > a && fabs(dir(l).cross(dir(q[b-1]))) < eps) {
      if (dir(l).dot(dir(q[b-1])) < 0) return {};
      if (out(l, q[b-1].first)) b--; // same dir, l tighter
      else continue;
    }
    q[b++] = l;
  }
  for (; b - a > 2 && out(q[a], inter(q[b-1], q[b-2])); b--);
  for (; b - a > 2 && out(q[b-1], inter(q[a], q[a+1])); a++);
  if (b - a < 3) return {};
  rep(i,a,b) // bounded: turns left by < pi at each corner
    if (dir(q[i]).cross(dir(q[i+1 == b ? a : i+1])) < eps)
      return {};
  vector<P> r;
  rep(i,a,b) r.push_back(inter(q[i], q[i+1 == b ? a : i+1]));
  return r;
}
```

ConvexHull.h "Point.h" 310954, 13 lines

Description:
Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.



Time: $\mathcal{O}(n \log n)$

```
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
  if (sz(pts) <= 1) return pts;
  sort(all(pts));
  vector<P> h(sz(pts)+1);
  int s = 0, t = 0;
  for (int it = 2; it--; s = --t, reverse(all(pts)))
    for (P p : pts) {
      while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
      h[t++] = p;
    }
  return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h "Point.h" c571b8, 12 lines

Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points). **Time:** $\mathcal{O}(n)$

```
typedef Point<ll> P;
array<P, 2> hullDiameter(vector<P> S) {
  int n = sz(S), j = n < 2 ? 0 : 1;
  pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
  rep(i,0,j)
    for (;; j = (j + 1) % n) {
      res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
      if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
        break;
    }
  return res.second;
}
```

PointInsideHull.h "Point.h", "sideOf.h", "OnSegment.h" 71446b, 14 lines

Description: Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included. **Time:** $\mathcal{O}(\log N)$

```
typedef Point<ll> P;

bool inHull(const vector<P>& l, P p, bool strict = true) {
  int a = 1, b = sz(l) - 1, r = !strict;
  if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
  if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
  if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p)<= -r)
    return false;
  while (abs(a - b) > 1) {
    int c = (a + b) / 2;
    (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
  }
  return sgn(l[a].cross(l[b], p)) < r;
}
```

LineHullIntersection.h "Point.h" 7cf45b, 39 lines

Description: Line vs convex polygon (ccw, no collinear points). `lineHull(line, poly)` returns $(-1,-1)$ if no collision, $(i,-1)$ if touching corner i, (i,i) if along side $(i,i+1)$, (i,j) if crossing sides $(i,i+1)$ and $(j,j+1)$ (a crossed corner i counts as side $(i,i+1)$), in the order the line hits them. `extrVertex` returns the hull point with the max projection onto a line. **Time:** $\mathcal{O}(\log n)$

```
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
  int n = sz(poly), lo = 0, hi = n;
  if (extr(0)) return 0;
  while (lo + 1 < hi) {
    int m = (lo + hi) / 2;
    if (extr(m)) return m;
    int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
    (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
  }
  return lo;
}

#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
  int endA = extrVertex(poly, (a - b).perp());
  int endB = extrVertex(poly, (b - a).perp());
  if (cmpL(endA) < 0 || cmpL(endB) > 0)
    return {-1, -1};
  array<int, 2> res;
  rep(i,0,2) {
    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
      int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
      (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
  }
  if (res[0] == res[1]) return {res[0], -1};
  if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
      case 0: return {res[0], res[0]};
      case 2: return {res[1], res[1]};
    }
  return res;
}
```

MinkowskiSum.h "Point.h" e9f890, 16 lines

Description: Minkowski sum $\{p+q\}$ of two convex polygons given in ccw order (at least 3 vertices, no three collinear). Returns a convex polygon in ccw order. Two convex polygons A, B intersect iff the origin is in $A + (-B)$, and their distance is the distance from the origin to it. With integer points, cross products must fit in 64 bits. **Time:** $\mathcal{O}(n+m)$

```
template<class P> vector<P> minkowski(vector<P> a, vector<P> b)
    {
  auto low = [](P p, P q) { return tie(p.y, p.x) < tie(q.y, q.x
      ); };
  rotate(a.begin(), min_element(all(a), low), a.end());
  rotate(b.begin(), min_element(all(b), low), b.end());
  int n = sz(a), m = sz(b);
  a.push_back(a[0]), a.push_back(a[1]);
  b.push_back(b[0]), b.push_back(b[1]);
  vector<P> r;
  for (int i = 0, j = 0; i < n || j < m;) {
    r.push_back(a[i] + b[j]);
    auto c = (a[i+1] - a[i]).cross(b[j+1] - b[j]);
    if (c >= 0 && i < n) i++;
    if (c <= 0 && j < m) j++;
  }
  return r;
}
```

8.4 Misc. Point Set Problems

ClosestPair.h "Point.h" ac41a6, 17 lines

Description: Finds the closest pair of points. **Time:** $\mathcal{O}(n \log n)$

```
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
  assert(sz(v) > 1);
  set<P> S;
  sort(all(v), [](P a, P b) { return a.y < b.y; });
  pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
  int j = 0;
  for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
      ret = min(ret, {(*lo - p).dist2(), {*lo, p}});
    S.insert(p);
  }
  return ret.second;
}
```

ManhattanMST.h "Point.h" df6f59, 23 lines

Description: Given N points, returns up to 4*N edges, which are guaranteed to contain a minimum spanning tree for the graph with edge weights w(p, q) = —p.x - q.x— + —p.y - q.y—. Edges are in the form (distance, src, dst). Use a standard MST algorithm on the result to find the final MST. **Time:** $\mathcal{O}(N \log N)$

```
typedef Point<int> P;
vector<array<int, 3>> manhattanMST(vector<P> ps) {
  vi id(sz(ps));
  iota(all(id), 0);
  vector<array<int, 3>> edges;
  rep(k,0,4) {
    sort(all(id), [&](int i, int j) {
         return (ps[i]-ps[j]).x < (ps[j]-ps[i]).y;});
    map<int, int> sweep;
    for (int i : id) {
      for (auto it = sweep.lower_bound(-ps[i].y);
                it != sweep.end(); sweep.erase(it++)) {
        int j = it->second;
        P d = ps[i] - ps[j];
        if (d.y > d.x) break;
        edges.push_back({d.y + d.x, i, j});
      }
      sweep[-ps[i].y] = i;
    }
    for (P& p : ps) if (k & 1) p.x = -p.x; else swap(p.x, p.y);
  }
  return edges;
}
```

RectangleUnion.h ab84f0, 32 lines

Description: Area of the union of axis-aligned rectangles. A rectangle is $\{x_1, y_1, x_2, y_2\}$ and covers $[x_1, x_2) \times [y_1, y_2)$. **Time:** $\mathcal{O}(N \log N)$

```
typedef array<ll, 4> Rect;
ll rectUnion(vector<Rect> r) {
  vector<ll> ys;
  for (Rect& a : r) ys.push_back(a[1]), ys.push_back(a[3]);
  sort(all(ys)); ys.erase(unique(all(ys)), ys.end());
  int m = sz(ys) - 1;
  if (m < 1) return 0;
  vi c(4*m); vector<ll> cov(4*m);
  auto upd = [&](auto&& self, int o, int lo, int hi, int l, int
       r, int d) {
    if (r <= lo || hi <= l) return;
    if (l <= lo && hi <= r) c[o] += d;
    else {
      int mid = (lo + hi) / 2;
      self(self, 2*o, lo, mid, l, r, d); self(self, 2*o+1, mid,
           hi, l, r, d);
    }
    cov[o] = c[o] ? ys[hi] - ys[lo] : hi - lo == 1 ? 0 : cov[2*
        o] + cov[2*o+1];
```

```
  };
  vector<array<ll, 4>> ev; // x, -delta, y1, y2
  for (Rect& a : r) if (a[0] < a[2] && a[1] < a[3]) {
    ev.push_back({a[0], -1, a[1], a[3]});
    ev.push_back({a[2], 1, a[1], a[3]});
  }
  sort(all(ev));
  ll ans = 0, px = 0;
  for (auto& e : ev) {
    ans += cov[1] * (e[0] - px); px = e[0];
    int l = (int)(lower_bound(all(ys), e[2]) - ys.begin());
    int h = (int)(lower_bound(all(ys), e[3]) - ys.begin());
    upd(upd, 1, 0, m, l, h, (int)(-e[1]));
  }
  return ans;
}
```

kdTree.h

"Point.h" 69ff55, 63 lines

Description: KD-tree (2d, can be extended to 3d)

```
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

bool on_x(P a, P b) { return a.x < b.x; }
bool on_y(P a, P b) { return a.y < b.y; }

struct Node {
  P pt; // if this is a leaf, the single point in it
  T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
  Node *first = 0, *second = 0;

  T distance(P p) { // min squared distance to a point
    T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
    T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
    return (P(x,y) - p).dist2();
  }

  Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
      x0 = min(x0, p.x); x1 = max(x1, p.x);
      y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
      // split on x if width >= height (not ideal...)
      sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
      // divide by taking half the array for each child (not
      // best performance with many duplicates in the middle)
      int half = sz(vp)/2;
      first = new Node({vp.begin(), vp.begin() + half});
      second = new Node({vp.begin() + half, vp.end()});
    }
  }
};

struct KDTree {
  Node* root;
  KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}

  pair<T, P> search(Node *node, P p) {
    if (!node->first) {
      // uncomment if we should not find the point itself:
      // if (p == node->pt) return {INF, P()};
      return make_pair((p - node->pt).dist2(), node->pt);
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->distance(p);
    if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

    // search closest side first, other side if needed
    auto best = search(f, p);
    if (bsec < best.first)
      best = min(best, search(s, p));
    return best;
  }

  // find nearest point to a point, and its squared distance
  // (requires an arbitrary operator< for Point)
  pair<T, P> nearest(P p) {
    return search(root, p);
  }
};
```

Strings (9)

KMP.h

d4375c, 16 lines

Description: pi[x] computes the length of the longest prefix of s that ends at x, other than s[0...x] itself (abacaba -> 0010123). Can be used to find all occurrences of a string. **Time:** $\mathcal{O}(n)$

```
vi pi(const string& s) {
  vi p(sz(s));
  rep(i,1,sz(s)) {
    int g = p[i-1];
    while (g && s[i] != s[g]) g = p[g-1];
    p[i] = g + (s[i] == s[g]);
  }
  return p;
}

vi match(const string& s, const string& pat) {
  vi p = pi(pat + '\0' + s), res;
  rep(i,sz(p)-sz(s),sz(p))
    if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
  return res;
}
```

Zfunc.h

ee09e2, 12 lines

Description: z[i] computes the length of the longest common prefix of s[i:] and s, except z[0] = 0. (abacaba -> 0010301) **Time:** $\mathcal{O}(n)$

```
vi Z(const string& S) {
  vi z(sz(S));
  int l = -1, r = -1;
  rep(i,1,sz(S)) {
    z[i] = i >= r ? 0 : min(r - i, z[i - l]);
    while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
      z[i]++;
    if (i + z[i] > r)
      l = i, r = i + z[i];
  }
  return z;
}
```

Manacher.h

e7ad79, 13 lines

Description: For each position in a string, computes p[0][i] = half length of longest even palindrome around pos i, p[1][i] = longest odd (half rounded down). **Time:** $\mathcal{O}(N)$

```
array<vi, 2> manacher(const string& s) {
  int n = sz(s);
  array<vi,2> p = {vi(n+1), vi(n)};
  rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
    int t = r-i+!z;
    if (i<r) p[z][i] = min(t, p[z][l+t]);
    int L = i-p[z][i], R = i+p[z][i]-!z;
    while (L>=1 && R+1<n && s[L-1] == s[R+1])
      p[z][i]++, L--, R++;
    if (R>r) l=L, r=R;
  }
  return p;
}
```

PalindromicTree.h

43784e, 24 lines

Description: Palindromic tree (eertree). Node 0 has length -1, node 1 is the empty palindrome, every other node is a distinct palindromic substring of the string (so there are `sz(t) - 2` of them). `link` is the longest proper palindromic suffix, `last` the node of the longest palindromic suffix of the current prefix. After `count()`, `cnt[v]` is the number of occurrences of palindrome v. **Time:** $\mathcal{O}(N)$ amortized, for a fixed alphabet

```
struct PalTree {
  struct Nd {
    int len, link, cnt = 0; array<int, 26> nx;
    Nd(int len, int link) : len(len), link(link) {nx.fill(0);}
  };
  vector<Nd> t{Nd(-1, 0), Nd(0, 0)};
  string s; int last = 1;
  void add(char ch) {
    s += ch;
    int c = ch - 'a', i = sz(s) - 1;
    auto up = [&](int v) {
      while (i - t[v].len - 1 < 0 || s[i - t[v].len - 1] != ch)
        v = t[v].link;
      return v;
    };
    int cur = up(last);
    if (!t[cur].nx[c]) {
      int nw = sz(t), lk = t[cur].len < 0 ? 1 : t[up(t[cur].
          link)].nx[c];
      t.emplace_back(t[cur].len + 2, lk);
      t[cur].nx[c] = nw;
    }
    last = t[cur].nx[c]; t[last].cnt++;
  }
  void count() { for (int v = sz(t); v-- > 2;) t[t[v].link].cnt
      += t[v].cnt; }
};
```

MinRotation.h

67652e, 8 lines

Description: Finds the lexicographically smallest rotation of a string. **Time:** $\mathcal{O}(N)$

Usage: `rotate(v.begin(), v.begin()+minRotation(v), v.end());`

```
int minRotation(string s) {
  int a=0, N=sz(s); s += s;
  rep(b,0,N) rep(k,0,N) {
    if (a+k==b || s[a+k]<s[b+k]) {b += max<int>(0,k-1); break;}
    if (s[a+k] > s[b+k]) { a = b; break; }
  }
  return a;
}
```

SuffixArray.h

47bad6, 22 lines

Description: `sa[i]` is the start of the i'th smallest suffix; size $n+1$, `sa[0] = n`. `lcp[i] = lcp(sa[i], sa[i-1])`, `lcp[0] = 0`. The input must not contain nul chars. **Time:** $\mathcal{O}(n \log n)$

```
struct SuffixArray {
  vi sa, lcp;
  SuffixArray(string s, int lim=256) { // or vector<int>
    s.push_back(0); int n = sz(s), k = 0, a, b;
    vi x(all(s)), y(n), ws(max(n, lim));
    sa = lcp = y, iota(all(sa), 0);
    for (int j=0, p=0; p < n; j = max<int>(1, j*2), lim = p) {
      p = j, iota(all(y), n - j);
```

```
    rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
    fill(all(ws), 0);
    rep(i,0,n) ws[x[i]]++;
    rep(i,1,lim) ws[i] += ws[i - 1];
    for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
    swap(x, y), p = 1, x[sa[0]] = 0;
    rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
      (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
  }
  for (int i = 0, j; i < n - 1; lcp[x[i++]] = k)
    for (k && k--, j = sa[x[i] - 1];
        s[i + k] == s[j + k]; k++);
 }
};
```

SuffixAutomaton.h

3ac832, 30 lines

Description: Minimal DFA accepting exactly the suffixes of the string (so every substring is a path from state 0). State v stands for all substrings that end at the same set of positions, with lengths `(len[link[v]], len[v]]`. Number of distinct substrings is $\sum_{v\neq 0}$ `len[v] - len[link[v]]`. After `count()`, `cnt[v]` is the number of occurrences of the strings of v. Append characters with `extend`. **Time:** $\mathcal{O}(N)$ states, $\mathcal{O}(N \cdot 26)$ memory, `count` in $\mathcal{O}(N \log N)$

```
struct SuffixAutomaton {
  struct S {
    int len, link = -1, cnt = 0; array<int, 26> nx;
    S(int len) : len(len) { nx.fill(-1); }
  };
  vector<S> t{S(0)}; int last = 0;
  void extend(char ch) {
    int c = ch - 'a', cur = sz(t), p = last;
    t.emplace_back(t[last].len + 1); t[cur].cnt = 1;
    for (; p >= 0 && t[p].nx[c] < 0; p = t[p].link) t[p].nx[c]
        = cur;
    if (p < 0) t[cur].link = 0;
    else {
      int q = t[p].nx[c];
      if (t[p].len + 1 == t[q].len) t[cur].link = q;
      else {
        int cl = sz(t);
        t.push_back(t[q]); t[cl].len = t[p].len + 1; t[cl].cnt
            = 0;
        for (; p >= 0 && t[p].nx[c] == q; p = t[p].link)
          t[p].nx[c] = cl;
        t[q].link = t[cur].link = cl;
      }
    }
    last = cur;
  }
  void count() {
    vi o(sz(t)); iota(all(o), 0);
    sort(all(o), [&](int a, int b) { return t[a].len > t[b].len
        ; });
    for (int v : o) if (t[v].link >= 0) t[t[v].link].cnt += t[v
        ].cnt;
  }
};
```

Hashing.h

2d2a67, 44 lines

Description: Self-explanatory methods for string hashing.

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
  ull x; H(ull x=0) : x(x) {}
  H operator+(H o) { return x + o.x + (x + o.x < x); }
  H operator-(H o) { return *this + ~o.x; }
  H operator*(H o) { auto m = (__uint128_t)x * o.x;
    return H((ull)m) + (ull)(m >> 64); }
  ull get() const { return x + !~x; }
  bool operator==(H o) const { return get() == o.get(); }
  bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (ll)1e11+3; // (order ~ 3e9; random also ok)

struct HashInterval {
  vector<H> ha, pw;
  HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
    pw[0] = 1;
    rep(i,0,sz(str))
      ha[i+1] = ha[i] * C + str[i],
      pw[i+1] = pw[i] * C;
  }
  H hashInterval(int a, int b) { // hash [a, b)
    return ha[b] - ha[a] * pw[b - a];
  }
};

vector<H> getHashes(string& str, int length) {
  if (sz(str) < length) return {};
  H h = 0, pw = 1;
  rep(i,0,length)
    h = h * C + str[i], pw = pw * C;
  vector<H> ret = {h};
  rep(i,length,sz(str)) {
    ret.push_back(h = h * C + str[i] - pw * str[i-length]);
  }
  return ret;
}

H hashString(string& s){H h{}; for(char c:s) h=h*C+c;return h;}
```

AhoCorasick.h

f35677, 66 lines

Description: Multiple pattern matching. `AhoCorasick ac(patterns);` the start node is 0. `find(word)` gives for each position the index of the longest word ending there, or -1. `findAll(-, word)` lists all words starting at each position, shortest first (up to $N\sqrt{N}$ without duplicate patterns). Duplicate patterns are allowed, empty ones are not. Longest words starting at each position: reverse all input. Large alphabets: split symbols into chunks, with sentinel bits for symbol boundaries. **Time:** construction takes $\mathcal{O}(26N)$, where N = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$.

```
struct AhoCorasick {
  enum {alpha = 26, first = 'A'}; // change this!
  struct Node {
    // (nmatches is optional)
    int back, next[alpha], start = -1, end = -1, nmatches = 0;
    Node(int v) { memset(next, v, sizeof(next)); }
  };
  vector<Node> N;
  vi backp;
  void insert(string& s, int j) {
    assert(!s.empty());
    int n = 0;
    for (char c : s) {
      int& m = N[n].next[c - first];
      if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
      else n = m;
    }
    if (N[n].end == -1) N[n].start = j;
    backp.push_back(N[n].end);
    N[n].end = j;
    N[n].nmatches++;
  }
  AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i,0,sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
      int n = q.front(), prev = N[n].back;
      rep(i,0,alpha) {
        int &ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1) ed = y;
        else {
          N[ed].back = y;
          (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
            = N[y].end;
          N[ed].nmatches += N[y].nmatches;
          q.push(ed);
        }
      }
    }
  }
  vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
      n = N[n].next[c - first];
      res.push_back(N[n].end);
      // count += N[n].nmatches;
    }
    return res;
  }
  vector<vi> findAll(vector<string>& pat, string word) {
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
      int ind = r[i];
      while (ind != -1) {
        res[i - sz(pat[ind]) + 1].push_back(ind);
        ind = backp[ind];
      }
    }
    return res;
  }
};
```

9.1 Suffix array and automaton facts

With `lcp[i] = lcp(sa[i], sa[i-1])`: the lcp of two suffixes with ranks $r_1 < r_2$ is $\min$ `lcp`$[r_1 + 1 \dots r_2]$ (a range minimum query). Distinct substrings: $\sum_{i\geq 1}(n - $ `sa[i]` $-$ `lcp[i]`$) = n(n+1)/2 - \sum$ `lcp`; suffix `sa[i]` adds the prefixes longer than `lcp[i]`, so the k'th distinct substring in lexicographic order is found by subtracting these counts along the suffix array. Longest common substring of s and u: build the automaton of s and run u through it, keeping a state v and a length (take a transition and add 1; if there is none, follow `link` and set the length to `len[v]`, until there is one); the answer is the largest length seen. Several strings: set `last = 0` before each string (all substrings are accepted and nothing else, and $\sum$ `len[v] - len[link[v]]` still counts the distinct substrings; the automaton may just have redundant states).

Various (10)

10.1 Intervals

IntervalMap.h 7d8e78, 21 lines

Description: Partitions $[lo, hi)$ into intervals that each hold a value. `assign` overwrites a range and merges equal neighbours. `each` calls `f(a, b, T& val)` on the pieces of $[l, r)$ and lets `f` modify the values (e.g. range add, range count). With only `assign`, also replaces a set of disjoint intervals: `T = bool`, `m.assign(l, r, 1)` adds, `0` removes. **Time:** amortized $\mathcal{O}(\log N)$ per assign, plus the pieces visited
Usage: `IntervalMap<int> m(0, n, 0); m.assign(l, r, v); m.each(l, r, [&](int a, int b, int& x){ ... }); m.get(i);`

```
template<class T> struct IntervalMap {
  map<int, T> m; int hi; // m[x] = value on [x, next key)
  typedef typename map<int, T>::iterator It;
  IntervalMap(int lo, int hi, T v) : hi(hi) {m[lo] = v; m[hi];}
  It split(int x) { // makes x a key
    It it = m.lower_bound(x);
    return it->first == x ? it :
      m.emplace_hint(it, x, prev(it)->second);
  }
  T get(int x) { return prev(m.upper_bound(x))->second; }
  template<class F> void each(int l, int r, F f) {
    It it = split(l), e = split(r);
    for (; it != e; ++it) f(it->first, next(it)->first, it->
        second);
  }
  void assign(int l, int r, T v) { // l < r
    It it = split(l), e = split(r);
    it->second = v; m.erase(next(it), e);
    if (e->first != hi && e->second == v) m.erase(e);
    if (it != m.begin() && prev(it)->second == v) m.erase(it);
  }
};
```

IntervalCover.h 9e9d8d, 19 lines

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add `|| R.empty()`. Returns empty set on failure (or if G is empty). **Time:** $\mathcal{O}(N \log N)$

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
  vi S(sz(I)), R;
  iota(all(S), 0);
  sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
  T cur = G.first;
  int at = 0;
  while (cur < G.second) { // (A)
    pair<T, int> mx = make_pair(cur, -1);
    while (at < sz(I) && I[S[at]].first <= cur) {
      mx = max(mx, make_pair(I[S[at]].second, S[at]));
      at++;
    }
    if (mx.second == -1) return {};
    cur = mx.first;
    R.push_back(mx.second);
  }
  return R;
}
```

10.2 Misc. algorithms

TernarySearch.h 9155b4, 11 lines

Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \ldots < f(i) \geq \cdots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the $<$ marked with (A) to $<=$, and reverse the loop at (B). To minimize f, change it to $>$, also at (B). **Time:** $\mathcal{O}(\log(b - a))$
Usage: `int ind = ternSearch(0,n-1,[&](int i){return a[i];});`

```
template<class F>
int ternSearch(int a, int b, F f) {
  assert(a <= b);
  while (b - a >= 5) {
    int mid = (a + b) / 2;
    if (f(mid) < f(mid+1)) a = mid; // (A)
    else b = mid+1;
  }
  rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
  return a;
}
```

10.3 Dynamic programming

DivideAndConquerDP.h d38d2b, 18 lines

Description: Given $a[i] = \min_{lo(i) \leq k < hi(i)}(f(i, k))$ where the (minimal) optimal k increases with i, computes $a[i]$ for $i = L..R - 1$. **Time:** $\mathcal{O}((N + (hi - lo)) \log N)$

```
struct DP { // Modify at will:
  int lo(int ind) { return 0; }
  int hi(int ind) { return ind; }
  ll f(int ind, int k) { return dp[ind][k]; }
  void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

  void rec(int L, int R, int LO, int HI) {
    if (L >= R) return;
    int mid = (L + R) >> 1;
    pair<ll, int> best(LLONG_MAX, LO);
    rep(k, max(LO,lo(mid)), min(HI,hi(mid)))
      best = min(best, make_pair(f(mid, k), k));
    store(mid, best.second, best.first);
    rec(L, mid, LO, best.second+1);
    rec(mid+1, R, best.second, HI);
  }
  void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

10.3.1 Slope trick

To keep a convex piecewise-linear $f(x)$ with integer slopes, store the points where the slope changes by 1: left ones in a max-heap L, right ones in a min-heap R, and the minimum value m. Add $|x - a|$: push a to both heaps, fix the order of the tops, and add the difference to m if they cross. Add $\max(0, x - a)$: push a to L, move the top of L to R. Add $\max(0, a - x)$: push a to R, move the top of R to L. Prefix minimum: clear R. Shift by c: lazy offsets for L and R.

10.3.2 Sum over subsets (SOS DP)

Bits are numbered from 0 on the right. Let $S(x, i)$ be the set of submasks $y \subseteq x$ that equal x on all bits $\geq i$ (only the lowest i bits differ), e.g. $S(1011010_2, 4)$ is the pattern 101?0?0 with ? free: $1010000, 1010010, 1011000, 1011010$. Then $S(x, 0) = \{x\}$, $S(x, n)$ is all submasks of x, and $S(x, i + 1) = S(x, i)$ if bit i of x is 0, else $S(x, i) \cup S(x \oplus 2^i, i)$ (disjoint: bit i of y is 1 or 0). So $dp[x][i] = \sum_{y \in S(x,i)} a[y]$ has $dp[x][0] = a[x]$ and $dp[x][i + 1] = dp[x][i] + [x_i = 1]\, dp[x \oplus 2^i][i]$. Layer i only reads entries with bit i clear, which it does not change, so one array is enough: $O(n2^n)$ time, $O(2^n)$ memory.

```
rep(i,0,n) rep(x,0,1<<n)
  if (x >> i & 1) f[x] += f[x ^ 1 << i];
```

Supersets: test `~x >> i & 1` and add `f[x ^ 1 << i]` (bit i is clear in x, so this is x with bit i set). Inverse (Mobius): same loops with $-=$. Any other operation works too (max, min, `|`), since the unions are disjoint. Pairs with $y \,\&\, z = 0$: z is a submask of $\sim y$.

10.4 Debugging tricks

- `signal(SIGSEGV, [](int) { _Exit(0); });` converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). `_GLIBCXX_DEBUG` failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- `feenableexcept(29);` kills the program on NaNs (`1`), 0-divs (`4`), infinities (`8`) and denormals (`16`).

10.5 Optimization tricks

`__builtin_ia32_ldmxcsr(40896);` disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- `x & -x` is the least bit in `x`.
- `for (int x = m; x; ) { --x &= m; ... }` loops over all subset masks of `m` (except `m` itself).
- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.

10.5.2 Pragmas

- `#pragma GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- `#pragma GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- `#pragma GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

10.6 Python

- Integers are unbounded, but `int(s)` and `str(x)` stop at 4300 digits with a `ValueError`: start with `sys.set_int_max_str_digits(0)` (a million digits take about 0.5 s).
- `math.isqrt(n)` is the exact integer square root; `int(math.sqrt(n))` is already wrong for $n = (10^{16}+1)^2 - 1$. Also `gcd`, `lcm`, `comb`, `perm`, `factorial`, `prod`.
- `pow(a, b, m)` is modular exponentiation and `pow(a, -1, m)` the modular inverse (`ValueError` if there is none). `//`, `%` and `divmod` round towards $-\infty$ (unlike C++). Also `x.bit_length()`, `x.bit_count()`, `int(s, base)`, `format(x, 'b')`.
- `decimal`: `getcontext().prec = 100` sets the digits kept in results. Build values from strings (`Decimal('0.1')`, not `Decimal(0.1)`). `.sqrt()`, `.ln()`, `.exp()`, `.log10()`, `.quantize(Decimal('0.01'), ROUND_HALF_UP)` (the default rounding is half-even: `2.665` gives `2.66`). Huge results such as $e^{3 \cdot 10^6}$ raise `Overflow` until `getcontext().Emax = MAX_EMAX`. `fractions.Fraction` is exact (`limit_denominator`).
- Input: `input = sys.stdin.readline` or `sys.stdin.buffer.read().split()`.
- Recursion: CPython 3.12 only needs `sys.setrecursionlimit(10**6)` for plain functions, but PyPy overflows its stack at depth 10^5 in the main thread. Run `main` in a thread: `threading.stack_size(2**29)`, `threading.Thread(target=main).start()` (2^{27} is enough for 10^5 levels, 2^{29} for 10^6). Recursion through `functools.lru_cache` fails on CPython 3.12 near depth 3300 whatever the limit: use a `dict` or iterate.
- `math.cbrt` (3.11+) does not exist on PyPy (Python 3.9); `bit_count` and `lcm` do.

Techniques (A)

techniques.txt 159 lines

```
Recursion
Divide and conquer
  Finding interesting points in N log N
Algorithm analysis
  Master theorem
  Amortized time complexity
Greedy algorithm
  Scheduling
  Max contiguous subvector sum
  Invariants
  Huffman encoding
Graph theory
  Dynamic graphs (extra book-keeping)
  Breadth first search
  Depth first search
  * Normal trees / DFS trees
  Dijkstra's algorithm
  MST: Prim's algorithm
  Bellman-Ford
  Konig's theorem and vertex cover
  Min-cost max flow
  Lovasz toggle
  Matrix tree theorem
  Maximal matching, general graphs
  Hopcroft-Karp
  Hall's marriage theorem
  Graphical sequences
  Floyd-Warshall
  Euler cycles
  Flow networks
  * Augmenting paths
  * Edmonds-Karp
  Bipartite matching
  Min. path cover
  Topological sorting
  Strongly connected components
  2-SAT
  Cut vertices, cut-edges and biconnected components
  Edge coloring
  * Trees
  Vertex coloring
  * Bipartite graphs (=> trees)
  * 3^n (special case of set cover)
  Diameter and centroid
  K'th shortest path
  Shortest cycle
Dynamic programming
  Knapsack
  Coin change
  Longest common subsequence
  Longest increasing subsequence
  Number of paths in a dag
  Shortest path in a dag
  Dynprog over intervals
  Dynprog over subsets
  Dynprog over probabilities
  Dynprog over trees
  3^n set cover
  Divide and conquer
  Knuth optimization
  Convex hull optimizations
  RMQ (sparse table a.k.a 2^k-jumps)
  Bitonic cycle
  Log partitioning (loop over most restricted)
Combinatorics
  Computation of binomial coefficients
  Pigeon-hole principle
  Inclusion/exclusion
  Catalan number
  Pick's theorem
Number theory
  Integer parts
  Divisibility
  Euclidean algorithm
  Modular arithmetic
  * Modular multiplication
  * Modular inverses
  * Modular exponentiation by squaring
  Chinese remainder theorem
  Fermat's little theorem
  Euler's theorem
  Phi function
  Frobenius number
  Quadratic reciprocity
  Pollard-Rho
  Miller-Rabin
  Hensel lifting
  Vieta root jumping
Game theory
  Combinatorial games
  Game trees
  Mini-max
  Nim
  Games on graphs
  Games on graphs with loops
  Grundy numbers
  Bipartite games without repetition
  General games without repetition
  Alpha-beta pruning
Probability theory
Optimization
  Binary search
  Ternary search
  Unimodality and convex functions
  Binary search on derivative
Numerical methods
  Numeric integration
  Newton's method
  Root-finding with binary/ternary search
  Golden section search
Matrices
  Gaussian elimination
  Exponentiation by squaring
Sorting
  Radix sort
Geometry
  Coordinates and vectors
  * Cross product
  * Scalar product
  Convex hull
  Polygon cut
  Closest pair
  Coordinate-compression
  Quadtrees
  KD-trees
  All segment-segment intersection
Sweeping
  Discretization (convert to events and sweep)
  Angle sweeping
  Line sweeping
  Discrete second derivatives
Strings
  Longest common substring
  Palindrome subsequences
  Knuth-Morris-Pratt
  Tries
  Rolling polynomial hashes
  Suffix array
  Suffix tree
  Aho-Corasick
  Manacher's algorithm
  Letter position lists
Combinatorial search
  Meet in the middle
  Brute-force with pruning
  Best-first (A*)
  Bidirectional search
  Iterative deepening DFS / A*
Data structures
  LCA (2^k-jumps in trees in general)
  Pull/push-technique on trees
  Heavy-light decomposition
  Centroid decomposition
  Lazy propagation
  Self-balancing trees
  Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
  Monotone queues / monotone stacks / sliding queues
  Sliding queue using 2 stacks
  Persistent segment tree
```