

Array.prototype.slice()

The `slice()` method of [Array](#) instances returns a [shallow copy](#) of a portion of an array into a new array object selected from `start` to `end` (`end` not included) where `start` and `end` represent the index of items in that array. The original array will not be modified.

Try it

JavaScript Demo: Array.slice()

```

1  const animals = ['ant', 'bison', 'camel', 'duck', 'elephant'];
2
3  console.log(animals.slice(2));
4  // Expected output: Array ["camel", "duck", "elephant"]
5
6  console.log(animals.slice(2, 4));
7  // Expected output: Array ["camel", "duck"]
8
9  console.log(animals.slice(1, 5));
10 // Expected output: Array ["bison", "camel", "duck", "elephant"]
11
12 console.log(animals.slice(-2));
13 // Expected output: Array ["duck", "elephant"]
14
15 console.log(animals.slice(2, -1));
16 // Expected output: Array ["camel", "duck"]
17
18 console.log(animals.slice());
19 // Expected output: Array ["ant", "bison", "camel", "duck", "elephant"]
20

```

Run ›

Reset

Syntax

JS

```

slice()
slice(start)
slice(start, end)

```

Parameters

`start` Optional

Zero-based index at which to start extraction, [converted to an integer](#).

- Negative index counts back from the end of the array — if `start < 0`, `start + array.length` is used.
- If `start < -array.length` or `start` is omitted, `0` is used.
- If `start >= array.length`, nothing is extracted.