


MDN Plus now available in [your](#) country! Support MDN [and](#) make it your own. [Learn more](#) ✨



Element.insertAdjacentElement()

The **insertAdjacentElement()** method of the [Element](#) interface inserts a given element node at a given position relative to the element it is invoked upon.

Syntax

```
insertAdjacentElement(position, element)
```

Parameters

position

A string representing the position relative to the `targetElement` ; must match (case-insensitively) one of the following strings:

- `'beforebegin'` : Before the `targetElement` itself.
- `'afterbegin'` : Just inside the `targetElement` , before its first child.
- `'beforeend'` : Just inside the `targetElement` , after its last child.
- `'afterend'` : After the `targetElement` itself.

element

The element to be inserted into the tree.

Return value

The element that was inserted, or `null` , if the insertion failed.

Exceptions

- **SyntaxError** [DOMException](#)
 - Thrown if the `position` specified is not a recognized value.
- **TypeError**
 - Thrown if the `element` specified is not a valid element.

Visualization of position names

```
<!-- beforebegin -->
<p>
  <!-- afterbegin -->
  foo
  <!-- beforeend -->
</p>
<!-- afterend -->
```

Note: The `beforebegin` and `afterend` positions work only if the node is in a tree and has an element parent.

Examples

```
beforeBtn.addEventListener('click', () => {
  const tempDiv = document.createElement('div');
  tempDiv.style.backgroundColor = randomColor();
  if (activeElem) {
    activeElem.insertAdjacentElement('beforebegin', tempDiv);
  }
  setListener(tempDiv);
});
```

```
afterBtn.addEventListener('click', () => {
  const tempDiv = document.createElement('div');
  tempDiv.style.backgroundColor = randomColor();
  if (activeElem) {
    activeElem.insertAdjacentElement('afterend', tempDiv);
  }
  setListener(tempDiv);
});
```

Have a look at our [insertAdjacentElement.html](#) demo on GitHub (see the [source code](#) too.) Here, we have a sequence of `<div>` elements inside a container. When one is clicked, it becomes selected and you can then press the *Insert before* and *Insert after* buttons to insert new divs before or after the selected element using `insertAdjacentElement()`.

Specifications

Specification
DOM Standard # dom-element-insertadjacentelement

Browser compatibility

[Report problems with this compatibility data on GitHub](#)

	Chrome	Edge	Firefox	Opera	Safari	Chrome Android	Firefox for Android
<code>insertAdjacentElement</code>	Chrome 1	Edge 17	Firefox 48	Opera 8	Safari 3	Chrome 18 Android	Firefox 48 for Android

Tip: you can click/tap on a cell for more information.

Full support Partial support Has more compatibility info.

See also

- [Element.insertAdjacentHTML\(\)](#)
- [Element.insertAdjacentText\(\)](#)
- [Node.insertBefore\(\)](#) (similar to `beforebegin`, with different arguments)

- [Node.appendChild\(\)](#) (same effect as beforeend)

Last modified: Sep 13, 2022, [by MDN contributors](#)