

MDN Plus now available in [your](#) country! Support MDN [and](#) make it your own. [Learn more](#) ✨

Element.insertAdjacentHTML()

The **insertAdjacentHTML()** method of the [Element](#) interface parses the specified text as HTML or XML and inserts the resulting nodes into the DOM tree at a specified position.

Syntax

```
insertAdjacentHTML(position, text)
```

Parameters

position

A string representing the position relative to the element. Must be one of the following strings:

"beforebegin"

Before the element. Only valid if the element is in the DOM tree and has a parent element.

"afterbegin"

Just inside the element, before its first child.

"beforeend"

Just inside the element, after its last child.

"afterend"

After the element. Only valid if the element is in the DOM tree and has a parent element.

text

The string to be parsed as HTML or XML and inserted into the tree.

Return value

None ([undefined](#)).

Exceptions

This method may raise a [DOMException](#) of one of the following types:

NoModificationAllowedError [DOMException](#)

Thrown if **position** is "beforebegin" or "afterend" and the element either does not have a parent or its parent is the Document object.

SyntaxError [DOMException](#)

Thrown if **position** is not one of the four listed values.

Description

The `insertAdjacentHTML()` method does not reparse the element it is being used on, and thus it does not corrupt the existing elements inside that element. This avoids the extra step of serialization, making it much faster than direct [innerHTML](#) manipulation.

We can visualize the possible positions for the inserted content as follows:

```
<!-- beforebegin -->
<p>
  <!-- afterbegin -->
  foo
  <!-- beforeend -->
</p>
<!-- afterend -->
```

Security considerations

When inserting HTML into a page by using `insertAdjacentHTML()`, be careful not to use user input that hasn't been escaped.

You should not use `insertAdjacentHTML()` when inserting plain text. Instead, use the [Node.textContent](#) property or the [Element.insertAdjacentText\(\)](#) method. This doesn't interpret the passed content as HTML, but instead inserts it as raw text.

Examples

Inserting HTML

HTML

```
<select id="position">
  <option>beforebegin</option>
  <option>afterbegin</option>
  <option>beforeend</option>
  <option>afterend</option>
</select>

<button id="insert">Insert HTML</button>
<button id="reset">Reset</button>

<p>
  Some text, with a <code id="subject">code-formatted element</code> inside it.
</p>
```

CSS

```
code {
  color: red;
}
```

JavaScript

```
const insert = document.querySelector('#insert');
insert.addEventListener('click', () => {
  const subject = document.querySelector('#subject');
  const positionSelect = document.querySelector('#position');
  subject.insertAdjacentHTML(positionSelect.value, '<strong>inserted text</strong>');
});
```

```
const reset = document.querySelector('#reset');
reset.addEventListener('click', () => {
  document.location.reload();
});
```

Result

beforebegin ▼ Insert HTML Reset

Some text, with a **code-formatted element** inside it.

Specifications

Specification
DOM Parsing and Serialization # dom-element-insertadjacenthtml

Browser compatibility

[Report problems with this compatibility data on GitHub](#)

	Chrome	Edge	Firefox	Opera	Safari	Chrome Android	Firefox for Android	Opera Android
insertAdjacentHTML	Chrome 1	Edge 17	Firefox 8	Opera 8	Safari 4	Chrome 18 Android	Firefox 8 for Android	Oper Andro

Tip: you can click/tap on a cell for more information.

Full support Partial support Has more compatibility info.

See also

- [Element.insertAdjacentElement\(\)](#)
- [Element.insertAdjacentText\(\)](#)
- [XMLSerializer](#) : Serialize a DOM tree into an XML string
- [hacks.mozilla.org/guest post](#) by Henri Sivonen including benchmark showing that insertAdjacentHTML can be way faster in some cases.

Last modified: Sep 14, 2022, [by MDN contributors](#)