

String.prototype.lastIndexOf()

The **lastIndexOf()** method, given one argument: a substring to search for, searches the entire calling string, and returns the index of the last occurrence of the specified substring. Given a second argument: a number, the method returns the last occurrence of the specified substring at an index less than or equal to the specified number.

Try it

JavaScript Demo: String.lastIndexOf()

```
1 const paragraph = 'The quick brown fox jumps over the lazy dog. If the dog ba
2
3 const searchTerm = 'dog';
4
5 console.log(`The index of the first "${searchTerm}" from the end is ${paragra
6 // expected output: "The index of the first "dog" from the end is 52"
7
```

Run › Reset

Syntax

lastIndexOf(searchString)

lastIndexOf(searchString, position)

Parameters

searchString

Substring to search for, [coerced to a string](#).

If the method is called with no arguments, `searchString` is coerced to `"undefined"`. Therefore, `"undefined".lastIndexOf()` returns `0` — because the substring `"undefined"` is found at position `0` in the string `"undefined"`. But

`"undefine".lastIndexOf()`, returns `-1` — because the substring `"undefined"` is not found in the string `"undefine"`.

position Optional

The method returns the index of the last occurrence of the specified substring at a position less than or equal to `position`, which defaults to `+Infinity`. If `position` is greater than the length of the calling string, the method searches the entire string. If `position` is less than `0`, the behavior is the same as for `0` — that is, the method looks for the specified substring only at index `0`.

- `'hello world hello'.lastIndexOf('world', 4)` returns `-1` — because, while the substring `world` does occurs at index `6`, that position is not less than or equal to `4`.