

String.prototype.replace()

The **replace()** method returns a new string with one, some, or all matches of a `pattern` replaced by a `replacement`. The `pattern` can be a string or a [RegExp](#), and the `replacement` can be a string or a function called for each match. If `pattern` is a string, only the first occurrence will be replaced. The original string is left unchanged.

Try it

JavaScript Demo: String.replace()

```
1 const p = 'The quick brown fox jumps over the lazy dog. If the dog reacted, w
2
3 console.log(p.replace('dog', 'monkey'));
4 // expected output: "The quick brown fox jumps over the lazy monkey. If the d
5
6
7 const regex = /Dog/i;
8 console.log(p.replace(regex, 'ferret'));
9 // expected output: "The quick brown fox jumps over the lazy ferret. If the d
10
```

Run ›

Reset

Syntax

replace(`pattern`, `replacement`)

Parameters

`pattern`

Can be a string or an object with a [Symbol.replace](#) method — the typical example being a [regular expression](#). Any value that doesn't have the `Symbol.replace` method will be coerced to a string.

`replacement`

Can be a string or a function.

- If it's a string, it will replace the substring matched by `pattern`. A number of special replacement patterns are supported; see the [Specifying a string as the replacement](#) section below.
- If it's a function, it will be invoked for every match and its return value is used as the replacement text. The arguments supplied to this function are described in the [Specifying a function as the replacement](#) section below.