

MA5810: Introduction to Data Mining

Week 4; Collaborate Session 1: Clustering

Martha Cooper, PhD

JCU Masters of Data Science

2021-07-27

Housekeeping

- Collaborate 1 = Tuesday 6.45-8pm (Martha)
- Collaborate 2 = Thursday 6.45-8pm (Martina)

For my Collaborate Sessions, you can get the [slides & R code](#) for each week here:

<https://github.com/MarthaCooper/MA5810>



Subject: MA5810 Intro to Data Mining

MA5810 Learning Outcomes

1. Overview of Data Mining and Examples
2. Unsupervised data mining methods e.g. clustering and outlier detection;
3. Unsupervised and supervised techniques for dimensionality reduction;
4. Supervised data mining methods for pattern classification;
5. Apply these concepts to real data sets using R (Today).

Today's Goals

- Understand how K -means clustering works
- Understand how to obtain the optimal value for K
- Understand the pros and cons of K -means clustering
- Apply K -means clustering on real datasets using R

Unsupervised Learning

A set of statistical tools to understand a set of features, X_1, \dots, X_p , without having an associated response variable, Y , to predict.

Data visualization & identification of subgroups

Clustering

A broad class of methods for discovering unknown subgroups (*clusters*) within data

Why Cluster?

- Bioinformatics - identify subtypes of cancer from gene expression data
- Marketing- identify subgroups of shoppers who buy certain products

Cluster Analysis

Clustering looks to find homogeneous subgroups among the observations

Observations should be:

- similar to observations within the same cluster
- different to observations in different cluster

How do we determine these similarities & differences?


Two approaches:

- K -means clustering
- Hierarchical Clustering


K-Means Clustering

- Partition a dataset into K distinct, non-overlapping clusters
- We define the number of clusters, K , and the K -Means algorithm will assign each observation to *one* of those clusters


K=2



K=3




K=4



How does *K*-means select the best clusters?

- Minimize total within cluster variation



K clusters *n* observations *p* variables

$$\text{minimise } \left\{ \sum_{k=1}^K \sum_{i=1}^n \sum_{j=1}^p (x_{ij}^{(k)} - c_{kj})^2 \right\}$$


*j*th variable for observation *x_i* in cluster *k* centroid of cluster *k* for the *j*th variable

The sum of within cluster variation across all clusters

K-means clustering algorithm

Algorithm 10.1 *K-Means Clustering*

1. Randomly assign a number, from 1 to K , to each of the observations. These serve as initial cluster assignments for the observations.
 2. Iterate until the cluster assignments stop changing:
 - (a) For each of the K clusters, compute the cluster *centroid*. The k th cluster centroid is the vector of the p feature means for the observations in the k th cluster.
 - (b) Assign each observation to the cluster whose centroid is closest (where *closest* is defined using Euclidean distance).
-




Repeating *K*-means clustering

- Each solution depends on the *initial, random cluster assignment*
- This is called the **local optimum**
- Because of this, we should:
 1. Repeat *K*-means algorithm
 2. Select the iteration that minimizes *within cluster variation*



Choosing K



Pros and Cons

Pros

- Scales to large data sets well
- Doesn't make any assumptions about data distribution
- Generalizes to clusters of different shapes and sizes

Cons

- Subjective
- Interpretation requires domain knowledge
- Exploratory data analysis
- Difficult to assess results

K-means clustering in R

```
library(cluster, warn.conflicts = F, quietly = T) #clustering algorithms
library(factoextra, warn.conflicts = F, quietly = T) #data visualization

head(iris) #data

dat <- iris[,1:4]
dat <- na.omit(dat) #what to do if NA values?
dat_scaled <- scale(dat) #why?

set.seed(6) #why?
kmeans_res <- kmeans(dat_scaled, centers = 3, nstart = 25) #centers? nstart?
str(kmeans_res)

fviz_cluster(kmeans_res, data = dat_scaled)
```

Interpretation using domain knowledge

- What do the clusters represent?

```
fviz_cluster(kmeans_res, #set up plot
              data = dat_scaled,
              geom = "point", # only shows points and not labels
              shape = 19, # define one shape for all clusters (a circle)
              alpha = 0)+ # make circles see-through
              geom_point(aes(colour = as.factor(kmeans_res$cluster),
                                shape = iris$Species))+ #colour by species
              ggtitle("Comparing Clusters and Iris Species") #add a title
```

- Conclusion?

Choosing K in R

```
total_sum_squares <- function(k){ #perform kmeans & calculate ss
  kmeans(dat_scaled, centers = k, nstart = 25)$tot.withinss
}

all_ks <- seq(1,20,1) #define a sequence of values for k

choose_k <- sapply(seq_along(all_ks), function(i){ #apply to all values
  total_sum_squares(all_ks[i])
})

choose_k_plot <- data.frame(k = all_ks, # dataframe for plotting
                           within_cluster_variation = choose_k)

head(choose_k_plot)
ggplot(choose_k_plot, aes(x = k, # plot
                        y = within_cluster_variation))+
  geom_point()+
  geom_line()+
  xlab("Number of Clusters (K)")+
  ylab("Within Cluster Variation")
```

Extra reading

- Chapter 10.3 of James *et al.*, [ISLR](#)
- STHDA [Factoextra R Package Guide](#)

References

- James *et al.*, [ISLR](#)

Slides

- xaringan, xaringantheme, remark.js, knitr, R Markdown