KNN Algorithm Hardware Accelerator

IOB-KNN User Guide, V0.1 , Build d0731ed

December 28, 2020

`www.iobundle.com` **Confidential**

Contents

List of Tables

List of Figures

1   Introduction

The IObundle KNN core includes a configurable hardware accelerator for the KNN machine learning algorithm. It is written in Verilog and includes a C software driver. The user may change the size of the module to fit in its own FPGAs balancing the compromise between desired performance and space available. The IP is currently supported for use in FPGAs.

2   Symbol

Figure 1: IP Core Symbol

3   Features

- Verilog KNN machine learning algorithm accelerator

- C software driver.

- Reset, enable, data and test point send and neighbour read functions.

- IOb-SoC native CPU interface.

- AXI4 Lite CPU interface (premium option).

4   Benefits

- Compact hardware implementation

- Can adapt the core size to different size FPGAs

- Can adapt to the algorithm parameters of the user

- Low power consumption ???

5   Deliverables

- Verilog source code

- User documentation for easy system integration

- Example integration in IOb-SoC (premium)

- FPGA synthesis and implementation scripts (premium)

- ASIC synthesis and place and route scripts (premium)

          www.iobundle.com   **Confidential**

6 Block Diagram and Description

A high-level block diagram of the IOB-KNN core is presented in Figure 6 and a brief explanation of each block is given in Table 1.


Figure 2: High-level block diagram

Block	Description
Register File	Configuration, control and status registers accessible by the sofware
KNN core	Size ajustable N Test-Point K Neighbour KNN Accelerator
Control	State Machine controlling the KNN data flow

Table 1: Block descriptions.

7   Synthesis Parameters

In this section are explained the synthesis parameters that can be changed in order to generate a bigger or smaller module to better fit the user needs.

8   Interface Signals

The interface signals of the I^{2}S/TDM transceiver core are described in the following tables.

Name	Direction	Width	Description
clk	input	1	System clock input
rst	input	1	System reset asynchronous and active high

Table 2: General Interface Signals

Name	Direction	Width	Description
valid	input	1	Native CPU interface valid signal
address	input	ADDR_W	Native CPU interface address signal
wdata	input	WDATA_W	Native CPU interface data write signal
wstrb	input	DATA_W/8	Native CPU interface write strobe signal
rdata	output	DATA_W	Native CPU interface read data signal
ready	output	1	Native CPU interface ready signal

Table 3: CPU Native Slave Interface Signals

         `www.iobundle.com`   **Confidential**

Name	Direction	Width	Description
s_axil_awaddr	input	ADDR_W	Address write channel address
s_axil_awcache	input	4	Address write channel memory type. Transactions set with Normal Non-cacheable Modifiable and Bufferable (0011).
s_axil_awprot	input	3	Address write channel protection type. Transactions set with Normal Secure and Data attributes (000).
s_axil_awvalid	input	1	Address write channel valid
s_axil_awready	output	1	Address write channel ready
s_axil_wdata	input	DATA_W	Write channel data
s_axil_wstrb	input	DATA_W/8	Write channel write strobe
s_axil_wvalid	input	1	Write channel valid
s_axil_wready	output	1	Write channel ready
s_axil_bresp	output	2	Write response channel response
s_axil_bvalid	output	1	Write response channel valid
s_axil_bready	input	1	Write response channel ready
s_axil_araddr	input	ADDR_W	Address read channel address
s_axil_arcache	input	4	Address read channel memory type. Transactions set with Normal Non-cacheable Modifiable and Bufferable (0011).
s_axil_arprot	input	3	Address read channel protection type. Transactions set with Normal Secure and Data attributes (000).
s_axil_arvalid	input	1	Address read channel valid
s_axil_arready	output	1	Address read channel ready
s_axil_rdata	output	DATA_W	Read channel data
s_axil_rresp	output	2	Read channel response
s_axil_rvalid	output	1	Read channel valid
s_axil_rready	input	1	Read channel ready

Table 4: CPU AXI4 Lite Slave Interface Signals

9 Registers

The software accessible registers of the KNN core are described in Table 5. The table gives information on the name, read/write capability, word aligned addresses, used word bits and a textual description.

Name	R/W	Addr	Bits	Initial Value	Description
KNN_RESET	W	0x00	0:0	0	KNN soft reset
KNN_ENABLE	W	0x04	0:0	0	KNN enable
KNN_B	W	0x08	DATA_W-1:0	0	Point B coordinates
KNN_LABEL	W	0x0c	LABEL-1:0	0	Point B label
KNN_INFO	R	0x10	LABEL-1:0	0	2000 Register Bank of the neighbours' Labels
KNN_A	R	0x14	DATA_W-1:0	0	200 Point A coordinates Bank

Table 5: Software accessible registers.

10 FPGA Results

The following are FPGA implementation results for two FPGA device families.

Resource	Used
LUTs	79053
Registers	86526
DSPs	200
BRAM	0

Table 6: Kintex Ultrascale

www.iobundle.com   **Confidential**