

# Data Aggregation

How to get data insights?



**SoftUni Team**  
Technical Trainers

Software University  
<http://softuni.bg>



# Table of Content





## Grouping

Consolidating data based on criteria



## Aggregate Functions

COUNT, SUM, MAX, MIN, AVG...



## Having

Using predicates while grouping

sli.do

#JavaDB



# Grouping

Consolidating data based on criteria

# Grouping

- Grouping allows taking data into **separate groups** based on a **common property**

Grouping column

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000

Can be  
aggregated



# GROUP BY

- With **GROUP BY** you can get each **separate** group and use an "aggregate" function over it (like Average, Min or Max):

```
SELECT e.`job_title`, count(employee_id)
FROM `employees` AS e
GROUP BY e.`job_title`;
```

Grouping  
Columns

# DISTINCT

- With **DISTINCT** you will get all unique values:

```
SELECT DISTINCT e.`job_title`  
FROM `employees` AS e;
```

Unique  
Values

# Problem: Departments Total Salaries

- Write a query which prints the total **sum** of salaries for each **department** in the soft\_uni database
  - Order them by DepartmentID (ascending)

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000



department_id	total_salary
1	20,000
2	30,000
3	15,000

Check your solution here: <https://judge.softuni.bg/Contests/Practice/Index/296#18>



# Solution: Departments Total Salaries

Grouping  
Column

New Column Alias

```
SELECT e.`department_id`,  
       SUM(e.`salary`) AS 'Total Salary'  
FROM `employees` AS e  
GROUP BY e.`department_id`  
ORDER BY e.`department_id`;
```

Table Alias

Grouping  
Columns




# Aggregate Functions

COUNT, SUM, MAX, MIN, AVG...

# Aggregate Functions

- Used to operate over **one** or **more** groups performing **data analysis** on every one
  - MIN, MAX, AVG, COUNT etc.
- They usually **ignore** NULL values

```
SELECT e.`department_id`,  
       MIN(e.`salary`) AS 'MinSalary'  
FROM `employees` AS e  
GROUP BY e.`department_id`;
```




	department_id	MinSalary
▶	1	32700.0000
	2	25000.0000
	3	23100.0000
	4	13500.0000
	5	12800.0000
	6	40900.0000
	7	9500.0000

# COUNT

- **COUNT** - counts the values (not nulls) in one or more columns based on grouping criteria

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000



department_name	SalaryCount
Database Support	2
Application Support	3
Software Support	1

# COUNT Syntax

- Note that when we use **COUNT** we will ignore any employee with **NULL** salary.

```
SELECT e.`department_id`,  
       COUNT(e.`salary`) AS 'Salary Count'  
FROM `employees` AS e  
GROUP BY e.`department_id`;
```

Grouping  
Column

New Column Alias


Grouping  
Columns



# SUM

- **SUM** - sums the values in a column

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000



department_name	total_salary
Database Support	20,000
Application Support	30,000
Software Support	15,000

# SUM Syntax

- If any department has no salaries **NULL** will be displayed.

```
SELECT e.`department_id`,  
       SUM(e.`salary`) AS 'TotalSalary'  
FROM `employees` AS e  
GROUP BY e.`department_id`;
```

Grouping  
Column


New Column Alias

Table Alias

Grouping  
Columns

- **MAX** - takes the maximum value in a column.

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000



department_name	max_salary
Database Support	20,000
Application Support	30,000
Software Support	15,000

# MAX Syntax

```
SELECT e.`department_id`,  
       MAX(e.`salary`) AS 'MaxSalary'  
FROM `employees` AS e  
GROUP BY e.`department_id`;
```

Grouping  
Column

New Column Alias


Table Alias

Grouping  
Columns

# MIN

- **MIN** takes the minimum value in a column.

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000



department_name	min_salary
Database Support	5,000
Application Support	5,000
Software Support	15,000



# MIN Syntax

```
SELECT e.`department_id`,  
       MIN(e.`salary`) AS 'MinSalary'  
FROM `employees` AS e  
GROUP BY e.`department_id`;
```

Grouping  
Column


New Column Alias

Table Alias

Grouping  
Columns

- **AVG** calculates the average value in a column.

employee	department_name	salary
Adam	Database Support	5,000
John	Database Support	15,000
Jane	Application Support	10,000
George	Application Support	15,000
Lila	Application Support	5,000
Fred	Software Support	15,000



department_name	average_salary
Database Support	10,000
Application Support	10,000
Software Support	15,000

# Demo: AVG Syntax

```
SELECT e.`department_id`,  
       AVG(e.`salary`) AS 'AvgSalary'  
FROM `employees` AS e  
GROUP BY e.`department_id`;
```

Grouping  
Column

New Column Alias

Table Alias

Grouping  
Columns



# Having

Using predicates while grouping

# Having Clause

- The **HAVING** clause is used to filter data based on **aggregate** values.
  - We cannot use it **without** grouping **before** that
- Any Aggregate functions in the "**HAVING**" clause and in the "**SELECT**" statement are executed one time only
- Unlike **HAVING**, the **WHERE** clause filters rows **before** the aggregation





# Having Clause: Example

- Filter departments which have **total** salary **more or equal** 15,000.

employee	department_name	salary	Total Salary
Adam	Database Support	5,000	20,000
John	Database Support	15,000	
Jane	Application Support	10,000	10,000
George	Application Support	15,000	
Lila	Application Support	5,000	
Fred	Software Support	15,000	15,000

Aggregated value



department_name	average_salary
Database Support	10,000
Software Support	15,000

# HAVING Syntax

Aggregate  
Function

Grouping  
Column

```
SELECT e.`department_id`,  
       SUM(e.salary) AS 'TotalSalary'  
FROM `employees` AS e  
GROUP BY e.`department_id`  
HAVING `TotalSalary` < 250000;
```

New  
Column Alias

Grouping  
Columns

Having  
Predicate

# Summary

- Grouping
- Aggregate Functions
- Having

```
SELECT
    SUM(e.`salary`) AS 'TotalSalary'
FROM `employees` AS e
GROUP BY e.`department_id`
HAVING SUM(e.`salary`) < 250000;
```



Databases

# Data Aggregation



## Questions?





# License

- This course (slides, examples, demos, videos, homework, etc.) is licensed under the "Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International" license



- Attribution: this work may contain portions from
  - "Databases" course by Telerik Academy under CC-BY-NC-SA license



# Free Trainings @ Software University

- Software University Foundation – [softuni.org](http://softuni.org)
- Software University – High-Quality Education, Profession and Job for Software Developers
  - [softuni.bg](http://softuni.bg)
- Software University @ Facebook
  - [facebook.com/SoftwareUniversity](https://facebook.com/SoftwareUniversity)
- Software University Forums
  - [forum.softuni.bg](http://forum.softuni.bg)

