

AJAX and jQuery AJAX

AJAX Concepts, XMLHttpRequest,
jQuery AJAX: \$.ajax(), \$.get(), \$.post()



SoftUni Team
Technical Trainers



Software University
<http://softuni.bg>

Table of Contents

1. AJAX Concepts
2. XMLHttpRequest
3. jQuery AJAX
 - Low-Level Interface
 - Shorthand Methods
 - Global Ajax Event Handlers
 - Promise interface
4. Same-origin policy / CORS
5. AJAX – Examples
 - Accessing Firebase with AJAX



Have a Question?

sli.do

#JSCORE




AJAX

The logo features the word "AJAX" in a bold, blue, sans-serif font. A large, blue, double-headed arrow is positioned over the "J", pointing both upwards and downwards. The background is white with a faint, light blue geometric pattern of circles and lines.


AJAX

Asynchronous JavaScript And XML


The conventional model

- 
- Based on complete HTML pages
 - Each user action required that a complete new page be loaded from the server
 - Bad user experience
 - All of the content had to be re-sent, even though only some of the information had changed
 - Inefficient bandwidth use

XMLHTTP

- 
- In 1996, the **iframe** tag was introduced by **Internet Explorer**
 - In 1998, the **Microsoft Outlook Web App team** developed the concept behind the **XMLHttpRequest** scripting object. It appeared as XMLHTTP in the second version of the MSXML library, which shipped with **Internet Explorer 5.0** in March 1999
 - The functionality of the **XMLHTTP ActiveX control in IE 5** was later implemented by Mozilla, Safari, Opera and other browsers as the **XMLHttpRequest** JavaScript object
 - Microsoft adopted the native **XMLHttpRequest** model as of Internet Explorer 7

What is AJAX?

- 
- AJAX == **Asynchronous JavaScript And XML**
 - A broad group of **Web technologies** that can be used to implement a Web application that communicates with a server in the **background**, without interfering with the current state of the page
 - **HTML** (or XHTML) and **CSS** for presentation
 - The Document Object Model (**DOM**) for dynamic display of and interaction with data
 - **JSON** or **XML** for the interchange of data, and **XSLT** for its manipulation
 - The **XMLHttpRequest** object for asynchronous communication
 - **JavaScript** to bring these technologies together

AJAX Use cases

- **Partial page rendering**

- Load HTML fragment and display it in a container

- **Web service**


- Load data as **JSON** / **XML** object and visualize it with **JavaScript** / **jQuery**

- **Manipulate domain objects**

- Using **RESTful** services




AJAX: Workflow





Web Client



Web Server

Using the XMLHttpRequest Object

XMLHttpRequest – Standard API for AJAX


```
<button onclick="loadRepos()">Load Repos</button>  
<div id="res"></div>
```

```
function loadRepos() {  
  let req = new XMLHttpRequest();  
  req.onreadystatechange = function() {  
    if (this.readyState == 4 && this.status == 200)  
      document.getElementById("res").textContent =  
        this.responseText;  
  };  
  req.open("GET",  
    "https://api.github.com/users/testnakov/repos", true);  
  req.send();  
}
```

Check your code here: <https://judge.softuni.bg/Contests/357>

XMLHttpRequest – Standard API for AJAX

```
var xhr = new XMLHttpRequest();
xhr.open('GET', 'myservice/username?id=some-unique-id');
xhr.onload = function() {
    if (xhr.status === 200) {
        alert('User\'s name is ' + xhr.responseText);
    }
    else {
        alert('Request failed. Returned status of ' + xhr.status);
    }
};
xhr.send();
```



jQuery AJAX

Simplified AJAX Calls with jQuery


jQuery AJAX

- **jQuery** simplifies how developers make AJAX calls
- Low-Level Interface
 - **jQuery.ajax()** - Perform an asynchronous HTTP (Ajax) request.
 - **jQuery.ajaxPrefilter()** - Handle custom Ajax options or modify existing options before each request is sent and before they are processed by \$.ajax().
 - **jQuery.ajaxSetup()** - Set default values for future Ajax requests. Its use is **not recommended**.
 - **jQuery.ajaxTransport()** - Creates an object that handles the actual transmission of Ajax data.



jQuery AJAX

- Shorthand Methods
 - `jQuery.get()` - Load data from the server using a HTTP GET request.
 - `jQuerygetJSON()` - Load JSON-encoded data from the server using a GET HTTP request
 - `jQuery.getScript()` - Load a JavaScript file from the server using a GET HTTP request, then execute it.
 - `jQuery.post()` - Load data from the server using a HTTP POST request.
 - `.load()` - Load data from the server and place the returned HTML into the matched element.



jQuery AJAX

- Global Ajax Event Handlers
 - `.ajaxComplete()` - Register a handler to be called when Ajax requests complete
 - `.ajaxError()` - Register a handler to be called when Ajax requests complete with an error
 - `.ajaxSend()` - Attach a function to be executed before an Ajax request is sent
 - `.ajaxStart()` - Register a handler to be called when the first Ajax request begins
 - `.ajaxStop()` - Register a handler to be called when all Ajax requests have completed
 - `.ajaxSuccess()` - Attach a function to be executed whenever an Ajax request completes successfully



jQuery VS Native XMLHttpRequest - GET

```
$.ajax('myservice/username', {
  data: {
    id: 'some-unique-id'
  }
})
.then(
  function success(name) {
    alert('User\'s name is ' +
name);
  },

  function fail(data, status) {
    alert('Request failed.
Returned status of ' + status);
  }
);
```

```
var xhr = new XMLHttpRequest();
xhr.open('GET',
'myservice/username?id=some-unique-
id');
xhr.onload = function() {
  if (xhr.status === 200) {
    alert('User\'s name is ' +
xhr.responseText);
  }
  else {
    alert('Request failed.
Returned status of ' + xhr.status);
  }
};
xhr.send();
```

jQuery VS Native XMLHttpRequest - POST

```
var newName = 'John Smith';

$.ajax('myservice/username?' + $.param({id: 'some-unique-id'}), {
  method: 'POST',
  data: {
    name: newName
  }
})
.then(
  function success(name) {
    if (name !== newName) {
      alert('Something went wrong. Name is now ' + name);
    }
  },



  function fail(data, status) {
    alert('Request failed. Returned status of ' + status);
  }
);
```

```
var newName = 'John Smith',
    xhr = new XMLHttpRequest();

xhr.open('POST', 'myservice/username?id=some-unique-id');
xhr.setRequestHeader('Content-Type', 'application/x-www-form-urlencoded');
xhr.onload = function() {
  if (xhr.status === 200 && xhr.responseText !== newName) {
    alert('Something went wrong. Name is now ' + xhr.responseText);
  }
  else if (xhr.status !== 200) {
    alert('Request failed. Returned status of ' + xhr.status);
  }
};
xhr.send(encodeURIComponent('name=' + newName));
```


jQuery AJAX

- Problem: create a **page** holding a **button**
 - Clicking the button should **load an html fragment** and display it inside a **div**



AJAX jQuery.load()

Load Title



Voilla!

I am a text loaded with AJAX request

Solution: jQuery.load()

ajax-load.html

```
<div id="text">  
  <h1>AJAX jQuery.load()</h1>  
  <button onclick="loadTitle()">Load Title</button>  
</div>
```

ajax-load.js

```
function loadTitle() {  
  $('#text').load("text.html");  
}
```

text.html

```
<h1>Voilla!</h1>  
<p>I am a text loaded  
with AJAX request</p>
```

Check your solution here: <https://judge.softuni.bg/Contests/357>


Submit in the judge the JS function **loadTitle()**




Same-origin policy / CORS

Same-origin policy

- The **same-origin** policy is a critical security mechanism that restricts how a document or script loaded from one origin can interact with a resource from another origin. It helps isolate potentially malicious documents, reducing possible attack vectors
- Two URLs have the same origin if the protocol, port (if specified), and host are the same for both
- Internet Explorer has two major exceptions to the same-origin policy
 - Trust Zones
 - Port




Main request: defines origin.




Cross-Origin Resource Sharing

- Cross-Origin Resource Sharing (**CORS**) is a mechanism that uses additional **HTTP headers** to tell a browser to let a web application running at one origin (domain) have permission to access selected resources from a server at a different origin
- Specification mandates that browsers "**preflight**" the request with an **HTTP OPTIONS** request method, and then, upon "**approval**" from the server, sending the actual request with the actual **HTTP request method**



Internet Explorer

- Internet Explorer < 8 does not support cross domain ajax calls
- Internet Explorer 8 and 9 are using XMLHttpRequest object




```
if(window.XMLHttpRequest){
    var xdr = new XMLHttpRequest();
    xdr.open("get", url);
    xdr.onprogress = function () { };
    xdr.ontimeout = function () { };
    xdr.onerror = function () { };
    xdr.onload = function() {
        console.log(xdr.responseText);
    };
    setTimeout(function () {xdr.send();}, 0);
}
```

Same-origin policy

- Scripts can execute AJAX requests
 - Either to their **origin** (same-origin policy)
 - Or when the remote server explicitly allows AJAX calls via CORS

Uses a special HTTP header:
Access-Control-Allow-Origin



```
$(document).ajaxError(function(event, req, settings) {  
    $('#text').text(`Error loading data: ${req.status}  
    (${req.statusText})`);  
});  
  
function loadTitle() {  
    $('#text').load("https://softuni.bg");  
}
```

This cross-origin AJAX
request will fail due to
missing CORS headers


Problem: Load GitHub Repos with AJAX

GitHub username:

```
<input type="text" id="username" value="testnakov" />  
<button onclick="loadRepos()">Load Repos</button>
```

```
<ul id="repos"></ul>
```

```
<script>  
  function loadRepos() {  
    // AJAX call ...  
  }  
</script>
```



Solution: Load GitHub Repos with AJAX

```
function loadRepos() {  
    $("#repos").empty();  
    let url = "https://api.github.com/users/" +  
        $("#username").val() + "/repos";  
    $.ajax({ url,  
        success: displayRepos,  
        error: displayError  
    });  
    function displayRepos(respos) { ... }  
    function displayError(err) { ... }  
}
```

Solution: Load GitHub Repos with AJAX (2)

```
function displayRepos(respos) {  
  for (let repo of respos) {  
    let link = $('<a>').text(repo.full_name);  
    link.attr('href', repo.html_url);  
    $("#repos").append($('<li>').append(link));  
  }  
}  
  
function displayError(err) {  
  $("#repos").append("<li>Error</li>");  
}
```

Check your solution here: <https://judge.softuni.bg/Contests/357>




AJAX – Examples

Using jQuery to Access REST APIs

Problem: Phonebook App in Firebase

- Create a mini **phonebook JS front-end app**
 - Hold your data in **Firebase**
 - Disable the authentication to simplify your work
 - Implement "**list phones**", "**add phone**", "**delete phone**"



Phonebook

- Kiril: +359 27474332 [\[Delete\]](#)
- Maria: +359 234737343 [\[Delete\]](#)
- Todor: +359 2344733234 [\[Delete\]](#)

Load

Create Contact



Person:

Phone:


Create

Solution: Setup a Firebase DB

- Open <https://console.firebase.google.com/>
- Create a new project
- Enable public read / write access



Solution: Add Sample Data in Firebase



The screenshot shows the Firebase Realtime Database console for a project named 'phonebook-nakov'. The left sidebar contains navigation links for Analytics, Authentication, Database (selected), Storage, Hosting, Test Lab, Crash Reporting, Notifications, and Remote Config. The main area displays the 'Realtime Database' interface with tabs for DATA, RULES, USAGE, and BACKUPS. The URL bar shows the database endpoint: `https://phonebook-nakov.firebaseio.com/`. The data tree shows a root node 'phonebook-nakov' with a value of 'null'. Below it, a 'Name' node is expanded, showing a 'first' node and a 'second' node. Each of these nodes has a 'person' and a 'phone' child. The 'person' values are 'Maria' and 'Todor', and the 'phone' values are '+359 234737343' and '+359 2344733234'. Each input field has a red 'X' icon for deletion. At the bottom, there are 'CANCEL' and 'ADD' buttons.

firebase

phonebook-nakov

Analytics

DEVELOP

Authentication

Database

Storage

Hosting

Test Lab

Crash Reporting

GROW

Notifications

Remote Config

Spark
Free \$0/month

UPGRADE

Realtime Database

DATA RULES USAGE BACKUPS

`https://phonebook-nakov.firebaseio.com/`

phonebook-nakov: null

Name phonebook

Name first

Name person Value Maria

Name phone Value +359 234737343


Name second

Name person Value Todor

Name phone Value +359 2344733234

CANCEL ADD

Solution: Test Your REST Service




The screenshot displays the REST Client application interface. The top toolbar includes buttons for Runner, Import, Builder, and Team Library, along with a SYNC OFF indicator and a notification bell. The address bar shows the URL `https://phonebook-na`. The main panel is divided into tabs: GET, Headers, Body, Pre-request Script, and Tests. The GET tab is active, showing the URL `https://phonebook-nakov.firebaseio.com/phonebook.json` and a Params tab. A blue Send button and a Save button are visible. Below the tabs, there are input fields for key and value, and buttons for Bulk Edit and Presets. The Body tab is selected, showing the response status `Status: 200 OK` and time `Time: 635 ms`. The response body is displayed in a code editor with a line number margin (1-10) and a Pretty/JSON toggle. The response is a JSON array with two objects:

```
1 {  
2   "first": {  
3     "person": "Maria",  
4     "phone": "+359 234737343"  
5   },  
6   "second": {  
7     "person": "Todor",  
8     "phone": "+359 2344733234"  
9   }  
10 }
```

Solution: Phonebook in Firebase – HTML

```
<h1>Phonebook</h1>
<ul id="phonebook"></ul>
<button id="btnLoad">Load</button>

<h2>Create Contact</h2>
Person: <input type="text" id="person" />
<br>
Phone: <input type="text" id="phone" />
<br>
<button id="btnCreate">Create</button>
```



← → ↻ 🔍 phonebook-firebase.html

Phonebook

Load

Create Contact

Person:

Phone:

Create

Solution: Phonebook in Firebase – JS Code

```
$(function () {  
  $('#btnLoad').click(loadContacts);  
  $('#btnCreate').click(createContact);  
  let baseUrl =  
    'https://phonebook-nakov.firebaseio.com/phonebook';  
  function loadContacts() { ... }  
  function displayContacts(contacts) { ... }  
  function displayError(err) { ... }  
  function createContact() { ... }  
  function deleteContact(key) { ... }  
});
```

Solution: Phonebook in Firebase – JS Code

```
function loadContacts() {  
    $("#phonebook").empty();  
    $.get(baseServiceUrl + '.json')  
        .then(displayContacts)  
        .catch(displayError);  
}  
  
function displayError(err) {  
    $("#phonebook").append($("<li>Error</li>"));  
}
```

Solution: Phonebook in Firebase – JS Code

```
function displayContacts(contacts) {  
  for (let key in contacts) {  
    let person = contacts[key]['person'];  
    let phone = contacts[key]['phone'];  
    let li = $("- ");  
    li.text(person + ': ' + phone + ' ');  
    $("#phonebook").append(li);  
    li.append($("<button>Delete</button>"))  
      .click(deleteContact.bind(this, key));  
  }  
}

```

Bind the event handler with
the **current key**

Solution: Phonebook in Firebase – JS Code

```
function createContact() {  
  let newContactJSON = JSON.stringify({  
    person: $('#person').val(),  
    phone: $('#phone').val()  
  });  
  $.post(baseServiceUrl + '.json', newContactJSON)  
    .then(loadContacts)  
    .catch(displayError);  
  $('#person').val('');  
  $('#phone').val('');  
}
```

Solution: Phonebook in Firebase – JS Code

```
function deleteContact(key) {  
  let request = {  
    method: 'DELETE',  
    url: baseUrl + '/' + key + '.json'  
  };  
  $.ajax(request)  
    .then(loadContacts)  
    .catch(displayError);  
}
```

The correct contact **key** will come as parameter (due to binding)

Check your solution here: <https://judge.softuni.bg/Contests/357>



Practice: jQuery AJAX


Live Exercises in Class (Lab)

- AJAX sends asynchronous HTTP requests from JS
- jQuery simplifies how developers use AJAX

```
$.ajax({ url, method: 'GET',  
  success: displayRepos,  
  error: displayError  
});  
function displayRepos(respos) { ... }  
function displayError(err) { ... }  
}
```



Questions?



SoftUni Diamond Partners



XSsoftware



SBTech
we know sports



telenor



SoftwareGroup
doing it right

NETPEAK



SmartIT



Postbank

Решения за твоето утре

**SUPER
HOSTING**
.BG

INDEAVR

Serving the high achievers



INFRAGISTICS®

LIEBHERR



æternity



codexio

SoftUni Organizational Partners



Trainings @ Software University (SoftUni)

- Software University – High-Quality Education and Employment Opportunities
 - softuni.bg
- Software University Foundation
 - <http://softuni.foundation/>
- Software University @ Facebook
 - facebook.com/SoftwareUniversity
- Software University Forums
 - forum.softuni.bg



- This course (slides, examples, demos, videos, homework, etc.) is licensed under the "Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International" license

