# **Introduction to MIPS programs**

COMP2611: Computer Organization

- □ You will learn the following in this tutorial:
  - MIPS data types and some pseudoinstructions.
  - □ the translation of program codes between MIPS and C++.

#### **MIPS**

MIPS data types

- the definition of MIPS data types

Program codes

- text segment
- pseudoinstructions
- exercises

**Exercises** 

## Sample MIPS program

```
# We need to declare "variables" & "Arrays" used in the program in a data segment.
# - The compiler recognizes .data as the beginning of data segment
.data
h: .word 1 2 3 4
                       # h is an array of size 4, each element is a word (32 bit)
s: .word 5
# The 3 lines below let the system know the program begins here
.text
.globl start
start:
# Write your program code here
la \$s0, h # Obtain starting address of array h, s0 = x (a constant)
w $1,8($s0) # $s1 = content in memory address x + 8 = 3 = h[2]
la $s2, s
lw $s3, -12($s2)
sub $s3, $s3, $s1
sw $s3, 0($s0)
```

- □ .ascii
  - □ String (without null terminator)
- □ .asciiz
  - □ String (with null terminator)
  - □ "z" refers to zero (ASCII code for the null character)
- □ .byte
  - Byte
  - □ values can be written in either base 10 or in hex

- .half
  - □ 2 bytes
  - □ values can be written in either base 10 or in hex
  - □ Half word aligned in memory
  - □ i.e. initial byte stored at addresses divisible by 2
- □ .word
  - □ 4 bytes
  - □ values can be written in either base 10 or in hex
  - □ word-aligned in memory
  - □ i.e. initial byte stored at addresses divisible by 4
- □ .space num
  - □ Reserves num bytes of space in memory.

## **Examples**

Variable name	Data type	Initialized value	Remarks
var1:	.half	14	# A half-word storing the integer 14
array1:	.word	5 6 7 8	# same as int array1[4] = {5,6,7,8} in C++
array2:	.word	3:5	# the part before ":" in the initialized value is # the initial value of each element in the # array, and the part after ":" is the array size. # same as int array2[5] = {3,3,3,3,3} in C++
string1:	.byte	0x32 # '2' in ASCII code 0x4a # 'J' in ASCII code 0 # '\0' in ASCII code	# string type is actually an array of char (a byte) # same as char string1[3] = {'2','J','\0'} in C++
string2:	.asciiz	"2J"	# equivalent to string1
array3:	.space	10	An array of 10 bytes is allocated for array3 in memory.

#### **MIPS**

MIPS data types

- the definition of MIPS data types

### Program codes

- text segment
- pseudoinstructions
- exercises

**Exercises** 

□ Under the .text segment of a MIPS program, we usually define the label \_\_start or main for the first instruction of the program code in execution, like:

```
.text
.globl __start
start:
```

- ☐ This label is often defined as a global label using .globl. A global label is a label that can be accessed across all the code files in a multiple-file assembly program. But you don't need to know this kind of program since we will not teach it.
- □ Defining this label or any others (using .globl or not) for the first instruction is optional.

## **Program compilation to instructions**

```
swap(int v[], int k)
High-level
               {int temp:
language
                 temp = v[k]:
program
                 v[k] = v[k+1]:
(in C)
                 v[k+1] = temp:
                Compiler
Assembly
              swap:
                   muli $2, $5.4
language
                   add
                      $2. $4.$2
program
                      $15. 0($2)
(for MIPS)
                      $16. 4($2)
                      $16. 0($2)
                   SW
                      $15. 4($2)
                   SW
                   jr
                      $31
                Assembler
          00000000101000010000000000011000
Binary machine
          00000000000110000001100000100001
language
          program
          (for MIPS)
```

## **MIPS pseudoinstructions**

☐ They are MIPS assembly instructions that do not have the corresponding machine instructions. Some examples are:

Instructions	Explanation	Example	C++ Equivalent
(Load Immediate) li Rdest, Imm	Move the immediate <i>Imm</i> (constant) into register <i>Rdest</i> .	li \$v0, 5	v0 = 5;
(move) move Rdest, Rsrc1	Copy the value of <i>Rsrc1</i> into register <i>Rdest</i> .	move \$a0, \$t0	a0 = t0;

Pseudoinstructions	Translation	Example	
(Load Immediate)	addi Rdest, Rdest, small	addi \$t0, \$t0, 0x0123	
li Rdest, small (16-bits)			
(Load Immediate)	lui Rdest, upper(big)	lui \$r1, 0x0123	
li Rdest, big (32-bits)	ori Rdest, Rdest, lower(big)	ori \$r1, \$r1, 0xabcd	
e.g. 0x0123abcd			
(move) move Rdest, Rsrc1	addi Rdest, Rsrc1, 0	addi \$t0, \$s0, 0	

Question 1: Write down the shortest sequence (any one) of MIPS instructions for the following C++ code, assuming each variable is stored in a different register (you name it):

$$a = a - 1;$$

Question 2: Write down the shortest sequence (any one) of MIPS instructions for the following C++ code, assuming each variable is stored in a different register (you name it):

$$b = a * 5;$$

Question 3: Write down the shortest sequence (any one) of MIPS instructions for the following C++ code, assuming the base address of the int array A is stored in the register s0. You can use some registers for storing temporary values.

$$A[2] = A[7] + 11;$$

Question 4: Write down the MIPS instructions for the following C++ codes, assuming each variable is stored in a different register (you name it). You can use some registers for storing temporary values.

```
if (d < 4) {
  if (d == 1)
     d = d + 4;
  else ++d;
}</pre>
```

#### **MIPS**

MIPS data types

- the definition of MIPS data types

Program codes

- text segment
- pseudoinstructions
- exercises

**Exercises** 

Question 1: Write down the shortest sequence (any one) of MIPS instructions for the following C++ code, assuming the base address of the array A of int elements is stored in the register s0 and each variable is stored in a different register (you name it). You can use some registers for storing temporary values.

$$A[c++] = A[b] + 17;$$

Question 2: Write down the MIPS instructions for the following C++ codes, assuming each variable is stored in a different register (you name it). You can use some registers for storing temporary values.

```
switch (d) {
    case 1: d = d + 4;
        break;
    case 4: d = d * 2;
        break;
    default: d--;
}
```

- ☐ You have learnt:
  - MIPS data types and some pseudoinstructions.
  - □ the translation of program codes between MIPS and C++.