

LECTURE 18: LINK ANALYSIS: PAGERANK AND HITS

How to Organize the Web?

2

□ How to organize the Web?

□ First try: Human curated Web directories

□ Yahoo, DMOZ, LookSmart


□ Second try: Web Search

□ Information Retrieval investigates:

Find relevant docs in a small
and trusted set

■ Newspaper articles, Patents, etc.

□ **But:** Web is **huge**, full of untrusted documents, random things, web spam, etc.



Web Search: 2 Challenges

3

2 challenges of web search:

- (1) Web contains many sources of information

Who to “trust”?

- **Trick:** Trustworthy pages may point to each other!

- (2) What is the “best” answer to query “newspaper”?

- No single right answer

- **Trick:** Pages that actually know about newspapers might all be pointing to many newspapers

Ranking Nodes on the Graph

4


- All web pages are not equally “important”

www.joe-schmoe.com vs. www.mit.edu

- We already know:

There is large diversity
in the web-graph
node connectivity.

**Let's rank the pages by
the link structure!**



Link Analysis Algorithms

5

- **We will cover the following Link Analysis approaches** to compute importances of nodes in a graph:
 - Hubs and Authorities (HITS)
 - Page Rank

Sidenote: Various notions of node centrality: Node u

- **Degree centrality** = degree of u
- **Betweenness centrality** = #shortest paths passing through u
- **Closeness centrality** = avg. length of shortest paths from u to all other nodes of the network
- **Eigenvector centrality** = like PageRank

Link Analysis


6

- **Goal** (back to the newspaper example):
 - Don't just find newspapers. Find “experts” – pages that link in a coordinated way to good newspapers
- **Idea: Links as votes**
 - **Page is more important if it has more links**
 - In-coming links? Out-going links?

- **Hubs and Authorities**

Each page has 2 scores:

- **Quality as an expert (hub):**
 - Total sum of votes of pages it pointed to
- **Quality as an content (authority):**
 - Total sum of votes of experts
- Principle of repeated improvement




Hubs and Authorities

7

Interesting pages fall into two classes:


1. **Authorities** are pages containing useful information

- Newspaper home pages
- Course home pages
- Home pages of auto manufacturers




2. **Hubs** are pages that link to authorities

- List of newspapers
- Course bulletin
- List of US auto manufacturers



Counting in-links: Authority

8




Each page starts with hub score 1
Authorities collect their votes

(Note this is idealized example. In reality graph is not bipartite and each page has both the hub and authority score)

Expert Quality: Hub

9




Hubs collect authority scores

(Note this is idealized example. In reality graph is not bipartite and each page has both the hub and authority score)

Reweighting

10



Authorities collect hub scores

(Note this is idealized example. In reality graph is not bipartite and each page has both the hub and authority score)

Mutually Recursive Definition

11

- **A good hub links to many good authorities**
- **A good authority is linked from many good hubs**
- **Model using two scores for each node:**
 - ▣ **Hub** score and **Authority** score
 - ▣ Represented as vectors h and a

Hubs and Authorities

12

□ Each page i has 2 scores:

- Authority score: a_i
- Hub score: h_i



HITS algorithm:

□ Initialize: $a_j(0) = 1/\sqrt{n}$, $h_i(0) = 1/\sqrt{n}$

□ Then keep iterating until convergence:

- $\forall i$: Authority: $a_i(t+1) = \sum_{j \rightarrow i} h_j(t)$
- $\forall i$: Hub: $h_i(t+1) = \sum_{i \rightarrow j} a_j(t)$
- $\forall i$: Normalize:

$$\sum_i (a_i(t+1))^2 = 1, \sum_j (h_j(t+1))^2 = 1 \quad h_i = \sum_{i \rightarrow j} a_j$$



Hubs and Authorities

13

- **HITS converges to a single stable point**

- **Notation:**

 - Vector $a = (a_1 \dots, a_n)$, $h = (h_1 \dots, h_n)$

 - Adjacency matrix A ($n \times n$): $A_{ij} = 1$ if $i \rightarrow j$

- **Then** $h_i = \sum_{i \rightarrow j} a_j$

 - can be rewritten as** $h_i = \sum_j A_{ij} \cdot a_j$

- **So:** $h = A \cdot a$

- **And likewise:** $a = A^T \cdot h$

Hubs and Authorities

14

□ HITS algorithm in vector notation:

□ Set: $a_i = h_i = \frac{1}{\sqrt{n}}$

Repeat until convergence:

□ $h = A \cdot a$

□ $a = A^T \cdot h$

□ Normalize a and h

□ **Then:** $a = A^T \cdot \underbrace{(A \cdot a)}_{\text{new } h}$
new a

□ **Thus, in $2k$ steps:**

$$a = (A^T \cdot A)^k \cdot a$$

$$h = (A \cdot A^T)^k \cdot h$$

Convergence criterion:

$$\sum_i \left(h_i^{(t)} - h_i^{(t-1)} \right)^2 < \varepsilon$$

$$\sum_i \left(a_i^{(t)} - a_i^{(t-1)} \right)^2 < \varepsilon$$

a is updated (in 2 steps):

$$a = A^T (A a) = (A^T A) a$$

h is updated (in 2 steps):

$$h = A (A^T h) = (A A^T) h$$

Repeated matrix powering

Eigenvalues & Eigenvectors

15

□ Definition:

- Let $R \cdot x = \lambda \cdot x$
for some scalar λ , vector x , matrix R
- Then x is an **eigenvector**, and λ is its **eigenvalue**

□ **Fact:**

- If R is symmetric ($R_{ij} = R_{ji}$)
(in our case $R = A^T \cdot A$ and $R = A \cdot A^T$ are symmetric)
- Then R has n orthogonal unit eigenvectors $x_1 \dots x_n$ that form a basis (coordinate system) with eigenvalues $\lambda_1 \dots \lambda_n$
($|\lambda_i| \geq |\lambda_{i+1}|$)
- **Authority** a is eigenvector of $R = ATA$
associated with largest eigenvalue λ_1
- Similarly: **hub** h is eigenvector of $R = AAT$ with the largest eigenvalue

PAGERANK

Links as Votes

17

- **Still the same idea: Links as votes**
 - ▣ **Page is more important if it has more links**
 - In-coming links? Out-going links?
- **Think of in-links as votes:**
 - ▣ www.stanford.edu has 23,400 in-links
 - ▣ www.joe-schmoe.com has 1 in-link
- **Are all in-links are equal?**
 - ▣ Links from important pages count more
 - ▣ Recursive question!


PageRank: The “Flow” Model

18

- A “vote” from an important page is worth more
- A page is important if it is pointed to by other important pages
- Define a “rank” r_j for node j

$$r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$$

d_i ... out-degree of node i



“Flow” equations:

$$r_y = r_y/2 + r_a/2$$

$$r_a = r_y/2 + r_m$$

$$r_m = r_a/2$$

PageRank: Matrix Formulation

19

□ Stochastic adjacency matrix M

□ Let page j has d_j out-links

□ If $j \rightarrow i$, then $M_{ij} = \frac{1}{d_j}$ else $M_{ij} = 0$

■ M is a **column stochastic matrix**

■ Columns sum to 1

□ Rank vector r : vector with an entry per page

□ r_i is the importance score of page i

□ $\sum_i r_i = 1$

□ The flow equations can be written

$$r = M \cdot r$$

$$r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$$

Random Walk Interpretation


20

- **Imagine a random web surfer:**

- ▣ At any time t , surfer is on some page i
- ▣ At time $t + 1$, the surfer follows an out-link from i uniformly at random
- ▣ Ends up on some page j linked from i
 - ▣ Process repeats indefinitely

- **Let:**

- $\mathbf{p}(t)$... vector whose i^{th} coordinate is the prob. that the surfer is at page i at time t
 - ▣ So, $\mathbf{p}(t)$ is a probability distribution over pages



The Stationary Distribution


21

□ Where is the surfer at time $t+1$?

□ Follows a link uniformly at random

$$p(t + 1) = M \cdot p(t)$$

■ Suppose the random walk reaches a state $p(t +$



$$p(t + 1) = M \cdot p(t)$$

PageRank: How to solve?

22

Given a web graph with n nodes, where the nodes are pages and edges are hyperlinks

- Assign each node an initial page rank
 - Repeat until convergence ($\sum_i |r_i^{(t+1)} - r_i^{(t)}| < \varepsilon$)
 - ▣ Calculate the page rank of each node

$$r_j^{(t+1)} = \sum_{i \rightarrow j} \frac{r_i^{(t)}}{d_i}$$


d_i out-degree of node i

PageRank: How to solve?

23

□ Power Iteration:

- Set $r_j = 1$
- $r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$
- And iterate



	y	a	m
y	1/2	1/2	0
a	1/2	0	1
m	0	1/2	0

$$\mathbf{r}_y = \mathbf{r}_y / 2 + \mathbf{r}_a / 2$$

$$\mathbf{r}_a = \mathbf{r}_y / 2 + \mathbf{r}_m$$

$$\mathbf{r}_m = \mathbf{r}_a / 2$$

□ Example:

$$\begin{bmatrix} \mathbf{r}_y \\ \mathbf{r}_a \\ \mathbf{r}_m \end{bmatrix} = \begin{bmatrix} 1/3 & 1/3 & 5/12 & 9/24 & & 6/15 \\ 1/3 & 3/6 & 1/3 & 11/24 & \dots & 6/15 \\ 1/3 & 1/6 & 3/12 & 1/6 & & 3/15 \end{bmatrix}$$

Iteration 0, 1, 2, ...

PageRank: Three Questions


24

$$r_j^{(t+1)} = \sum_{i \rightarrow j} \frac{r_i^{(t)}}{d_i} \quad \text{or equivalently} \quad \mathbf{r} = \mathbf{M}\mathbf{r}$$

- Does this converge?
- Does it converge to what we want?
- Are results reasonable?

Does this converge?

25



$$r_j^{(t+1)} = \sum_{i \rightarrow j} \frac{r_i^{(t)}}{d_i}$$


□ **Example:**

$$\begin{array}{l} \mathbf{r}_a \\ \mathbf{r}_b \end{array} = \begin{array}{cccc} 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \end{array}$$

Iteration 0, 1, 2, ...

Does it converge to what we want?

26



$$r_j^{(t+1)} = \sum_{i \rightarrow j} \frac{r_i^{(t)}}{d_i}$$

□ **Example:**

$$\begin{matrix} r_a \\ r_b \end{matrix} = \begin{matrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \end{matrix}$$

Iteration 0, 1, 2, ...


RageRank: Problems

27

2 problems:

- (1) Some pages are **dead ends** (have no out-links)
 - ▣ Such pages cause importance to “leak out”

- (2) **Spider traps**
(all out-links are within the group)
 - ▣ Eventually spider traps absorb all importance



Problem: Spider Traps


28

□ Power Iteration:

▣ Set $r_j = 1$

▣ $r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$

■ And iterate



	y	a	m
y	1/2	1/2	0
a	1/2	0	0
m	0	1/2	1

$$\mathbf{r}_y = \mathbf{r}_y/2 + \mathbf{r}_a/2$$

$$\mathbf{r}_a = \mathbf{r}_y/2$$

$$\mathbf{r}_m = \mathbf{r}_a/2 + \mathbf{r}_m$$

□ Example:


$$\begin{bmatrix} \mathbf{r}_y \\ \mathbf{r}_a \\ \mathbf{r}_m \end{bmatrix} = \begin{array}{cccccc} 1/3 & 2/6 & 3/12 & 5/24 & & 0 \\ 1/3 & 1/6 & 2/12 & 3/24 & \dots & 0 \\ 1/3 & 3/6 & 7/12 & 16/24 & & 1 \end{array}$$

Iteration 0, 1, 2, ...

Solution: Random Teleports

29

- **The Google solution for spider traps:** **At each time step, the random surfer has two options**
 - ▣ With prob. β , follow a link at random
 - ▣ With prob. $1 - \beta$, jump to some page uniformly at random
 - ▣ Common values for β are in the range 0.8 to 0.9
- **Surfer will teleport out of spider trap within a few time steps**




Problem: Dead Ends

30

□ Power Iteration:

- Set $r_j = 1$
- $r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$
- And iterate



	y	a	m
y	$\frac{1}{2}$	$\frac{1}{2}$	0
a	$\frac{1}{2}$	0	0
m	0	$\frac{1}{2}$	0

$$r_y = r_y/2 + r_a/2$$

$$r_a = r_y/2$$

$$r_m = r_a/2$$

□ Example:


$$\begin{bmatrix} r_y \\ r_a \\ r_m \end{bmatrix} = \begin{bmatrix} 1/3 & 2/6 & 3/12 & 5/24 & & 0 \\ 1/3 & 1/6 & 2/12 & 3/24 & \dots & 0 \\ 1/3 & 1/6 & 1/12 & 2/24 & & 0 \end{bmatrix}$$

Iteration 0, 1, 2, ...



Solution: Always Teleport

31

- **Teleports:** Follow random teleport links with probability 1.0 from dead-ends
 - Adjust matrix accordingly



	y	a	m
y	$\frac{1}{2}$	$\frac{1}{2}$	0
a	$\frac{1}{2}$	0	0
m	0	$\frac{1}{2}$	0



	y	a	m
y	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{3}$
a	$\frac{1}{2}$	0	$\frac{1}{3}$
m	0	$\frac{1}{2}$	$\frac{1}{3}$

Solution: Random Jumps

32

- **Google's solution:** At each step, random surfer has two options:

- With probability β , follow a link at random
- With probability $1-\beta$, jump to some random page

- **PageRank equation** [Brin-Page, 98]

$$r_j = \sum_{i \rightarrow j} \beta \frac{r_i}{d_i} + (1 - \beta) \frac{1}{n}$$

d_i ... out-degree
of node i

The above formulation assumes that M has no dead ends. We can either preprocess matrix M (**bad!**) or explicitly follow random teleport links with probability 1.0 from dead-ends. See P. Berkhin, *A Survey on PageRank Computing*, Internet Mathematics, 2005.

PageRank & Eigenvectors

33

□ PageRank as a principal eigenvector

$$r = M \cdot r \quad \text{or equivalently} \quad r_j = \sum_i \frac{r_i}{d_i}$$

□ But we really want:

$$r_j = \beta \sum_i \frac{r_i}{d_i} + (1 - \beta) \frac{1}{n}$$

d_i ... out-degree
of node i

□ Let's define:

$$M'_{ij} = \beta M_{ij} + (1 - \beta) \frac{1}{n}$$

□ Now we get what we want:

$$r = M' \cdot r$$

□ What is $1 - \beta$?

- In practice 0.15 (5 links and jump)

Note: M is a sparse matrix but M' is dense (all entries $\neq 0$). In practice we never “materialize” M but rather we use the “sum” formulation

PageRank: The Complete Algorithm

34

See P. Berkhin, *A Survey on PageRank Computing*, Internet Mathematics, 2005.

□ Input: A and β

- Adjacency matrix A of a directed graph with spider traps and dead ends
- Parameter β

□ Output: PageRank vector r


- Set: $r_j^{(0)} = 1/n$
- **Repeat until:** $\sum_j |r_j^{(t)} - r_j^{(t-1)}| < \varepsilon$
 - $\forall j: r'_j{}^{(t)} = \sum_{i \rightarrow j} \beta \frac{r_i^{(t-1)}}{d_i}$, if in-deg. of j is 0 then $r'_j{}^{(t)} = 0$
 - Now re-insert the leaked PageRank:

$$\forall j: r_j^{(t)} = r'_j{}^{(t)} + (1 - S)/n$$

Where: $S = \sum_j r'_j{}^{(t)}$

Example

35



PageRank and HITS

36

- **PageRank and HITS are two solutions to the same problem:**
 - ▣ **What is the value of an in-link from u to v ?**
 - ▣ In the PageRank model, the value of the link depends on the **links into u**
 - ▣ In the HITS model, it depends on the value of the other links **out of u**
- **The destinies of PageRank and HITS post-1998 were very different**