
γ analysis update in $B^\pm o (K^+K^-\pi^+\pi^-)_D K^\pm$ decays

Martin Tat

Oxford LHCb

15th March 2021





Outline

- Summary of last time
- 2 Binning scheme
- 3 First look at LHCb data
- 4 BESIII double tag analysis
- Summary

Summary of last time

- $B^{\pm} \rightarrow DK^{\pm}$, $D \rightarrow K^{+}K^{-}\pi^{+}\pi^{-}$, arXiv:hep-ph/0611272
- Model independent measurement with BESIII strong phase input
- Estimate 2000 B events from LHCb Run 1 and 2
 - Benchmark: $\sigma(\gamma) = 11^{\circ}$ from model dependent fit
 - LHCb amplitude model in AmpGen, arXiv:1811.08304
- Pull study to test and optimize binning scheme
 - Simulated 1000 experiments with 2000 events each
 - Strong phases from amplitude model using MC integration

Binning scheme

• Aim: Pick binning scheme to maximize x_{\pm} and y_{\pm} sensitivity

Event yield in bin i


$$\begin{split} N_{i}^{+} &= h_{B^{+}} \Big(\bar{K}_{i} + \left(x_{+}^{2} + y_{+}^{2} \right) K_{i} + 2 \sqrt{K_{i} \bar{K}_{i}} \big(x_{+} c_{i} - y_{+} s_{i} \big) \Big) \\ N_{-i}^{+} &= h_{B^{+}} \Big(K_{i} + \left(x_{+}^{2} + y_{+}^{2} \right) \bar{K}_{i} + 2 \sqrt{K_{i} \bar{K}_{i}} \big(x_{+} c_{i} + y_{+} s_{i} \big) \Big) \\ x_{\pm} &= r_{B} \cos(\delta_{B} \pm \gamma), \quad y_{\pm} = r_{B} \sin(\delta_{B} \pm \gamma) \end{split}$$

- Previously: Rectangular parameterization of 5D phase space
- Better and simpler:
 - Generate C++ source code for amplitude model using AmpGen
 - Evaluate amplitude directly in analysis
 - Decide bin based on strong phase and amplitude ratio directly

Strong phase and amplitude ratio

$$\mathcal{A}(D^0)/\mathcal{A}(\bar{D^0}) = r_D \exp(i\delta_D)$$

Naive ampltiude binning scheme



Optimize bin widths


- Optimize x_{\pm} , y_{\pm} sensitivity
- ullet Vary bin edges, keep symmetric around $\delta_D=0$

Binning Q value


$$\begin{split} Q^2 &= 1 - \sum_i \frac{\kappa_i \bar{K}_i (1 - c_i^2 - s_i^2)}{N_i} / \sum_i K_i \\ Q^2 &\approx \sum_i N_i (c_i^2 + s_i^2) / \sum_i N_i \end{split}$$

• Can achieve $Q \approx 0.90$ with 8 bins \implies expect $\sigma(\gamma) = 12^{\circ}$

Variable widths binning scheme




Pull study with variable widths binning



Achieved γ precision of $\sigma(\gamma) = 12^{\circ}$

Binning along r_D


- \bullet Further optimization by binning along r_D
- Claim: Can use **same** c_i and s_i in bin i and i'
- Can push $\sigma(\gamma)$ down by $0.5^{\circ}-1^{\circ}$




First look at LHCb data

- DaVinci scripts from $K_S\pi^+\pi^-$ analysis
- Have obtained full Run 2 data and MC
- DaVinci issues with Run 1, unable to run DecayTreeFitter
- Event selection:
 - Initial rectangular cuts
 - Gradient Boosted Decision Tree
 - Final cuts
 - Mass fit

First look at LHCb data






BDT sample preparation

- Signal training sample: $B \to D\pi$ MC samples
- Background training sample: High mass sideband in data
 - $5800 \, \text{MeV} < m(Dh) < 7000 \, \text{MeV}$
- Signal region: $5080 \,\mathrm{MeV} < m(Dh) < 5800 \,\mathrm{MeV}$
- Initial cuts:
 - Standard trigger requirements
 - Bachelor $P < 100 \, \text{GeV}$ and has RICH
 - ullet K $^{\pm}$ daughters $P < 100\,\mathrm{GeV}$ and has RICH
 - DecayTreeFitter convergence
 - $|m(D) m_{PDG}(D)| < 25 \,\text{MeV}$

BDT training




(b) BDT output on a logarithmic scale

Final selection


- PID cut for bachelor at 4
 - Bach_PIDK > 4 for $B \rightarrow DK$
 - Bach_PIDK < 4 for $B \to D\pi$
- K^{\pm} daughter PID cut at -5
- DecayTreeFitter $\ln\left(\chi^2\right) < 3$
- *B-D* flight significance at 0.5
- BDT working point at 0.75
- Not optimized yet

Mass plots after final selection



Mass fit


- Signal shape: Double Crystal Ball
 - ullet Tail parameters taken from fit to MC $B o D\pi$
 - Width and mean is floated



Mass fit

- Combinatorial background: Exponential curve
- Partially reconstructed background:
 - Shape parameters taken from LHCb-ANA-2017-057.1
 - $B^{\pm} \rightarrow (D^{*0} \rightarrow D^0[\pi^0])\pi^{\pm}$: HORNSdini
 - $B^0 \rightarrow (D^{*\pm} \rightarrow D^0[\pi^{\mp}])\pi^{\pm}$: HORNSdini
 - $B^{\pm} \rightarrow D^0 \rightarrow (\rho^{\pm} \rightarrow \pi^{\pm} [\pi^0]) \pi^{\pm}$: HORNSdini
 - $B^{\pm} \rightarrow (D^{*0} \rightarrow D^0[\gamma])\pi^{\pm}$: HILLdini
- Further complication for $B \rightarrow DK$ mode:
 - Cross-feed from $B \to D\pi$: Double Crystal Ball with same tail parameters as signal for now
 - Mis-ID of partially reconstructed background: Haven't considered yet, absorb into a Gaussian for now


Mass fit plots



- Signal
- Partially reconstructed background
- Combinatorial background (dashed)
- Cross feed
- Mis-ID of partially reconstructed background


BESIII double tag analysis

Produce *D* mesons through $e^+e^- \rightarrow \psi(3770) \rightarrow D^0\bar{D^0}$:




BESIII double tag analysis

Double tagged signal $(K^+K^-\pi^+\pi^-)$ with known CP tag $(\pi^+\pi^-)$



BESIII double tag analysis

Single tagged
$$(\pi^+\pi^-)$$



Double tag method

•
$$M_i = h(K_i \mp 2c_i\sqrt{K_i\bar{K}_i} + \bar{K}_i)$$


•
$$M_{ij} = h(K_i\bar{K}_j + \bar{K}_iK_j - 2\sqrt{K_i\bar{K}_iK_j\bar{K}_j}(c_ic_j + s_is_j))$$

• Normalization constant h depends on single tagged yields

Double tag progress


- Implemented 14 tag modes so far, with another 5 to come (full list in backup slides)
- Run over the full 2010+2011 MC $D^0\bar{D^0}$ dataset
- Single tagged yield:
 - Fit $m_{BC} = \sqrt{E_{\text{beam}}^2 \mathbf{p}_D^2}$
 - Double Crystal Ball for signal
 - Argus PDF for background
- Double tagged yield
 - $\Delta E = E_D E_{\text{beam}}$ cut
 - ullet Fit double Gaussian and 2nd order polynomial to ΔE
 - Cut at $[-3\sigma, 3\sigma]$ ($[-4\sigma, 3\sigma]$ for π^0 modes)
 - Subtract flat background from sidebands

ΔE fits




See backup for other tag modes

M_{BC} fits



(a) $KK\pi\pi$ beam constrained mass



(b) $\pi\pi\pi^0$ beam constrained mass

Summary

Summary:

- Binning scheme is satisfactory
- Started mass fits with LHCb data
- Most tag modes in BESIII analysis are ready

Next steps:


- Understand partially reconstructed backgrounds in LHCb data
- Finish implementing all tag modes in BESIII analysis, analyse peaking backgrounds

Backup slides: DaVinci error

DaVinci error message:


```
BZDPL_DZKKPIPL... INFO 'upleTolobecayFreefitter:: The INFO message is suppressed : Renaming duplicate to Bu_constDBPV_0B_plplus_0'
BZDPL_DZKKPIPL... INFO 'upleTolobecayFreeFitter:: The INFO message is suppressed : Renaming duplicate to Bu_constDBPV_0B_plplus_1'
BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_1D : BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_1D : StatusCode=FAILURE
BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_1D : StatusCode=FAILURE
BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_1D : StatusCode=FAILURE
BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_1D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_1D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TUpleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_0D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TupleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_0D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TupleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_0D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TupleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_0D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TupleTolobecayFreeFitter:: Tuple entry error : Bu_constDBPV_0B_plplus_1D : Bu_constDBPV_0B_plplus_0D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TupleTolobecayFreeFitter: Tuple entry error : Bu_constDBPV_0B_plplus_0D : Dplus_0D : STATUSCODEFAILURE
BZDPL_DZKKPIPL... ERROR TupleTolobecayFreeFitter: Tuple entry error : Bu_cons
```


Backup slides: Pull study naive amplitude binning




Backup slides: List of tag modes

- Flavour tags:
 - Κπ. Κππ⁰
- CP tags:
 - KK, ππ, πππ⁰
 - $K_S\pi^0$, $K_S\pi^0\pi^0$, $K_S^0\eta$, $K_S^0\eta'(\pi\pi\eta)$, $K_S^0\eta'(\rho\gamma)$
 - $K_S^0 \omega(\pi \pi \pi^0)$, $K_S^0 \eta(\pi \pi \pi^0)$, $K_S^0 \phi$
 - $K_{S}^{0}\pi^{+}\pi^{-}$
 - $K^+K^-\pi^+\pi^-$
- Will also include:
 - Κπππ, Κεν_ε
 - $K_L \pi^0$, $K_L \pi^0 \pi^0$, $K_L \omega$







(a) $K\pi$ tag




(b) $K\pi\pi^0$ tag




(a) $K_S\pi^0$ tag




(b) $K_S \pi^0 \pi^0 tag$



(a) $K_S\eta$ tag



(b) $K_S \eta'(\pi \pi \eta)$ tag



KSpipipiO Single Tag Δ E

40000

35000

25000

10000

10000

5000

10000

5000

10000

5000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

10000

(b) $K_S(\eta,\omega)(\pi\pi\pi^0)$ tag

