

1	Setup	1
1.1	header.h	1
1.2	Bash for c++ compile with header.h	1
1.3	Bash for run tests c++ . .	1
1.4	Bash for run tests python .	1
1.4.1	Auxiliary helper stuff	2
2	Python	2
2.1	Graphs	2
2.1.1	BFS	2
2.1.2	Dijkstra	2
2.2	Dynamic Programming . .	2
2.3	Trees	2
2.4	Number Theory / Combinatorics	2
2.4.1	nCk % prime	2
2.5	Strings	2
2.5.1	LCS	2
2.6	Geometry	3
2.7	Other Algorithms	3
2.7.1	Rotate matrix	3
2.8	Other Data Structures . . .	3
2.8.1	Segment Tree	3
2.9	Other Mathematics	3
3	C++	3
3.1	Graphs	3
3.1.1	BFS	3
3.1.2	DFS	3

1 Setup

1.1 header.h

```
1 #pragma once
2 #include <bits/stdc++.h>
3 using namespace std;
4
5 #define ll long long
6 #define ull unsigned ll
7 #define ld long double
8 #define pl pair<ll, ll>
9 #define pi pair<int, int>
10 #define vl vector<ll>
11 #define vi vector<int>
12 #define vvi vector<vi>
13 #define vvl vector<vl>
14 #define vpl vector<pl>
15 #define vpi vector<pi>
16 #define vld vector<ld>
```

3.1.3	Dijkstra	4
3.1.4	Floyd-Warshall . . .	4
3.1.5	Kruskal	4
3.1.6	Hungarian algorithm	4
3.2	Dynamic Programming . .	5
3.2.1	Longest Increasing Subsequence	5
3.3	Trees	5
3.4	Number Theory / Combinatorics	5
3.4.1	Modular exponentiation	5
3.4.2	GCD	6
3.4.3	Sieve of Eratosthenes	6
3.4.4	Fibonacci % prime .	6
3.4.5	nCk % prime	6
3.5	Strings	6
3.5.1	Aho-Corasick algorithm	6
3.6	Geometry	7
3.6.1	essentials.cpp	7
3.6.2	Convex Hull	7
3.7	Other Algorithms	7
3.8	Other Data Structures . . .	7
3.8.1	Disjoint set	7
3.8.2	Fenwick tree	8
3.9	Other Mathematics	8

```
17 #define in(el, cont) (cont.find(el) != cont.end())
18
19 constexpr int INF = 2000000010;
20 constexpr ll LLINF = 90000000000000000010LL;
21
22 template <typename T, template <typename ELEM, typename ALLOC = std::
    allocator<ELEM> > class Container>
23 std::ostream& operator<<(std::ostream& o, const Container<T>& container) {
24     typename Container<T>::const_iterator beg = container.begin();
25     if (beg != container.end()) {
26         o << *beg++;
27         while (beg != container.end()) {
28             o << " " << *beg++;
29         }
30     }
31     return o;
32 }
33
34 // int main() {
35 //     ios::sync_with_stdio(false); // do not use cout + printf
36 //     cin.tie(NULL);
37 //     cout << fixed << setprecision(12);
38 //     return 0;
39 // }
```

1.2 Bash for c++ compile with header.h

```
1 #!/bin/bash
2 if [ $# -ne 1 ];then echo "Usage: $0 <input_file>"; exit 1;fi
3 f="$1";d=code;/o=a.out
4 [ -f $d/$f ] || { echo "Input file not found: $f"; exit 1; }
5 g++ -I$d $d/$f -o $o && echo "Compilation successful. Executable '$o'
    created." || echo "Compilation failed."
```

1.3 Bash for run tests c++

```
1 g++ $1/$1.cpp -o $1/$1.out
2 for file in $1/*.in; do diff <($1/$1.out < "$file") "${file%.in}.ans"; done
```

1.4 Bash for run tests python

```
1 for file in $1/*.in; do diff <(python3 $1/$1.py < "$file") "${file%.in}.ans
    "; done
```

1.4.1 Auxiliary helper stuff

```
1 #include "header.h"
2
3 int main() {
4     // Read in a line including white space
5     string line;
6     getline(cin, line);
7     // When doing the above read numbers as follows:
8     int n;
9     getline(cin, line);
10    stringstream ss(line);
11    ss >> n;
12
13    // Count the number of 1s in binary represnatation of a number
14    ull number;
15    __builtin_popcountll(number);
16 }
```

2 Python

2.1 Graphs

2.1.1 BFS

```
1 from collections import deque
2 def bfs(g, roots, n):
3     q = deque(roots)
4     explored = set(roots)
5     distances = [float("inf")]*n
6     distances[0][0] = 0
7
8     while len(q) != 0:
9         node = q.popleft()
10        if node in explored: continue
11        explored.add(node)
12        for neigh in g[node]:
13            if neigh not in explored:
14                q.append(neigh)
15                distances[neigh] = distances[node] + 1
16    return distances
```

2.1.2 Dijkstra

```
1 from heapq import *
2 def dijkstra(n, root, g): # g = {node: (cost, neigh)}
3     dist = [float("inf")]*n
4     dist[root] = 0
5     prev = [-1]*n
6
7     pq = [(0, root)]
8     heapify(pq)
9     visited = set([])
10
11    while len(pq) != 0:
```

```
12    _, node = heappop(pq)
13
14    if node in visited: continue
15    visited.add(node)
16
17    # In case of disconnected graphs
18    if node not in g:
19        continue
20
21    for cost, neigh in g[node]:
22        alt = dist[node] + cost
23        if alt < dist[neigh]:
24            dist[neigh] = alt
25            prev[neigh] = node
26            heappush(pq, (alt, neigh))
27    return dist
```

2.2 Dynamic Programming

2.3 Trees

2.4 Number Theory / Combinatorics

2.4.1 nCk % prime

```
1 # Note: p must be prime and k < p
2 def fermat_binom(n, k, p):
3     if k > n:
4         return 0
5     # calculate numerator
6     num = 1
7     for i in range(n-k+1, n+1):
8         num *= i % p
9     num %= p
10    # calculate denominator
11    denom = 1
12    for i in range(1, k+1):
13        denom *= i % p
14    denom %= p
15    # numerator * denominator^(p-2) (mod p)
16    return (num * pow(denom, p-2, p)) % p
```

2.5 Strings

2.5.1 LCS

```
1 def longestCommonSubsequence(text1, text2): # O(m*n) time, O(m) space
2     n = len(text1)
3     m = len(text2)
4
5     # Initializing two lists of size m
6     prev = [0] * (m + 1)
7     cur = [0] * (m + 1)
8
9     for idx1 in range(1, n + 1):
```

```

10     for idx2 in range(1, m + 1):
11         # If characters are matching
12         if text1[idx1 - 1] == text2[idx2 - 1]:
13             cur[idx2] = 1 + prev[idx2 - 1]
14         else:
15             # If characters are not matching
16             cur[idx2] = max(cur[idx2 - 1], prev[idx2])
17
18     prev = cur.copy()
19
20     return cur[m]

```

2.6 Geometry

2.7 Other Algorithms

2.7.1 Rotate matrix

```

1 def rotate_matrix(m):
2     return [[m[j][i] for j in range(len(m))] for i in range(len(m[0])
3             -1,-1,-1)]

```

2.8 Other Data Structures

2.8.1 Segment Tree

```

1 N = 100000 # limit for array size
2 tree = [0] * (2 * N) # Max size of tree
3
4 def build(arr, n): # function to build the tree
5     # insert leaf nodes in tree
6     for i in range(n):
7         tree[n + i] = arr[i]
8
9     # build the tree by calculating parents
10    for i in range(n - 1, 0, -1):
11        tree[i] = tree[i << 1] + tree[i << 1 | 1]
12
13 def updateTreeNode(p, value, n): # function to update a tree node
14     # set value at position p
15     tree[p + n] = value
16     p = p + n
17
18     i = p # move upward and update parents
19     while i > 1:
20         tree[i >> 1] = tree[i] + tree[i ^ 1]
21         i >>= 1
22
23 def query(l, r, n): # function to get sum on interval [l, r]
24     res = 0
25     # loop to find the sum in the range
26     l += n
27     r += n
28     while l < r:
29         if l & 1:
30             res += tree[l]

```

```

31         l += 1
32         if r & 1:
33             r -= 1
34             res += tree[r]
35         l >>= 1
36         r >>= 1
37     return res

```

2.9 Other Mathematics

3 C++

3.1 Graphs

3.1.1 BFS

```

1 #include "header.h"
2 #define graph unordered_map<ll, unordered_set<ll>>
3 vi bfs(int n, graph& g, vi& roots) {
4     vi parents(n+1, -1); // nodes are 1..n
5     unordered_set<int> visited;
6     queue<int> q;
7     for (auto x: roots) {
8         q.emplace(x);
9         visited.insert(x);
10    }
11    while (not q.empty()) {
12        int node = q.front();
13        q.pop();
14
15        for (auto neigh: g[node]) {
16            if (not in(neigh, visited)) {
17                parents[neigh] = node;
18                q.emplace(neigh);
19                visited.insert(neigh);
20            }
21        }
22    }
23    return parents;
24 }
25 vi reconstruct_path(vi parents, int start, int goal) {
26     vi path;
27     int curr = goal;
28     while (curr != start) {
29         path.push_back(curr);
30         if (parents[curr] == -1) return vi(); // No path, empty vi
31         curr = parents[curr];
32     }
33     path.push_back(start);
34     reverse(path.begin(), path.end());
35     return path;
36 }

```

3.1.2 DFS Cycle detection / removal

```

1 #include "header.h"
2 void removeCyc(ll node, unordered_map<ll, vector<pair<ll, ll>>>& neighs,
   vector<bool>& visited,
3 vector<bool>& recStack, vector<ll>& ans) {
4     if (!visited[node]) {
5         visited[node] = true;
6         recStack[node] = true;
7         auto it = neighs.find(node);
8         if (it != neighs.end()) {
9             for (auto util: it->second) {
10                 ll nnode = util.first;
11                 if (recStack[nnode]) {
12                     ans.push_back(util.second);
13                 } else if (!visited[nnode]) {
14                     removeCyc(nnode, neighs, visited, recStack, ans);
15                 }
16             }
17         }
18     }
19     recStack[node] = false;
20 }

```

3.1.3 Dijkstra

```

1 #include "header.h"
2 vector<int> dijkstra(int n, int root, map<int, vector<pair<int, int>>>& g) {
3     unordered_set<int> visited;
4     vector<int> dist(n, INF);
5     priority_queue<pair<int, int>> pq;
6     dist[root] = 0;
7     pq.push({0, root});
8     while (!pq.empty()) {
9         int node = pq.top().second;
10        int d = -pq.top().first;
11        pq.pop();
12
13        if (in(node, visited)) continue;
14        visited.insert(node);
15
16        for (auto e : g[node]) {
17            int neigh = e.first;
18            int cost = e.second;
19            if (dist[neigh] > dist[node] + cost) {
20                dist[neigh] = dist[node] + cost;
21                pq.push({-dist[neigh], neigh});
22            }
23        }
24    }
25    return dist;
26 }

```

3.1.4 Floyd-Warshall

```

1 #include "header.h"
2 // g[i][j] = inf if not path from i to j
3 // if g[i][i] < 0, i is contained in a negative cycle

```

```

4 void warshall(vvl g) {
5     for (int i=0; i<g.size(); ++i) {
6         for (int j=0; j<g.size(); ++j) {
7             for (int k=0; k<g.size(); ++k) {
8                 if (g[i][k] < LLINF and g[k][j] < LLINF and g[i][j] > g[i][k]
9                     + g[k][j]) {
10                    g[i][j] = g[i][k] + g[k][j];
11                }
12            }
13        }
14    }
15 }

```

3.1.5 Kruskal Minimum spanning tree of undirected weighted graph

```

1 #include "header.h"
2 #include "disjoint_set.h"
3 // O(E log E)
4 pair<set<pair<ll, ll>>, ll> kruskal(vector<tuple<ll, ll, ll>>& edges, ll n)
5 {
6     set<pair<ll, ll>> ans;
7     ll cost = 0;
8
9     sort(edges.begin(), edges.end());
10    DisjointSet<ll> fs(n);
11
12    ll dist, i, j;
13    for (auto edge: edges) {
14        dist = get<0>(edge);
15        i = get<1>(edge);
16        j = get<2>(edge);
17
18        if (fs.find_set(i) != fs.find_set(j)) {
19            fs.union_sets(i, j);
20            ans.insert({i, j});
21            cost += dist;
22        }
23    }
24    return pair<set<pair<ll, ll>>, ll> {ans, cost};
25 }

```

3.1.6 Hungarian algorithm

```

1 #include "header.h"
2
3 template <class T> bool ckmin(T &a, const T &b) { return b < a ? a = b, 1 :
4     0; }
5 /**
6  * Given J jobs and W workers (J <= W), computes the minimum cost to assign
7  * each
8  * prefix of jobs to distinct workers.
9  * @tparam T a type large enough to represent integers on the order of J *
10 * max(|C|)
11 * @param C a matrix of dimensions JxW such that C[j][w] = cost to assign j-
12 * th
13 * job to w-th worker (possibly negative)
14 *
15 * @return a vector of length J, with the j-th entry equaling the minimum
16 * cost
17 * to assign the first (j+1) jobs to distinct workers
18 */

```

```

14  */
15  template <class T> vector<T> hungarian(const vector<vector<T>> &C) {
16      const int J = (int)size(C), W = (int)size(C[0]);
17      assert(J <= W);
18      // job[w] = job assigned to w-th worker, or -1 if no job assigned
19      // note: a W-th worker was added for convenience
20      vector<int> job(W + 1, -1);
21      vector<T> ys(J), yt(W + 1); // potentials
22      // -yt[W] will equal the sum of all deltas
23      vector<T> answers;
24      const T inf = numeric_limits<T>::max();
25      for (int j_cur = 0; j_cur < J; ++j_cur) { // assign j_cur-th job
26          int w_cur = W;
27          job[w_cur] = j_cur;
28          // min reduced cost over edges from Z to worker w
29          vector<T> min_to(W + 1, inf);
30          vector<int> prv(W + 1, -1); // previous worker on alternating path
31          vector<bool> in_Z(W + 1); // whether worker is in Z
32          while (job[w_cur] != -1) { // runs at most j_cur + 1 times
33              in_Z[w_cur] = true;
34              const int j = job[w_cur];
35              T delta = inf;
36              int w_next;
37              for (int w = 0; w < W; ++w) {
38                  if (!in_Z[w]) {
39                      if (ckmin(min_to[w], C[j][w] - ys[j] - yt[w]))
40                          prv[w] = w_cur;
41                      if (ckmin(delta, min_to[w])) w_next = w;
42                  }
43              }
44              // delta will always be non-negative,
45              // except possibly during the first time this loop runs
46              // if any entries of C[j_cur] are negative
47              for (int w = 0; w <= W; ++w) {
48                  if (in_Z[w]) ys[job[w]] += delta, yt[w] -= delta;
49                  else min_to[w] -= delta;
50              }
51              w_cur = w_next;
52          }
53          // update assignments along alternating path
54          for (int w; w_cur != W; w_cur = w) job[w_cur] = job[w = prv[w_cur]];
55          answers.push_back(-yt[W]);
56      }
57      return answers;
58 }

```

3.2 Dynamic Programming

3.2.1 Longest Increasing Subsequence

```

1  #include "header.h"
2  template<class T>
3  vector<T> index_path_lis(vector<T>& nums) {
4      int n = nums.size();
5      vector<T> sub;
6      vector<int> subIndex;
7      vector<T> path(n, -1);
8      for (int i = 0; i < n; ++i) {

```

```

9          if (sub.empty() || sub[sub.size() - 1] < nums[i]) {
10             path[i] = sub.empty() ? -1 : subIndex[sub.size() - 1];
11             sub.push_back(nums[i]);
12             subIndex.push_back(i);
13             } else {
14                 int idx = lower_bound(sub.begin(), sub.end(), nums[i]) - sub.begin();
15                 path[i] = idx == 0 ? -1 : subIndex[idx - 1];
16                 sub[idx] = nums[i];
17                 subIndex[idx] = i;
18             }
19         }
20         vector<T> ans;
21         int t = subIndex[subIndex.size() - 1];
22         while (t != -1) {
23             ans.push_back(t);
24             t = path[t];
25         }
26         reverse(ans.begin(), ans.end());
27         return ans;
28     }
29     // Length only
30     template<class T>
31     int length_lis(vector<T> &a) {
32         set<T> st;
33         typename set<T>::iterator it;
34         for (int i = 0; i < a.size(); ++i) {
35             it = st.lower_bound(a[i]);
36             if (it != st.end()) st.erase(it);
37             st.insert(a[i]);
38         }
39         return st.size();
40     }

```

3.3 Trees

3.4 Number Theory / Combinatorics

3.4.1 Modular exponentiation Or use pow() in python

```

1  #include "header.h"
2  ll mod_pow(ll base, ll exp, ll mod) {
3      if (mod == 1) return 0;
4      if (exp == 0) return 1;
5      if (exp == 1) return base;
6
7      ll res = 1;
8      base %= mod;
9      while (exp) {
10         if (exp % 2 == 1) res = (res * base) % mod;
11         exp >>= 1;
12         base = (base * base) % mod;
13     }
14
15     return res % mod;
16 }

```

3.4.2 GCD Or use math.gcd() in python

```
1 #include "header.h"
2 ll gcd(ll a, ll b) {
3     if (a == 0) {
4         return b;
5     }
6     return gcd(b % a, a);
7 }
```

3.4.3 Sieve of Eratosthenes

```
1 #include "header.h"
2
3 vector<ll> primes;
4 void getprimes(ll n) {
5     vector<bool> p(n, true);
6     p[0] = false;
7     p[1] = false;
8     for(ll i = 0; i < n; i++) {
9         if(p[i]) {
10             primes.push_back(i);
11             for(ll j = i*2; j < n; j+=i) {
12                 p[j] = false;
13             }
14         }
15     }
16 }
```

3.4.4 Fibonacci % prime

```
1 #include "header.h"
2 const ll MOD = 1000000007;
3 unordered_map<ll, ll> Fib;
4 ll fib(ll n) {
5     if (n < 2) return 1;
6     if (Fib.find(n) != Fib.end()) return Fib[n];
7     Fib[n] = (fib((n + 1) / 2) * fib(n / 2) + fib((n - 1) / 2) * fib((n - 2) / 2)) % MOD;
8     return Fib[n];
9 }
```

3.4.5 nCk % prime

```
1 #include "header.h"
2 ll binom(ll n, ll k) {
3     ll ans = 1;
4     for(ll i = 1; i <= min(k, n-k); ++i) ans = ans*(n+1-i)/i;
5     return ans;
6 }
7 ll mod_nCk(ll n, ll k, ll p ){
8     ll ans = 1;
9     while(n){
10         ll np = n%p, kp = k%p;
11         if(kp > np) return 0;
```

```
12         ans *= binom(np, kp);
13         n /= p; k /= p;
14     }
15     return ans;
16 }
```

3.5 Strings

3.5.1 Aho-Corasick algorithm Also can be used as Knuth-Morris-Pratt algorithm

```
1 #include "header.h"
2
3 map<char, int> cti;
4 int cti_size;
5 template <int ALPHABET_SIZE, int (*mp)(char)>
6 struct AC_FSM {
7     struct Node {
8         int child[ALPHABET_SIZE], failure = 0, match_par = -1;
9         vi match;
10         Node() { for (int i = 0; i < ALPHABET_SIZE; ++i) child[i] = -1; }
11     };
12     vector<Node> a;
13     vector<string> &words;
14     AC_FSM(vector<string> &words) : words(words) {
15         a.push_back(Node());
16         construct_automaton();
17     }
18     void construct_automaton() {
19         for (int w = 0, n = 0; w < words.size(); ++w, n = 0) {
20             for (int i = 0; i < words[w].size(); ++i) {
21                 if (a[n].child[mp(words[w][i])] == -1) {
22                     a[n].child[mp(words[w][i])] = a.size();
23                     a.push_back(Node());
24                 }
25                 n = a[n].child[mp(words[w][i])];
26             }
27             a[n].match.push_back(w);
28         }
29         queue<int> q;
30         for (int k = 0; k < ALPHABET_SIZE; ++k) {
31             if (a[0].child[k] == -1) a[0].child[k] = 0;
32             else if (a[0].child[k] > 0) {
33                 a[a[0].child[k]].failure = 0;
34                 q.push(a[0].child[k]);
35             }
36         }
37         while (!q.empty()) {
38             int r = q.front(); q.pop();
39             for (int k = 0, arck; k < ALPHABET_SIZE; ++k) {
40                 if ((arck = a[r].child[k]) != -1) {
41                     q.push(arck);
42                     int v = a[r].failure;
43                     while (a[v].child[k] == -1) v = a[v].failure;
44                     a[arck].failure = a[v].child[k];
45                     a[arck].match_par = a[v].child[k];
46                     while (a[arck].match_par != -1
47                             && a[a[arck].match_par].match.empty())
48                         a[arck].match_par = a[a[arck].match_par].match_par;
```

```

49     }
50 }
51 }
52 }
53 void aho_corasick(string &sentence, vvi &matches){
54     matches.assign(words.size(), vi());
55     int state = 0, ss = 0;
56     for (int i = 0; i < sentence.length(); ++i, ss = state) {
57         while (a[ss].child[mp(sentence[i])] == -1)
58             ss = a[ss].failure;
59         state = a[state].child[mp(sentence[i])]
60             = a[ss].child[mp(sentence[i])];
61         for (ss = state; ss != -1; ss = a[ss].match_par)
62             for (int w : a[ss].match)
63                 matches[w].push_back(i + 1 - words[w].length());
64     }
65 }
66 };
67 int char_to_int(char c) {
68     return cti[c];
69 }

```

3.6 Geometry

3.6.1 essentials.cpp

```

1 #include "../header.h"
2 using C = ld; // could be long long or long double
3 constexpr C EPS = 1e-10; // change to 0 for C=ll
4 struct P { // may also be used as a 2D vector
5     C x, y;
6     P(C x = 0, C y = 0) : x(x), y(y) {}
7     P operator+ (const P &p) const { return {x + p.x, y + p.y}; }
8     P operator- (const P &p) const { return {x - p.x, y - p.y}; }
9     P operator* (C c) const { return {x * c, y * c}; }
10    P operator/ (C c) const { return {x / c, y / c}; }
11    C operator* (const P &p) const { return x*p.x + y*p.y; }
12    C operator^ (const P &p) const { return x*p.y - p.x*y; }
13    P perp() const { return P{y, -x}; }
14    C lensq() const { return x*x + y*y; }
15    ld len() const { return sqrt((ld)lensq()); }
16    static ld dist(const P &p1, const P &p2) {
17        return (p1-p2).len(); }
18    bool operator==(const P &r) const {
19        return ((*this)-r).lensq() <= EPS*EPS; }
20 };
21 C det(P p1, P p2) { return p1^p2; }
22 C det(P p1, P p2, P o) { return det(p1-o, p2-o); }
23 C det(const vector<P> &ps) {
24     C sum = 0; P prev = ps.back();
25     for(auto &p : ps) sum += det(p, prev), prev = p;
26     return sum;
27 }
28 // Careful with division by two and C=ll
29 C area(P p1, P p2, P p3) { return abs(det(p1, p2, p3))/C(2); }
30 C area(const vector<P> &poly) { return abs(det(poly))/C(2); }
31 int sign(C c){ return (c > C(0)) - (c < C(0)); }
32 int ccw(P p1, P p2, P o){ return sign(det(p1, p2, o)); }

```

```

33
34 // Only well defined for C = ld.
35 P unit(const P &p) { return p / p.len(); }
36 P rotate(P p, ld a) { return P{p.x*cos(a)-p.y*sin(a), p.x*sin(a)+p.y*cos(a)}; }

```

3.6.2 Convex Hull

```

1 #include "header.h"
2 #include "essentials.cpp"
3 struct ConvexHull { // O(n lg n) monotone chain.
4     size_t n;
5     vector<size_t> h, c; // Indices of the hull are in 'h', ccw.
6     const vector<P> &p;
7     ConvexHull(const vector<P> &p) : n(_p.size()), c(n), p(_p) {
8         std::iota(c.begin(), c.end(), 0);
9         std::sort(c.begin(), c.end(), [this](size_t l, size_t r) -> bool {
10             return p[l].x != p[r].x ? p[l].x < p[r].x : p[l].y < p[r].y; });
11         c.erase(std::unique(c.begin(), c.end(), [this](size_t l, size_t r) {
12             return p[l] == p[r]; }), c.end());
13         for (size_t s = 1, r = 0; r < 2; ++r, s = h.size()) {
14             for (size_t i : c) {
15                 while (h.size() > s && ccw(p[h.end()-2], p[h.end()-1], p[i]) <= 0)
16                     h.pop_back();
17                 h.push_back(i);
18             }
19             if (h.size() > 1) h.pop_back();
20         }
21         size_t size() const { return h.size(); }
22         template <class T, void U(const P &, const P &, const P &, T &)>
23         void rotating_calipers(T &ans) {
24             if (size() <= 2)
25                 U(p[h[0]], p[h.back()], p[h.back()], ans);
26             else
27                 for (size_t i = 0, j = 1, s = size(); i < 2 * s; ++i) {
28                     while (det(p[h[(i + 1) % s]], p[h[i % s]], p[h[(j + 1) % s]] - p[h[j]]) >= 0)
29                         j = (j + 1) % s;
30                     U(p[h[i % s]], p[h[(i + 1) % s]], p[h[j]], ans);
31                 }
32         }
33     };
34 // Example: furthest pair of points. Now set ans = 0LL and call
35 // ConvexHull(pts).rotating_calipers<ll, update>(ans);
36 void update(const P &p1, const P &p2, const P &o, ll &ans) {
37     ans = max(ans, (ll)max((p1 - o).lensq(), (p2 - o).lensq()));
38 }

```

3.7 Other Algorithms

3.8 Other Data Structures

3.8.1 Disjoint set (i.e. union-find)

```

1 template <typename T>
2 class DisjointSet {
3     typedef T * iterator;
4     T *parent, n, *rank;
5     public:
6         // O(n), assumes nodes are [0, n)
7         DisjointSet(T n) {
8             this->parent = new T[n];
9             this->n = n;
10            this->rank = new T[n];
11
12            for (T i = 0; i < n; i++) {
13                parent[i] = i;
14                rank[i] = 0;
15            }
16        }
17
18        // O(log n)
19        T find_set(T x) {
20            if (x == parent[x]) return x;
21            return parent[x] = find_set(parent[x]);
22        }
23
24        // O(log n)
25        void union_sets(T x, T y) {
26            x = this->find_set(x);
27            y = this->find_set(y);
28
29            if (x == y) return;
30
31            if (rank[x] < rank[y]) {
32                T z = x;
33                x = y;
34                y = z;
35            }
36
37            parent[y] = x;
38            if (rank[x] == rank[y]) rank[x]++;
39        }
40 };

```

```

15     while(k) {
16         ans += tree[k];
17         k -= k & (-k);
18     }
19     return ans;
20 }

```

3.9 Other Mathematics

3.8.2 Fenwick tree (i.e. BIT) eff. update + prefix sum calc.

```

1 #include "header.h"
2 #define maxn 200010
3 int t,n,m,tree[maxn],p[maxn];
4
5 void update(int k, int z) {
6     while (k <= maxn) {
7         tree[k] += z;
8         k += k & (-k);
9         // cout << "k: " << k << endl;
10    }
11 }
12
13 int sum(int k) {
14     int ans = 0;

```