

Accelerating Synology RAID 6 (SHR-2) reshapes

Cite as: Martin Paul Eve, "Accelerating Synology RAID 6 (SHR-2) reshapes", *eve.gd: Martin Paul Eve*, January 03, 2020, <https://doi.org/10.59348/r1n4g-g3187>.

Urgh. I had a RAID 6 reshape on my NAS that was projected to take 28 days to complete, I kid you not. It was stuck at an abysmal 4MB/s transfer rate. Here's how to unblock it.

First, follow [all the advice on general raid speedups](#) – assuming md2 is your RAID device and you need to replace sd[DEVICE] below with the correct block devices that constitute the array:

```
echo 50000 > /proc/sys/dev/raid/speed_limit_min
```

```
echo 100000 > /proc/sys/dev/raid/speed_limit_max
```

```
blockdev --setra 65536 /dev/md2
```

```
echo 32768 > /sys/block/md2/md/stripe_cache_size
```

```
echo 1 > /sys/block/sd[DEVICE]/device/queue_depth
```

This is all common advice that it is easy to find. But I was still stuck at the hideous transfer rate. I was worried there was a firmware fault with my drives. What unblocked it for me was:

```
echo max > /sys/block/md2/md/sync_max
```

Bingo. Up to 45MB/s now, even during heavy write usage from other processes.