Aurora: Module Relay x8

Stakeholders statements

Prepared for

Technical Staff

October 2026



Disclosure is prohibited

Revision History

Version	Date	Author	Description
0.1.0	2026-07-02	Martin Pellizzer	Starting version

Table of Contents

Revision History 2

Table of Contents 3

statements 28

statement 1 . . . 28

statement . . . 28

Answer . . . 28

Question . . . 28

Stakeholder . . . 28

statement 2 . . . 29

statement . . . 29

Answer . . . 29

Question . . . 29

Stakeholder . . . 29

statement 3 . . . 30

statement . . . 30

Answer . . . 30

Question . . . 30

Stakeholder . . . 30

statement 4 . . . 31

statement . . . 31

Answer . . . 31

Question . . . 31

Stakeholder . . . 31

statement 5 . . . 32

statement . . . 32
Answer . . . 32
Question . . . 32
Stakeholder . . . 32
statement 6 . . . 33
statement . . . 33
Answer . . . 33
Question . . . 33
Stakeholder . . . 33
statement 7 . . . 34
statement . . . 34
Answer . . . 34
Question . . . 34
Stakeholder . . . 34
statement 8 . . . 35
statement . . . 35
Answer . . . 35
Question . . . 35
Stakeholder . . . 35
statement 9 . . . 36
statement . . . 36
Answer . . . 36
Question . . . 36
Stakeholder . . . 36
statement 10 . . . 37
statement . . . 37
Answer . . . 37

Question . . . 37
Stakeholder . . . 37
statement 11 . . . 38
statement . . . 38
Answer . . . 38
Question . . . 38
Stakeholder . . . 38
statement 12 . . . 39
statement . . . 39
Answer . . . 39
Question . . . 39
Stakeholder . . . 39
statement 13 . . . 40
statement . . . 40
Answer . . . 40
Question . . . 40
Stakeholder . . . 40
statement 14 . . . 41
statement . . . 41
Answer . . . 41
Question . . . 41
Stakeholder . . . 41
statement 15 . . . 42
statement . . . 42
Answer . . . 42
Question . . . 42

Stakeholder 42
statement 16 43
statement 43
Answer 43
Question 43
Stakeholder 43
statement 17 44
statement 44
Answer 44
Question 44
Stakeholder 44
statement 18 45
statement 45
Answer 45
Question 45
Stakeholder 45
statement 19 46
statement 46
Answer 46
Question 46
Stakeholder 46
statement 20 47
statement 47
Answer 47
Question 47
Stakeholder 47
statement 21 48

statement 48
Answer 48
Question 48
Stakeholder 48
statement 22 49
statement 49
Answer 49
Question 49
Stakeholder 49
statement 23 50
statement 50
Answer 50
Question 50
Stakeholder 50
statement 24 51
statement 51
Answer 51
Question 51
Stakeholder 51
statement 25 52
statement 52
Answer 52
Question 52
Stakeholder 52
statement 26 53
statement 53

Answer . . . 53
Question . . . 53
Stakeholder . . . 53
statement 27 . . . 54
statement . . . 54
Answer . . . 54
Question . . . 54
Stakeholder . . . 54
statement 28 . . . 55
statement . . . 55
Answer . . . 55
Question . . . 55
Stakeholder . . . 55
statement 29 . . . 56
statement . . . 56
Answer . . . 56
Question . . . 56
Stakeholder . . . 56
statement 30 . . . 57
statement . . . 57
Answer . . . 57
Question . . . 57
Stakeholder . . . 57
statement 31 . . . 58
statement . . . 58
Answer . . . 58
Question . . . 58

Stakeholder . . . 58
statement 32 . . . 59
statement . . . 59
Answer . . . 59
Question . . . 59
Stakeholder . . . 59
statement 33 . . . 60
statement . . . 60
Answer . . . 60
Question . . . 60
Stakeholder . . . 60
statement 34 . . . 61
statement . . . 61
Answer . . . 61
Question . . . 61
Stakeholder . . . 61
statement 35 . . . 62
statement . . . 62
Answer . . . 62
Question . . . 62
Stakeholder . . . 62
statement 36 . . . 63
statement . . . 63
Answer . . . 63
Question . . . 63
Stakeholder . . . 63

statement 37 . . . 64
statement . . . 64
Answer . . . 64
Question . . . 64
Stakeholder . . . 64
statement 38 . . . 65
statement . . . 65
Answer . . . 65
Question . . . 65
Stakeholder . . . 65
statement 39 . . . 66
statement . . . 66
Answer . . . 66
Question . . . 66
Stakeholder . . . 66
statement 40 . . . 67
statement . . . 67
Answer . . . 67
Question . . . 67
Stakeholder . . . 67
statement 41 . . . 68
statement . . . 68
Answer . . . 68
Question . . . 68
Stakeholder . . . 68
statement 42 . . . 69
statement . . . 69

Answer . . . 69
Question . . . 69
Stakeholder . . . 69
statement 43 . . . 70
statement . . . 70
Answer . . . 70
Question . . . 70
Stakeholder . . . 70
statement 44 . . . 71
statement . . . 71
Answer . . . 71
Question . . . 71
Stakeholder . . . 71
statement 45 . . . 72
statement . . . 72
Answer . . . 72
Question . . . 72
Stakeholder . . . 72
statement 46 . . . 73
statement . . . 73
Answer . . . 73
Question . . . 73
Stakeholder . . . 73
statement 47 . . . 74
statement . . . 74
Answer . . . 74

Question . . . 74
Stakeholder . . . 74
statement 48 . . . 75
statement . . . 75
Answer . . . 75
Question . . . 75
Stakeholder . . . 75
statement 49 . . . 76
statement . . . 76
Answer . . . 76
Question . . . 76
Stakeholder . . . 76
statement 50 . . . 77
statement . . . 77
Answer . . . 77
Question . . . 77
Stakeholder . . . 77
statement 51 . . . 78
statement . . . 78
Answer . . . 78
Question . . . 78
Stakeholder . . . 78
statement 52 . . . 79
statement . . . 79
Answer . . . 79
Question . . . 79
Stakeholder . . . 79

statement 53 . . . 80
statement . . . 80
Answer . . . 80
Question . . . 80
Stakeholder . . . 80
statement 54 . . . 81
statement . . . 81
Answer . . . 81
Question . . . 81
Stakeholder . . . 81
statement 55 . . . 82
statement . . . 82
Answer . . . 82
Question . . . 82
Stakeholder . . . 82
statement 56 . . . 83
statement . . . 83
Answer . . . 83
Question . . . 83
Stakeholder . . . 83
statement 57 . . . 84
statement . . . 84
Answer . . . 84
Question . . . 84
Stakeholder . . . 84
statement 58 . . . 85

statement . . . 85
Answer . . . 85
Question . . . 85
Stakeholder . . . 85
statement 59 . . . 86
statement . . . 86
Answer . . . 86
Question . . . 86
Stakeholder . . . 86
statement 60 . . . 87
statement . . . 87
Answer . . . 87
Question . . . 87
Stakeholder . . . 87
statement 61 . . . 88
statement . . . 88
Answer . . . 88
Question . . . 88
Stakeholder . . . 88
statement 62 . . . 89
statement . . . 89
Answer . . . 89
Question . . . 89
Stakeholder . . . 89
statement 63 . . . 90
statement . . . 90
Answer . . . 90

Question 90
Stakeholder 90
statement 64 91
statement 91
Answer 91
Question 91
Stakeholder 91
statement 65 92
statement 92
Answer 92
Question 92
Stakeholder 92
statement 66 93
statement 93
Answer 93
Question 93
Stakeholder 93
statement 67 94
statement 94
Answer 94
Question 94
Stakeholder 94
statement 68 95
statement 95
Answer 95
Question 95

Stakeholder 95
statement 69 96
statement 96
Answer 96
Question 96
Stakeholder 96
statement 70 97
statement 97
Answer 97
Question 97
Stakeholder 97
statement 71 98
statement 98
Answer 98
Question 98
Stakeholder 98
statement 72 99
statement 99
Answer 99
Question 99
Stakeholder 99
statement 73 100
statement 100
Answer 100
Question 100
Stakeholder 100
statement 74 101

statement . . . 101
Answer . . . 101
Question . . . 101
Stakeholder . . . 101
statement 75 . . . 102
statement . . . 102
Answer . . . 102
Question . . . 102
Stakeholder . . . 102
statement 76 . . . 103
statement . . . 103
Answer . . . 103
Question . . . 103
Stakeholder . . . 103
statement 77 . . . 104
statement . . . 104
Answer . . . 104
Question . . . 104
Stakeholder . . . 104
statement 78 . . . 105
statement . . . 105
Answer . . . 105
Question . . . 105
Stakeholder . . . 105
statement 79 . . . 106
statement . . . 106

Answer . . . 106
Question . . . 106
Stakeholder . . . 106
statement 80 . . . 107
statement . . . 107
Answer . . . 107
Question . . . 107
Stakeholder . . . 107
statement 81 . . . 108
statement . . . 108
Answer . . . 108
Question . . . 108
Stakeholder . . . 108
statement 82 . . . 109
statement . . . 109
Answer . . . 109
Question . . . 109
Stakeholder . . . 109
statement 83 . . . 110
statement . . . 110
Answer . . . 110
Question . . . 110
Stakeholder . . . 110
statement 84 . . . 111
statement . . . 111
Answer . . . 111
Question . . . 111

Stakeholder 111
statement 85 112
statement 112
Answer 112
Question 112
Stakeholder 112
statement 86 113
statement 113
Answer 113
Question 113
Stakeholder 113
statement 87 114
statement 114
Answer 114
Question 114
Stakeholder 114
statement 88 115
statement 115
Answer 115
Question 115
Stakeholder 115
statement 89 116
statement 116
Answer 116
Question 116
Stakeholder 116

statement 90 . . . 117
statement . . . 117
Answer . . . 117
Question . . . 117
Stakeholder . . . 117
statement 91 . . . 118
statement . . . 118
Answer . . . 118
Question . . . 118
Stakeholder . . . 118
statement 92 . . . 119
statement . . . 119
Answer . . . 119
Question . . . 119
Stakeholder . . . 119
statement 93 . . . 120
statement . . . 120
Answer . . . 120
Question . . . 120
Stakeholder . . . 120
statement 94 . . . 121
statement . . . 121
Answer . . . 121
Question . . . 121
Stakeholder . . . 121
statement 95 . . . 122
statement . . . 122

Answer . . . 122
Question . . . 122
Stakeholder . . . 122
statement 96 . . . 123
statement . . . 123
Answer . . . 123
Question . . . 123
Stakeholder . . . 123
statement 97 . . . 124
statement . . . 124
Answer . . . 124
Question . . . 124
Stakeholder . . . 124
statement 98 . . . 125
statement . . . 125
Answer . . . 125
Question . . . 125
Stakeholder . . . 125
statement 99 . . . 126
statement . . . 126
Answer . . . 126
Question . . . 126
Stakeholder . . . 126
statement 100 . . . 127
statement . . . 127
Answer . . . 127

Question . . . 127
Stakeholder . . . 127
statement 101 . . . 128
statement . . . 128
Answer . . . 128
Question . . . 128
Stakeholder . . . 128
statement 102 . . . 129
statement . . . 129
Answer . . . 129
Question . . . 129
Stakeholder . . . 129
statement 103 . . . 130
statement . . . 130
Answer . . . 130
Question . . . 130
Stakeholder . . . 130
statement 104 . . . 131
statement . . . 131
Answer . . . 131
Question . . . 131
Stakeholder . . . 131
statement 105 . . . 132
statement . . . 132
Answer . . . 132
Question . . . 132
Stakeholder . . . 132

statement 106 . . . 133
statement . . . 133
Answer . . . 133
Question . . . 133
Stakeholder . . . 133
statement 107 . . . 134
statement . . . 134
Answer . . . 134
Question . . . 134
Stakeholder . . . 134
statement 108 . . . 135
statement . . . 135
Answer . . . 135
Question . . . 135
Stakeholder . . . 135
statement 109 . . . 136
statement . . . 136
Answer . . . 136
Question . . . 136
Stakeholder . . . 136
statement 110 . . . 137
statement . . . 137
Answer . . . 137
Question . . . 137
Stakeholder . . . 137
statement 111 . . . 138

statement . . . 138
Answer . . . 138
Question . . . 138
Stakeholder . . . 138
statement 112 . . . 139
statement . . . 139
Answer . . . 139
Question . . . 139
Stakeholder . . . 139
statement 113 . . . 140
statement . . . 140
Answer . . . 140
Question . . . 140
Stakeholder . . . 140
statement 114 . . . 141
statement . . . 141
Answer . . . 141
Question . . . 141
Stakeholder . . . 141
statement 115 . . . 142
statement . . . 142
Answer . . . 142
Question . . . 142
Stakeholder . . . 142
statement 116 . . . 143
statement . . . 143
Answer . . . 143

Question . . . 143
Stakeholder . . . 143
statement 117 . . . 144
statement . . . 144
Answer . . . 144
Question . . . 144
Stakeholder . . . 144
statement 118 . . . 145
statement . . . 145
Answer . . . 145
Question . . . 145
Stakeholder . . . 145
statement 119 . . . 146
statement . . . 146
Answer . . . 146
Question . . . 146
Stakeholder . . . 146
statement 120 . . . 147
statement . . . 147
Answer . . . 147
Question . . . 147
Stakeholder . . . 147
statement 121 . . . 148
statement . . . 148
Answer . . . 148
Question . . . 148

Stakeholder 148
statement 122 149
statement 149
Answer 149
Question 149
Stakeholder 149
statement 123 150
statement 150
Answer 150
Question 150
Stakeholder 150
statement 124 151
statement 151
Answer 151
Question 151
Stakeholder 151
statement 125 152
statement 152
Answer 152
Question 152
Stakeholder 152
statement 126 153
statement 153
Answer 153
Question 153
Stakeholder 153
statement 127 154

statement 154
Answer 154
Question 154
Stakeholder 154

statements

statement 1

statement

The Relay Module shall execute relay-output commands received from CORE

Answer

The Relay Module shall reliably and deterministically execute relay-output commands received from the CORE, provide the CORE with output status and module diagnostics, and transition its outputs to defined safe states when required by system-level fault conditions.

Question

What exactly is the responsibility of the Relay Module within Aurora?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	1
Answer ID	1
Stakeholder Role	System Architect
Question Text	What exactly is the responsibility of the Relay Module within Aurora?
Answer Text	The Relay Module shall reliably and deterministically execute relay-output commands received from the CORE, provide the CORE with output status and module diagnostics, and transition its outputs to defined safe states when required by system-level fault conditions.
statement Text	The Relay Module shall execute relay-output commands received from CORE

statement 2

statement

The Relay Module shall provide CORE with output status

Answer

The Relay Module shall reliably and deterministically execute relay-output commands received from the CORE, provide the CORE with output status and module diagnostics, and transition its outputs to defined safe states when required by system-level fault conditions.

Question

What exactly is the responsibility of the Relay Module within Aurora?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	1
Answer ID	1
Stakeholder Role	System Architect
Question Text	What exactly is the responsibility of the Relay Module within Aurora?
Answer Text	The Relay Module shall reliably and deterministically execute relay-output commands received from the CORE, provide the CORE with output status and module diagnostics, and transition its outputs to defined safe states when required by system-level fault conditions.
statement Text	The Relay Module shall provide CORE with output status

statement 3

statement

The Relay Module shall provide CORE with module diagnostics

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall provide CORE with module diagnostics

statement 4

statement

The Relay Module shall transition its outputs to safe states when system-level fault

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall transition its outputs to safe states when system-level fault

statement 5

statement

The Relay Module shall provide eight indipendently controlled relay-driven channels

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall provide eight indipendently controlled relay-driven channels

statement 6

statement

The Relay Module shall manage activation of each channel

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall manage activation of each channel

statement 7

statement

The Relay Module shall manage deactivation of each channel

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall manage deactivation of each channel

statement 8

statement

The Relay Module shall monitor output faults

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall monitor output faults

statement 9

statement

The Relay Module shall communicate channels status to CORE

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall communicate channels status to CORE

statement 10

statement

The Relay Module shall communicate channels diagnostics to CORE

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall communicate channels diagnostics to CORE

statement 11

statement

The Relay Module shall communicate to CORE via Modbus RTU protocol

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall communicate to CORE via Modbus RTU protocol

statement 12

statement

The Relay Module shall communicate to CORE via RS-485 hardware standard

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall communicate to CORE via RS-485 hardware standard

statement 13

statement

The Relay Module shall enforce local fault-handling

Answer

The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.

Question

Which functions of the overall Aurora system are allocated specifically to the Relay Module?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	2
Answer ID	2
Stakeholder Role	System Architect
Question Text	Which functions of the overall Aurora system are allocated specifically to the Relay Module?
Answer Text	The Relay Module shall provide eight independently controlled relay-driver channels, manage their activation and deactivation, monitor relevant module/output faults, communicate their status and diagnostics to the CORE via Modbus RTU over RS-485, and enforce defined local fault-handling behavior.
statement Text	The Relay Module shall enforce local fault-handling

statement 14

statement

The Relay Module shall turn ON/OFF outputs within specified time

Answer

Each output shall independently assume the ON or OFF state commanded by the CORE within the specified response time, while preventing an individual channel fault from affecting the other channels and maintaining the output's defined safe behavior under fault conditions.

Question

What behavior does the system require from each of the eight relay outputs?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	3
Answer ID	3
Stakeholder Role	System Architect
Question Text	What behavior does the system require from each of the eight relay outputs?
Answer Text	Each output shall independently assume the ON or OFF state commanded by the CORE within the specified response time, while preventing an individual channel fault from affecting the other channels and maintaining the output's defined safe behavior under fault conditions.
statement Text	The Relay Module shall turn ON/OFF outputs within specified time

statement 15

statement

The Relay Module shall prevent one faulty channel to affect other channels

Answer

Each output shall independently assume the ON or OFF state commanded by the CORE within the specified response time, while preventing an individual channel fault from affecting the other channels and maintaining the output's defined safe behavior under fault conditions.

Question

What behavior does the system require from each of the eight relay outputs?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	3
Answer ID	3
Stakeholder Role	System Architect
Question Text	What behavior does the system require from each of the eight relay outputs?
Answer Text	Each output shall independently assume the ON or OFF state commanded by the CORE within the specified response time, while preventing an individual channel fault from affecting the other channels and maintaining the output's defined safe behavior under fault conditions.
statement Text	The Relay Module shall prevent one faulty channel to affect other channels

statement 16

statement

The Relay Module shall maintain the output defined safe behavior under fault conditions

Answer

Each output shall independently assume the ON or OFF state commanded by the CORE within the specified response time, while preventing an individual channel fault from affecting the other channels and maintaining the output's defined safe behavior under fault conditions.

Question

What behavior does the system require from each of the eight relay outputs?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	3
Answer ID	3
Stakeholder Role	System Architect
Question Text	What behavior does the system require from each of the eight relay outputs?
Answer Text	Each output shall independently assume the ON or OFF state commanded by the CORE within the specified response time, while preventing an individual channel fault from affecting the other channels and maintaining the output's defined safe behavior under fault conditions.
statement Text	The Relay Module shall maintain the output defined safe behavior under fault conditions

statement 17

statement

The Relay Module shall detect communication timeout with CORE

Answer

Upon detecting a communication timeout with the CORE, every relay output shall transition to its predefined safe state, which shall be OFF unless a system-level hazard analysis explicitly requires another state.

Question

What must happen to every relay output when communication with the CORE is lost?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	4
Answer ID	4
Stakeholder Role	System Architect
Question Text	What must happen to every relay output when communication with the CORE is lost?
Answer Text	Upon detecting a communication timeout with the CORE, every relay output shall transition to its predefined safe state, which shall be OFF unless a system-level hazard analysis explicitly requires another state.
statement Text	The Relay Module shall detect communication timeout with CORE

statement 18

statement

The Relay Module shall transition to its outputs to predefined safe state when timeout with CORE

Answer

Upon detecting a communication timeout with the CORE, every relay output shall transition to its predefined safe state, which shall be OFF unless a system-level hazard analysis explicitly requires another state.

Question

What must happen to every relay output when communication with the CORE is lost?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	4
Answer ID	4
Stakeholder Role	System Architect
Question Text	What must happen to every relay output when communication with the CORE is lost?
Answer Text	Upon detecting a communication timeout with the CORE, every relay output shall transition to its predefined safe state, which shall be OFF unless a system-level hazard analysis explicitly requires another state.
statement Text	The Relay Module shall transition to its outputs to predefined safe state when timeout with CORE

statement 19

statement

The Relay Module shall transition to defined safe state when in failure state

Answer

Any Relay Module failure that could compromise safe operation shall cause the affected outputs to transition to their defined safe states, prevent unintended activation, and provide sufficient fault information to the CORE to initiate the appropriate Aurora system fault response.

Question

What is the required system behavior if the Relay Module itself fails?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	5
Answer ID	5
Stakeholder Role	System Architect
Question Text	What is the required system behavior if the Relay Module itself fails?
Answer Text	Any Relay Module failure that could compromise safe operation shall cause the affected outputs to transition to their defined safe states, prevent unintended activation, and provide sufficient fault information to the CORE to initiate the appropriate Aurora system fault response.
statement Text	The Relay Module shall transition to defined safe state when in failure state

statement 20

statement

The Relay Module shall prevent unintended activation when in failure state

Answer

Any Relay Module failure that could compromise safe operation shall cause the affected outputs to transition to their defined safe states, prevent unintended activation, and provide sufficient fault information to the CORE to initiate the appropriate Aurora system fault response.

Question

What is the required system behavior if the Relay Module itself fails?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	5
Answer ID	5
Stakeholder Role	System Architect
Question Text	What is the required system behavior if the Relay Module itself fails?
Answer Text	Any Relay Module failure that could compromise safe operation shall cause the affected outputs to transition to their defined safe states, prevent unintended activation, and provide sufficient fault information to the CORE to initiate the appropriate Aurora system fault response.
statement Text	The Relay Module shall prevent unintended activation when in failure state

statement 21

statement

The Relay Module shall provide sufficient fault information to CORE when in failure state

Answer

Any Relay Module failure that could compromise safe operation shall cause the affected outputs to transition to their defined safe states, prevent unintended activation, and provide sufficient fault information to the CORE to initiate the appropriate Aurora system fault response.

Question

What is the required system behavior if the Relay Module itself fails?

Stakeholder

System Architect

Field	Value
Stakeholder ID	1
Question ID	5
Answer ID	5
Stakeholder Role	System Architect
Question Text	What is the required system behavior if the Relay Module itself fails?
Answer Text	Any Relay Module failure that could compromise safe operation shall cause the affected outputs to transition to their defined safe states, prevent unintended activation, and provide sufficient fault information to the CORE to initiate the appropriate Aurora system fault response.
statement Text	The Relay Module shall provide sufficient fault information to CORE when in failure state

statement 22

statement

The Relay Module shall execute commands deterministically

Answer

The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.

Question

Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	6
Answer ID	6
Stakeholder Role	CORE Firmware Engineer
Question Text	Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?
Answer Text	The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.
statement Text	The Relay Module shall execute commands deterministically

statement 23

statement

The Relay Module shall manage its eight physical driver outputs

Answer

The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.

Question

Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	6
Answer ID	6
Stakeholder Role	CORE Firmware Engineer
Question Text	Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?
Answer Text	The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.
statement Text	The Relay Module shall manage its eight physical driver outputs

statement 24

statement

The Relay Module shall perform local hardware diagnostics

Answer

The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.

Question

Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	6
Answer ID	6
Stakeholder Role	CORE Firmware Engineer
Question Text	Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?
Answer Text	The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.
statement Text	The Relay Module shall perform local hardware diagnostics

statement 25

statement

The Relay Module shall report its status to CORE

Answer

The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.

Question

Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	6
Answer ID	6
Stakeholder Role	CORE Firmware Engineer
Question Text	Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?
Answer Text	The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.
statement Text	The Relay Module shall report its status to CORE

statement 26

statement

The Relay Module shall report its faults to CORE

Answer

The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.

Question

Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	6
Answer ID	6
Stakeholder Role	CORE Firmware Engineer
Question Text	Which responsibilities belong to the CORE and which responsibilities belong to the Relay Module?
Answer Text	The CORE shall own all system-level decisions, sequencing, interlocks, operating modes and desired relay states, while the Relay Module shall execute those commands deterministically, manage its eight physical driver outputs, perform local hardware diagnostics, and report its status and faults to the CORE.
statement Text	The Relay Module shall report its faults to CORE

statement 27

statement

The Relay Module shall report the state of all eight outputs

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report the state of all eight outputs

statement 28

statement

The Relay Module shall report the module health

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report the module health

statement 29

statement

The Relay Module shall report individual channel faults

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report individual channel faults

statement 30

statement

The Relay Module shall report communication status

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report communication status

statement 31

statement

The Relay Module shall report electrical identification

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report electrical identification

statement 32

statement

The Relay Module shall report thermal identification

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report thermal identification

statement 33

statement

The Relay Module shall report diagnostics identification

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report diagnostics identification

statement 34

statement

The Relay Module shall report firmware identification

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report firmware identification

statement 35

statement

The Relay Module shall report hardware identification

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report hardware identification

statement 36

statement

The Relay Module shall report any condition preventing reliable output control

Answer

The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.

Question

What information must the Relay Module provide back to the CORE?

Stakeholder

CORE Firmware Engineer

Field	Value
Stakeholder ID	2
Question ID	8
Answer ID	8
Stakeholder Role	CORE Firmware Engineer
Question Text	What information must the Relay Module provide back to the CORE?
Answer Text	The Relay Module shall report the state of all eight outputs, module health, individual channel faults, communication status, relevant electrical/thermal diagnostics, firmware/hardware identification, and any condition preventing reliable output control.
statement Text	The Relay Module shall report any condition preventing reliable output control

statement 37

statement

The Relay Module shall reliably energize its assigned relay coil across the full specified supply

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall reliably energize its assigned relay coil across the full specified supply

statement 38

statement

The Relay Module shall independently energize its assigned relay coil across the full specified supply

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall independently energize its assigned relay coil across the full specified supply

statement 39

statement

The Relay Module shall energize its assigned relay coil across the full specified temperature

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil across the full specified temperature

statement 40

statement

The Relay Module shall energize its assigned relay coil across the full specified tolerance range

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil across the full specified tolerance range

statement 41

statement

The Relay Module shall energize its assigned relay coil with adequate voltage

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with adequate voltage

statement 42

statement

The Relay Module shall energize its assigned relay coil with adequate voltage margin

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with adequate voltage margin

statement 43

statement

The Relay Module shall energize its assigned relay coil with adequate current margin

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with adequate current margin

statement 44

statement

The Relay Module shall energize its assigned relay coil with continuous-duty

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with continuous-duty

statement 45

statement

The Relay Module shall energize its assigned relay coil with continuous-duty capability

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with continuous-duty capability

statement 46

statement

The Relay Module shall energize its assigned relay coil with short-circuit protection

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with short-circuit protection

statement 47

statement

The Relay Module shall energize its assigned relay coil with overload protection

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with overload protection

statement 48

statement

The Relay Module shall energize its assigned relay coil with no unintended activation during reset conditions

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with no unintended activation during reset conditions

statement 49

statement

The Relay Module shall energize its assigned relay coil with no unintended activation during fault conditions

Answer

Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.

Question

What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	11
Answer ID	11
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical specifications of the eight relay-driver outputs, based on the physical relays they must control?
Answer Text	Each driver shall independently and reliably energize its assigned relay coil across the full specified supply, temperature, and tolerance range, with adequate voltage/current margin, continuous-duty capability, short-circuit/overload protection, and no unintended activation during reset or fault conditions.
statement Text	The Relay Module shall energize its assigned relay coil with no unintended activation during fault conditions

statement 50

statement

The Relay Module shall operate with coils that have a defined nominal voltage

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have a defined nominal voltage

statement 51

statement

The Relay Module shall operate with coils that have allowable voltage range

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have allowable voltage range

statement 52

statement

The Relay Module shall operate with coils that have nominal current

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have nominal current

statement 53

statement

The Relay Module shall operate with coils that have maximum current

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have maximum current

statement 54

statement

The Relay Module shall operate with coils that have defined resistance

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have defined resistance

statement 55

statement

The Relay Module shall operate with coils that have defined inductance

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have defined inductance

statement 56

statement

The Relay Module shall operate with coils that have defined inrush behavior

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have defined inrush behavior

statement 57

statement

The Relay Module shall operate with coils that have defined continuous-duty rating

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have defined continuous-duty rating

statement 58

statement

The Relay Module shall operate with coils that have operate characteristics that are fully compatible with its corresponding driver

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have operate characteristics that are fully compatible with its corresponding driver

statement 59

statement

The Relay Module shall operate with coils that have release characteristics that are fully compatible with its corresponding driver

Answer

Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.

Question

What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	12
Answer ID	12
Stakeholder Role	Electrical Engineer
Question Text	What are the electrical characteristics of the physical relay coils connected to each of the eight driver outputs?
Answer Text	Each relay coil shall have a defined nominal voltage, allowable voltage range, nominal and maximum current, resistance/inductance, inrush behavior, continuous-duty rating, and release/operate characteristics that are fully compatible with its corresponding driver.
statement Text	The Relay Module shall operate with coils that have release characteristics that are fully compatible with its corresponding driver

statement 60

statement

The Relay Module shall operate correctly over the complete specified nominal supply range

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range

statement 61

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including component tolerances

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including component tolerances

statement 62

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including steady-state variation

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including steady-state variation

statement 63

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including startup conditions

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including startup conditions

statement 64

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including brownouts

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including brownouts

statement 65

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including overvoltage

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including overvoltage

statement 66

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including ripple

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including ripple

statement 67

statement

The Relay Module shall operate correctly over the complete specified nominal supply range, including transient disturbances from cabinet

Answer

The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.

Question

What is the required input supply voltage range, including tolerances and transient conditions?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	13
Answer ID	13
Stakeholder Role	Electrical Engineer
Question Text	What is the required input supply voltage range, including tolerances and transient conditions?
Answer Text	The module shall operate correctly over the complete specified nominal supply range, including component tolerances, steady-state variation, startup conditions, brownouts, overvoltage, ripple, and transient disturbances expected in the Aurora electrical cabinet.
statement Text	The Relay Module shall operate correctly over the complete specified nominal supply range, including transient disturbances from cabinet

statement 68

statement

The Relay Module shall have drivers with appropriately sized suppressions

Answer

Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.

Question

What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	14
Answer ID	14
Stakeholder Role	Electrical Engineer
Question Text	What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?
Answer Text	Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.
statement Text	The Relay Module shall have drivers with appropriately sized suppressions

statement 69

statement

The Relay Module shall have drivers with appropriately sized suppressions, such as a flyback diode

Answer

Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.

Question

What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	14
Answer ID	14
Stakeholder Role	Electrical Engineer
Question Text	What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?
Answer Text	Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.
statement Text	The Relay Module shall have drivers with appropriately sized suppressions, such as a flyback diode

statement 70

statement

The Relay Module shall have drivers with appropriately sized suppressions, such as a TVS/clamp network

Answer

Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.

Question

What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	14
Answer ID	14
Stakeholder Role	Electrical Engineer
Question Text	What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?
Answer Text	Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.
statement Text	The Relay Module shall have drivers with appropriately sized suppressions, such as a TVS/clamp network

statement 71

statement

The Relay Module shall limit the coil-generated transient to a safe level without exceeding driver ratings

Answer

Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.

Question

What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	14
Answer ID	14
Stakeholder Role	Electrical Engineer
Question Text	What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?
Answer Text	Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.
statement Text	The Relay Module shall limit the coil-generated transient to a safe level without exceeding driver ratings

statement 72

statement

The Relay Module shall limit the coil-generated transient to a safe level without causing unacceptable relay release-time delays

Answer

Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.

Question

What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	14
Answer ID	14
Stakeholder Role	Electrical Engineer
Question Text	What protection is required to handle the inductive voltage transient generated when a relay coil is de-energized?
Answer Text	Each driver output shall incorporate appropriately sized suppression, such as a flyback diode or TVS/clamp network, to limit the coil-generated transient to a safe level without exceeding driver ratings or causing unacceptable relay release-time delays.
statement Text	The Relay Module shall limit the coil-generated transient to a safe level without causing unacceptable relay release-time delays

statement 73

statement

The Relay Module shall transition all relay outputs to defined safe state during out-of-range brownout

Answer

During power loss or an out-of-range brownout, all relay outputs shall transition to and remain in their defined safe state without unintended activation, and after power restoration the module shall initialize deterministically with outputs disabled until valid control from the CORE is established.

Question

What electrical behavior is required during power loss, brownout, and restoration of power?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	15
Answer ID	15
Stakeholder Role	Electrical Engineer
Question Text	What electrical behavior is required during power loss, brownout, and restoration of power?
Answer Text	During power loss or an out-of-range brownout, all relay outputs shall transition to and remain in their defined safe state without unintended activation, and after power restoration the module shall initialize deterministically with outputs disabled until valid control from the CORE is established.
statement Text	The Relay Module shall transition all relay outputs to defined safe state during out-of-range brownout

statement 74

statement

The Relay Module shall transition all relay outputs to defined safe state during power loss

Answer

During power loss or an out-of-range brownout, all relay outputs shall transition to and remain in their defined safe state without unintended activation, and after power restoration the module shall initialize deterministically with outputs disabled until valid control from the CORE is established.

Question

What electrical behavior is required during power loss, brownout, and restoration of power?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	15
Answer ID	15
Stakeholder Role	Electrical Engineer
Question Text	What electrical behavior is required during power loss, brownout, and restoration of power?
Answer Text	During power loss or an out-of-range brownout, all relay outputs shall transition to and remain in their defined safe state without unintended activation, and after power restoration the module shall initialize deterministically with outputs disabled until valid control from the CORE is established.
statement Text	The Relay Module shall transition all relay outputs to defined safe state during power loss

statement 75

statement

The Relay Module shall initialize deterministically with outputs disabled until valid control from the CORE is established after power restoration

Answer

During power loss or an out-of-range brownout, all relay outputs shall transition to and remain in their defined safe state without unintended activation, and after power restoration the module shall initialize deterministically with outputs disabled until valid control from the CORE is established.

Question

What electrical behavior is required during power loss, brownout, and restoration of power?

Stakeholder

Electrical Engineer

Field	Value
Stakeholder ID	3
Question ID	15
Answer ID	15
Stakeholder Role	Electrical Engineer
Question Text	What electrical behavior is required during power loss, brownout, and restoration of power?
Answer Text	During power loss or an out-of-range brownout, all relay outputs shall transition to and remain in their defined safe state without unintended activation, and after power restoration the module shall initialize deterministically with outputs disabled until valid control from the CORE is established.
statement Text	The Relay Module shall initialize deterministically with outputs disabled until valid control from the CORE is established after power restoration

statement 76

statement

The Relay Module shall locally enforce the safety-related output constraints for its eight relay channels

Answer

The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.

Question

What safety functions, if any, are assigned specifically to the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	16
Answer ID	16
Stakeholder Role	Safety Engineer
Question Text	What safety functions, if any, are assigned specifically to the Relay Module?
Answer Text	The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.
statement Text	The Relay Module shall locally enforce the safety-related output constraints for its eight relay channels

statement 77

statement

The Relay Module shall locally enforce the fail-safe behavior for its eight relay channels

Answer

The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.

Question

What safety functions, if any, are assigned specifically to the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	16
Answer ID	16
Stakeholder Role	Safety Engineer
Question Text	What safety functions, if any, are assigned specifically to the Relay Module?
Answer Text	The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.
statement Text	The Relay Module shall locally enforce the fail-safe behavior for its eight relay channels

statement 78

statement

The Relay Module shall detect relevant hardware faults

Answer

The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.

Question

What safety functions, if any, are assigned specifically to the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	16
Answer ID	16
Stakeholder Role	Safety Engineer
Question Text	What safety functions, if any, are assigned specifically to the Relay Module?
Answer Text	The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.
statement Text	The Relay Module shall detect relevant hardware faults

statement 79

statement

The Relay Module shall detect relevant output faults

Answer

The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.

Question

What safety functions, if any, are assigned specifically to the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	16
Answer ID	16
Stakeholder Role	Safety Engineer
Question Text	What safety functions, if any, are assigned specifically to the Relay Module?
Answer Text	The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.
statement Text	The Relay Module shall detect relevant output faults

statement 80

statement

The Relay Module shall transition affected outputs to their predefined safe states independently of higher-level system decisions

Answer

The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.

Question

What safety functions, if any, are assigned specifically to the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	16
Answer ID	16
Stakeholder Role	Safety Engineer
Question Text	What safety functions, if any, are assigned specifically to the Relay Module?
Answer Text	The Relay Module shall locally enforce the safety-related output constraints and fail-safe behavior defined for its eight relay channels, detect relevant hardware and output faults, and transition affected outputs to their predefined safe states independently of higher-level system decisions.
statement Text	The Relay Module shall transition affected outputs to their predefined safe states independently of higher-level system decisions

statement 81

statement

The Relay Module shall have a formally defined safe state for all its outputs based on its associated hazard analysis

Answer

Each of the eight relay outputs shall have a formally defined safe state based on its associated hazard analysis, with OFF/de-energized as the default safe state unless a documented safety analysis requires a specific output to remain energized.

Question

What is the required safe state for each of the eight relay outputs?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	17
Answer ID	17
Stakeholder Role	Safety Engineer
Question Text	What is the required safe state for each of the eight relay outputs?
Answer Text	Each of the eight relay outputs shall have a formally defined safe state based on its associated hazard analysis, with OFF/de-energized as the default safe state unless a documented safety analysis requires a specific output to remain energized.
statement Text	The Relay Module shall have a formally defined safe state for all its outputs based on its associated hazard analysis

statement 82

statement

The Relay Module shall have OFF/de-energized as the default safe state unless a documented safety analysis requires a specific output to remain energized

Answer

Each of the eight relay outputs shall have a formally defined safe state based on its associated hazard analysis, with OFF/de-energized as the default safe state unless a documented safety analysis requires a specific output to remain energized.

Question

What is the required safe state for each of the eight relay outputs?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	17
Answer ID	17
Stakeholder Role	Safety Engineer
Question Text	What is the required safe state for each of the eight relay outputs?
Answer Text	Each of the eight relay outputs shall have a formally defined safe state based on its associated hazard analysis, with OFF/de-energized as the default safe state unless a documented safety analysis requires a specific output to remain energized.
statement Text	The Relay Module shall have OFF/de-energized as the default safe state unless a documented safety analysis requires a specific output to remain energized

statement 83

statement

The Relay Module shall immediately prevent unsafe output activation when it detects an internal fault capable of compromising safe operation

Answer

When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.

Question

What shall happen to each relay output when the Relay Module detects an internal fault?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	18
Answer ID	18
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when the Relay Module detects an internal fault?
Answer Text	When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.
statement Text	The Relay Module shall immediately prevent unsafe output activation when it detects an internal fault capable of compromising safe operation

statement 84

statement

The Relay Module shall force all affected outputs to their defined safe states when it detects an internal fault capable of compromising safe operation

Answer

When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.

Question

What shall happen to each relay output when the Relay Module detects an internal fault?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	18
Answer ID	18
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when the Relay Module detects an internal fault?
Answer Text	When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.
statement Text	The Relay Module shall force all affected outputs to their defined safe states when it detects an internal fault capable of compromising safe operation

statement 85

statement

The Relay Module shall latch the fault as required when it detects an internal fault capable of compromising safe operation

Answer

When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.

Question

What shall happen to each relay output when the Relay Module detects an internal fault?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	18
Answer ID	18
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when the Relay Module detects an internal fault?
Answer Text	When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.
statement Text	The Relay Module shall latch the fault as required when it detects an internal fault capable of compromising safe operation

statement 86

statement

The Relay Module shall report the fault as required when it detects an internal fault capable of compromising safe operation

Answer

When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.

Question

What shall happen to each relay output when the Relay Module detects an internal fault?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	18
Answer ID	18
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when the Relay Module detects an internal fault?
Answer Text	When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.
statement Text	The Relay Module shall report the fault as required when it detects an internal fault capable of compromising safe operation

statement 87

statement

The Relay Module shall prevent reactivation until the fault-clear conditions are satisfied when it detects an internal fault capable of compromising safe operation

Answer

When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.

Question

What shall happen to each relay output when the Relay Module detects an internal fault?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	18
Answer ID	18
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when the Relay Module detects an internal fault?
Answer Text	When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.
statement Text	The Relay Module shall prevent reactivation until the fault-clear conditions are satisfied when it detects an internal fault capable of compromising safe operation

statement 88

statement

The Relay Module shall prevent reactivation until the reauthorization conditions are satisfied when it detects an internal fault capable of compromising safe operation

Answer

When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.

Question

What shall happen to each relay output when the Relay Module detects an internal fault?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	18
Answer ID	18
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when the Relay Module detects an internal fault?
Answer Text	When the Relay Module detects an internal fault capable of compromising safe operation, it shall immediately prevent unsafe output activation, force all affected outputs to their defined safe states, latch or report the fault as required, and prevent reactivation until the fault-clear and reauthorization conditions are satisfied.
statement Text	The Relay Module shall prevent reactivation until the reauthorization conditions are satisfied when it detects an internal fault capable of compromising safe operation

statement 89

statement

The Relay Module shall autonomously transition every output to its predefined safe state when communication with the CORE is lost beyond the defined safety timeout

Answer

When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.

Question

What shall happen to each relay output when communication with the CORE is lost?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	19
Answer ID	19
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when communication with the CORE is lost?
Answer Text	When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.
statement Text	The Relay Module shall autonomously transition every output to its predefined safe state when communication with the CORE is lost beyond the defined safety timeout

statement 90

statement

The Relay Module shall maintain a predefined safe state when communication with the CORE is lost beyond the defined safety timeout

Answer

When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.

Question

What shall happen to each relay output when communication with the CORE is lost?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	19
Answer ID	19
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when communication with the CORE is lost?
Answer Text	When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.
statement Text	The Relay Module shall maintain a predefined safe state when communication with the CORE is lost beyond the defined safety timeout

statement 91

statement

The Relay Module shall report the communication fault when communication with CORE is restored

Answer

When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.

Question

What shall happen to each relay output when communication with the CORE is lost?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	19
Answer ID	19
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when communication with the CORE is lost?
Answer Text	When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.
statement Text	The Relay Module shall report the communication fault when communication with CORE is restored

statement 92

statement

The Relay Module shall require explicit reauthorization from CORE before returning to normal operation

Answer

When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.

Question

What shall happen to each relay output when communication with the CORE is lost?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	19
Answer ID	19
Stakeholder Role	Safety Engineer
Question Text	What shall happen to each relay output when communication with the CORE is lost?
Answer Text	When communication with the CORE is lost beyond the defined safety timeout, the Relay Module shall autonomously transition every output to its predefined safe state, maintain that state, report the communication fault when communication is restored, and require explicit reauthorization before returning to normal operation.
statement Text	The Relay Module shall require explicit reauthorization from CORE before returning to normal operation

statement 93

statement

The Relay Module shall locally enforce output-level safety constraints

Answer

The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.

Question

Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	20
Answer ID	20
Stakeholder Role	Safety Engineer
Question Text	Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?
Answer Text	The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.
statement Text	The Relay Module shall locally enforce output-level safety constraints

statement 94

statement

The Relay Module shall locally enforce watchdog/communication-loss responses

Answer

The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.

Question

Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	20
Answer ID	20
Stakeholder Role	Safety Engineer
Question Text	Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?
Answer Text	The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.
statement Text	The Relay Module shall locally enforce watchdog/communication-loss responses

statement 95

statement

The Relay Module shall locally enforce internal fault handling

Answer

The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.

Question

Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	20
Answer ID	20
Stakeholder Role	Safety Engineer
Question Text	Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?
Answer Text	The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.
statement Text	The Relay Module shall locally enforce internal fault handling

statement 96

statement

The Relay Module shall locally enforce defined safe-state behavior without relying solely on the CORE

Answer

The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.

Question

Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?

Stakeholder

Safety Engineer

Field	Value
Stakeholder ID	4
Question ID	20
Answer ID	20
Stakeholder Role	Safety Engineer
Question Text	Which safety decisions must be made by the CORE, and which must be enforced locally by the Relay Module?
Answer Text	The CORE shall make all system-level safety decisions, operating-mode and shutdown decisions, while the Relay Module shall locally enforce output-level safety constraints, watchdog/communication-loss responses, internal fault handling, and the defined safe-state behavior without relying solely on the CORE.
statement Text	The Relay Module shall locally enforce defined safe-state behavior without relying solely on the CORE

statement 97

statement

The Relay Module shall manage the eight relay outputs to control or influence the ozone-generation process by operating the required process equipment and auxiliaries-such as ozone-generation power, cooling, gas/air or oxygen supply, valves, purge/ventilation, and other process actuators—according to the defined process sequence and interlocks

Answer

The eight relay outputs shall control or influence the ozone-generation process by operating the required process equipment and auxiliaries—such as ozone-generation power, cooling, gas/air or oxygen supply, valves, purge/ventilation, and other process actuators—according to the defined process sequence and interlocks.

Question

What process functions are controlled or influenced by the eight relay outputs of the Relay Module?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	21
Answer ID	21
Stakeholder Role	Process Engineer
Question Text	What process functions are controlled or influenced by the eight relay outputs of the Relay Module?
Answer Text	The eight relay outputs shall control or influence the ozone-generation process by operating the required process equipment and auxiliaries—such as ozone-generation power, cooling, gas/air or oxygen supply, valves, purge/ventilation, and other process actuators—according to the defined process sequence and interlocks.
statement Text	The Relay Module shall manage the eight relay outputs to control or influence the ozone-generation process by operating the required process equipment and auxiliaries-such as ozone-generation power, cooling, gas/air or oxygen supply, valves, purge/ventilation, and other process actuators—according to the defined process sequence and interlocks

statement 98

statement

The Relay Module shall include a startup sequence that verifies all required permissives

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that verifies all required permissives

statement 99

statement

The Relay Module shall include a startup sequence that establishes the required gas flow

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that establishes the required gas flow

statement 100

statement

The Relay Module shall include a startup sequence that establishes the supporting utilities

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that establishes the supporting utilities

statement 101

statement

The Relay Module shall include a startup sequence that enables cooling

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that enables cooling

statement 102

statement

The Relay Module shall include a startup sequence that enables other auxiliaries

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that enables other auxiliaries

statement 103

statement

The Relay Module shall include a startup sequence that confirms healthy operating feedback of auxiliaries

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that confirms healthy operating feedback of auxiliaries

statement 104

statement

The Relay Module shall include a startup sequence that energizes the ozone-generation system

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that energizes the ozone-generation system

statement 105

statement

The Relay Module shall include a startup sequence that transitions Aurora to the normal ozone-production state when the startup sequence is complete

Answer

The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.

Question

What is the required sequence of operations for starting ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	22
Answer ID	22
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for starting ozone generation?
Answer Text	The startup sequence shall verify all required permissives, establish the required gas flow and supporting utilities, enable cooling and other auxiliaries, confirm their healthy operating feedback, energize the ozone-generation system, and only then transition Aurora to the normal ozone-production state.
statement Text	The Relay Module shall include a startup sequence that transitions Aurora to the normal ozone-production state when the startup sequence is complete

statement 106

statement

The Relay Module shall include a shutdown sequence that disables ozone generation

Answer

The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.

Question

What is the required sequence of operations for stopping ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	23
Answer ID	23
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for stopping ozone generation?
Answer Text	The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.
statement Text	The Relay Module shall include a shutdown sequence that disables ozone generation

statement 107

statement

The Relay Module shall include a shutdown sequence that maintains the required cooling

Answer

The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.

Question

What is the required sequence of operations for stopping ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	23
Answer ID	23
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for stopping ozone generation?
Answer Text	The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.
statement Text	The Relay Module shall include a shutdown sequence that maintains the required cooling

statement 108

statement

The Relay Module shall include a shutdown sequence that maintains the required gas-flow/purge functions for the specified post-run period

Answer

The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.

Question

What is the required sequence of operations for stopping ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	23
Answer ID	23
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for stopping ozone generation?
Answer Text	The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.
statement Text	The Relay Module shall include a shutdown sequence that maintains the required gas-flow/purge functions for the specified post-run period

statement 109

statement

The Relay Module shall include a shutdown sequence that maintains the safely de-energizes the remaining auxiliaries in the defined order

Answer

The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.

Question

What is the required sequence of operations for stopping ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	23
Answer ID	23
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for stopping ozone generation?
Answer Text	The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.
statement Text	The Relay Module shall include a shutdown sequence that maintains the safely de-energizes the remaining auxiliaries in the defined order

statement 110

statement

The Relay Module shall include a shutdown sequence that maintains the confirms that the process has reached the stopped state

Answer

The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.

Question

What is the required sequence of operations for stopping ozone generation?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	23
Answer ID	23
Stakeholder Role	Process Engineer
Question Text	What is the required sequence of operations for stopping ozone generation?
Answer Text	The shutdown sequence shall first disable ozone generation, maintain the required cooling and gas-flow/purge functions for the specified post-run period, safely de-energize the remaining auxiliaries in the defined order, and finally confirm that the process has reached the stopped state.
statement Text	The Relay Module shall include a shutdown sequence that maintains the confirms that the process has reached the stopped state

statement 111

statement

The Relay Module shall permit ozone generation only when all required utilities are available

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when all required utilities are available

statement 112

statement

The Relay Module shall permit ozone generation only when gas flow is within their specified limits

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when gas flow is within their specified limits

statement 113

statement

The Relay Module shall permit ozone generation only when cooling is within their specified limits

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when cooling is within their specified limits

statement 114

statement

The Relay Module shall permit ozone generation only when required valves are in their correct states

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when required valves are in their correct states

statement 115

statement

The Relay Module shall permit ozone generation only when required auxiliaries are in their correct states

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when required auxiliaries are in their correct states

statement 116

statement

The Relay Module shall permit ozone generation only when no active safety interlock is violated

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when no active safety interlock is violated

statement 117

statement

The Relay Module shall permit ozone generation only when no active process interlock is violated

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when no active process interlock is violated

statement 118

statement

The Relay Module shall permit ozone generation only when all required feedback signals are valid

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when all required feedback signals are valid

statement 119

statement

The Relay Module shall permit ozone generation only when the system is in an authorized operating mode

Answer

Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.

Question

What conditions must be satisfied before ozone generation is permitted to start?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	24
Answer ID	24
Stakeholder Role	Process Engineer
Question Text	What conditions must be satisfied before ozone generation is permitted to start?
Answer Text	Ozone generation shall be permitted only when all required utilities are available, gas flow and cooling are within their specified limits, required valves and auxiliaries are in their correct states, no active safety or process interlock is violated, all required feedback signals are valid, and the system is in an authorized operating mode.
statement Text	The Relay Module shall permit ozone generation only when the system is in an authorized operating mode

statement 120

statement

The Relay Module shall immediately stop ozone generation whenever a condition capable of creating an unsafe or uncontrolled process state is detected

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation whenever a condition capable of creating an unsafe or uncontrolled process state is detected

statement 121

statement

The Relay Module shall immediately stop ozone generation when detected a loss of required gas flow

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected a loss of required gas flow

statement 122

statement

The Relay Module shall immediately stop ozone generation when detected a loss of required cooling

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected a loss of required cooling

statement 123

statement

The Relay Module shall immediately stop ozone generation when detected a critical equipment failure

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected a critical equipment failure

statement 124

statement

The Relay Module shall immediately stop ozone generation when detected hazardous process-variable limits

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected hazardous process-variable limits

statement 125

statement

The Relay Module shall immediately stop ozone generation when detected loss of required safety permissives

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected loss of required safety permissives

statement 126

statement

The Relay Module shall immediately stop ozone generation when detected emergency shutdown

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected emergency shutdown

statement 127

statement

The Relay Module shall immediately stop ozone generation when detected defined critical interlock

Answer

Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.

Question

What process conditions require ozone generation to stop immediately?

Stakeholder

Process Engineer

Field	Value
Stakeholder ID	5
Question ID	25
Answer ID	25
Stakeholder Role	Process Engineer
Question Text	What process conditions require ozone generation to stop immediately?
Answer Text	Ozone generation shall stop immediately whenever a condition capable of creating an unsafe or uncontrolled process state is detected, including loss of required gas flow or cooling, critical equipment failure, hazardous process-variable limits, loss of required safety permissives, emergency shutdown, or any other defined critical interlock.
statement Text	The Relay Module shall immediately stop ozone generation when detected defined critical interlock