


Try Applications Manager to find out why your apps are slow.



Grid, Chart, Map. 100% Store compliant. Try for free! [telerik.com/win8](http://telerik.com/win8)

Getting Started

Getting Started with Web API 2 (C#)

Pro ASP.NET Web API

ASP.NET Web API Poster

ASP.NET Web API Poster (Grayscale)

Creating Web APIs

Web API Clients

Web API Routing and Actions

Working with HTTP

Formats and Model Binding

OData

Security

Hosting ASP.NET Web API

Testing and Debugging

Extensibility

Additional Resources

# Getting Started with ASP.NET Web API 2 (C#)


By Mike Wasson | January 21, 2012

Like 159

Tweet 78

HTTP is not just for serving up web pages. It is also a powerful platform for building APIs that expose services and data. HTTP is simple, flexible, and ubiquitous. Almost any platform that you can think of has an HTTP library, so HTTP services can reach a broad range of clients, including browsers, mobile devices, and traditional desktop applications.

ASP.NET Web API is a framework for building web APIs on top of the .NET Framework. In this tutorial, you will use ASP.NET Web API to create a web API that returns a list of products. The front-end web page uses jQuery to display the results.



[Download the completed project.](#)


## Requirements

This tutorial uses [Visual Studio 2013](#).


## Create a Web API Project

Start Visual Studio and select **New Project** from the **Start** page. Or, from the **File** menu, select **New** and then **Project**.

In the **Templates** pane, select **Installed Templates** and expand the **Visual C#** node. Under **Visual C#**, select **Web**. In the list of project templates, select **ASP.NET Web Application**. Name the project "ProductsApp" and click **OK**.



In the **New ASP.NET Project** dialog, select the **Empty** template. Under "Add folders and core references for", check **Web API**. Click **OK**.




You can also create a Web API project using the "Web API" template. The Web API template uses ASP.NET MVC to provide API help pages. I'm using the Empty template for this tutorial because I want to show Web API without MVC. In general, you don't need to know ASP.NET MVC to use Web API.

## Adding a Model

A *model* is an object that represents the data in your application. ASP.NET Web API can automatically serialize your model to JSON, XML, or some other format, and then write the serialized data into the body of the HTTP response message. As long as a client can read the serialization format, it can deserialize the object. Most clients can parse either XML or JSON. Moreover, the client can indicate which format it wants by setting the Accept header in the HTTP request message.

Let's start by creating a simple model that represents a product.

If Solution Explorer is not already visible, click the **View** menu and select **Solution Explorer**. In Solution Explorer, right-click the Models folder. From the context menu, select **Add** then select **Class**.



Name the class "Product". Add the following properties to the **Product** class.

```
namespace ProductsApp.Models
{
    public class Product
    {
        public int Id { get; set; }
    }
}
```


```
        public string Name { get; set; }
        public string Category { get; set; }
        public decimal Price { get; set; }
    }
}
```

## Adding a Controller


In Web API, a *controller* is an object that handles HTTP requests. We'll add a controller that can return either a list of products or a single product specified by ID.

**Note** If you have used ASP.NET MVC, you are already familiar with controllers. Web API controllers are similar to MVC controllers, but inherit the **ApiController** class instead of the **Controller** class.


In **Solution Explorer**, right-click the the Controllers folder. Select **Add** and then select **Controller**.




In the **Add Scaffold** dialog, select **Web API Controller - Empty**. Click **Add**.



In the **Add Controller** dialog, name the controller "ProductsController". Click **Add**.



The scaffolding creates a file named ProductsController.cs in the Controllers folder.



You don't need to put your controllers into a folder named Controllers. The folder name is just a convenient way to organize your source files.

If this file is not open already, double-click the file to open it. Replace the code in this file with the following:

```
using ProductsApp.Models;
using System;
using System.Collections.Generic;
using System.Linq;
using System.Net;
using System.Web.Http;

namespace ProductsApp.Controllers
{
    public class ProductsController : ApiController
    {
        Product[] products = new Product[]
        {
            new Product { Id = 1, Name = "Tomato Soup", Category = "Groceries", Price = 1 },
            new Product { Id = 2, Name = "Yo-yo", Category = "Toys", Price = 3.75M },
            new Product { Id = 3, Name = "Hammer", Category = "Hardware", Price = 16.99M }
        };

        public IEnumerable<Product> GetAllProducts()
        {
            return products;
        }

        public IHttpActionResult GetProduct(int id)
        {
            var product = products.FirstOrDefault((p) => p.Id == id);
            if (product == null)
            {
                return NotFound();
            }
            return Ok(product);
        }
    }
}
```

To keep the example simple, products are stored in a fixed array inside the controller class. Of course, in a real application, you would query a database or use some other external data source.

The controller defines two methods that return products:

- The `GetAllProducts` method returns the entire list of products as an **`IEnumerable<Product>`** type.
- The `GetProductById` method looks up a single product by its ID.

That's it! You have a working web API. Each method on the controller corresponds to one or more URIs:

Controller Method	URI
<code>GetAllProducts</code>	<code>/api/products</code>
<code>GetProductById</code>	<code>/api/products/<i>id</i></code>

For the `GetProductById` method, the *id* in the URI is a placeholder. For example, to get the product with ID of 5, the URI is `api/products/5`.


For more information about how Web API routes HTTP requests to controller methods, see [Routing in ASP.NET Web API](#).




# Calling the Web API with Javascript and jQuery

In this section, we'll add an HTML page that uses AJAX to call the web API. We'll use jQuery to make the AJAX calls and also to update the page with the results.

In Solution Explorer, right-click the project and select **Add**, then select **New Item**.



In the **Add New Item** dialog, select the **Web** node under **Visual C#**, and then select the **HTML Page** item. Name the page "index.html".



Replace everything in this file with the following:

```
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <title>Product App</title>
</head>
<body>

  <div>
    <h2>All Products</h2>
    <ul id="products" />
  </div>
  <div>
    <h2>Search by ID</h2>
    <input type="text" id="prodId" size="5" />
    <input type="button" value="Search" onclick="find();" />
    <p id="product" />
  </div>

  <script src="http://ajax.aspnetcdn.com/ajax/jquery/jquery-2.0.3.min.js"></script>
  <script>
    var uri = 'api/products';

    $(document).ready(function () {
      // Send an AJAX request
      $.getJSON(uri)
        .done(function (data) {
          // On success, 'data' contains a list of products.
```

```

        $.each(data, function (key, item) {
            // Add a list item for the product.
            $('<li>', { text: formatItem(item) }).appendTo($('#products'));
        });
    });

    function formatItem(item) {
        return item.Name + ': $' + item.Price;
    }

    function find() {
        var id = $('#prodId').val();
        $.getJSON(uri + '/' + id)
            .done(function (data) {
                $('#product').text(formatItem(data));
            })
            .fail(function (jqXHR, textStatus, err) {
                $('#product').text('Error: ' + err);
            });
    }
}
</script>
</body>
</html>

```

There are several ways to get jQuery. In this example, I used the [Microsoft Ajax CDN](#). You can also download it from <http://jquery.com/>, and the ASP.NET "Web API" project template includes jQuery as well.

## Getting a List of Products

To get a list of products, send an HTTP GET request to `/api/products`.

The jQuery [getJSON](#) function sends an AJAX request. For response contains array of JSON objects. The **done** function specifies a callback that is called if the request succeeds. In the callback, we update the DOM with the product information.

```

$(document).ready(function () {
    // Send an AJAX request
    $.getJSON(apiUrl)
        .done(function (data) {
            // On success, 'data' contains a list of products.
            $.each(data, function (key, item) {
                // Add a list item for the product.
                $('<li>', { text: formatItem(item) }).appendTo($('#products'));
            });
        });
});

```

## Getting a Product By ID

To get a product by ID, send an HTTP GET request to `/api/products/id`, where *id* is the product ID.

```


function find() {
    var id = $('#prodId').val();
    $.getJSON(apiUrl + '/' + id)
        .done(function (data) {
            $('#product').text(formatItem(data));
        })
        .fail(function (jqXHR, textStatus, err) {
            $('#product').text('Error: ' + err);
        });
}

```


We still call **getJSON** to send the AJAX request, but this time we put the ID in the request URI. The response from this request is a JSON representation of a single product.

## Running the Application


Press F5 to start debugging the application. The web page should look like the following:



To get a product by ID, enter the ID and click Search:



If you enter an invalid ID, the server returns an HTTP error:



## Using F12 to View the HTTP Request and Response

When you are working with an HTTP service, it can be very useful to see the HTTP request and request messages. You can do this by using the F12 developer tools in Internet Explorer 9. From Internet Explorer 9, press **F12** to open the tools. Click the **Network** tab and press **Start Capturing**. Now go back to the web page and press **F5** to reload the web page. Internet Explorer will capture the HTTP traffic between the browser and the web server. The summary view shows all the network traffic for a page:

F12

File Find Disable View Images Cache Tools Validate | Browser Mode: IE9 Doc

HTML CSS Console Script Profiler **Network**

Stop capturing
 Go to detailed view

URL	Met...	Result	Type	Received	Taken
http://localhost:26481/	GET	200	text/html	1.66 KB	78 ms
/Content/css?v=ji3nO1pdg6VLv3CV...	GET	200	text/css	0.89 KB	47 ms
/Content/themes/base/css?v=UM62...	GET	200	text/css	24.73 KB	63 ms
/Scripts/js?v=4h5IPNUsLiFoa0vqrItj...	GET	200	text/javascript	325.88...	62 ms
/Scripts/jquery-1.6.2.min.js	GET	304	application/x-ja...	176 B	47 ms
/api/products/	GET	200	application/json	398 B	281 ms

Locate the entry for the relative URI "api/products/". Select this entry and click **Go to detailed view**. In the detail view, there are tabs to view the request and response headers and bodies. For example, if you click the **Request headers** tab, you can see that the client requested "application/json" in the Accept header.

HTML CSS Console Script Profiler **Network**

Stop capturing
 Back to summary view
 < Prev

URL: http://localhost:26481/api/products/

Request headers	Request body	Response headers	Response body	Cookies	Initiator	Timings
Key	Value					
Request	GET /api/products/ HTTP/1.1					
X-Requested-With	XMLHttpRequest					
Accept	application/json, text/javascript, */*; q=0.01					
Referer	http://localhost:26481/					
Accept-Language	en-us					
Accept-Encoding	gzip, deflate					
User-Agent	Mozilla/5.0 (compatible; MSIE 9.0; Windows NT 6.0; Trident/5.0)					
Host	localhost:26481					
Connection	Keep-Alive					

If you click the Response body tab, you can see how the product list was serialized to JSON. Other browsers have similar functionality. Another useful tool is [Fiddler](#), a web debugging proxy. You can use Fiddler to view your HTTP traffic, and also to compose HTTP requests, which gives you full control over the HTTP headers in the request.


### Next Steps

- For a more complete example of an HTTP service that supports POST, PUT, and DELETE actions, see [Creating a Web API that Supports CRUD Operations](#).
- For more about creating fluid and responsive web applications on top of an HTTP service, see [ASP.NET Single Page Application](#).
- You can make your web API available over the Internet by deploying it to a hosting provider. Microsoft offers free web hosting for up to 10 web sites in a [free Windows Azure trial account](#). For information about how to deploy a Visual Studio web project to a Windows Azure Web Site, see [Deploying an ASP.NET Web Application to a Windows Azure Web Site](#).

Like
 159

Tweet
 78

### Author Information



**Mike Wasson** – Mike Wasson is a programmer-writer at Microsoft.

Comments (52) [You must be logged in to leave a comment.](#)  
[Show Comments](#)





Test less. Build more.  
Scan your site for common coding issues.

Scan your site now

