

# COURSE "AUTOMATED PLANNING: THEORY AND PRACTICE"

## CHAPTER 09: GOAL COUNT - A SIMPLE DOMAIN INDEPENDENT HEURISTIC FUNCTION

Teacher: **Marco Roveri** - [marco.roveri@unitn.it](mailto:marco.roveri@unitn.it)  
M.S. Course: Artificial Intelligence Systems (LM)  
A.A.: 2025-2026  
Where: DISI, University of Trento  
URL: <https://shorturl.at/A81hf>



Last updated: Wednesday 15<sup>th</sup> October, 2025

# TERMS OF USE AND COPYRIGHT

## USE

This material (including video recording) is intended solely for students of the University of Trento registered to the relevant course for the Academic Year 2025-2026.

## SELF-STORAGE

Self-storage is permitted only for the students involved in the relevant courses of the University of Trento and only as long as they are registered students. Upon the completion of the studies or their abandonment, the material has to be deleted from all storage systems of the student.

## COPYRIGHT

The copyright of all the material is held by the authors. Copying, editing, translation, storage, processing or forwarding of content in databases or other electronic media and systems without written consent of the copyright holders is forbidden. The selling of (parts) of this material is forbidden. Presentation of the material to students not involved in the course is forbidden. The unauthorised reproduction or distribution of individual content or the entire material is not permitted and is punishable by law.

The material (text, figures) in these slides is authored by Jonas Kvarnström and Marco Roveri.

# HEURISTICS GIVEN STRUCTURED STATES

- In planning, we often want **domain-independent** heuristics
  - Should work for **any** planning domain - how?
- Take advantage of **structured high-level representation**!

## PLAIN STATE TRANSITION SYSTEM

- We are in state 572242104485172012
- The goal is to be in one of the  $10^{47}$  states in  $S_g = \{s[482293], s[482294], \dots\}$
- Should we try action A297295283291 leading to state 572342104485172016?
- Or may be action A297295283292 leading to state 572342104485175202?

## CLASSICAL REPRESENTATION

- We are in a state where **disk 1 is on top of disk 2**
- The goal is for all disks to be on peg C
- Should we try (take B), leading to a state where we are holding disk 1?
- ...




# AN INTUITIVE HEURISTIC

- Assumptions
  - *Forward state space planning*: Nodes  $n$  are states  $s$
  - Classical expressivity: goal is a set of *ground literals*  
 $\{ (on\ A\ B),\ (not\ (handempty)) \}$
- An **intuitive** idea for  $h(s)$ :
  - Try to estimate the number of **actions** required to **reach the goal** from  $s$ 
    - Should be **related** to how many **goal facts** are not yet achieved in  $s$
  - Let  $h(s) = \text{number of goal literals that are not achieved in } s$ 
    - $h(s) = |(g^+ \setminus s) \cup (g^- \setminus s)|$
    - Not the expected **cost** to achieve those goals!
- An associated **search strategy**:
  - Let's use **Greedy Best First Search**!

# COUNTING REMAINING GOALS


- Count the number of "missing" goal literals!



Optimal plan: (unstack A C) (stack A B) (pickup C)(stack C A)


# COUNTING REMAINING GOALS (CONT.)

- A **perfect** solution? **No!**
  - We must often **unachieve** individual goal literals to get closer to the goal!



Optimal plan: (unstack A C) (putdown A) (pickup B) (stack B C) (pickup A) (stack A B)

## EXAMPLE: BLOCK WORLD - A\* SEARCH, BASED ON GOAL COUNT!




18 actions in  $\pi$

States: 6463 calculated, 3222 visited

(With Dijkstra 43150/33436 - improved  
but we can do better!)


- $h(s_0) = 1$ : Only one "missing" literal
- For a long time, all **useful** successors appear to **increase** remaining cost
  - Removing a block that must be moved
- And many **useless** successors appear to **decrease** remaining cost
  - Building towers that will need to be torn down



Not very  
informative

## COUNTING REMAINING GOALS (CONT.)

- Admissible? No!
  - (Doesn't matter in our chosen search strategy!)



- Can we **make** it admissible?
  - Yes: Divide** by the maximum number of facts modified by any action!



# COUNTING REMAINING GOALS: ANALYSIS

- What we see for this example...
  - Not very much: **All heuristics have weaknesses!**

Even the **best planners** will make "strange" choices, visit **tens**, **hundreds** or even **thousands** of "unproductive" nodes for every action in the final plan!

The heuristic should make sure we don't need to visit **millions**, **billions** or even **trillions** of "unproductive" nodes for every action in the final plan!

- But a thorough empirical analysis would tell us:
  - **This** heuristic is **far** from being sufficient!

# EXAMPLE STATISTICS: PLANNING COMPETITION 2011

- Elevators domain, problem 1
  - $A^*$  with goal counter heuristics
    - States: 108,922,864 generated, ... gave up!
  - LAMA 2011 planner, good heuristics, other strategy:
    - Solution: 79 steps, 369 cost
    - States: 13,236 generated, 425 evaluated/expanded
- Elevators domain, problem 5
  - LAMA 2011 planner
    - Solution: 112 steps, 523 cost
    - States: 41,811 generated, 1,317 evaluated/expanded
- Elevators domain, problem 20
  - LAMA 2011 planner
    - Solution: 354 steps, 2182 cost
    - States: 1,364,657 generated, 14,984 evaluated/expanded

<http://www.plg.inf.uc3m.es/ipc2011-deterministic/>

<https://www.icaps-conference.org/competitions/>

- Important insight
  - Even a state-of-the-art planner can't go *directly* to a goal state!
  - Generates *many* more states than those actually on the path to the goal...

# REFERENCES I

- [1] Hector Geffner and Blai Bonet. *A Concise Introduction to Models and Methods for Automated Planning*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool Publishers, 2013. ISBN 9781608459698. doi: 10.2200/S00513ED1V01Y201306AIM022. URL <https://doi.org/10.2200/S00513ED1V01Y201306AIM022>.
- [2] Malik Ghallab, Dana S. Nau, and Paolo Traverso. *Automated planning - theory and practice*. Elsevier, 2004. ISBN 978-1-55860-856-6.
- [3] Malik Ghallab, Dana S. Nau, and Paolo Traverso. *Automated Planning and Acting*. Cambridge University Press, 2016. ISBN 978-1-107-03727-4. URL <http://www.cambridge.org/de/academic/subjects/computer-science/artificial-intelligence-and-natural-language-processing/automated-planning-and-acting?format=HB>.
- [4] Patrik Haslum, Nir Lipovetzky, Daniele Magazzeni, and Christian Muise. *An Introduction to the Planning Domain Definition Language*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool Publishers, 2019. doi: 10.2200/S00900ED2V01Y201902AIM042. URL <https://doi.org/10.2200/S00900ED2V01Y201902AIM042>.