

Infrastructure Comparison Tables

Martina Castellucci

Comparison Tables

Docker vs Docker Compose vs Udocker

Feature	Docker	Docker Compose	Udocker
Root Access	Required for daemon	Depends on setup	Not required; runs in user space
Use Case	Running individual containers	Orchestrating multi-container apps	Running containers in HPC without root
Security	Host-level access required	Shares Docker context	User-level, no root access
Deployment	CLI or GUI	Uses YAML config files	CLI compatible with Docker images

Cloud Models

Model	Description and Responsibility
IaaS (Infrastructure as a Service)	Provides virtualized computing resources over the internet. The user manages the operating system, storage, deployed applications, and runtime. Examples include AWS EC2, Google Compute Engine, Microsoft Azure VM.
PaaS (Platform as a Service)	Provides a platform allowing customers to develop, run, and manage applications without dealing with infrastructure. The provider handles OS, middleware, and runtime. Examples: Heroku, Google App Engine.
SaaS (Software as a Service)	Offers ready-to-use software applications over the web. The provider manages everything from infrastructure to software. Users only interact with the interface. Examples: Gmail, Dropbox, Microsoft 365.

Cooling Techniques

Method	Description
Air Cooling	Uses fans and heat sinks to remove heat from components. It is the most economical method, ideal for general-purpose systems, but becomes inefficient in high-density setups.
Liquid Cooling	Employs a coolant fluid circulated via tubes and blocks to draw heat away from processors and components. Offers superior thermal performance and quieter operation.
Immersion Cooling	Submerges entire components or servers in a dielectric fluid. It ensures uniform cooling, reduces noise, and is used in high-performance, energy-efficient data centers.

File Systems

File System	Usage and Characteristics
ext4	Widely used local file system on Linux. Supports journaling, fast performance, good for general-purpose servers.
xfs	High-performance journaling FS for parallel I/O. Efficient for large files and used in enterprise Linux systems.
NFS	Network File System. Enables sharing files over network. Suitable for shared storage in clusters.
GPFS (IBM Spectrum Scale)	Parallel file system for HPC. Provides scalability and high-throughput for large workloads.
Lustre	Designed for large-scale parallel file systems in supercomputers and clusters. Open source and scalable.

Kubernetes vs Docker

Aspect	Docker	Kubernetes
Function	Tool to build, run, and manage containers on a single host	Orchestration system to deploy, scale, and manage containers across multiple hosts
Scalability	Limited to a single host (or Docker Swarm)	Designed for scaling across many machines and fault tolerance
Networking	Provides simple bridge and host networking	Built-in service discovery and load balancing via Services
Use Case	Local development, small deployments	Production-grade orchestration of microservices at scale

Cloud vs Virtualization

Aspect	Description
Virtualization	Virtualization allows multiple operating systems to run on the same physical hardware by abstracting the hardware using a hypervisor (e.g., KVM, VMware ESXi). It forms the basis for cloud computing but can be used independently in on-prem setups.
Cloud Computing	A service delivery model that provides access to computing resources (VMs, storage, databases, etc.) over the internet. Built on top of virtualization, it adds elasticity, scalability, APIs, billing, and managed services.

Recall vs Backfill vs Reservation

Term	Meaning
Recall	The process of reclaiming allocated but unused or idle resources (e.g., from preemptible or low-priority jobs) so they can be reassigned. Useful in opportunistic environments.
Backfill	A scheduling strategy where smaller jobs are temporarily scheduled in idle gaps between larger reservations, improving overall resource utilization without delaying high-priority jobs.
Reservation	Explicit allocation of compute resources for a specific user, group, or job at a future time. Ensures resource availability for time-sensitive workloads.

OSI vs TCP/IP Models

Layer	OSI Model	TCP/IP Model
Layer 7	Application	Application
Layer 6	Presentation	– (merged into Application)
Layer 5	Session	– (merged into Application)
Layer 4	Transport	Transport
Layer 3	Network	Internet
Layer 2	Data Link	Network Access
Layer 1	Physical	Network Access

TOR (The Onion Router) Architecture

Layer	Function
Entry Node	First relay in the TOR network. It knows the user's IP address and establishes an encrypted path to the next node.
Relay Node	Intermediate node that passes traffic in encrypted form. It does not know the source or final destination.
Exit Node	Final node in the circuit. It decrypts the last layer and forwards the request to the destination server. It sees the destination but not the source.

HTCondor vs SLURM

Feature	HTCondor	SLURM (HPC Scheduler)
Scheduling Model	Opportunistic scheduling with late-binding	Resource-reservation with partitioned scheduling
Target Use	High Throughput Computing (HTC), grid environments	High Performance Computing (HPC), tightly coupled tasks
Fault Tolerance	Supports checkpointing and job migration	Limited fault tolerance; job restarts on failure
Resource Match	Uses ClassAds to match jobs with resources	Uses queues and partitions, less dynamic
Scalability	Scales across heterogeneous systems in a grid	Scales efficiently in tightly integrated clusters

INFN CNAF vs Other Sites

Location	Description
INFN CNAF	National computing center (Tier-1) in Bologna. Offers large-scale storage, computing, and data services for LHC and Italian research. Connected to GRID, provides access to HPC and HTC resources.
Other Sites	Regional centers (Tier-2 or Tier-3). Focused on localized support, smaller infrastructure, often used for pre-processing or analysis tied to larger collaborations.

Amdahl's Law: Speedup vs Efficiency

Metric	Formula and Explanation
Speedup (S)	$S = \frac{1}{(1-P) + \frac{P}{N}}$ — quantifies how much faster a program runs when parallelized, where P is the parallelizable portion and N the number of processors.
Efficiency (E)	$E = \frac{S}{N}$ — evaluates how effectively the parallel resources are being used; close to 1 means optimal utilization.

Power vs Storage

Aspect	Metric / Description
Power	Measured in Watts. TDP (Thermal Design Power) indicates the max heat a component generates; influences cooling requirements.
Storage	Measured in GB/TB. Performance determined by latency, throughput, and IOPS (Input/Output Operations Per Second).

Node vs Job

Entity	Description
Node	A compute resource — physical or virtual — in a cluster that executes assigned jobs. Often includes CPUs, RAM, and access to shared storage.
Job	A user-defined task or process submitted to a scheduler for execution on one or more nodes. Can be serial, parallel, or array-based.

Server vs Data Center vs Distributed

System Type	Scope and Characteristics
Server	A single machine offering computing or storage services. Can be physical or virtual and may serve multiple users or applications.
Data Center	A facility that houses many servers with supporting infrastructure (cooling, power, security). Centralized and managed IT operations.
Distributed Computing	A computing model in which components located on networked computers communicate and coordinate to achieve a common goal. Supports scalability and fault tolerance.

CPU vs GPU

Feature	CPU (Central Processing Unit)	GPU (Graphics Processing Unit)
Purpose	General-purpose computing	Parallel processing, mainly for graphics and large-scale computations
Cores	Fewer (2–64), optimized for sequential tasks	Hundreds to thousands of cores, optimized for parallel tasks
Latency	Low latency per task	Higher latency per task
Throughput	Lower overall throughput	Very high throughput
Use Case	OS management, general logic, low-latency tasks	Deep learning, image rendering, matrix operations

Single-core vs Multi-core CPU

Aspect	Single-core CPU	Multi-core CPU
Definition	One execution core per CPU	Multiple cores in a single CPU chip
Parallelism	Executes one thread at a time	Executes multiple threads simultaneously
Performance	Slower for multitasking	Better multitasking and parallel computing
Power Consumption	Typically lower	More power, but better performance/watt
Use Cases	Embedded devices, old systems	Modern desktops, servers, smartphones

The 5 Vs of Big Data

V	Description
Volume	Refers to the huge amounts of data generated every second (e.g., terabytes, petabytes)
Velocity	Speed at which data is generated, processed, and analyzed
Variety	Different types of data: structured, semi-structured, unstructured
Veracity	Quality and trustworthiness of data; presence of noise and uncertainty
Value	The usefulness of the data once processed and analyzed

DAS vs NAS vs SAN

Type	Description
DAS (Direct Attached Storage)	Storage attached directly to a server or workstation without a network
NAS (Network Attached Storage)	File-level storage shared over a network; uses protocols like NFS, SMB
SAN (Storage Area Network)	Block-level storage accessed over a high-speed network, typically via Fibre Channel or iSCSI

Edge vs Fog vs Cloud Computing

Model	Description
Edge Computing	Processing done near the data source (e.g., sensors); reduces latency and bandwidth
Fog Computing	Intermediate layer between edge and cloud; distributes computing/storage closer to edge
Cloud Computing	Centralized processing in data centers; offers scalability, redundancy, and global access

AWS and IaaS Example

Service	Description
AWS EC2	Elastic Compute Cloud; provides resizable compute capacity in the cloud (IaaS)
AWS S3	Simple Storage Service; object storage with web interface, often used with EC2
AWS VPC	Virtual Private Cloud; isolated network for AWS resources
Relation to IaaS	AWS provides IaaS by allowing users to manage VMs, storage, and networking infrastructure

Batch Computing vs Cloud Computing

Feature	Batch Computing	Cloud Computing
Job Execution	Scheduled in queues, managed by local scheduler	On-demand job execution via cloud APIs
Resource Allocation	Static, predefined	Elastic and scalable
Cost Model	Fixed, shared among users	Pay-per-use (metered billing)
Infrastructure	On-premise or academic clusters	Hosted and managed by provider (e.g., AWS, Azure)

Batch Computing vs Grid Computing

Aspect	Batch Computing	Grid Computing
Scope	Typically within a single organization or cluster	Federated, across multiple administrative domains
Resource Sharing	Centralized, static	Decentralized, dynamic sharing
Middleware	Simple batch schedulers (e.g., SLURM, PBS)	Grid middleware (e.g., gLite, Globus, ARC)
Security	Based on local users	Often uses certificates and federated identities

Scheduler vs Cloud Provider

Aspect	Scheduler (e.g., SLURM, HTCondor)	Cloud Provider (e.g., AWS, Azure)
Responsibility	Manages job queueing, prioritization, and execution on a cluster	Provides infrastructure and services for compute, storage, and networking
Control	Full control over resource management	Limited to APIs and services offered
Location	Local clusters or HPC/HTC systems	Remote, virtualized data centers
Scalability	Bound to physical resources	Virtually unlimited scaling

Dockerfile vs Docker Image

Concept	Dockerfile	Docker Image
Definition	Script with instructions to build an image	Executable snapshot of a container environment
Use	Written by developer to define build steps	Created after Dockerfile is built; used to run containers
Example COPY . /app	FROM python:3.8 myimage:v1 (result of docker build)	

Digital Twins

Term	Description
Digital Twin	A digital representation of a real-world object or system that is updated with real-time data. Used for monitoring, simulation, and optimization (e.g., industrial IoT, smart cities).

Cloud-Aware vs Cloud-Native Efficiency

Aspect	Cloud-Aware	Cloud-Native
Definition	Applications adapted to run in cloud	Applications designed for cloud from the ground up
Architecture	Monolithic or partially containerized	Microservices, containers, orchestration (Kubernetes)
Scaling	Manual or limited automation	Automatic, elastic scaling
Efficiency	Limited by legacy architecture	Fully optimized for distributed environments

IP vs MAC Address + Common IPs

Term	Description
IP Address	Logical address used for routing on network layer (e.g., 192.168.0.1)
MAC Address	Physical address tied to network interface; layer 2 identifier (e.g., 00:1A:2B:3C:4D:5E)
127.0.0.1	Loopback address (localhost); used for internal testing
0.0.0.0	Non-routable address; binds to all available interfaces

Checksums

Term	Description
Checksum	A value derived from data to detect errors or integrity loss. Common algorithms: MD5, SHA-1, SHA-256.
Use Cases	File verification, network transmission, package downloads

BLASTn vs BWA

Tool	BLASTn	BWA
Purpose	Nucleotide sequence similarity search	Read alignment to reference genome
Algorithm	Seed-and-extend; local alignment	Burrows-Wheeler Transform; global or semi-global
Speed	Slower, especially with large datasets	Very fast, optimized for NGS data
Use Case	Annotating genes, database comparison	DNA-seq data preprocessing, variant calling

HTT (High Throughput Technologies)

Term	Description
High Throughput Technologies	Techniques that allow simultaneous processing of a large number of samples or data points (e.g., microarrays, NGS, mass spectrometry). Key in omics and screening platforms.

WMS (Workflow Management Systems)

System	Description
WMS	Tools that help define, manage, and execute data pipelines (e.g., Snakemake, Nextflow, Galaxy). Support reproducibility, scalability, and parallelism in bioinformatics and big data workflows.

Vocabulary: Key Infrastructure Terms

Term	Definition
Switch	Network device that connects devices within a LAN and forwards data based on MAC addresses.
Router	Device that connects multiple networks and routes packets based on IP addresses. Often links LANs to WANs.
Hub	Basic network device that broadcasts data to all connected devices; no intelligence like a switch.
LAN (Local Area Network)	Network covering a small geographic area (e.g., office, home), typically high-speed.
WAN (Wide Area Network)	Network covering a large area, such as the internet or inter-office networks.
Hardware	The physical components of a computer or infrastructure (CPU, memory, disk, etc.).
Software	Programs and operating systems that run on hardware and control tasks.
Kernel	Core of the operating system that manages system resources and communication between hardware and software.
Host	A device (physical or virtual) that provides services and has an operating system installed.
OS (Operating System)	System software that manages computer hardware, software resources, and provides services for applications.
HDD (Hard Disk Drive)	Traditional spinning magnetic storage device, high capacity, slower access.
SSD (Solid State Drive)	Fast, non-volatile flash memory storage device with no moving parts.
NFS (Network File System)	Protocol that allows file access over a network as if local; used in shared UNIX/Linux environments.
NUMA (Non-Uniform Memory Access)	Memory architecture where access time depends on the memory's location relative to the processor.
UMA (Uniform Memory Access)	Architecture where all processors share physical memory uniformly.
L1 Cache	The smallest and fastest memory level, located closest to the CPU core; typically stores instructions and data.
L2 Cache	Larger than L1, slower but still fast; stores data used less frequently. Often shared among cores.
L3 Cache	Shared among all cores in a processor; bigger but slower than L2, reduces memory latency at higher levels.
RAID (Redundant Array of Independent Disks)	A method of storing data on multiple hard disks for redundancy and performance, using various levels (RAID 0, 1, 5, etc.) ²

Vocabulary: Key Infrastructure Terms 2)

Tiered Storage	Storage architecture that uses multiple storage media (e.g., SSD, HDD, tape) ranked by speed/cost, and data is moved accordingly.
Hyperthreading	Intel technology that allows one physical CPU core to execute two threads simultaneously to improve parallelism.
Throughput	The amount of data processed in a given time, often measured in bits per second or IOPS in storage.
Grid Computing	Distributed computing model where resources across multiple locations are federated and used collectively.
Cloud Computing	Delivery of computing services (compute, storage, networking) over the internet on demand.
Edge Computing	Processing data close to where it is generated (e.g., IoT sensors) to reduce latency.
Fog Computing	Extends cloud to be closer to edge devices, offering computation, storage, and networking.
Stream Processing	Real-time processing of continuous data streams (e.g., Kafka, Flink).
ALU (Arithmetic Logic Unit)	Part of the CPU that performs arithmetic and logical operations.
Control Unit	CPU component that directs operations of the processor; it fetches, decodes, and executes instructions.
I/O (Input/Output)	Interface between the computer and external devices; includes peripherals and network input/output.
Container	Lightweight, portable, and self-sufficient unit that includes everything needed to run a piece of software.
Docker	Popular container platform that automates deployment of applications inside containers.

Common Command Reference Table

Command	Function / Description
<code>docker pull <image></code>	Download an image from a Docker registry (e.g., Docker Hub)
<code>docker push <image></code>	Upload an image to a Docker registry
<code>docker run <image></code>	Create and start a container from an image
<code>docker create <image></code>	Create a container without starting it
<code>docker build -t <name> .</code>	Build an image from a Dockerfile in the current directory
<code>docker volume create <name></code>	Create a named volume (persistent storage for containers)
<code>docker-compose up</code>	Start all services defined in a docker-compose.yml file
<code>docker-compose down</code>	Stop and remove services, networks, volumes defined in the compose file
<code>udocker run <container></code>	Execute a container without requiring root privileges (HPC environments)
<code>condor_submit <file></code>	Submit a job to HTCondor using the specified job description file
<code>condor_q</code>	View the status of submitted jobs in the queue
<code>condor_status</code>	Show the status of machines in the Condor pool
<code>cat /proc/cpuinfo</code>	Display detailed CPU architecture and core information
<code>free -m</code>	Show memory usage in megabytes
<code>df -h</code>	Show available disk space on mounted file systems (human readable)
<code>mount</code>	List all currently mounted filesystems
<code>lsblk</code>	Show all block devices and partitions
<code>md5sum <file></code>	Generate or verify MD5 checksum for a file
<code>time <command></code>	Measure the time taken to execute a command (e.g., <code>time blastn</code>)
<code>blastn -query file -db nt -out res</code>	Run a nucleotide BLAST search