

The Merging Systems Identification (MeSsl) Algorithm.

Martín de los Rios, Mariano Domínguez, Dante Paz

July 30, 2015

Table of contents

1

Why searching merging galaxy clusters?

- Study dark matter particle properties.
- Test cosmological models.
- Study Intra-Clusters Medium properties.

2

The MeSsl Algorithm

- Machine learning algorithm applied for identification of substructures.
- Application of the MeSsl Algorithm to spectroscopy catalogues

3

Future Work

1 Why searching merging galaxy clusters?


- Study dark matter particle properties.
- Test cosmological models.
- Study Intra-Clusters Medium properties.

2 The MeSsl Algorithm

- Machine learning algorithm applied for identification of substructures.
- Application of the MeSsl Algorithm to spectroscopy catalogues

3 Future Work

You can study dark matter particle properties




Markevitch et al. 2004

- Desfasaje entre la materia oscura y el gas:

$\tau_s = \frac{\sigma}{m} \Sigma_s$ donde σ es la sección eficaz, m es la masa de la partícula y Σ_s es la densidad superficial de DM. La densidad superficial promediada dentro de $r = r_{tr}$ es $\Sigma \approx 0.2 gcm^{-2}$, entonces, asumiendo simetría esférica y pidiendo que $\tau_s < 1$ tenemos: $\frac{\sigma}{m} < 5 cm^2 g^{-1}$.

Cúmulo	$\frac{\sigma}{m}$
Bullet Cluster	$< 5 cm^2/g$
Musket Ball	$< 7 cm^2/g$
Baby Bullet	$< 4 cm^2/g$

- La gran velocidad del cúmulo secundario:



$$\bar{p} = mv_s \left[1 - 4 \int_{\sin \alpha_c}^1 x^2 \left(x^2 - \frac{V^2}{v^2} (1 - x^2) \right)^{1/2} dx \right] \approx 0.1mv_s \quad (1)$$

$$\frac{d(v - v_{ff})}{dt} = \frac{\bar{p}n}{M_s} = \frac{\bar{p}}{m} \frac{\sigma}{m} \rho_m v \quad (2)$$

$$v - v_{ff} = \frac{\bar{p}}{m} \frac{\sigma}{m} \Sigma_m \quad (3)$$

$$v - v_{ff} < 1000 \text{ km/s} \quad (4)$$

$$\frac{\sigma}{m} < 7 \text{ cm}^2/\text{g} \quad (5)$$

- La supervivencia del cúmulo secundario.

$$\chi = 1 - 2 \frac{v_{esc}^2}{v_0^2} \quad (6)$$



$$\tau_m = \frac{\sigma}{m} \Sigma_m \quad (7)$$

$$\chi \tau_m = \frac{\sigma}{m} \Sigma_m \left[1 - 2 \frac{v_{esc}^2}{v_0^2} \right] \quad (8)$$

$$\chi \tau_m < 0.3 \quad (9)$$

$$\frac{\sigma}{m} < 1 \text{ cm}^2 / g \quad (10)$$

Harvey et al. 2015



$$\frac{\sigma}{m} \leq 0.47 \text{ cm}^2/\text{g}$$

You can test your favourite cosmological model.

- Estudio de la probabilidad de que un cúmulo tenga una velocidad similar a la del bullet cluster.
 - Hayashi et al. 2006
 - Farrar y Rosen 2007
 - Lee y Komatsu 2010
 - Forero-Romero et al. 2010
 - Thompson y Nagamine 2011
 - Watson et al. 2013
- Estudios con simulaciones hidrodinámicas
 - Springel & Farrar. 2005
 - Milosavljevic et al. 2007
 - Mastropietro & Burket. 2008
 - Lage & Farrar 2014

The Rise and Fall of a challenger by Thompson (2014).

- They investigate the probability of finding such a high-velocity pair in large-volume N-body simulations, particularly focusing on differences between halo finding algorithms.
- When employing the Rockstart (Behroozi et al 1013) halo finder that considers particle velocities, they find numerous Bullet-like pair candidates that closely match not only the high pairwise velocity, but also the mass, mass ratio, separation distance, and collision angle that have been shown to produce the Bullet Cluster.
- The probability of finding a massive, high pairwise velocity pair among halos with $M_{\text{halo}} \geq 10^{14} M_{\odot}$ is 4.6×10^{-4} using RS, while it is $\approx 45\times$ lower using a friends-of-friends (FOF) based approach as in previous studies.

High velocity tail of Bullet like pairs.




Figure : Probability distribution function of massive halo pairs in largest simulation (L4500) identified by FOF (Red solid line) and RS (Blue solid line).

You can study the ICM properties.




Figure : Zhang et al. 2014


1 Why searching merging galaxy clusters?

- Study dark matter particle properties.
- Test cosmological models.
- Study Intra-Clusters Medium properties.

2 The MeSsl Algorithm

- Machine learning algorithm applied for identification of substructures.
- Application of the MeSsl Algorithm to spectroscopy catalogues

3 Future Work



Clusters identification.

- We construct a mock catalogue based on the results of the application of the SAM Model of Guo et al. 2010 to the Millenium simulation.

Clusters identification.


- We construct a mock catalogue based on the results of the application of the SAM Model of Guo et al. 2010 to the Millenium simulation.
- We Perform a friend-of-friend algorithm (*Merchan & Zandivares 2002*) to the mock catalog in order to identify the clusters.

Clusters identification.


- We construct a mock catalogue based on the results of the application of the SAM Model of Guo et al. 2010 to the Millenium simulation.
- We Perform a friend-of-friend algorithm (*Merchan & Zandivares 2002*) to the mock catalog in order to identify the clusters.
- We assign each identified cluster with a fof-group in the simulation.



Study of the merger trees.

- Based on the subhalos merger trees, we construct the merger tree for every fo group in the simulation.



- Dressler-Shectman test.
- Non gaussianity test.
- Color.
- Number of galaxies.





Study of the identified substructures.

- We ran a second stage of a random forest algorithm, applied to the galaxies.

Study of the identified substructures.

- We ran a second stage of a random forest algorithm, applied to the galaxies.
- In order to define substructures we identify clumps of galaxies based on their proximity, using a mixture of gaussians weighted by the probability of each galaxy of being part of a substructure, calculated with the RF.

Study of the identified substructures.

- We ran a second stage of a random forest algorithm, applied to the galaxies.
- In order to define substructures we identify clumps of galaxies based on their proximity, using a mixture of gaussians weighted by the probability of each galaxy of being part of a substructure, calculated with the RF.
- After the substructure identification, each one was related with the subhalo in the mock that have more galaxies in the group identified by mclust.

Study of the identified substructures.

- We ran a second stage of a random forest algorithm, applied to the galaxies.
- In order to define substructures we identify clumps of galaxies based on their proximity, using a mixture of gaussians weighted by the probability of each galaxy of being part of a substructure, calculated with the RF.
- After the substructure identification, each one was related with the subhalo in the mock that have more galaxies in the group identified by mclust.
- After that, we estimate the velocity dispersion and the virial radius.

$$\begin{aligned}
 R_{vir} &= \frac{\pi}{2} \frac{ngal(ngal - 1)}{\sum_{i>j}^{ngal} R_{ij}^{-1}} \\
 \sigma &= \frac{\sqrt{\pi}}{ngal(ngal - 1)} \sum_{i=1}^{ngal-1} \omega_i g_i \\
 \omega_i &= i(ngal - i) \\
 g_i &= v_{i+1} - v_i
 \end{aligned}$$

(11)

Study of the identified substructures.

- We compare the center of the identified substructures with the centers of the associated subhalos, finding a good estimation.

Study of the identified substructures.

- We compare the center of the identified substructures with the centers of the associated subhalos, finding a good estimation.
- We compare the virial radius of the identified substructures with the virial radius of the subhalos, finding that we are overestimating the real values.

Study of the identified substructures.

- We compare the center of the identified substructures with the centers of the associated subhalos, finding a good estimation.
- We compare the virial radius of the identified substructures with the virial radius of the subhalos, finding that we are overestimating the real values.
- We compare the velocity dispersion of the identified substructures with the velocity dispersion of the associated subhalos, finding that our values are in good concordance with the real values.

With this association between substructure and subhalos in the mock, we find 3 cases:

- 1 Clusters where we identify the type 0 subhalo (the principal subhalo of the fof group) and a type 1 subhalo.

With this association between substructure and subhalos in the mock, we find 3 cases:


- 1 Clusters where we identify the type 0 subhalo (the principal subhalo of the fof group) and a type 1 subhalo.
- 2 Clusters where we identify two type 1 subhalos.

With this association between substructure and subhalos in the mock, we find 3 cases:



- 1 Clusters where we identify the type 0 subhalo (the principal subhalo of the fof group) and a type 1 subhalo.
- 2 Clusters where we identify two type 1 subhalos.
- 3 Clusters where Mclust find two substructures that are associated to the same type 0 subhalo.

With this association between substructure and subhalos in the mock, we find 3 cases:

- 1 Clusters where we identify the type 0 subhalo (the principal subhalo of the fof group) and a type 1 subhalo.
- 2 Clusters where we identify two type 1 subhalos.
- 3 Clusters where Mclust find two substructures that are associated to the same type 0 subhalo.




Mock Clusters




Application of the MeSsl Algorithm to spectroscopy catalogues

- We find 12 Clusters with high probability of been in a merger in the SDSS DR7.

Abell 1991




- We find 7 Clusters with high probability of been in a merger in the WINGS Clusters.



- We find 15 Clusters with high probability of been in a merger in the HECs Clusters.

Abell 2631



1 Why searching merging galaxy clusters?

- Study dark matter particle properties.
- Test cosmological models.
- Study Intra-Clusters Medium properties.

2 The MeSsl Algorithm

- Machine learning algorithm applied for identification of substructures.
- Application of the MeSsl Algorithm to spectroscopy catalogues

3 Future Work

Future Work

- Perform astrophysical test over our sample of colliding cluster candidates of the catalog looking for impose some constraints on dark matter particle properties.

Future work.

- Apply the detection method to more deep real catalogs.

We will make a lighth-cone mock (Merson et al. 2012) and re-calibrate our machine learning algorithm for high-redshift clusters in order to study the dynamics status of deep real catalogs like the EDISc and the Morphs Clusters.

Future Work

Reconstruct the 3d merger with the Bayesian techniques presented by *Dawson et al. 2012*.




Figure : Distribution of posterior probability in the 3D distance (Mpc) and 3D velocity (Km/s) space for a simulated merging cluster, red dot indicates the real current values. Others kinematical parameters like Time since Collision or velocity at the merger time are also well recovered.

Future Work

Study the physics properties of the galaxies that belong to the identified substructures, ordering them in a temporal line by the merger state.

Future Work

Construct a catalog of relaxed clusters in order to study the dark matter equation of state (Serra & Dominguez 2011).



THANK YOU