RETRIEVAL, EXECUTION AND DATA PROCESSING FOR LLM SERVICES

I build services that use AI to make people's lives better.

For each project, the parts I contributed: the problem, the alternatives I weighed, why I chose one, how I built it and how I verified it.

Jaehyeong Kim

AI Engineer | Backend Engineer

kkuldangi2@gmail.com | martinel2.github.io

I lead the AI work on Fruition, a team-built, LLM Wiki-based knowledge workspace. On evaluation sets I wrote and reviewed with my team, I raised RAG answer accuracy from 71.7% to 93.0% and AI document-editing success from 85.6% to 88.9%, designing evaluation, approval and rollback so AI does not answer from wrong evidence or change users' documents on its own.

I weigh accuracy, cost and response time against each other, confirm the trade-off with an evaluation, and then choose the implementation that fits the service.

RAG evidence selection: answer accuracy 71.7% → 93.0%, evidence sufficiency 70.0% → 95.4%

I thought wrong evidence makes the whole answer untrustworthy, so I replaced evidence selection with Jev. At adoption, GPT cost about 2.5× more and tuning search weights kept scores flat. I later re-evaluated on a set I wrote and reviewed with my team, fixed a request-batching bug and cut candidates from 300 to 200.

Agent execution environment: user-defined skills behind approval, edit success 85.6% → 88.9%

Users repeat different tasks, so I let them define their own Skills. I judged that users can't trust AI that changes documents freely, so code checks permissions and scope, and changes apply only after approval. Code checks missed omitted requests, so drafts get a semantic evaluation and one rewrite at most.

Data pipelines: PDF body text 96.1%, table cells 99.3%; drug conversion $200 estimated → $11.18 spent (about 94% lower)

AnyDoc extracts body text; tables and equations are read separately. Sentence-block deduplication reduced the 2025 drug dataset from 1GB to 326MB, and Batch API kept about 44,000 records within budget.

CASE STUDIES

Contents

FRUITION

01 RAG evidence selection p.6

02 Agent Skills and approval p.14

03 MCP integration p.22

04 Task cancellation and rollback p.27

05 PDF conversion p.32

06 Parallel document analysis p.38

07 Coding agent orchestration p.40

PILLTIP

08 Drug data conversion: $200 estimated → $11.18 spent p.47

09 Medication chatbot: health profiles kept internal p.52

MORE

10 Beyond project development p.56

Rhwp | Fixing HWPX save errors

APPTIVE | Backend mentoring

945-day Baekjoon problem-solving streak

11 Project reflections p.57

PROJECT OVERVIEW

Fruition

An AI workspace that organizes uploaded documents into an LLM-generated Wiki, answers questions using source evidence through RAG, and edits documents in natural language. It is deployed on AWS EKS and is now in alpha testing. Software copyright registration completed; patent application filed with a provisional specification.

How it started

Started when a teammate raised a pain point with managing documents, which we refined through design thinking. The goal was to fix the frustration of saving many documents but failing to find them when needed.

GitHub | AI repository ↗

Team and my role

MY ROLE

AI

All AI features: PDF conversion, Wiki generation, RAG retrieval and grounded answers, the document-editing Agent

01 **Lead for all AI features**

02 **MSA design contribution**

03 **MCP integration**

Backend, 1	The entire Spring-based backend
Frontend & DevOps, 1	The entire frontend and MSA-based deployment on AWS
Design	External designer
Mentors, 3	Gen AI quality and evaluation / backend / milestones, MSA design and documentation

Features and service screens



Document editing and AI assistant

I led the AI features that interpret requests and generate and validate edits. Teammates implemented the editor and assistant UI.



Wiki generation and queries

documents are organized into the structure I designed, with concepts linked. I built evidence lookup for questions over the resulting Wiki. Teammates implemented the graph and search UI.

Architecture

시스템 아키텍처

브라우저는 Spring Boot API를 통해 데이터와 AI Service을 사용합니다.

기술	구현
Next.js	문서 · Wiki · Chat · Agent UI
Spring Boot	인증 · 권한 · 워크스페이스 · 상태
FastAPI	Ingest · Query · Lint · 문서 편집 Agent
PostgreSQL	관계 · 버전 · 작업 상태
MinIO	원본 · Markdown · artifact


14

Service responsibilities


I led all AI features; teammates owned frontend and backend. We finalized MSA with mentors based on my initial design.

System architecture

| C1 전체 시스템 아키텍처 간략화



| C2 Fruition 시스템 일부 구체화



the overall system (top) and Fruition's internal components (bottom). I owned the AI features centred on llmPipeline (FastAPI, Python, LangGraph); teammates owned the frontend, backend and AWS deployment.

CASE 01 Fruition / AI Agent, RAG, Jev

RAG evidence selection: answer accuracy 71.7% → 93.0%, evidence sufficiency 95.4% on a fixed set

Fruition answers from uploaded documents, so I thought wrong evidence would make the whole answer untrustworthy. After seeing Jev improve request routing, I applied it to evidence selection. I then re-evaluated on a set I wrote and reviewed with my team, confirmed answer accuracy of 71.7% → 93.0% under identical conditions, and fixed what the evaluation exposed.

2026.09 ~ 2026.11

Jev 1.13.0 | BGE-M3 | BM25 | RAG | Quality evaluation

Background

Existing retrieval missed needed evidence and attached evidence even to unanswerable questions, leading to wrong answers. I believed accurate information is this project's core, so I checked each step: the correct sources were all in the initial candidates, but limiting checks to the first 8 pages dropped them for 76 of 90 questions. I needed a step that picks the right evidence and says when there is none.

What solving it enables

If evidence is wrong, the whole answer can't be trusted, and users who lose trust don't come back. Since the core of the project is giving users the information they need on accurate evidence, high accuracy is what makes users trust the product, keep using it and pay again.

RAG answer accuracy (Jev off → on)
71.7% → 93.0%

Evidence sufficiency (Jev off → on)
70.0% → 95.4%

Wrong answers (plain RAG → Wiki RAG)
7.3% → 1.0%

Experiments and improvements

1 Routing comparison and the decision to try RAG

Problem

Some questions were misclassified as document edits, leading to the wrong action. Task types and additional conditions needed to be selected more accurately and quickly.

Experiment and result

Applied Jev, a choice-based decision model released on September 14, to routing questions, document edits, document creation and folder organization.

Across 98 requests, correct task types and additional conditions totaled 77 for the existing JSON approach, 63 for GPT-5-nano given the same options, and 81 for Jev. Median decision time improved from 8.967s to 0.658s.

I measured API cost on the same 100 questions: about $0.0408 for Jev against about $0.1027 for the GPT approach given the same options.

Decision

Jev showed promise on accuracy, speed and cost alike, so I decided to apply it to evidence selection, which the existing retrieval had not solved.

I chose Jev for two reasons. First, having GPT pick the evidence cost about 2.5 times as much even with the same options and took longer, too heavy for a step that checks hundreds of candidates per question; re-ranking by tuning retrieval scores did not help either, as scores stayed similar across many hybrid weights and RRF settings. Second, embeddings sometimes failed to separate differences in Korean phrasing, so fitting one weight to questions from different fields would bring only small gains. Rather than polishing the ranking further, I had a model judge the needed evidence directly from the collected candidates.

Experiments and improvements (continued)

2 Full-corpus inspection: evidence coverage on all 90 answerable questions

Problem

Using the original question for retrieval and increasing semantic-score weight raised top-1 correct retrieval from 50 to 57 out of 110 questions. However, the experiment had some bias, and reliable evidence selection on new questions remained unsolved. Delivering reliable answers to general questions is the core of the project, so this quality had to improve.

Experiment and result

Tested whether Jev could find evidence missed by retrieval. It inspected all 2,020 evidence units in a test Wiki without retrieval filtering and returned at most 8, matching the existing return limit.

In a semantic evaluation allowing paraphrases, coverage on 90 answerable questions rose from 24/90 (26.7%) to 90/90 (100%). It returned no evidence for all 10 unanswerable questions. Median processing time was 1.511s for the original approach and 5.338s for Jev. Jev processed 26 batches of 80, with up to 4 in parallel.

Full-corpus inspection took 2,600 calls for 100 questions, and the API reported roughly 124.5M input and 6.47M output tokens. I did not confirm the billed amount.

To understand the size of the gap I traced where the existing retrieval dropped the answer. The page holding the reference sentence was in the initial candidate pool for all 90 questions, but 76 fell out at the step that limits inspection to the top 8 pages, 8 at the threshold of 85% of the best in-page score, and the remaining 2 at the final 8-evidence cap and the related-page lookup.

Decision

The existing retrieval was discarding the answer before selection even began, so the gap cannot be read as a difference in selection ability over the same candidates. Full-corpus access found the evidence, but inspecting everything per question would grow calls as documents grew. Rather than set the deployment scope from this 90-question wiki alone, I decided to narrow candidates through retrieval first and let Jev pick the final evidence.

Experiments and improvements (continued)

3 Controlled comparison on 500 candidates: 87.50% coverage

Problem

Checking every piece of evidence was too costly to use in the service as-is. The evaluation questions were also concentrated in certain documents and included document titles. The original search judged from only some pages while Jev saw all evidence, so it was hard to tell whether the accuracy gap came from judgment or from access scope. I had to cut candidates and match the comparison conditions.

Experiment and result

Created 100 new questions from 9 papers (80 answerable, 20 unanswerable) and fixed them before the runs. Both methods received the same 500 candidates with returns capped at 8, reference answers were excluded from inputs, and GPT and Gemini graded without seeing method names.

Coverage rose from 66.25% to 87.50%, but sequential candidate processing raised median time from the original 0.431s to 9.090s.

Decision

Jev selected better evidence under the same conditions, so I kept retrieval for candidate collection and Jev for final selection. Results on public papers and self-authored questions were not treated as general accuracy, and reducing the waiting added by sequential processing became the next task.

Experiments and improvements (continued)

4 300 candidates and a parallelism comparison to reduce latency

Problem

Answers start only after evidence selection finishes, so processing time is the user's waiting time. A 9.090s median for 500 candidates processed sequentially was far too long against the previous 0.431s to be usable. Still, the higher accuracy was worth keeping, so I set out to cut the time.

Experiment and result

Since candidate count drives cost and speed, I cut candidates from the top 500 to 300 and ran up to 4 batches in parallel. Time fell to 2.251s, while questions with all required evidence increased from 70 to 73.

The parallel count had been set without evidence, so I re-ran the same 100 questions with only parallelism changed to 4, 6, 8 and 10. Median selection time was 2.066, 1.165, 0.945 and 0.886s, and blind grading of the 42 questions whose selections differed gave 37, 38, 36 and 37 fully supported, with no real difference.

Decision

Beyond 8 the gain was only 0.06s, and in production concurrent requests grow as workers × parallelism, so I chose 8. At 1.137s including candidate filtering it is still slower than the original 0.431s; I rejected cutting candidates further then because, on that set, some required evidence ranked below 250.

I adopted Jev despite the added latency because accurate evidence is central to the service.

Experiments and improvements (continued)

5 Comparing candidate generators to find the limits of the production setting

Problem

Jev can only choose from what reaches it, so evidence missing from the candidate pool is unreachable. I needed to know how far the production candidate generator preserved the answer-bearing evidence.

Experiment and result

Reusing stored scores, I regenerated rankings for four candidate generators and compared how well each preserved the 97 pre-registered citation groups across the 80 answerable questions: BGE-M3 alone, the production hybrid (0.75 embedding + 0.25 normalized BM25), RRF, and an alternating union.

At 100 candidates, the questions that preserved every citation were 74/80 for BGE-M3 alone, 63/80 for the production hybrid, 63/80 for RRF and 65/80 for the alternating union. MRR@500 over each citation's best rank was 0.1811 for BGE-M3 alone against 0.1245 for the production hybrid, with median ranks of 19 and 40. Beyond 300 candidates the four converged to 79/80 and 78/80.

Decision

The production hybrid weighting ranks answer-bearing evidence lower than plain BGE-M3. At the 300 candidates used then the gap is small, so I left production unchanged and recorded it as the first condition to fix before cutting candidates further.

Experiments and improvements (continued)

6 Re-evaluating on a real-world set and improving evidence selection

Problem

I needed to check whether results from 9 papers held for what users actually upload, such as statutes, statistics and technical documents. Evaluation models also differed by feature, so results could not be stated on one basis.


Experiment and result

I wrote 100 questions from 11 public documents, reviewed them with my team and froze them with sha256. All LLMs were fixed to gpt-6-luna, every case ran three times, and code checks plus blind Claude grading decided the results. With Jev off, answer accuracy was 71.7% and evidence sufficiency 70.0%; with Jev on, 93.0% and 95.4%.

The evaluation exposed a bug that double-counted request size and split candidates into small batches. After the fix, on 20 questions × 3 runs, Jev calls fell from 460 to 227, input tokens from 7.13M to 5.25M, and evidence sufficiency rose from 94.1% to 100%. Comparing 300, 200, 150 and 100 candidates gave evidence sufficiency of 95.0, 95.4, 95.0 and 95.0% and gold-citation recall of 0.873, 0.868, 0.849 and 0.808.

Decision

I chose 200, where recall held, cutting Jev cost (nearly proportional to candidates) by about a third. This reversed my earlier decision not to cut candidates further, based on the new set. In request routing, with few options, Jev and the LLM were close at 91.8% and 92.2%, so I now describe Jev's benefit there as response time (3.42s → 0.51s) rather than accuracy.



Correct answers on a fixed set: 215/300 → 279/300; average end-to-end response 5.5s

RAG answer accuracy (Jev off → on)
71.7% → 93.0%
215/300 → 279/300, 100 questions × 3 runs

Evidence sufficiency (Jev off → on)
70.0% → 95.4%
168/240 → 229/240

Wrong answers (plain RAG → Wiki RAG)
7.3% → 1.0%
22/300 → 3/300, same questions and answer model

I ran 100 questions that I wrote and reviewed with my team three times each, with Jev off and on. Answer accuracy rose from 71.7% to 93.0%, and the share where the selected evidence alone could produce the answer rose from 70.0% to 95.4%. Against plain RAG on the same questions, unsupported claims fell from 4.9% to 1.9%. The earlier adoption experiment (9 papers, coverage 66.25% → 91.25%) used a different set and grading, so it is not compared directly.

Scope and tradeoffs

Retrieval stays a fixed pipeline (semantic and keyword search plus Wiki graph traversal) that shows the answer, evidence, related pages and search path separately. I held off on a self-planning Query Agent because of cost and hallucination risk, and will add one when a question needs repeated planning and replanning; until then the fixed pipeline uses fewer calls and is easier to debug. Accuracy came at a cost in time and money. End-to-end responses average 5.5s, slower than plain RAG's 4.3s under the same conditions. Cost is about $2.7 per 1,000 requests against $0.19–0.35 with Jev off, estimated from actual tokens and unit prices. Correctly declining unanswerable questions was 57/60, below plain RAG's 60/60, so that is the next task. Retrieval gathers candidates and Jev decides, so the selector can be swapped.

Introducing Jev | TypeSafe AI ↗

CASE 02 Fruition / AI Agent, User-defined Skills, HITL, Prompt injection

User-defined Agent Skills: designing controlled execution

I built Agent Skills so users can define and reuse repetitive work such as writing meeting notes. I also thought users must be able to trust every document AI changes, so I designed review, publishing and change approval as one flow and implemented it with AI coding tools.

2026.08 - 2026.09 ~ 2026.11

LangGraph | Agent Skill | Prompt injection defenses | LLM Evaluation | Human-in-the-loop | Context engineering | Rolling conversation memory | LangSmith | LLM observability

Background

Each user repeats different tasks, such as organising meeting notes, so developers couldn't build them all in advance. AI edit drafts also reached users with parts of the request missing or sentences awkwardly changed, and code checks on format and scope couldn't catch it. That made a stable service impossible: leaving tasks that need the same output every time to luck frustrates users. Since users prepay for API usage, it could also become a reason not to pay again.

What solving it enables

If AI edits vary and users have to ask again, their prepaid credits go to rework, and users who see that as waste hesitate to pay again. Stable results and no changes before approval let them trust recurring tasks to it and keep using it.

Real-world set, before evaluator fix
77 / 90

Real-world set, after evaluator fix
80 / 90

Development regression set (draft replay)
94 → 104 / 114

CASE 02 Agent Skills and approval

Decisions and implementation

1 Authoring and publishing user-defined instructions

Problem

Recurring tasks such as meeting notes vary by user, so developers cannot prebuild every workflow. Yet making users repeat the same request process for a recurring task each time is inconvenient.

Decision

Let users define and reuse natural-language instructions instead of adding each workflow as a feature. Treat AI-generated instructions as proposals until users review them.

Implementation

Turned natural-language requests into reusable Markdown Skills. Users review and edit drafts; the Skill and version are stored on final publication. A published skill is appended as an immutable version rather than overwritten, with a separate pointer to the version that runs. Which run used which version of the instructions stays traceable, so an earlier definition survives a problematic new version.

Verification

Skill module unit tests confirm that authoring returns only a proposal and stores nothing, that publishing creates a new version and points the active version at it, and that published Skills load from other workspaces and via slash commands. When the feature was finished, 74 Skill module tests and all 546 pipeline tests passed.

Decisions and implementation (continued)

2 Checking instructions for permission and approval bypasses

Problem

User instructions and reference documents could contain personal data or directions to bypass permissions and approval. Such intent can be phrased many ways, and users can edit drafts after review.

Decision

Use code for explicit risk and permission checks, and an LLM to detect rephrased bypass intent. Do not allow publication based only on an earlier check after users edit the content.

Implementation

Applied rule checks to input and reference documents. The server verified that risky phrases reported by the LLM existed in the source. After checking access and original documents, it sent only necessary structure to the model. Publication reran checks on the final content. Risky phrases were not silently deleted; only user-requested regeneration removed them and rechecked the result.

Verification

Rule checks cover 25 phrases in six categories (approval bypass, permission escalation, forbidden tools, policy weakening, hidden-prompt requests, role override), plus emails, phone, resident registration, card and account numbers, and seven kinds of credentials. Tests confirm that instructions such as 'move the documents without approval' or 'ignore previous instructions and run shell' in a reference are blocked before any model call, that the position of a phrase flagged by the LLM matches where the server finds it in the source, and that an email added at final publish is blocked without being stored. Blocked input is shown with its location so users can fix it or regenerate.

Decisions and implementation (continued)

3 Previewing changes and applying them after approval

Problem

Even with a published Skill, hallucination can create, edit or organise documents in ways the user did not want, and having to go roll them back each time frustrates users. So the documents and content to be changed had to be confirmed separately at execution.

Decision

Separate instruction publication from approval of actual changes. Keep task classification in the router and execution in the executor, while letting users inspect what will change.

Implementation

Displayed before/after diffs for edits and a folder-and-document move plan for organization. Code checked output format and edit scope; only approved changes were executed.

Verification

With 6 documents, the plan–approve–execute check made no changes before approval. After approval, it created 3 topic folders and moved the documents.

Decisions and implementation (continued)

4 Deciding the scope of conversation context and edit input

Problem

Long conversations or large documents to edit inflate model input, raising the cost and waiting time users bear. I had to decide what to keep and what to cut.

Decision

Keep the last six messages (about three exchanges) verbatim and compress everything older into a rolling summary. For edits, send only the target line range plus surrounding context, and refuse a range that straddles the boundary of a table or code block.

Implementation

Once recent messages reach six, the rolling summary is regenerated from the previous summary plus those messages; if the summarization call fails the summary is left unchanged so the conversation does not break. The router receives the summary and recent messages along with the routing decisions from earlier turns, so it can resolve what a referring expression points back to. Edit input is cut to the target line range with context lines above and below, and ranges crossing a structural boundary are rejected.

Verification

For a 1,000-line document the model received 1,786 of 31,999 characters (5.58%), and 1.12% for 5,000 lines; p95 time to build the input was 7.7ms and 34.4ms. Tests confirm that every range partly crossing a table, code block or math block is refused, and in 3 real HTTP requests a partial code-block selection was blocked with 422.

Decisions and implementation (continued)

5 Tracing LLM runs while bounding sensitive data

Problem

The evaluation loop ran as plain Python, so extraction, evaluation, correction and retry could not be inspected stage by stage. Turning tracing on, however, would send raw tool lookups and personal data to an external tracing tool, weakening security.

Decision

I separated what has to be observable from what must not leave the system. Graphs that decide answer quality get node-level tracing; the agent graph that edits a user's own documents runs with tracing off and keeps raw content out of persisted state.

Implementation

Rebuilt the evaluation loop as a LangGraph graph so answer generation, evaluation and retry each surface as their own node. Even with tracing configured on, a missing key leaves graph execution intact and skips only tracing, which avoids warnings and pointless network retries. The agent graph disables tracing and excludes raw tool lookups from persisted state, and that state is deleted before the run record once retention ends. The prompt log I write myself masks numeric personal data before writing.

Verification

Ran real requests and confirmed that graph nodes and model call spans appear in the trace. Timing experiments run with tracing and prompt logging both disabled, so instrumentation overhead stays out of the measured times.

Decisions and implementation (continued)

6 End-to-end evaluation on a real-world set and evaluator improvement

Problem

The 114-draft regression set rechecks drafts that already exist, so it could not show quality when a request actually runs from start to finish.

Decision

I wrote 30 edit requests, reviewed them with my team and froze them. Each ran through the full editing feature and counted as a success only after passing both code checks and blind Claude grading.

Implementation

Reviewing the results showed the built-in evaluator failing list and table conversions just for dropping connectives and hedges. I extended the criterion used for shortening and summarising to format conversions, while changed figures or article numbers and missing content the user asked to keep still fail.

Verification

With gpt-6-luna, 30 requests × 3 runs rose from 77/90 (85.6%) to 80/90 (88.9%), and cases that passed the built-in check but failed grading fell from 9 to 6. By scope: selection 18/18, whole document 17/18, append to end 16/18, current section 29/36, so section edits remain the weak spot. Evaluated the same way, folder organisation scored 59/60 and folder lookup 18/18.



Reusable tasks and approval workflow; edit success on a real-world set 85.6% → 88.9%

Real-world set, before evaluator fix	Real-world set, after evaluator fix	Development regression set (draft replay)
77 / 90	**80 / 90**	**94 → 104 / 114**
85.6%	88.9%	82.5% → 91.2%

Users can define recurring tasks, publish them as Skills and reuse them. The final instructions are rechecked on publication, and actual document changes require a preview and user approval. A plan–approve–execute check of folder organisation on 6 documents confirmed it worked correctly. In end-to-end runs of 30 requests I wrote and reviewed with my team, three times each, edit success rose from 77/90 to 80/90. Earlier in development, editing quality was compared on a fixed regression set of 114 drafts from 19 request types. Fixing a validation rule and the retry input, evaluating fulfillment and meaning separately and allowing one rewrite raised passes from 94 to 104 (98 with code fixes alone). No edit is returned if a draft fails again. AI drafts instructions and edits, code checks permissions and execution scope, and users decide publication and final application.

Scope and tradeoffs

Normalized average editing-evaluation time increased from 11.11s to 18.92s. I accepted the latency but limited the number of rewrites.

Building user-defined Agent Skills (Korean) ↗

The two sides of LLM evaluation for reliability (Korean) ↗

CASE 03 Fruition / MCP, OAuth, Human-in-the-loop

MCP integration: connecting external AI proposals to web approval and storage

I built MCP integration so users can work with Fruition documents and Wiki pages through their own Codex or Claude Code and model. External AI handles retrieval and change proposals; Fruition keeps its existing authorization, web approval, storage and billing paths.

2026.11

MCP OAuth Codex Claude Code Human-in-the-loop Idempotency

Background

Using Fruition knowledge from an external AI tool required connecting both retrieval and document changes. Giving AI direct write and approval authority could save changes users had never reviewed. Revoked connections and stale document versions also needed explicit handling.

What solving it enables

Users can work with their existing AI tools and models while reusing Fruition documents and Wiki pages, reviewing and approving actual changes in the web app.

Real clients	Discovered tools	Additional feature tests
2	21	39 passed

CASE 03 MCP integration

Separating responsibilities and verifying real clients

1 Separating external model work from service authority

Problem

A separate integration path could drift from existing authorization, storage and approval rules.

Decision

Let the user's model understand documents and draft changes while Fruition retains authority over access and execution.

Implementation

Bound OAuth connections to a user, workspace, client and scope, checking current permissions on each request. Connected document and Wiki retrieval, ingestion and edit proposals, plus PDF, Skill and meeting tools.

Verification

Confirmed discovery of 21 tools in a real Claude Code connection. Tool discovery was kept separate from successful execution of every tool.

2 Separating proposals from web approval and storage

Problem

AI approving its own changes, or a document changing after review, could save something the user never approved.

Decision

Expose no MCP approval tool. Require a person to review the preview and quote in the web app.

Implementation

Fixed the approved version, hash, scope and price, and rechecked permissions and conflicts immediately before writes. Used receipts stored with changes for billing and returned the same result for duplicate submissions.

Verification

With synthetic documents, verified ingestion → web approval → Wiki search and page retrieval → edit proposal → web approval and storage → source reread in both Codex and Claude Code. Claude changed only Monday to Wednesday, preserving the owner and line breaks.

Separating responsibilities and verifying real clients (continued)

3 Verifying connection revocation and version boundaries

Problem

Retained tokens and confusion between metadata versions and body revisions could break access revocation or reject valid edits.

Decision

Authorize against current connection state and detect body conflicts using the body revision.

Implementation


Fixed missing gateway routes, edit-range calculation and body/metadata version confusion found during real-client checks. Disconnecting one user connection blocks new access without disabling other active connections.


Verification

Confirmed natural OAuth token refresh in both clients. After disconnecting Codex, its next real access was blocked with HTTP 403 while Claude’s connection stayed active. An edit proposal using an older body revision was rejected with SOURCE_CHANGED.

CASE 03 MCP integration

Improved processing flow





MCP submits proposals; the user approves in Fruition's web app. Existing services apply the change, and a subsequent read confirms the stored result.

Verified ingestion, retrieval, approval, editing and rereading in Codex and Claude Code

Verified the core flow in two real clients using synthetic test accounts and documents. Codex changed body revision 1 → 2 and Claude Code 3 → 4; each reread the final source and hash through MCP. Also verified that disconnecting one connection blocks its access while another remains active. Additional feature checks passed 33 PostgreSQL integration tests and 6 unit/contract tests.

Scope and tradeoffs

These are dev-merged changes and isolated-environment results recorded on November 9, 2026, not a production release or execution proof for all 21 tools. Full native execution of the expanded PDF, Skill and meeting flows remains unverified. Automatic Wiki updates after source edits were not verified. Test quotes are not production prices.

Actual Codex Wiki search screenshot ↗

Real clients

2

Core flow verified in Codex and Claude Code

Discovered tools

21

Tool listing confirmed in Claude Code

Additional feature tests

39 passed

33 PostgreSQL integration + 6 unit/contract

CASE 04 Fruition / AI Agent, Compensating recovery, Audit history

Cancelling an AI task and undoing what it already saved

In a service where AI changes documents, I thought users can't hand work to AI unless cancelling is reliable. Stopping execution leaves saved document, folder, Wiki and Skill changes behind, so I built a path that reverses even committed changes in reverse order. To keep contributions other jobs made correctly, I restored pages without only the cancelled contribution.

2026.08 — 2026.09

Compensating recovery | Idempotency keys | Append-only history | PostgreSQL execution lock | Audit history

Background

An AI task runs across several stores and cannot be wrapped in one long transaction, so I had to decide what a cancellation should undo and how far it should reach.

What solving it enables

If AI changes remain after a user cancels, their data is damaged, which leads to churn and support requests. Reliable undo lets users hand even large tasks to AI with confidence, which grows credit usage.

Stores covered by recovery	Recovery execution	Cancellation becomes final
3	No model calls	On confirmed recovery

CASE 04 Task cancellation and rollback

Decisions and implementation

1 Deciding that stopping execution was not enough

Problem

An AI task saves documents, folders, wiki pages and skills several times between model calls, so stopping execution left part of a cancelled task in place. Yet execution spanning the core DB, the AI DB and object storage could not be wrapped in one long transaction either.

Decision

I chose to undo already-committed changes too. Asking the model to perform the inverse cannot guarantee original values, approval scope or idempotency, and locking the whole service in one transaction cannot absorb long-running model, HTTP and object-storage work or its failures, so both were rejected.

Implementation

The AI side derives reverse actions from the run record while the backend performs atomic recovery of business data. Agent tools store a pre-change snapshot with reverse-action arguments and an idempotency key tied to the original approval, and ordinary tasks record before and after values through each database's triggers inside the same transaction. Object storage persists the original and the intended result before writing.

Verification

A test that runs the real worker makes model creation fail during recovery and confirms the cancellation finishes without any model or gateway call. Cancelling a two-folder, six-document organisation task at each of 9 points returned the workspace to its original state, and after a lost response a new worker resumed recovery with the same idempotency key.

Decisions and implementation (continued)

2 Blocking later writes and undoing children first

Problem

A handler still running after a cancellation would overwrite recovered values, and undoing a parent first left the changes its children had made behind. Recovery could fail, leaving users unable to return to the version they wanted.

Decision

Persist the cancellation first to block later writes, and once the running handler finishes, undo children first in reverse order.

Implementation

The agent turn and recovery share one PostgreSQL execution lock. The lock releases when a worker connection ends, so a leftover in-progress record cannot block recovery. Body recovery is saved as a new revision, so a late event cannot overwrite the source again.

Verification

Tests confirm that writes after cancellation are refused, recovery waits for the running handler, and children are restored before their parent. Even after the running process was force-killed, recovery waited on the same lock and finished, and a late event from an earlier revision could not overwrite the restored body. If another user later changed the data, recovery did not overwrite it and stayed retryable; cancelling again after the conflict cleared completed normally.

Decisions and implementation (continued)

3 Recovering without erasing other tasks' contributions

Problem

A wiki concept page merges contributions from several documents, so overwriting it with an older snapshot also removed valid contributions added later by other documents.

Decision


Removing just the relevant part from the finished result was hard because which sentence came from which document cannot be told apart reliably. Restoring an entire older snapshot was rejected too, because information is lost if a new document contributed in between. Instead the history is append-only and recovery excludes only the target contribution before reassembling.

Implementation

Operations, page revisions and per-document contributions are recorded append-only, and recovery restores or reassembles the page with the target contribution excluded. Pages and history are soft-deleted rather than removed, which preserves the audit trail.

Verification

Right before recovery, the contribution list (operation, revision, active flag) is re-read under a lock, and recovery is refused if it differs from the preview. Tests confirm that pages are rebuilt from the selected contributions only and that if any page fails, no current state changes. Recovery itself is recorded as a new operation and revision.



A cancelled task's changes are undone while other tasks' contributions survive

Stores covered by recovery

3

core DB, AI DB, object storage

Recovery execution

No model calls

Reverse actions from the run record only

Cancellation becomes final

On confirmed recovery

Otherwise kept retryable

Content, names, parents and ordering that users see are restored, while version, audit and idempotency records are kept. Recovery runs from the run record alone, with no model settings or calls, and it checks current values and downstream references so it never overwrites another task's work. Cancellation is final only once full recovery is confirmed; conflicts and unclear outcomes stay retryable. For a feature where AI edits a user's documents, I settled what could be undone and what had to be recorded before building it. In a manual run on real Gemini, Kafka, PostgreSQL and Redis, nothing changed before approval, and cancelling during the last document move restored 2 folders and 6 documents with 8 inverse operations.

Scope and tradeoffs

This case is about design and unit-level verification; I did not measure a recovery success rate under production traffic. Preserving per-source contributions from ingest onward costs storage. Without a snapshot of the remaining combination a page has to be reassembled, and older tasks carried no snapshot, so runs and queues had to be drained before deploying.

CASE 05 Fruition / PDF conversion, Data pipeline

PDF → Markdown: 96.1% body text and 99.3% table cells restored across 15 PDFs

To use papers, which mostly arrive as PDFs, as knowledge, table figures and equations had to survive conversion to Markdown first. So I traced where AI repair dropped content and split processing paths by original layout and content type.

2026.07 — 2026.09 ~ 2026.11

Open-source PDF conversion: AnyDoc, Docling | LLM API | sLLM (Qwen2.5 7B) | Python | LLM-as-a-Judge

Background

Graduate students, our core users, mostly work with papers distributed as PDFs. I tried open-source tools that convert PDFs to Markdown so they could be used as knowledge, but table row/column relationships and equations came out broken.

What solving it enables

If PDF restoration is poor and key figures go missing, the document can't fully enter the Wiki and users get a lower-quality service. I thought that could make users leave.

Body text restored (15 PDFs × 3 runs)
96.1%

Table cells restored (15 PDFs × 3 runs)
99.3%

Adoption experiment: Docling → improved pipeline
45.17% → 89.89%

CASE 05 PDF conversion

Experiments and improvements

1 Selective repair and missed errors

Problem

Open-source conversion broke table row/column relationships and equations, so the key figures in PDF papers came out in a form hard to bring into the Wiki. I needed a way to repair the damaged parts.

Experiment and result

Docling extracted the structure, and only damaged tables and equations were repaired with local Qwen sLLMs. Tables, where row/column positions matter, were handled mainly by the vision model (qwen2.5vl:7b); equations were drafted by the text model (qwen2.5:7b) and checked by the vision model only when needed. This restored more than applying both models to everything and cut sLLM processing time by about 42%. Keeping OCR and prompts unchanged and only re-cropping images with Docling's strict bboxes fixed two previously failing equations.

Evaluating repaired and untouched regions separately, 85 of the 96 sLLM-repaired regions passed, but 107 errors or omissions remained in untouched content. A separate experiment adding OCR comparison raised the pass rate from 80.00% to 97.53%, but also selected 50 correct regions for repair; processing took about 12 minutes 35 seconds.

Decision

Selecting repair targets missed errors, and extra checks to catch them added cost. I decided to test whether having the vision sLLM read every original page could avoid this dependence on damage detection.

Experiments and improvements (continued)

2 Table/equation errors and cost in full-page sLLM conversion

Problem

Letting AI decide what to fix missed errors, and adding OCR checks also flagged correct content, increasing check time and cost. I needed a way to pick and fix only the damaged parts.

Experiment and result

Full conversion of 25 research PDFs with the vision sLLM (qwen2.5vl:7b), which can check the original page directly, (415 pages) achieved a 91.92% content-preservation pass rate. However, only 58.84% of tables and equations fully matched in values and structure, and processing every page imposed a heavy processing load.

Decision

I judged that sending all content through the model the same way was the problem. Body text should use AI only where needed, and tables and equations should get inputs that preserve their structure. So I split the paths for body, tables and equations, and looked for fast body extraction with AI fixes only where needed.

Experiments and improvements (continued)

3 Comparing text extraction, adopting AnyDoc, and moving to commercial APIs

Problem

Full-page sLLM processing still left table/equation errors, and sending all body text to the model was a heavy load. To cut that load and improve speed and accuracy, I needed separate repair for the tables and equations that usually break, alongside fast body extraction.

Experiment and result

I found AnyDoc on Threads and, after seeing its GitHub comparison with Docling, tested it on the same 4 PDFs (30 pages).

The recorded Docling run took 134.19s, while AnyDoc text extraction took 1.68s, about 80 times shorter. Docling's time also included OCR and table analysis. One AnyDoc document had garbled characters because the PDF lacked mappings from character codes to actual characters.

Decision

The processing scopes differed, so this was not an 80-fold improvement in complete conversion. Still, AnyDoc was useful for fast text extraction. I kept separate table/equation repair, switched body extraction to AnyDoc, used AI on garbled or misordered pages, and preserved original figures. With no early users yet, running GPU servers for an sLLM would cost more than it saved, so from this point I switched the repair model to commercial LLM APIs.

Experiments and improvements (continued)

4 Finding remaining weaknesses by evaluating real documents by type

Problem


The earlier evaluation used 4 mostly academic PDFs (30 pages), so quality on the statutes, policy documents, scans and mixed-layout documents target users upload was unknown.

Experiment and result

I converted 15 documents (111 pages) across 5 types (text, table, multi-column, scan, mixed) three times each with the production converter, and all 45 runs finished without error. Comparing page images with the results using Claude and counting every element gave headings 97.6%, body text 96.1%, table cells 99.3%, equations 100% and images 91.3%, without human review.

Decision

PDFs with a text layer were stable at 100% headings, 98.7% body text and 99.5% table cells. Scans sometimes lost a whole page (all three runs of the statute reproduction, two runs of the 1978 report), so that page loss became the next improvement.



15 PDFs by type: 96.1% body text, 99.3% table cells restored (adoption experiment 45.17% → 89.89%)

Body text restored (15 PDFs × 3 runs)

96.1%

98.7% for PDFs with a text layer

Table cells restored (15 PDFs × 3 runs)

99.3%

1 misread number among 12,675 cells

Adoption experiment: Docling → improved pipeline

45.17% → 89.89%

30 pages total

I converted 15 statutes, policy documents, papers, scans and mixed-layout documents (111 pages) three times each with the production converter and counted every element that survived: headings 97.6%, body text 96.1%, table cells 99.3%, equations 100%, images 91.3%. For the 12 PDFs with a text layer, body text was 98.7% and table cells 99.5%. In the earlier adoption experiment, I evaluated the existing Docling and the improved pipeline by splitting the same papers into 445 evaluation units covering body text, tables, equations and other content, and comparing them with the originals. The practical pass rate rose from 201 (45.17%) to 400 (89.89%), and the strict rate, which requires values and symbols to match exactly, rose from 193 (43.37%) to 393 (88.31%).

Scope and tradeoffs

Internal LLM evaluation of 4 PDFs (30 pages). Minor differences were allowed for text, headings and figures; tables and equations had to match in values, symbols and structure. In the by-type evaluation, Claude wrote the reference data and judged the results, without human review. The two evaluations differ in documents and metrics, so they are not compared directly.

Trying a small LLM for PDF → Markdown (Korean) ↗

Trying the open-source PDF converter AnyDoc (Korean) ↗

CASE 06 Fruition / Kafka asynchronous processing, AI pipeline

Parallel document analysis: 282.11s → 73.89s

Wiki generation ran sequentially, and I was concerned slow processing of large documents would hurt the user experience. I measured the effect and resource cost of more Workers and set separate scaling rules for analysis and embedding.

2026.09

AI pipeline | Kafka | PostgreSQL | Concurrency and memory


Background

Sequential processing made later documents wait for external AI responses, and more workers also mean more API calls and memory, so I had to find how far to scale. I used Kafka because it can replay messages and keeps order within a key, so long AI jobs run asynchronously while IDs prevent duplicates. 1 → 4 Workers cut analysis from 282.11s to 73.89s. Raising concurrent requests per Worker from 2 to 4 slowed it to 95.92s, and two embedding jobs on one GPU stretched each from about 9.5s to 19–21s, so the two stages got separate scaling rules.

What solving it enables

I was concerned that a slow Wiki keeps users from using their uploads, so they may leave before seeing value. A shorter wait lets them search and ask right after upload.

1 worker	4 workers	Combined process memory
282.11s	73.89s	About 4×



73.8% less analysis time for 4 documents, 300 queued jobs with zero loss

1 worker	4 workers	Combined process memory
282.11s	**73.89s**	**About 4×**
4 documents, 8 calls	Up to 8 concurrent API requests	351.7 → 1,401.0MiB

With 4 workers and 2 concurrent requests each, total processing time for 4 documents fell by about 73.8%. Combined process memory rose from 351.7MiB to 1,401.0MiB, about fourfold. Of 16 facts fixed in advance, 10, 14 and 11 were fully preserved with 1, 2 and 4 workers, so although each condition ran once on a small sample, I did not treat quality as identical. I excluded raising concurrent requests further and parallelising embedding generation on the same GPU, since both made things slower. External-response waits and device contention are different bottlenecks, so each stage needed its own scaling approach. Replaying saved AI responses for 100 documents under 3 configurations processed all 300 jobs without omissions or failures. Judging that the memory increase could be absorbed by distributing AI functions on EKS as MSA, I used at most 4 workers for parallel document processing.

Scope and tradeoffs

One analysis run per configuration on the same documents. These are not end-to-end timings including storage and post-processing.

CASE 07 Fruition / Coding agent orchestration, Cross-service changes

Coding agents across 5 repositories: 78 PRs created, decisions and review owned by a human

After running an agent loop for an August MSA migration, I extended it to changes across five repositories in October. Agents investigated, implemented and reviewed; I chose trade-offs, set scope and acceptance criteria, and challenged unsupported findings. The two-day effort produced 78 PRs and 43 issues.

2026.08 / 2026.10

Coding agents | Claude Code | Code review | Decision records | MSA

Background

A model-deprecation issue led to discovery that some features ignored the user-selected model and used hardcoded models. Changes spread across five repositories. Agents could invent issues, implement only part of a plan or review against decisions that had never reached the issue tracker.

What solving it enables

Keep cross-service changes aligned with agreed behavior, while preventing incomplete work and false review findings from turning into further rework.

PRs created	Plan alignment	Incomplete closed issues
78	43 / 45	7 / 31

CASE 07 Coding agent orchestration

Decisions and review practices

1 Grouping changes and retaining human decisions

Problem

One model issue expanded into cross-service work; deciding every fix separately would duplicate policy decisions.

Experiment and result

Grouped related issues by scope. Agents presented options and trade-offs, while I chose policies and required plans and verification records before implementation.

Decision

Use agents for exploration and implementation while retaining decisions about product behavior and scope.

2 Reviewing in a fresh session against recorded decisions

Problem

The implementation session was also reviewing its own work, and issues still contained superseded decisions.

Experiment and result

Started reviews in a new session, required match/mismatch judgments and compared against the plan. Added decision records to the original issues to reconcile the review basis.

Decision

A decision is incomplete until it is recorded where future reviewers can find it.

Decisions and review practices (continued)

3 Checking reviewers and reopening unfinished work

Problem

A reviewer claimed roughly 60 days of log retention and proposed new issues for work that should already have been complete.

Experiment and result


Rechecking found a log-specific S3 version rule giving roughly 31 days, not 60. Required file and line evidence. Reviewed 31 closed issues, found 7 unfinished and reopened the originals.


Decision

Verify findings before changing code. Finish agreed requirements rather than continuously expanding the backlog.

CASE 07 Coding agent orchestration

Improved processing flow





October workflow: a fresh review session checks decisions, and findings need file and line evidence before changes are made.

78 PRs created in 2 days; incomplete closure found in 7 of 31 issues

From the night of October 10 through October 12, agents created 78 PRs and 43 issues across five repositories. Plan-alignment reviews recorded 21 matches among 42 PRs initially and 43 among 45 later; three PRs entered the review set, so the denominator changed. Reviewing 31 recently closed issues found 7 with unfinished requirements, which were reopened with remaining-work checklists. This is separate from the August migration: 16 PRs merged over five days, with 13 required fixes before merge. Agents wrote the code; I set plans and criteria, chose design trade-offs and controlled scope. In October, AI-repository changes merged to dev after review; other repository owners retained merge decisions.

Scope and tradeoffs

October figures come from my published retrospective. PR creation counts are not merged or deployed feature counts, and review alignment is not a defect-free guarantee. The review population changed, so the two snapshots are not a controlled before/after rate. Broader desktop OAuth work was deferred to keep focus on the agreed changes.

AI agents and 78 PRs in 2 days (Korean) ↗

PRs created

78

5 repositories, Oct 10–12

Plan alignment

43 / 45

Final review snapshot; initially 21 / 42

Incomplete closed issues

7 / 31

Reopened with remaining-work checklists

PROJECT OVERVIEW

Pilltip

A personalized AI medication service that explains drug information in plain language and helps users manage their own and their family's medications and schedules.

How it started

Started as a Pusan National University capstone project. Drug information is scattered, so it is hard to check whether a given medicine is safe for your current health condition. We set out to make that easy.

GitHub repository ↗

Team and my role

MY ROLE

Backend & AI

Drug and supplement DB, search and autocomplete, reminders, risk and caution information, data preparation, AI chatbot

01 **Backend and AI development**

02 **Drug and supplement modeling, search, autocomplete and risk information**

03 **Medication reminders and logs**

04 **Friends and family**


05 **Data pipeline: about $200 estimated, $11.18 actually spent**

06 **RAG-based AI chatbot**

07 **Extended support to health functional foods after exhibition feedback**


Android, 1	The Kotlin-based Android app
Backend & security, 1	User DB, login, questionnaires, AES-GCM encryption
Design	Designer

Features and service screens




Drug search and DUR

I owned the drug DB, search, autocomplete and risk information. My data pipeline rewrote descriptions in plain language. The image shows search results and caution tags.




Medication reminders and logs

I implemented FCM notifications and medication records.



Family profiles

I implemented switching between family members to view their medication information, as well as deep-link friend invitations. This screen shows profile switching.



AI chatbot

I implemented orchestration between RAG search and DUR checks. This presentation example is not an evaluation of medical accuracy.

CASE 08 Pilltip / Data pipeline, GPT Batch API, PySpark

Drug data pipeline: $200 estimated → $11.18 spent

Pilltip helps users understand whether they can take a medicine right now, so I thought turning difficult drug information into easy wording was the core. To keep the feature within budget, I reduced the number and cost of model calls and processed 1GB of drug data for an actual $11.18. In 2026 I reproduced the same cleaning in PySpark to measure each step.

2025.07 | reproduced 2026.10

Data pipeline · GPT Batch API · PySpark · MinHashLSH

Background

Rewriting about 44,000 drug records (about 1GB) as-is was estimated to cost about $200 in API calls. I needed a way to explain every drug within budget without cutting the number of drugs covered.

What solving it enables

I judged that if conversion cost exceeded the budget, we would have to cut the drugs we explain and narrow the service. Lowering the cost per conversion, I thought, would let the same budget cover every drug.

Estimated cost for original text
About $200

Actual API spending
$11.18

Exact deduplication
−94.1%

CASE 08 **Drug data conversion: $200 estimated → $11.18 spent**

Problem analysis and implementation

1 Removing exact duplicate sentences

Problem

Converting about 44,000 records totaling 1GB was estimated to cost about $200 in API usage. I needed to cover all drugs within budget.

Experiment and result

Examined 100 records and found about 70% duplicate content. Used this sample and a work plan to secure 7 days for preprocessing. Split text into sentence blocks, merged exact matches and preserved links from each drug to its blocks.

Decision

Convert repeated sentences once and reuse them rather than cover fewer drugs.

2 GPT Batch API conversion and mapping results back to drugs

Problem

Deduplication reduced input, but I still needed to minimize model costs.

Experiment and result

The work did not require immediate responses during service use, so batch waiting was acceptable. Converted unique sentences with GPT Batch API, then reused the preserved drug-to-block mappings to attach results to each drug. Actual API spending was $11.18 versus about $200 estimated for all original text.

Decision

Combined deduplication and batch conversion to deliver the feature without reducing drug coverage.

Problem analysis and implementation (continued)

3 2026 PySpark reproduction: measuring ending normalization and similar-sentence merging

Problem

Part of the 2025 code and the raw files no longer existed, so the effect of stages after exact deduplication could not be shown in numbers.

Experiment and result

Re-collected 42,714 products from the MFDS public API, split them into 3,299,602 blocks following the XML structure, and reproduced normalization and exact deduplication in PySpark. Then applied an ending-normalization dictionary and MinHashLSH (character 3-grams, Jaccard distance), comparing reduction and merged samples at thresholds 0.1, 0.2 and 0.3. PySpark split about 3.24 million blocks across cores and can scale to a cluster as data grows.

Decision

At 0.3, text shrank 18.78% but sentences about different conditions (Lapp vs. total lactase deficiency) merged, and at 0.2 some precaution sentences were lost. Wrong merges are costly for medical information, so I chose 0.1 (a further 6.69%) with guards that merge only when numbers and applicability conditions match.

CASE 08 **Drug data conversion: $200 estimated → $11.18 spent**

Improved processing flow






그림 6-7 <블럭화한 의약품 복용법 및 주의사항 중 일부>

그림 8-9 <블럭 매핑한 의약품 복용법 및 주의사항 중 일부>

Converted each repeated sentence once and kept per-drug mappings to attach results. In 2026 the same process was reproduced in PySpark and measured.

Actual API spend $11.18, PySpark reproduction cut text by 94.1%

In 2025, sentence-block deduplication reduced about 1GB of drug data to 326MB. I completed conversion for $11.18 in actual API spending versus about $200 estimated for all original text. Reusing converted unique sentences kept the feature within budget without reducing the set of drugs covered. Part of the 2025 preparation code no longer existed, so in 2026 I re-collected 42,714 products (960MB of plain text) from the MFDS public API and reproduced the same preparation in PySpark. 3,236,626 blocks reduced to 176,648 unique blocks, cutting text from 744MB to 44.1MB (−94.1%). An ending-normalization dictionary then removed 0.78%, and MinHashLSH similar-sentence merging a further 6.69%.

Scope and tradeoffs

About $200 was the upfront estimate; $11.18 was actual spending. Seven days of preprocessing labour are not included. The 2026 figures come from re-collected data, not the 2025 dataset. The reproduction code was written with AI coding tools; I designed the experiment and chose the thresholds. The 1GB → 326MB figures describe the original 2025 work; 744MB → 44.1MB describes the separate 2026 reproduction.

Estimated cost for original text

About $200

Estimate

Actual API spending

$11.18

2025 conversion

Exact deduplication

−94.1%

2026 PySpark reproduction, 744MB → 44.1MB

CASE 09 Pilltip / AI Agent, Sensitive data boundaries

Medication chatbot: keeping health profiles out of external AI inputs

Pilltip has to guide medication by health condition, but I thought that health information is the most sensitive personal data. So I built a chatbot that guides medication through RAG-based AI orchestration while separating symptom-based drug search from profile-based decisions. It uses the model's language understanding, while code controls how far the sensitive profile is used.

2025.09

Spring AI | Weaviate | RAG | AI Orchestration

Background

Users describe symptoms in different words from drug indications, so keyword search could not match symptoms to drugs. Personalization also needed pregnancy status, current medications and underlying conditions, but sending that health profile to an external LLM as-is would make it hard to control where sensitive data goes.

What solving it enables

I judged that sending health information to external AI brings leak risk and regulatory burden, while not sending it loses personalisation, the core feature. Handling the decision internally, I thought, could protect both.

Design and implementation

1 Semantic search connecting symptoms to drug indications

Problem

Everyday symptom descriptions and drug indications use different words for the same meaning. Related information needed to be found without exact keyword matches.

Decision

I first started building a symptom synonym dictionary and wrote code for it. But there were too many symptoms, and when users described several at once the dictionary entries overlapped. I still had to pick the drugs that fit that person, yet vague drug descriptions matched almost every symptom. So I used semantic search to link natural-language symptoms to drug indications, and split processing paths by what each question needed.

Implementation

Among free vector databases with hybrid search I tried Milvus first, but it was too heavy, so I stored drug indications in the lighter Weaviate. Because the backend was Spring, I ran orchestration with Spring AI on the same server instead of adding a separate Python container. Stored drug indications in Weaviate for semantic symptom search. Built paths for drug discovery, medication risks and dosage information according to the question.

Verification

In user-scenario E2E tests in August 2025, natural-language symptoms were routed to the right path (drug search, medication risk, dosage). I did not keep a numeric accuracy evaluation per symptom.

Design and implementation (continued)

2 Internal health-profile processing, separate from external AI inputs

Problem

Personalization required pregnancy status, medications and underlying conditions, but sending those profiles to an external LLM risked exposing sensitive information.

Decision


At first I considered sending the health profile to the external AI with sensitive content filtered out. But there were too many expressions and cases to filter, and I judged that code could not cover them all. So I separated understanding symptom language from deciding profile conditions, and kept profile decisions in internal code where inputs and rules can be controlled directly.

Implementation

Excluded pregnancy, medication and underlying-condition fields from external LLM inputs. Connected internal profile decisions to symptom search results to provide personalized information.

Verification

Pregnancy status, current medications and underlying conditions are never put into external LLM inputs; an internal tool uses them to judge contraindications, duplicates and interactions and filter out unsuitable drugs. The AI guidance on the drug detail screen did not send these three fields either.



Separating symptom search from internal health-profile decisions

Enabled natural-language drug discovery while excluding pregnancy status, current medications and underlying conditions from external LLM inputs. Explicitly separated information sent to AI from information evaluated by internal code. In a domain that handles sensitive data, I settled the boundary between what the model may judge and what code stays responsible for before writing the implementation.

Scope and tradeoffs

Internal code has to change when profile conditions change, but keeping sensitive health information from reaching external models came first, so I handled this decision in code instead of AI. This removes specific profile fields from external input; it is not a measurement of leak prevention on every path. As users grow, I think AI processing should move to a separate service.

BEYOND THE PROJECTS

Beyond project development

Rhwp | Fixing HWPX save errors

Gave Claude Code a work plan and contribution rules to automate the flow from issue analysis to PR; 7 PRs merged, including the textFlow preservation fix (#1213), and listed as a contributor.

GitHub repository ↗

APPTIVE | Backend mentoring

Used my experience as a mentee to improve teaching. Led 6 mentoring and code-review sessions for 12 mentees.

945-day Baekjoon problem-solving streak

Aiming for one problem a day, I reached a 945-day streak on solved.ac. 1,659 problems solved, solved.ac Platinum IV.

Solutions repository ↗

ENGINEERING JOURNAL

Project reflections

ARCHITECTURE / Data ownership

Moving to MSA and learning from feedback

Shifted from splitting by feature to defining data ownership. Documented both the benefits of asynchronous processing and the added operational burden.

PLANNING / Defining user problems

Reflections on design thinking

Revisited feature-first planning and brought together the team's difficulties finding documents to define the problem we would solve together.

AGENT ENGINEERING / Decisions & review

AI agents and 78 PRs in 2 days

Human decisions, independent review and unfinished issues across five repositories.

More blog posts ↗

CONTACT

Jaehyeong Kim

AI Engineer | Backend Engineer

kkuldangi2@gmail.com

martinel2.github.io

github.com/Martinel2

I lead the AI work on Fruition, a team-built, LLM Wiki-based knowledge workspace. On evaluation sets I wrote and reviewed with my team, I raised RAG answer accuracy from 71.7% to 93.0% and AI document-editing success from 85.6% to 88.9%, designing evaluation, approval and rollback so AI does not answer from wrong evidence or change users' documents on its own.

I weigh accuracy, cost and response time against each other, confirm the trade-off with an evaluation, and then choose the implementation that fits the service.