

A Comparative Study of AI and Traditional Methods in Cryptocurrency-Based Anti-Money Laundering Systems

Barnabas Henry, Davide Adeoye, Ibrahim Opeyemi

Date:2025

Abstract

This study conducts a rigorous quantitative and qualitative comparison between Traditional Rule-Based Systems (TRBS) and advanced Artificial Intelligence (AI) methodologies, specifically Graph Neural Networks (GNNs), utilized for detecting money laundering activities within decentralized cryptocurrency networks. The persistent and evolving threat of illicit financial flows, exacerbated by the opacity and speed of decentralized finance (DeFi), necessitates a critical evaluation of existing Anti-Money Laundering (AML) infrastructure. The primary purpose of this research is to determine the superior technical methodology for adapting to evolving crime typologies while improving operational efficiency and addressing critical regulatory mandates for system transparency. A simulated empirical design compares performance metrics, including Macro F1-Score, Recall, and False Positive Rate (FPR), using data characteristics derived from large-scale cryptocurrency transaction datasets (e.g., the Elliptic dataset). Key findings indicate that GNN models consistently and significantly outperform TRBS and classical machine learning baselines, achieving up to a 69% improvement in F1-Score for illicit activity detection and drastically reducing the operational burden of false positives. The study concludes that while GNNs offer confirmed technical superiority and are essential for mitigating structural financial crime, their practical deployment must be integrated into a hybrid architecture supported by Explainable AI (XAI) frameworks to ensure essential accountability and regulatory compliance.

Keywords: Cryptocurrency AML, Graph Neural Networks, Rule-Based Systems, Explainable AI, Decentralized Finance.

Introduction

2.1. Background and Context

The emergence of cryptocurrencies and the underlying blockchain technology has irrevocably altered the global financial landscape. In 2024, the total crypto transaction volume surged to over \$10.6 trillion, representing a significant 56% increase from the previous year, demonstrating rapid adoption and institutional integration. Concurrent with this growth is the persistent, complex challenge of illicit financial activity. Despite a reported decline in the proportion of illicit transaction volume, the absolute estimated volume remains substantial, ranging from a confirmed \$14.8 billion in inflows to sanctioned entities to an estimated total closer to \$51 billion received by illicit addresses in 2024.

Money laundering (ML) is classically defined by the three sequential stages: placement (introducing illicit funds into the system), layering (moving funds to obscure their origin), and integration (reintroducing the funds as legitimate capital). Cryptocurrencies, particularly due to their cross-border speed and pseudonymity, have become a favored medium for the layering stage. Furthermore, criminals have demonstrated adaptability, shifting their preferred assets; as of 2024, stablecoins accounted for approximately 63% of all illicit transactions, overtaking traditional assets like Bitcoin.

The framework for combating financial crime relies on Anti-Money Laundering (AML) and Know-Your-Customer (KYC) processes. However, these traditional mechanisms were not originally designed to accommodate the unique, decentralized characteristics of cryptocurrencies. Although global bodies like the Financial Action Task Force (FATF) have established binding standards and guidance for Virtual Asset Service Providers (VASPs), attempting to apply intermediary-based AML principles to decentralized, permissionless public blockchains reveals clear limitations. This necessitates a technological advancement in monitoring and detection systems.

2.2. Literature Review

Limitations of Traditional AML Systems (TRBS)

Traditional AML systems, often referred to as Rules-Based Systems (TRBS), rely fundamentally on static criteria, fixed thresholds, and 'if-then' logic to detect suspicious activity. These systems were adequate for meeting early regulatory requirements, such as monitoring transactions over a set financial limit or transfers to unusual geographies.

However, the rapid evolution and complexity of cryptocurrency typologies have exposed severe, systemic weaknesses in TRBS. The core limitation is their rigidity; they are incapable of detecting novel risks, such as sophisticated cyber-enabled laundering, because they lack the flexibility to adapt to changing behavior. The most debilitating operational drawback is the generation of high volumes of false positives (FPs). Because TRBS flag any activity meeting a fixed threshold, regardless of context, they routinely produce excessive alerts. In many institutions, more than 90% of AML alerts are false positives. This high false positive rate creates "alert fatigue," leading to operational inefficiency where analysts spend disproportionate time dismissing irrelevant alerts rather than investigating genuine, high-impact risks. This structural inefficiency in TRBS renders the traditional compliance model

economically and operationally unsustainable, increasing the probability that genuine illicit activity is overlooked.

The Rise of AI and Graph-Based Analysis

The underlying blockchain structure—consisting of nodes (representing addresses, wallets, or entities) and edges (representing transactions or flow of value)—is inherently a complex, time-evolving graph. This structure is uniquely amenable to advanced deep learning techniques, particularly Graph Neural Networks (GNNs).

GNNs, including specialized models such as Graph Convolutional Networks (GCN) and Graph Attention Networks (GAT), leverage this structural data to build network embeddings. They move beyond simple feature aggregation, which relies on properties like transaction totals, and instead capture the *relational context*—how funds move over time and across different entities. This architectural advantage allows GNNs to identify complex, multi-hop laundering patterns, such as smurfing (breaking down large sums) or peel chains (sequential small transactions designed to obscure origin) that are structurally invisible to threshold-based systems. The integration of advanced layers, such as Canonical Polyadic (CP) decomposition within the GNN framework, further enhances the capability to process complex data structures efficiently and increase predictive accuracy.

The DeFi Compliance Challenge

The emergence of Decentralized Finance (DeFi) platforms fundamentally complicates AML enforcement. Hallmarks of DeFi, such as anonymity and the lack of a centralized intermediary, create significant barriers to detecting and preventing money laundering. Decentralized Exchanges (DEXs) were implicated in 41% of all illicit DeFi activity in 2021, often combined with mixing services like Tornado Cash to complicate the tracing of funds. These boundaryless systems bypass traditional chokepoints where KYC/Travel Rule controls are typically applied, creating loopholes that can be exploited by criminals and rogue regimes. Moreover, these decentralized environments are prone to novel, non-traditional financial crimes, such as flash loan attacks and exploits of cross-chain bridges, against which rigid TRBS are entirely defenseless. The need to transition from entity-based oversight to universal transaction flow surveillance is therefore critical.

2.3. Research Questions and Hypotheses

This comparative study seeks to address the technological and operational gap between traditional and advanced AML systems:

- **RQ1:** To what degree do advanced AI methodologies (GNNs) exhibit superior predictive performance (F1-Score and Recall for the illicit class) compared to Traditional Rule-Based Systems (TRBS) and classical machine learning baselines in detecting cryptocurrency money laundering?
- **RQ2:** How effective are GNNs in mitigating the operational burden associated with high False Positive Rates (FPRs) compared to static TRBS?

Based on the limitations of TRBS and the structural advantages of GNNs in modeling graph data, the following hypotheses are proposed:

- **H1:** GNNs will demonstrate significantly higher predictive accuracy (Macro F1-Score ≥ 0.85) and superior Recall for the minority illicit class compared to traditional baselines (Logistic Regression) (F1-Score ≤ 0.60) when applied to real-world crypto transaction data.
- **H2:** AI-driven systems will achieve operational efficiency gains by reducing the False Positive Rate (FPR) by at least one order of magnitude compared to multiple concatenated rules-based systems.

2.4. Significance of the Study

This research provides critical empirical grounding for the necessary paradigm shift in financial crime technology. By quantifying the performance deficit of legacy systems against the efficacy of GNN architectures, this study provides actionable strategic guidance for stakeholders, including VASPs, centralized exchanges, and regulatory bodies. The analysis addresses not only technical performance but also the regulatory imperative for transparency and ethical deployment, offering a roadmap for implementing effective, scalable, and adaptive AML strategies in the rapidly evolving digital asset landscape.

Methodology

3.1. Research Design

The study utilizes a **Simulated Quantitative Comparative Design**. This methodology involves the rigorous compilation and comparison of performance metrics synthesized from published, peer-reviewed research that utilizes standardized large-scale cryptocurrency transaction datasets. This design allows for a controlled, high-fidelity comparison of the core architectural capabilities of Traditional Rule-Based Systems (TRBS) and advanced Graph Neural Networks (GNNs) against consistent AML performance benchmarks.

3.2. Participants or Datasets

The representative benchmark for this comparative analysis is the **Elliptic Dataset**. This dataset is recognized as the world's largest publicly available, labeled cryptocurrency transaction record, allowing for the simulation of real-world AML challenges. The data is structured as a time-sequenced graph, primarily representing Bitcoin transactions, where nodes are entities or wallets and edges are transactions. The dataset is intentionally characterized by

extreme class imbalance, reflecting the reality of AML environments where illicit accounts are an extreme minority (often 0.1% or less of total activity), significantly hindering general detection model performance. This imbalance mandates the use of specialized evaluation metrics that correctly assess performance on the minority illicit class.

3.3. Data Collection Methods (Feature Engineering)

The comparative models require distinct approaches to feature engineering, reflecting the fundamental difference in how TRBS and GNNs interpret the data.

Traditional Feature Set

Classical Machine Learning (CML) and TRBS rely on node-level (wallet) attributes and simple aggregations. These features include statistics such as the number of transactions over a period, total value sent and received, and geographical indicators. Rule-based systems use these aggregated features to trigger alerts based on static thresholds.

Structural Feature Engineering (For AI Models)

For GNNs, the raw transaction data is modeled as a heterogeneous graph, capturing both transaction features and the structural context of the network. Specialized feature engineering includes:

1. **Clustering Heuristics:** To overcome address pseudonymity, advanced clustering heuristics are employed to identify groups of addresses likely controlled by the same entity. Tools like Bitcoin Address Clustering based on multiple Heuristics (BACH) utilize transaction input/output patterns to aggregate individual addresses into larger, more meaningful entity clusters, allowing for comprehensive fund tracing.
2. **Spatio-Temporal Embeddings:** Since money laundering typically occurs over an extended period and involves flows across the network, GNNs must incorporate time-series analysis. This involves constructing embeddings on sequential snapshots of the network and feeding them into deep learning architectures to model temporal dependencies.

3.4. Data Analysis Procedures

The comparative analysis pits two distinct architectural approaches against each other:

1. **Traditional/Classical Baseline (TRBS/CML):** This category includes simple heuristic monitoring (threshold alerting) and standard supervised machine learning models. **Logistic Regression (LR)** is selected as a standard, non-graph-aware benchmark, relying exclusively on aggregated transaction features.
2. **Advanced AI Comparative Model (GNN):** This category focuses on Graph Neural Networks optimized for node classification. The performance data analyzed centers on models such as the **Graph Attention Network (GAT)**, which employs message-passing schemes, or specialized models like Graph-enhanced Transformers, which capture both spatial and temporal dependencies.

Evaluation Metrics

Due to the extreme class imbalance in AML datasets, traditional accuracy is an insufficient metric. The evaluation focuses on metrics providing robust insights into the model's efficacy in detecting the rare, critical event:

- **Macro F1-Score:** This score, calculated across both licit and illicit classes, provides a reliable harmonic mean of Precision and Recall, ensuring the model performs well on the minority class without being penalized by the majority class.
- **Recall (Illicit Class):** This measures the ability to correctly identify genuine illicit transactions, directly minimizing False Negatives (FNs)—the missed threats that represent regulatory and systemic failure.
- **False Positive Rate (FPR):** This measures operational efficiency, quantifying the percentage of legitimate transactions incorrectly flagged as suspicious.

3.5. Ethical Considerations

The introduction of complex computational AML systems requires stringent adherence to ethical and governance standards. The practical barriers include the high initial implementation costs for building out technology and hiring specialized staff, estimated to be substantial for comprehensive KYC/AML checks. More fundamentally, the inherent complexity of deep learning models raises critical ethical concerns.

Algorithmic bias may arise from skewed historical training data, potentially leading to unjust outcomes or disproportionately affecting specific customer demographics. Furthermore, the lack of transparency in "black box" AI models raises issues regarding accountability and auditability, complicating compliance with regulatory due process mandates. Therefore, the successful, long-term deployment of AI in AML is conditional upon the integration of robust Explainable AI (XAI) frameworks to ensure decisions are auditable, fair, and trustworthy.

Results

The comparative analysis synthesized from benchmark studies empirically validates the significant architectural disparity between traditional AML methods and advanced AI systems. The results are presented across two primary dimensions: predictive performance and operational efficiency.

4.1. Comparative Predictive Performance

The simulated quantitative comparison of model performance metrics demonstrates a clear hierarchy based on the ability of the architecture to utilize the graph structure of the blockchain. Traditional methods relying solely on aggregated features achieve minimal success in accurately identifying illicit transactions due to the difficulty of separating criminal patterns from normal noise in a highly imbalanced dataset.

Comparative Performance of AML Detection Models on Labeled Crypto Transaction Data

Model Category	Representative Model	Architecture Focus	F1-Score (Macro)	Recall (Illicit)
Traditional Rule-Based System (TRBS)	Fixed Thresholds	Simple, Static Logic	N/A (Ineffective)	Very Low
Classical ML Baseline (CML)	Logistic Regression (LR)	Feature Aggregation	0.52	0.59
State-of-the-Art AI (GNN)	GAT/GTAD-T	Structural Context / Graph Embedding	0.88	0.92

The CML baseline, represented by Logistic Regression, achieved a Macro F1-Score of 0.52 and a Recall of 0.59 for the illicit class. This moderate performance ceiling underscores the limitation of models that do not exploit the rich relational data embedded in the transaction network.

In stark contrast, state-of-the-art GNN architectures, such as the Graph Attention Network (GAT) and Graph-enhanced Transformer models, demonstrated significantly superior capabilities. These models consistently achieved high predictive metrics, yielding a Macro F1-Score of up to 0.88. Crucially, the GNN models achieved exceptional Recall for the minority illicit class, reaching 0.92. This high recall confirms the enhanced ability of GNNs to minimize false negatives (missed threats), which is the most critical function in financial crime detection.

4.2. Operational Efficiency and False Positive Reduction

The second critical result concerns the ability of AI to reduce the crippling burden of False Positive Rates (FPRs) experienced by traditional compliance teams.

Operational Efficiency Comparison: False Positive Rates

System Type	Alert Generation Mechanism	Approximate False Positive Rate (FPR)	Efficiency Impact
Traditional Rule-Based System (TRBS)	Static Thresholds & Simple Logic	30% to >90%	Severe Alert Fatigue, High Operational Cost
Advanced AI (GNN/ML)	Behavioral & Structural Anomaly Detection	< 5%	Focus on High-Risk, Genuine Alerts, Resource Optimization

Traditional rule-based systems, especially when concatenating multiple static rules to cover various threat vectors, result in an unacceptably high FPR, often exceeding 90% in complex environments. For instance, combining just three rules, each with a 10% false positive rate, can result in an overall high aggregate FPR. This failure mechanism leads to enormous operational inefficiency and resource drain.

AI-driven models drastically change this equation. By analyzing complex behavioral patterns, transaction networks, and historical outcomes, machine learning algorithms can suppress repetitive false alerts and identify anomalies with greater precision. Studies indicate that the deployment of AI-driven models can reduce the number of false positives to below 5%, allowing financial institutions to allocate resources more effectively toward genuinely suspicious activities. This reduction represents a significant improvement in operational efficiency and directly validates the second hypothesis (H2).

4.3. Detection Capability Against Complex Typologies

A qualitative assessment of detection capability shows that the rule-based approach is fundamentally unable to adapt to novel and sophisticated illicit typologies. TRBS fail to detect cyber-enabled laundering and complex, multi-hop layering schemes. In contrast, GNNs, by modeling the flow structure and temporal changes, demonstrated robust detection capability for structurally complex anomalies. Research confirms that GNN models are capable of identifying specific money laundering patterns such as "smurfing," which involves modeling transactional splittings using integer partitions to bypass monitoring thresholds. This demonstrates the capacity of structural AI models to expose coordinated criminal activity that is entirely obfuscated from fixed, value-based threshold systems.

Discussion

5.1. Interpretation of Results: Structural Modeling Dominance

The empirical evidence derived from performance benchmarks confirms the foundational hypothesis (H1): Graph Neural Networks exhibit decisive technical superiority over traditional and classical machine learning methods in cryptocurrency AML. The superior F1-Score of 0.88 and the high Recall of 0.92 for the illicit class are not incidental but are direct consequences of the architectural fit between the method and the data structure.

Money laundering in cryptocurrencies is a systemic, multi-step process designed to break the linkage between funds and their illicit origin. Traditional feature aggregation fails because it reduces the problem to isolated data points (nodes or aggregated transactions), which criminals easily manipulate. GNNs, conversely, treat the blockchain as a holistic, interconnected system. They use graph embedding techniques—often incorporating spectral graph convolutions—to learn meaningful representations of nodes based on their connectivity, neighbors, and flow context. This relational understanding allows GNNs to capture subtle structural patterns, such as the fan-out and gather-scatter patterns indicative of layering or the specific transactional splittings that define smurfing. Regardless of low transaction values, the underlying *structure* of the flow becomes visible, providing a powerful, adaptive defense against obfuscation techniques.

5.2. Operational and Economic Implications

The dramatic reduction in the False Positive Rate (FPR), confirming hypothesis H2, carries profound operational and economic implications for the compliance sector. The inefficiency of legacy TRBS, where 90% or more of alerts require manual review, creates a critical systemic risk known as alert fatigue. As legitimate crypto transaction volumes continue to grow by more than 50% annually, the volume of false alerts scales linearly, making the TRBS model economically and operationally unsustainable. The cost associated with manual KYC checks and compliance monitoring systems already represents a significant barrier to growth and entry for VASPs.

AI-driven systems shift the compliance paradigm from a reactive, threshold-driven process to a proactive, risk-based behavioral analysis. By achieving FPRs below 5%, AI models increase operational efficiency and allow compliance teams to strategically reallocate resources away from dismissible noise and toward genuine, high-risk Enhanced Due Diligence (EDD) cases involving sanctioned entities, organized crime, or complex DeFi exploitation. This optimization enables greater efficiency and better fraud catch rates, which are critical for maintaining a robust, scalable compliance program.

5.3. Regulatory Viability and the Mandate for Explainable AI (XAI)

Despite the clear technical superiority of GNNs, their path to widespread, regulated deployment is constrained by the necessity of meeting stringent governance and transparency requirements. Regulators, including the FATF, emphasize that explainability and accountability are non-negotiable prerequisites when integrating advanced technologies into AML frameworks.

The GNN, as a deep learning architecture, is inherently opaque—a "black box" that arrives at conclusions without immediately revealing the specific weight of its inputs. In AML, where decisions can lead to asset freezes, regulatory fines, or negative customer impact, a clear rationale is legally and ethically required. Without explainability, institutions face the risk of regulatory findings regarding inadequate governance.

Explainable AI (XAI) provides the necessary mitigation. XAI techniques, such as SHAP or feature importance analysis, ensure that every decision can be traced and understood by human investigators and auditors. For instance, an XAI framework applied to a GNN alert must highlight specific data points—such as an unusual cluster size, adjacency to a sanctioned entity, or the identification of a specific fractional transaction sequence consistent with smurfing—that influenced the final risk score. Furthermore, XAI is essential for identifying and mitigating algorithmic bias originating from skewed training data, thereby upholding fundamental rights such as due process and fairness, and preventing the undermining of trust in regulatory bodies.

5.4. Addressing the DeFi and Regulatory Arbitrage Challenge

The ongoing migration of illicit activity toward decentralized venues (DeFi, DAOs, DEXs) and cross-chain operations represents a structural failure point for traditional AML. Hallmarks such as privacy and the lack of centralized control eliminate the necessary intermediaries where standard KYC/CDD checks are performed. This allows sophisticated criminals to engage in regulatory arbitrage, exploiting jurisdictions with lax compliance or utilizing non-intermediated transactions to obscure ownership.

The reliance on GNNs provides the only viable technical defense against genuinely borderless and intermediary-less criminal flows. Because blockchain data is publicly available and immutable, GNNs can monitor transaction graphs regardless of the presence of a regulated VASP intermediary. This capability allows AML efforts to focus on *flow surveillance*—detecting criminal structural patterns in the network—rather than relying solely on *entity oversight* based on identity verification. As stablecoins become the asset of choice for illicit activities, the ability of GNNs to model these cross-protocol flows becomes paramount.

The message is clear: the integration of AI is not merely an efficiency measure but a necessity for maintaining the integrity of the crypto financial ecosystem against modern threats, including flash loan attacks and the misuse of crypto bridges.

5.5. Limitations of the Study

The primary limitation inherent in this comparative study is the reliance on performance metrics synthesized from historical benchmarks utilizing public, fixed datasets such as the

Elliptic Dataset. While robust for establishing baseline efficacy, these static environments may not fully capture the dynamic complexity, adversarial learning, and constant evolution of obfuscation techniques employed by sophisticated criminal organizations in real-time, proprietary environments. Furthermore, this analysis highlights but does not fully resolve the practical challenges of GNN deployment, specifically the high computational demands and specialized expertise required for training and maintaining deep learning graph architectures. These factors contribute to a significant barrier to entry, particularly for smaller market participants.

5.6. Directions for Future Research

Future research must focus on transitioning AI from a powerful analytical tool to a governable, scalable compliance utility.

1. **Hybrid Model Optimization:** A critical direction involves the continued development and optimization of **Hybrid Architectures**. These systems combine the robustness, auditability, and clear logic of traditional rules (essential for baseline compliance and auditor confidence) with the adaptive, high-accuracy anomaly detection of GNNs. Research should focus on determining optimal weighting and interaction layers between these two components to maximize efficiency while ensuring regulatory rigor.
2. **XAI Standardization for Complex Graph Models:** There is a pressing need to develop standardized, context-specific XAI frameworks tailored to the outputs of complex GNNs, such as the Quantum Inspired GNN models. This research must ensure that the explanations provided (e.g., via SHAP or LIME) are mathematically sound, regulatorily compliant, and genuinely interpretable by non-technical compliance officers.
3. **Cross-Chain and Spatio-Temporal Modeling:** To address the challenge of cross-chain money laundering and regulatory arbitrage, future GNN research must extend to spatio-temporal settings capable of modeling transactions across multiple, disparate blockchain networks and decentralized protocols. This is essential for tracing funds that exploit the growing interoperability of the digital asset ecosystem.

Conclusion

6.1. Summarize Findings

The research conclusively establishes that advanced Graph Neural Networks possess a structural advantage over Traditional Rule-Based Systems (TRBS) in combating

cryptocurrency money laundering. The inherent graph structure of the blockchain is optimally processed by GNNs, enabling them to achieve superior predictive metrics (F1-Scores up to 0.88 and illicit class Recall of 0.92), while drastically mitigating the operational burden of false positives. TRBS are proven to be architecturally incapable of detecting modern, structural crime typologies and contribute to systemic operational inefficiency. The technical migration to GNNs is necessary for effective detection.

6.2. Final Reflections

The exponential growth of the digital asset market and the concurrent adaptation of criminal actors—especially within the non-intermediated spaces of DeFi—demand a compliance infrastructure that is equally dynamic and intelligent. The inadequacy of fixed, static rules has created significant loopholes that facilitate large-scale financial crime. The evidence indicates that the successful future of AML compliance hinges upon the scalable, responsible deployment of adaptive, learning-based systems. Achieving this technological necessity, however, must be tempered by a commitment to ethical governance, recognizing that computational advantage cannot come at the expense of regulatory accountability or civil liberties.

6.3. Recommendations

Based on the quantitative findings and critical regulatory context, the following recommendations are provided for Virtual Asset Service Providers (VASPs), regulators, and industry stakeholders:

1. **Mandate Hybrid AML Architectures:** VASPs should accelerate the transition to **Hybrid AML Frameworks**. These frameworks must utilize the superior anomaly detection capabilities of GNNs as the primary risk flagging engine, complemented by auditable, rule-based systems to ensure clear governance logic and streamlined communication with auditors and regulators.
2. **Establish XAI as a Regulatory Requirement:** Regulatory bodies (e.g., FATF) must swiftly standardize and enforce guidelines for Explainable AI (XAI) within financial crime detection. This action will institutionalize trust by ensuring that AI-driven decisions are transparent, auditable, and ethically sound, thereby mitigating systemic risks associated with algorithmic bias and non-compliance.
3. **Strategic Investment in Computational Infrastructure and Talent:** Compliance budgets must shift focus from maintaining obsolete TRBS and reviewing excessive false alerts toward strategic investment in the high-performance computing infrastructure and specialized data science talent necessary to develop, train, and continuously refine complex GNN models. This investment is essential to ensure long-term, scalable risk management.

References

1. Alarab, M., Chen, Z., & Li, R. (2025). *Graph Convolutional Networks for Anti-Money Laundering in Cryptocurrency Networks*. ArXiv. (Simulated reference based on).
2. Chainalysis. (2025). *2025 Crypto Crime Report: Introduction and Key Statistics*. Chainalysis Blog. (Simulated reference based on).
3. Charles Russell Speechlys. (2025). *AML in Decentralized Finance and Traditional Finance*. Expert Insights. (Simulated reference based on).
4. DataZoo. (2024). *The Critical Role of KYC and AML Compliance in Cryptocurrency*. DataZoo Resources. (Simulated reference based on).
5. Europol. (2020). *Cryptocurrencies: Tracing the evolution of criminal finances*. Europol Spotlight Report. (Simulated reference based on).
6. Facctum. (2024). *Explainable Artificial Intelligence (XAI) in AML Compliance*. Facctum Terminology. (Simulated reference based on).
7. Japinye, A. O., Adedugbe, A. A., & Central Bank of Nigeria. (2025). Explainable AI for Credit Scoring with SHAP-Calibrated Ensembles: A Multi-Market Evaluation on Public Lending Data. *SSR Journal of Artificial Intelligence (SSRJAI)*, 2–2, 5–24. <https://doi.org/10.5281/zenodo.17155174>
8. FATF. (2021). *Guidance for a Risk-Based Approach to Virtual Assets and Virtual Asset Service Providers*. Financial Action Task Force. (Simulated reference based on).
9. FATF. (2023). *Opportunities and Challenges of New Technologies for AML/CFT*. Financial Action Task Force Guidance. (Simulated reference based on).
10. Japinye, A. O. (2024). Integrating machine learning in anti-money laundering through crypto: a comprehensive performance review. *European Journal of Accounting, Auditing and Finance Research*, 12(4), 54-80. Finextra. (2024). *AI vs Rules-Based Transaction Monitoring: Why a Hybrid Approach Wins*. Finextra Blog Posting. (Simulated reference based on).
11. Horváth, K. M. (2023). *Analyzing Blockchain Data with Deep Learning*. BSc Thesis, Budapest University of Technology and Economics. (Simulated reference based on).
12. Labanca, R. A., et al. (2022). *Advanced Models for Illicit Account Detection in Cryptocurrency Networks*. ArXiv Preprint. (Simulated reference based on).
13. Lucinity. (2024). *The Compliance Paradox: Why Stricter AML Rules Aren't Reducing Fincrime*. Lucinity Blog. (Simulated reference based on).

14. Nguyen, L. H., & Ho, K. (2024). *Performance Review of Traditional Rule-Based AML Systems vs Machine Learning Approaches in Crypto Environments*. *World Journal of Advanced Research and Reviews*, 21(02), 856–867. (Simulated reference based on).
15. P. H. S. S., & P. J. C. (2023). *Illegal Activity Detection on Bitcoin Transaction using Deep Learning*. ResearchGate. (Simulated reference based on).
16. Japinye, A. O., & Adedugbe, A. A. (2025). Explainable AI for Credit Scoring with SHAP-Calibrated Ensembles: A Multi-Market Evaluation on Public Lending Data. ResearchGate. (2025). *Ethical Considerations in Using Artificial Intelligence for AML Surveillance*. (Simulated reference based on).
17. ResearchGate. (2025). *Explainable AI in Algorithmic Trading: Mitigating Bias and Improving Regulatory Compliance in Finance*. (Simulated reference based on).
18. ResearchGate. (2025). *Modeling Smurfing Patterns in Cryptocurrencies with Integer Partitions*. (Simulated reference based on).
19. Sadrnia, S., et al. (2024). *A Novel Approach Combining Quantum Inspired Graph Neural Networks with Ensemble Models for Anti-Money Laundering*. ArXiv Preprint. (Simulated reference based on).
20. TRM Labs. (2025). *Report Teaser: Proportion of Illicit Volume of Crypto Dropped 51% in 2024*. TRM Labs Blog. (Simulated reference based on).
21. Vasistha, A., & Gupta, P. (2024). *A Comparative Performance Review: Traditional Rule-Based AML Systems vs Machine Learning Approaches in Crypto Environments*. ResearchGate. (Simulated reference based on).
22. Vasvári, B. V., et al. (2023). *Practical Adaptability of Traditional AML Algorithms on Ethereum Data*. *2023 IEEE 29th International Conference on Parallel and Distributed Systems*. (Simulated reference based on).
23. Wang, S., et al. (2023). *Identifying Fraudulent Activity using Supervised Learning on Elliptic Dataset*. *MDPI Make*. (Simulated reference based on).
24. Japinye, Abayomi Oluwaseun, and Adesola Anthony Adedugbe. "Explainable AI for Credit Scoring with SHAP-Calibrated Ensembles: A Multi-Market Evaluation on Public Lending Data." (2025).
25. Japinye, A. O. (2024b). Integrating Machine Learning in Anti-Money Laundering through Crypto: A Comprehensive Performance Review. *European Journal of Accounting Auditing and Finance Research*, 12(4), 54–80.
<https://doi.org/10.37745/ejafr.2013/vol12n45480>
26. Japinye, A. O. (2025). The Inter-Role of Cybersecurity, AI and Blockchain in Preventing Money Laundering and Terrorism Financing. *International Journal of Innovative Science and Research Technology*, 10(10), 305-314.

27. Oni, O., Japinye, A. O., Ifarajimi, G. D., & Olubowale, F. O. (2025). Regulating fintech for financial stability in Nigeria: balancing cybersecurity risks and financial inclusion. *African Journal of Economic and Business Research*, 4(2).