



UNIVERSITÀ
DEGLI STUDI
FIRENZE

Scuola di Scienze Matematiche, Fisiche e Naturali
Laurea Magistrale in Data Science, Calcolo Scientifico &
Intelligenza Artificiale

Master Thesis

ANTI-MONEY LAUNDERING WITH GRAPH
NEURAL NETWORKS

NAME SURNAME

Advisor: *prof. Name Surname*

Co-Advisor: *prof. Name Surname*

Academic Year 2023-2024

ABSTRACT

CONTENTS

1	Introduction	7
1.1	Traditional AML methods	7
1.2	The Growing Challenge	7
1.3	GNN for fraud detection	8
1.4	Structure of the Dissertation	8
2	Financial Crime and Money Laundering	9
2.1	The Limitations of the Lonely Scammer	9
2.2	Fraud Rings	10
2.3	ML patterns	10
3	Ethics, Privacy and Regulations	11
4	State of the Art	13
5	Proposed Approach and Methodology	15
6	Experiments	17
6.1	Experimental Settings	17
6.2	Hyperparameter Tuning	17
6.3	Experimental Results and Discussion	17
7	Challenges	19
8	Conclusion	21
9	Future Directions	23
A	Software	25

LIST OF FIGURES

"Citation"
— *citation's author*

INTRODUCTION

Money laundering (ML) is the criminal process of disguising or concealing the origin, identity, and ownership of illegally acquired funds. Its detection has become a foundational pillar of modern economic security. The rapid digitization of financial services has opened new possibilities for fraudulent activities. Undetected ML leads to massive economic losses for individuals and institutions, undermines the public trust in the financial system and frequently serves to finance criminal organizations. The scale of this phenomenon is staggering: the United Nations Office on Drugs and Crime (UNODC) estimates that between 2% and 5% of global GDP is laundered annually, with less than 1% of these illicit financial flows being successfully intercepted [5, 3]. Consequently, developing robust mechanisms to identify and stop it is critically important to preserving both market integrity and social stability.

1.1 TRADITIONAL AML METHODS

1.2 THE GROWING CHALLENGE

Detecting fraud is becoming increasingly difficult. The sheer volume and velocity of digital transactions make manual oversight impossible and heavily strain classical machine learning architectures. Furthermore, the rise of decentralized finance (DeFi), Web3, and cryptocurrencies has introduced a paradigm of pseudo-anonymity that complicates traditional tracing. On top of that, the sophistication of the techniques used by scammers is constantly evolving. As Cuèllar (2003) noted, *"raising the marginal cost of perpetrating criminal activity can itself conceivably have counterintuitive effects. To the extent that criminals engaged in crimes for profit are acting rationally, then raising the cost of crime can discourage smaller operations and clear the market allowing more sophisticated criminal organizations to innovate and take more control from less organized criminals"* [2]. Hence, to prevent

inadvertently incentivizing sophisticated criminal networks, detection mechanisms must be updated continuously. The framework proposed in this study leverages deep learning models that support online updates, ensuring that the detection algorithm remains aligned with the most recent transaction patterns.

1.3 GNN FOR FRAUD DETECTION

1.4 STRUCTURE OF THE DISSERTATION

FINANCIAL CRIME AND MONEY LAUNDERING

2.1 THE LIMITATIONS OF THE LONELY SCAMMER

Individual scammers typically rely on simple and intuitive techniques to introduce illicit funds into the legitimate economy. One of the most prevalent methods is known as “smurfing”. In simple terms, smurfing involves breaking down a large sum of illicit money into many smaller, inconspicuous chunks to deposit them without raising suspicion.

More formally, individual scammers rely on smurfing to avoid Anti-Money Laundering (AML) detection mechanisms, which usually flag transactions above a specific threshold $\tilde{x}$. By splitting their initial illicit funds x into smaller transactions x_n , such that each transaction satisfies $x_n \leq \tilde{x}$, they minimize the risk of detection [1]. The mathematical expectation of profit π_s for a scammer engaging in smurfing can be defined as:

$$\pi_s = x(1 - v) \tag{2.1}$$

where x represents the total initial illicit funds, and $v \in (0, 1)$ is the friction cost or commission proportion associated with the smurfing process (e.g., the fee paid to mules).

While smurfing is effective for small amounts, its scalability is severely limited. When attempting to launder much larger volumes of funds, an individual scammer operating from a single account faces a significantly higher probability of detection $(1 - p)$, where p is the probability of successfully avoiding detection. If caught, the scammer is subjected to a severe monetary penalty T , which includes both the total confiscation of the funds and associated judicial fines [1]. Therefore, operating as a “lonely scammer” becomes mathematically and practically unviable for large-scale operations due to the massive expected cost of $(1 - p)T$.

2.2 FRAUD RINGS

In regard to overcome those issues, criminals have improved their techniques by employing highly sophisticated obfuscation tactics. Instead of acting alone, they form complex “fraud rings” to distribute illicit funds across vast networks of temporary accounts. To further break the traceable link between sender and receiver, illicit actors frequently use cyclic transfers and cryptocurrency **mixers** services that pool together funds from multiple users, mix them, and redistribute them at random intervals and amounts. These advanced tactics create dense, highly camouflaged transaction topologies that easily evade threshold-based rules and simple heuristic detection methods.

To achieve their goal they utilize a strategy of transaction layering, often characterized by a topological depth L , and network diversification to obscure the money trail [1, 4]. By spreading the funds through a complex topology, the fraud ring successfully increases its non-detection probability p_L , which now depends explicitly on the layering depth L . The expected profit of a fraud ring utilizing L layers can be mathematically expressed as:

$$E[\pi_L] = p_L x - (1 - p_L)T - c(L) \quad (2.2)$$

where $E[\pi_L]$ is the expected profit, p_L is the enhanced probability of evading detection when L layers are used, x is the total illicit funds, T is the total penalty if caught, and $c(L)$ represents the monotonic cost function associated with establishing and maintaining the L transaction layers. Because the fraud ring dramatically increases the probability of evading detection ($p_L \rightarrow 1$ as L increases), the expected payoff remains highly profitable even when factoring in the complex layering costs $c(L)$ [1].

2.3 ML PATTERNS

3

ETHICS, PRIVACY AND REGULATIONS

STATE OF THE ART

5

PROPOSED APPROACH AND METHODOLOGY

EXPERIMENTS

6.1 EXPERIMENTAL SETTINGS

6.2 HYPERPARAMETER TUNING

6.3 EXPERIMENTAL RESULTS AND DISCUSSION

7

CHALLENGES

CONCLUSION

FUTURE DIRECTIONS

A

SOFTWARE

BIBLIOGRAPHY

- [1] Alfredo Contreras and Edgar Villa Pérez. Strategic choices in money laundering: Smurfing, layering, and financial over-diversification. *Journal of Economic Criminology*, 11:100199, 2026. (Cited on pages 9 and 10.)
- [2] Mariano-Florentino Cuéllar. The tenuous relationship between the knowing act of money laundering and its underlying crimes. *Columbia Law Review*, 103(2):312–431, 2003. (Cited on page 7.)
- [3] Europol. Does crime still pay? criminal asset recovery in the eu. Technical report, Europol, 2016. (Cited on page 7.)
- [4] Xiaoqi Li, Wenkai Li, Zhijie Liu, Meikang Qiu, Zhiquan Liu, Sen Nie, Zongwei Li, Shi Wu, and Yuqing Zhang. Scamsweeper: Detecting illegal accounts in web3 scams via transactions analysis. *IEEE Transactions on Information Forensics and Security*, 2025. (Cited on page 10.)
- [5] United Nations Office on Drugs and Crime (UNODC). *Estimating illicit financial flows resulting from drug trafficking and other transnational organized crimes*. UNODC Vienna, 2011. (Cited on page 7.)