Date: 21/02/2024 **Security in Computing**

Practical 6:

Aim: Configuring a Zone-Based Policy Firewall.

- Topology Daigram:



- Assigning IP Adress:



IP Configuration

Interface FastEthernet0

IP Configuration

○ DHCP ● Static

IP Address 192.168.1.3

Subnet Mask 255.255.255.0

Default Gateway 192.168.1.1

DNS Server



IP Configuration

○ DHCP ● Static

IP Address 192.168.3.3

Subnet Mask 255.255.255.0

Default Gateway 192.168.3.1

DNS Server



IOS Command Line Interface

```
%LINK-5-CHANGED: Interface Serial0/0/0, changed state to down
Router(config-if)#
%LINK-5-CHANGED: Interface Serial0/0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial0/0/0, changed
state to up

Router(config-if)#exit
Router(config)#interface Serial0/0/0
Router(config-if)#ip address 10.1.1.1 255.0.0.0
Router(config-if)#ip address 10.1.1.1 255.255.255.252
Router(config-if)#no shut
Router(config-if)#interface GigabitEthernet0/0
Router(config-if)#ip address 192.168.1.1 255.255.255.0
Router(config-if)#no shut
Router(config-if)#^Z
Router#
%SYS-5-CONFIG_I: Configured from console by console
exit
```



IOS Command Line Interface

```
Router>en
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#host R2
R2(config)#interface Serial0/0/0
R2(config-if)#ip address 10.1.1.2 255.255.255.252
R2(config-if)#no shut'
                     ^
% Invalid input detected at '^' marker.

R2(config-if)#no shut
R2(config-if)#interface Serial0/0/1
R2(config-if)#ip address 10.2.2.2 255.255.255.252
R2(config-if)#no shut
R2(config-if)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console

R2#exit
```



IOS Command Line Interface

```
Router>en
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#host R3
R3(config)#interface Serial0/0/0
R3(config-if)#ip address 10.2.2.1 255.255.255.252
R3(config-if)#no shut
R3(config-if)#interface GigabitEthernet0/0
R3(config-if)#ip address 192.168.3.1 255.255.255.0
R3(config-if)#no shut
R3(config-if)#^Z
R3#
%SYS-5-CONFIG_I: Configured from console by console
 exit
```

- Displaying IP Adress details in routers



```
Router>show ip interface brief
Interface              IP-Address      OK? Method Status
Protocol

GigabitEthernet0/0     192.168.1.1     YES manual up
up

GigabitEthernet0/1     unassigned      YES unset  administratively down
down

Serial0/0/0            10.1.1.1        YES manual up
up

Serial0/0/1            unassigned      YES unset  administratively down
down

Vlan1                  unassigned      YES unset  administratively down
down
Router>
```



```
R2>show ip interface brief
Interface              IP-Address      OK? Method Status
Protocol

GigabitEthernet0/0     unassigned      YES unset  up
down

GigabitEthernet0/1     unassigned      YES unset  administratively down
down

Serial0/0/0            10.1.1.2        YES manual up
up

Serial0/0/1            10.2.2.2        YES manual up
up

Vlan1                  unassigned      YES unset  administratively down
down
R2>
```



```
R3>show ip interface brief
Interface              IP-Address      OK? Method Status
Protocol

GigabitEthernet0/0     192.168.3.1     YES manual up
up

GigabitEthernet0/1     unassigned      YES unset  administratively down
down

Serial0/0/0            10.2.2.1        YES manual up
up

Serial0/0/1            unassigned      YES unset  administratively down
down

Vlan1                  unassigned      YES unset  administratively down
down
R3>
```

- <u>Configuring router</u>



```
Router>en
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#router rip
Router(config-router)#network 192.168.1.0
Router(config-router)#network 10.1.1.0
Router(config-router)#^Z
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#exit
```



```
R2>en
R2#config t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#router rip
R2(config-router)#network 10.1.1.0
R2(config-router)#network 10.2.2.0
R2(config-router)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console

R2#exit
```



```
R3>en
R3#config t
Enter configuration commands, one per line.  End with CNTL/Z.
R3(config)#router rip
R3(config-router)#network 10.2.2.0
R3(config-router)#network 192.168.3.0
R3(config-router)#^Z
R3#
%SYS-5-CONFIG_I: Configured from console by console

R3#exit
```

- Showing IP route:



```
Router>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B -
BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS
inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C       10.1.1.0/30 is directly connected, Serial0/0/0
L       10.1.1.1/32 is directly connected, Serial0/0/0
R       10.2.2.0/30 [120/1] via 10.1.1.2, 00:00:09, Serial0/0/0
     192.168.1.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.1.0/24 is directly connected, GigabitEthernet0/0
L       192.168.1.1/32 is directly connected, GigabitEthernet0/0
R    192.168.3.0/24 [120/2] via 10.1.1.2, 00:00:09, Serial0/0/0
Router>
```



```
R2>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B -
BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS
inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 4 subnets, 2 masks
C       10.1.1.0/30 is directly connected, Serial0/0/0
L       10.1.1.2/32 is directly connected, Serial0/0/0
C       10.2.2.0/30 is directly connected, Serial0/0/1
L       10.2.2.2/32 is directly connected, Serial0/0/1
R    192.168.1.0/24 [120/1] via 10.1.1.1, 00:00:11, Serial0/0/0
R    192.168.3.0/24 [120/1] via 10.2.2.1, 00:00:29, Serial0/0/1
R2>
```



```
R3>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B -
BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS
inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
R       10.1.1.0/30 [120/1] via 10.2.2.2, 00:00:02, Serial0/0/0
C       10.2.2.0/30 is directly connected, Serial0/0/0
L       10.2.2.1/32 is directly connected, Serial0/0/0
R    192.168.1.0/24 [120/2] via 10.2.2.2, 00:00:02, Serial0/0/0
     192.168.3.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.3.0/24 is directly connected, GigabitEthernet0/0
L       192.168.3.1/32 is directly connected, GigabitEthernet0/0
R3>
```

- Configure SSH on R2



```
R2>en
R2#config t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#ip domain-name securityincomputing.com
R2(config)#username admin secret pwd
R2(config)#line vty 0 4
R2(config-line)#login local
R2(config-line)#transport input ssh
R2(config-line)#crypto key zeroize rsa
% No Signature RSA Keys found in configuration.

R2(config)#crypto key generate rsa
The name for the keys will be: R2.securityincomputing.com
Choose the size of the key modulus in the range of 360 to 2048 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.

How many bits in the modulus [512]: 1024
% Generating 1024 bit RSA keys, keys will be non-exportable...[OK]

R2(config)#ip ssh time-out 90
*Mar 1 0:25:59.0:  %SSH-5-ENABLED: SSH 1.99 has been enabled
R2(config)#ip ssh authentication-retries 2
R2(config)#ip ssh version 2
R2(config)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console

R2#exit
```

- Verify basic network connectivity before ACL configuration



```
Packet Tracer SERVER Command Line 1.0
SERVER>ping 192.168.3.1

Pinging 192.168.3.1 with 32 bytes of data:

Reply from 192.168.3.1: bytes=32 time=2ms TTL=253
Reply from 192.168.3.1: bytes=32 time=2ms TTL=253
Reply from 192.168.3.1: bytes=32 time=2ms TTL=253
Reply from 192.168.3.1: bytes=32 time=2ms TTL=253

Ping statistics for 192.168.3.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 2ms, Average = 2ms

SERVER>ping 192.168.3.3

Pinging 192.168.3.3 with 32 bytes of data:

Request timed out.
Reply from 192.168.3.3: bytes=32 time=7ms TTL=125
Reply from 192.168.3.3: bytes=32 time=10ms TTL=125
Reply from 192.168.3.3: bytes=32 time=2ms TTL=125

Ping statistics for 192.168.3.3:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 10ms, Average = 6ms

SERVER>
```



```
Packet Tracer PC Command Line 1.0
PC>ping 192.168.1.3

Pinging 192.168.1.3 with 32 bytes of data:

Reply from 192.168.1.3: bytes=32 time=11ms TTL=125
Reply from 192.168.1.3: bytes=32 time=2ms TTL=125
Reply from 192.168.1.3: bytes=32 time=4ms TTL=125
Reply from 192.168.1.3: bytes=32 time=9ms TTL=125

Ping statistics for 192.168.1.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 11ms, Average = 6ms

PC>ssh -l admin 10.2.2.2
Open
Password:



R2>
```



URL http://192.168.1.3

Cisco Packet Tracer

Welcome to Cisco Packet Tracer. Opening doors to new opportunities. Mind Wide Open.

Quick Links:
A small page
Copyrights
Image page
Image

- Enable the security technology package on R



```
R3>show version
Technology Package License Information for Module:'c1900'

----------------------------------------------------------------
Technology    Technology-package           Technology-package
              Current       Type           Next reboot
-----------------------------------------------------------------
ipbase        ipbasek9      Permanent      ipbasek9
security      None          None           None
data          None          None           None

Configuration register is 0x2102
```



```
R3>en
R3#config t
Enter configuration commands, one per line.  End with CNTL/Z.
R3(config)#license boot module c1900 technology-package securityk9
ACCEPT? [yes/no]: yes
% use 'write' command to make license boot config take effect on next
boot
%IOS_LICENSE_IMAGE_APPLICATION-6-LICENSE_LEVEL: Module name = C1900 Next
reboot level = securityk9 and License = securityk9

R3(config)#exit
R3#
%SYS-5-CONFIG_I: Configured from console by console
R3#reload
```



```
Router>show version
 Technology Package License Information for Module:'c1900'

 ----------------------------------------------------------------
 Technology    Technology-package           Technology-package
               Current       Type           Next reboot
 -----------------------------------------------------------------
 ipbase        ipbasek9      Permanent      ipbasek9
 security      securityk9    Evaluation     securityk9
 data          None          None           None

 Configuration register is 0x2102
```

- Create the Firewall Zones , Class Maps and ACLs on R3:



```
Router>en
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#zone security IN-ZONE
Router(config-sec-zone)#exit
Router(config)#zone security OUT-ZONE
Router(config-sec-zone)#exit
Router(config)#access-list 101 permit ip 192.168.3.0 0.0.0.255 any
Router(config)#class-map type inspect match-all IN-NET-CLASS-MAP
Router(config-cmap)#match access-group 101
Router(config-cmap)#exit
Router(config)#policy-map type inspect IN-2-OUT-PMAP
Router(config-pmap)#class type inspect IN-NET-CLASS-MAP
Router(config-pmap-c)#inspect
%No specific protocol configured in class IN-NET-CLASS-MAP for
inspection. All protocols will be inspected
Router(config-pmap-c)#exit
Router(config-pmap)#exit
Router(config)#zone-pair security IN-2-OUT-ZPAIR source IN-ZONE
destination OUT-ZONE
Router(config-sec-zone-pair)#service-policy type inspect IN-2-OUT-PMAP
Router(config-sec-zone-pair)#exit
Router(config)#interface GigabitEthernet0/0
Router(config-if)#zone-member security IN-ZONE
Router(config-if)#exit
Router(config)#interface Serial0/0/0
Router(config-if)#zone-member security OUT-ZONE
Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#copy running-config startup-config
Destination filename [startup-config]?
Building configuration...
[OK]
Router#exit
```

- Test Firewall Functionality from IN-ZONE to OUT-ZONE :



```
Packet Tracer PC Command Line 1.0
PC>ping 192.168.1.3

Pinging 192.168.1.3 with 32 bytes of data:

Reply from 192.168.1.3: bytes=32 time=11ms TTL=125
Reply from 192.168.1.3: bytes=32 time=2ms TTL=125
Reply from 192.168.1.3: bytes=32 time=4ms TTL=125
Reply from 192.168.1.3: bytes=32 time=9ms TTL=125

Ping statistics for 192.168.1.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 11ms, Average = 6ms

PC>ssh -l admin 10.2.2.2
Open
Password:



R2>
```



```
Router>en
Router#show policy-map type inspect zone-pair sessions

policy exists on zp IN-2-OUT-ZPAIR
 Zone-pair: IN-2-OUT-ZPAIR

  Service-policy inspect : IN-2-OUT-PMAP

    Class-map: IN-NET-CLASS-MAP (match-all)
      Match: access-group 101
      Inspect

    Class-map: class-default (match-any)
      Match: any
      Drop (default action)
        0 packets, 0 bytes
Router#
```



Cisco Packet Tracer

Welcome to Cisco Packet Tracer. Opening doors to new opportunities. Mind Wide Open.

Quick Links:
A small page
Copyrights
Image page
Image



```
Router>en
Router#show policy-map type inspect zone-pair sessions

policy exists on zp IN-2-OUT-ZPAIR
 Zone-pair: IN-2-OUT-ZPAIR

  Service-policy inspect : IN-2-OUT-PMAP

    Class-map: IN-NET-CLASS-MAP (match-all)
      Match: access-group 101
      Inspect

    Class-map: class-default (match-any)
      Match: any
      Drop (default action)
        0 packets, 0 bytes
Router#
```

- Test Firewall Functionality from OUT-ZONE to IN-ZONE



```
SERVER>ping 192.168.3.3

Pinging 192.168.3.3 with 32 bytes of data:

Reply from 192.168.1.1: Destination host unreachable.
Request timed out.
Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.

Ping statistics for 192.168.3.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```



```
R2>ping 192.168.3.3

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.3.3, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

R2>
```