



KLE Technological
University
Creating Value
Leveraging Knowledge

School
of
Electronics and Communication Engineering

Internship Project Report
on
Driver Assistance System Controller
(DASy)

By:

Prajwal T P

USN: 01FE20BEC218

Semester: VIII, 2023-2024

Under the Guidance of:

Dr. Prabha C Nissimagoudar

KLE Technological University

Kiran Kamble

Bosch Global Software Technologies


K.L.E SOCIETY'S
KLE Technological University,
HUBBALLI-580031
2022-2023





SCHOOL OF ELECTRONICS AND COMMUNICATION
ENGINEERING

CERTIFICATE

This is to Certify that "Prajwal T P" (01FE20BEC218) studying in final year has undergone Industrial Internship in Bosch Global Software Technologies at Bengaluru from 2 February 2024 to 31 May 2024 in partial fulfillment for the award for Bachelor of Engineering in Electronics and Communication in the School of Electronics and Communication Engineering of KLE Technological University, Hubballi for the academic year 2023-2024.


Dr. Prabha C Nissimgoudar
Guide


Dr. Suneeta v. Budihal
Head of School


Dr. Basavaraj S. A.
Registrar

External Viva:

Name of Examiners

- 1.
- 2.

Signature with date

Madhura H
Assistant Manager
Human Resource

LETTER OF REFERENCE

Bosch Global Software
Technologies Private Limited
(CIN:
U72400KA1997PTC023164)
123, Industrial Layout,
Hosur Road, Koramangala
Bengaluru 560095 INDIA
Tel +91 80 6657-5757
Fax +91 80 6657-1404
www.boschsoftwaretechnologies.com

Internship Completion Certificate

Date: 15-05-2024

This is to certify that **Prajwal T P (E.No : 35587711)** from **KLE Technological University - Hubballi** has carried out an internship on “**DASy – IDC5**” from **02-02-2024** to **31-05-2024** under the guidance of **Kiran Kamble (MS/ESY-XC)**.

We appreciate your valuable contribution and wish you success in your future endeavours.

Bosch Global Software Technologies Private Limited.

Digitally signed
by pki, BOSCH,
APAC, M, A,
Madhura.H
Date:
2024.05.16
16:40:47 +05'30'
Madhura H
Assistant Manager
Human Resource

ACKNOWLEDGMENT

I would like to take this opportunity to acknowledge the contributions of several people whose invaluable help facilitated the completion of this project. I extend my earnest gratitude to university guide **Prof. Prabha C Nissingoudar**, Department of Electronics and Communication Engineering, for their unending guidance, encouragement and timely inputs throughout the duration of the internship. I thank **Dr.Suneeta V Budihal**, Head of School of Electronics and Communication Engineering for her invaluable suggestions and expert advice. I am extremely indebted by the invaluable support given by **Kiran Kamble**, Project Manager, BGSW for his constant support and motivation. I will always be thankful to my Team Manager and my Mentors **Anil Sanjappa** ,**Ganesh B** and **Anusha Reddy** for their huge support during the journey and even my colleagues for their support in completing the internship work.

- By Prajwal T P

ABSTRACT

The advent of automated driving heralds a transformative era in the automotive industry, promising unprecedented levels of safety, efficiency, and convenience on the road. However, as the complexity of automated driving functions continues to escalate, the limitations of current Electronic Control Units (ECUs) become increasingly apparent. Recognizing this pressing need for innovation, Bosch has pioneered the development of the Driver Assistance System Domain Controller, known as DASy. DASy represents a paradigm shift in the realm of vehicle computing, offering a sophisticated solution to the burgeoning demands of automated driving. Unlike conventional ECUs, which may struggle to cope with the intricate algorithms and data processing requirements of advanced driving functions, DASy is purpose-built to excel in this domain. By leveraging cutting-edge hardware and software technologies, DASy empowers vehicles to navigate complex traffic scenarios with unparalleled precision and reliability. At the heart of DASy lies Bosch's unwavering commitment to pushing the boundaries of automotive innovation. Drawing upon decades of expertise in automotive electronics and systems integration, Bosch has engineered DASy to serve as the cornerstone of next-generation automated driving platforms. Whether it's real-time sensor fusion, predictive analytics, or adaptive decision-making, DASy seamlessly orchestrates a myriad of functions to ensure a seamless and safe driving experience. Moreover, DASy embodies a modular and scalable architecture, enabling automakers to adapt and evolve their automated driving systems with ease. As the automotive landscape continues to evolve, DASy stands poised to meet the evolving needs of both manufacturers and consumers, ushering in a new era of mobility that is defined by intelligence, efficiency, and safety.

In conclusion, DASy represents a pivotal advancement in the quest for fully automated driving. By addressing the shortcomings of traditional ECUs and delivering a robust, future-proof computing platform, Bosch has set a new standard for vehicle computers. With DASy at the helm, the vision of a safer, smarter, and more sustainable future on the road is closer than ever before.

About the department : EVC-RB-XC

The Bosch XC Division is a specialized unit within Bosch that focuses on developing Electronic Control Units (ECUs) for safety-critical applications in the automotive industry. These ECUs play a crucial role in managing and controlling various functions within vehicles, such as engine control, transmission, and anti-lock braking systems. The XC Division's expertise lies in creating ECUs for advanced driver assistance systems (ADAS) and autonomous driving. Their rigorous testing and validation processes ensure safety, reliability, and real-time performance.

Our department primarily works on Mercedes-Benz related ADAS and DASy projects. Under RB, there are teams for testing and integration. Mohammed Shiraj Jaffer is the head of our department. Under him are a total of four managers. Sanjeeb Kumar Das is the manager of our RB4 section. My primary focus was on DASy programming.

Contents

1	Introduction	2
1.1	Motivation	2
1.2	Objectives	4
1.3	Literature survey	4
1.3.1	Leohold, J., et al. (2020). Future Automotive Computing Platforms: Opportunities and Challenges. IEEE Micro, 40(2), 18-27. . .	4
1.3.2	Bosch. (2020). Driver Assistance Systems.	5
1.3.3	Litman, T. (2020). Autonomous vehicle implementation predictions: Implications for transport planning. Victoria Transport Policy Institute.	5
1.3.4	AUTOSAR Software Architecture	6
1.4	Need Statement	6
1.5	Problem statement	6
1.6	Organization of the report	7
2	ECU Programming	8
2.1	Functional block diagram	8
2.2	Final design	9
2.2.1	DLB (Data Log Book Test)	9
2.2.2	MTA (measurement technique adapter)	10
2.2.3	RFT (Robustness Flash Loop Test)	10
2.2.4	Software Tools Used	12
3	Implementation details	16
3.1	Specifications and final system architecture	16
3.2	Flowchart	18
4	Results and Analysis	19
4.1	Conclusion	20
4.2	Future Scope	20
4.2.1	Application in the societal context	20
	Appendix	22

Chapter 1

Introduction

The intriguing prospect of automated driving, which presents a picture of safer, more effective transportation, beckons in the constantly developing field of automobile technology. But as this future approaches, a significant obstacle appears: the current generation of Electronic Control Units (ECUs) can become unstable due to the growing complexity of driving operations. Bosch, a trailblazing force in automotive engineering, recognizes the need for innovation and responds with a game-changing solution: the Driver Assistance System Domain Controller, or DASy. create a picture of the path ahead and determine the best driving tactics in real time.

Once in DASy's possession, this preprocessed data serves as the foundation for a high-precision 360-degree representation of the environment surrounding the vehicle. By means of methodical processing and analysis, DASy integrates an all-encompassing perspective of the surroundings, endowing the vehicle with unmatched situational awareness. Using this model as a canvas, DASy's integrated functions create a picture of the path ahead and determine the best driving tactics in real time.

Along with having a large bandwidth capacity, DASy also has a powerful processor, driven by a microcontroller that is at the forefront of technical advancement. DASy's processing power surpasses 3000 DMIPS, allowing it to effortlessly handle the intricacies of everyday driving situations. It does this by coordinating a sophisticated network of algorithms to create a comprehensive picture of the road ahead.

DASy is a shining example of technology progress toward fully autonomous driving. DASy is designed specifically for this role, in contrast to its predecessors, which can find it difficult to handle the intricate algorithms and data streams included in advanced driving systems. DASy uses cutting-edge hardware and software to manage the complexities of contemporary traffic conditions with unmatched efficiency and precision.

1.1 Motivation

Transportation will be revolutionized by automated driving, which will make it safer and more effective. On the other hand, the increasing complexity of modern driving operations is a substantial challenge for existing Electronic Control Units (ECUs). Bosch responds to this with a novel technology known as the DASy, or Driver Assistance System Domain Controller. By digesting and merging sensor data into a high-precision 360-degree image of the vehicle's surroundings, DASy overcomes the drawbacks of conventional ECUs. Optimal driving techniques are made possible by this real-time situational awareness, which improves efficiency and safety. Bosch's DASy is a crucial advancement in automotive

technology, addressing the need for more capable and stable vehicle control systems. It enhances vehicle situational awareness and decision-making capabilities, bringing us closer to the future of fully autonomous driving. This report highlights the importance of DASy in this transformative journey.

1.2 Objectives

The primary goals of the project are laid forth in this section. These goals will be kept in mind during the whole endeavor. Therefore, the goals are as follows:

1. Understanding the Customer Requirements
2. Understanding different testing methods used in this project
3. Understanding the usage of CANoe tool
4. Execution of test cases using CANoe tool
5. Analysis of the test report

1.3 Literature survey

1.3.1 Leohold, J., et al. (2020). Future Automotive Computing Platforms: Opportunities and Challenges. IEEE Micro, 40(2), 18-27.

This paper explores the emerging opportunities and challenges associated with future automotive computing platforms. It emphasizes the rapid evolution of vehicle electronics and the increasing complexity of automated driving systems. The authors discuss the limitations of current Electronic Control Units (ECUs) and the need for more advanced computing solutions to manage the high demands of modern vehicles.

- Key points include:
 - Technological Advancements: The paper details advancements in hardware and software technologies that are essential for the development of next-generation automotive computing platforms. This includes improvements in processing power, data handling capabilities, and real-time decision-making.
 - Architectural Innovations: The authors highlight the importance of modular and scalable architectures, which enable flexibility and adaptability in automotive systems. Such architectures are crucial for accommodating future updates and integrating new functionalities.
 - Challenges: The paper identifies several challenges, such as ensuring system reliability, managing the vast amounts of data generated by sensors, and addressing security and privacy concerns.
 - Opportunities: It also outlines the potential benefits of advanced computing platforms, including enhanced vehicle safety, improved performance, and the ability to support fully autonomous driving.

Overall, the paper provides a comprehensive overview of the current state and future prospects of automotive computing platforms, emphasizing the need for continuous innovation to meet the evolving demands of the automotive industry.

1.3.2 Bosch. (2020). Driver Assistance Systems.

This paper from Bosch discusses the company's advancements in driver assistance systems, particularly focusing on the development of the Driver Assistance System Domain Controller (DASy). It highlights the need for more advanced and reliable computing solutions as automated driving functions become increasingly complex. The DASy is presented as a sophisticated solution designed to handle the high demands of automated driving with greater efficiency and reliability than traditional Electronic Control Units (ECUs). The paper outlines DASy's capabilities, including real-time data processing, sensor fusion, and adaptive decision-making, and emphasizes its modular and scalable architecture, which allows for easy adaptation and evolution. Overall, the paper underscores Bosch's commitment to innovation in automotive technology and its role in advancing the future of automated driving systems.

1.3.3 Litman, T. (2020). Autonomous vehicle implementation predictions: Implications for transport planning. Victoria Transport Policy Institute.

This paper by Todd Litman examines the potential impacts of autonomous vehicle (AV) implementation on transport planning. It provides a comprehensive analysis of how AV technologies might transform transportation systems, influence urban planning, and affect societal trends.

- Key points include:
 - Adoption Timeline: Litman discusses the predicted timeline for AV adoption, suggesting that while significant progress is being made, widespread use of fully autonomous vehicles may take longer than some optimistic projections suggest. He emphasizes a gradual implementation with mixed traffic conditions where both autonomous and human-driven vehicles coexist.
 - Potential Benefits: The paper outlines several potential benefits of AVs, including improved road safety, reduced traffic congestion, enhanced mobility for non-drivers, and more efficient land use. AVs could also contribute to environmental benefits through optimized driving patterns and reduced emissions.
 - Challenges and Risks: Litman also addresses various challenges and risks associated with AV implementation. These include technical and regulatory hurdles, cybersecurity threats, privacy concerns, and potential negative impacts on employment in driving-related occupations.
 - Implications for Transport Planning: The author highlights the need for adaptive transport planning strategies to accommodate the gradual integration of AVs. This includes updating infrastructure, revising regulations, and considering new urban designs that facilitate AV operations. Transport planners are encouraged to take a proactive approach to maximize the benefits and mitigate the risks associated with AVs.

Overall, the paper emphasizes that while AVs hold significant promise, their successful implementation requires careful planning and consideration of a wide range of factors to ensure that the transition leads to a sustainable and equitable transportation system.

1.3.4 AUTOSAR Software Architecture

In this paper [2], explains an architecture in which the data moves from one defined level of processing to another. The layered Architecture was developed to create a common standardized software architecture for designing automotive electronic control units (ECUs). The AUTOSAR architecture is based on a 3-layered architecture model, developed jointly by the stakeholders of the automotive industry including – the automobile manufacturers, the suppliers, and the tool developers. The layered architecture is in top-down approach and maps software modules of layers along with showing their relationship with each other. The three layers run on microcontroller.

The three main layers are as follows:

1. Application Layer
2. Runtime Environment (RTE) Layer
3. Basic Software (BSW) Layer

With the AUTOSAR software architecture the software part of an AUTOSAR application can be developed as independent as possible from the hardware parts. The software architecture enables this with two main abstraction layers, namely the Runtime Environment layer and the Basic Software layer . The Basic Software layer additionally provides services that can be used by each AUTOSAR application. Through that, frequently used functionality is also encapsulated and provided by the AUTOSAR software architecture. On the Application layer the AUTOSAR Software Components are using Ports that encapsulate interfaces to guarantee type safety during the communication between these components. The communication itself is handled by the Virtual Function Bus (VFB). The VFB as specification is represented during runtime by the Runtime Environment, which is generated uniquely for each ECU in the AUTOSAR system. This concept also supports the creation of nearly hardware independent software in the automotive industry and therefor reduces the complexity of the resulting systems.

1.4 Need Statement

The current generation of Electronic Control Units (ECUs) in vehicles faces instability due to the increasing complexity of driving operations. To overcome this obstacle and enable safer, more effective transportation, there is a need for an innovative solution that integrates data from various sensors, processes it efficiently, and provides real-time decision-making capabilities. The Driver Assistance System Domain Controller (DASy) fulfills this need by creating a comprehensive 360-degree environment representation and determining optimal driving tactics.

1.5 Problem statement

The current generation of Electronic Control Units (ECUs) faces instability due to the growing complexity of driving operations. As the automotive industry moves toward fully autonomous driving, there is a critical need for an innovative solution that can seamlessly integrate data from various sensors, process it efficiently, and provide real-time decision-making capabilities. The Driver Assistance System Domain Controller (DASy) aims to

address this need by creating a comprehensive 360-degree environment representation and determining optimal driving tactics.

1.6 Organization of the report

The subjects of each chapter are summarised below. Chapter 1 contains the introduction to the report as well as the initial steps required to understand the title and problem description. Additionally, a literature review that provides a brief explanation of each algorithm is included. The design details of the issue statement are described in Chapter 2. A functional block diagram and design theory are also presented. In Chapter 3, the problem statement's implementation is discussed. The information provided includes the description of the components used and the algorithm used to implement the different features. Chapter 4 describes the results of the project. Chapter 5 contains the project's conclusion part.

Chapter 2

ECU Programming

This section describes the complete ECU Programming cluster and modules used in the testing of DASy-ECU.

2.1 Functional block diagram

The functions and connections between various elements within a given system can be described using a functional block diagram, one of the several forms of block diagrams already in use. Such a functional block diagram can show how one system works by utilizing blocks to represent the various parts of the system. Figure 2.1 below displays such a block diagram.




Figure 2.1: Test Process execution of Data Log Book Test

First, we gather specific requirements from the customer related to the system or software being tested. Next, we create test cases using CAPL, a language that allows custom scripting for simulating communication on the CAN bus. These scripted test cases are then executed within CANoe, a comprehensive automotive testing tool. Finally, after test execution, we generate a detailed report summarizing the results, including both passed and failed test cases. This systematic approach ensures thorough testing and accurate reporting.

2.2 Final design

The programming cluster is doing numerous tests, the three most crucial modules of which are as follows:

1. DLB (Data Log Book Test)
2. MTA (Measurement Technique Adapter)
3. RFT (Robustness Flash loop test)

2.2.1 DLB (Data Log Book Test)

In the context of Data Log Book (DLB) testing for autonomous vehicles, we meticulously examine data stored in the NOR flash memory. This critical information includes time coordinates, trigger details, and signatures, totaling 128 bytes(64 Bytes of Data and 64 Bytes of Signature). By analyzing this data, we can pinpoint whether accidents were caused by sensor hardware issues or application software glitches. Our thorough investigation contributes to enhancing safety and refining autonomous vehicle systems.

Test Bench Interconnections:




Figure 2.2: Test Process execution of Data Log Book Test

In our test setup, we utilize the DASY ECU as the central component. DASY integrates Advanced Driver Assistance Systems (ADAS) and collects data from various sensors. The Vector VN 5640 acts as an interface between the ECU and the testbench, facilitating communication via both CAN and Ethernet networks. Additionally, we employ the Technica Tool for direct ECU flashing. This tool connects directly to the ECU and interfaces with the test bench via an Ethernet-to-USB converter .

2.2.2 MTA (measurement technique adapter)

In modern vehicles, a network of Electronic Control Units (ECUs) collaborates to manage various functions. At the heart of this system lies the “Functional ECU” (F-DASy), which processes inputs from subsidiary nodes—such as the dashboard, Adaptive Cruise Control, and seatbelt ECUs. These nodes transmit critical data to the F-DASy, ensuring seamless communication and coordination. To assess the F-DASy’s workload, we monitor metrics like packet reception. Additionally, the “Measurement ECU” (M-DASy) plays a pivotal role by transmitting signals to the F-DASy. This intricate interplay ensures optimal performance and minimizes data loss, safeguarding the vehicle’s functionality and safety.

Test bench Interconnections:




Figure 2.3: Block Diagram for MTA interconnections

In the testing process, the Functional ECU (F-DASy) and Measurement ECU (M-DASy) play pivotal roles. These ECUs are connected using a sandwich board, which acts as an interface placed between them. The sandwich board contains interconnections facilitating communication between the two ECUs. Additionally, a VN5640 box serves as an interface for Ethernet and CAN communication. This intricate setup ensures seamless data exchange and coordination, contributing to the optimal performance and safety of the vehicle.

2.2.3 RFT (Robustness Flash Loop Test)

ECU Programming:

ECU programming involves the process of programming or reprogramming an Engine Control Unit (ECU) in a vehicle. The primary goal is to ensure that the software (SW) is compatible with the specific ECU and vice versa. Customer perspective testing is performed to meet the customer’s requirements, and series ECUs are commonly used for testing. Ensuring hardware compatibility and performing SW flashing are essential aspects of ECU programming.

Types of Tests :

1. Full Test Execution:

- Requirement-Based (RQM Guidelines): These tests determine whether the ECU is programmable under all instances, following the guidelines set by the Requirements Management (RQM) process.
- Extended Flashing Tests (EFT): Although part of the RQM test plan, these tests are performed due to customer campaigns. They involve using the Monaco Flashing Tool.
- Robustness Flashing Tests (RFT): Also part of the RQM test plan, these continuous flashing tests are conducted based on customer campaigns using the Monaco Flashing Tool.

2. Regression Tests: These tests execute only those test cases (TCs) that are in a “TRUE” state for the regression category within the RQM test lists.

Test bench Interconnections:




Figure 2.4: Block Diagram for MTA interconnections

2.2.4 Software Tools Used

Software system design comprises of softwares being used to generate the report in order to analyse the response from the ECU and also if there are any issues or the failed test cases we can rectify them by getting into the previous stages. Further the softwares like the DASy Flash is used to flash the .hex file.

CANoe:

CANoe (Controller Area Network Open Environment) is a comprehensive software tool developed by Vector Informatik, widely used in the automotive industry for developing, testing, and analyzing entire automotive networks and ECUs (Electronic Control Units). It allows engineers to simulate complete vehicle networks, facilitating the testing and validation of communication between different ECUs without requiring physical hardware, thereby accelerating development processes and reducing costs. CANoe supports diagnostic protocols and performs extensive network testing to ensure all components function correctly and communicate as intended. Initially focused on CAN networks, CANoe now supports multiple bus systems such as LIN, FlexRay, MOST, and Ethernet, making it versatile for modern automotive networking needs. It integrates with various hardware modules, enabling real-time testing and data logging from actual vehicle systems, which is crucial for validating ECU performance under real-world conditions. CANoe also features powerful visualization tools for analyzing network traffic and data, aiding engineers in interpreting complex data and identifying issues quickly. Additionally, it supports automated test sequences, enhancing testing efficiency and consistency, particularly for regression testing during the development cycle. Overall, CANoe is an essential tool for automotive engineers, offering comprehensive functionalities for the design, development, testing, and validation of vehicle network systems, making it a cornerstone in modern automotive technology development.




Figure 2.5: CANoe Environment

- **Network Simulation and Testing:** CANoe can simulate entire vehicle networks, allowing engineers to test and validate the communication between different ECUs without needing physical hardware. This capability accelerates development processes and reduces costs.
- **Diagnostic Testing:** CANoe supports diagnostic protocols and can perform extensive testing of vehicle networks, ensuring that all components are functioning correctly and communicating as intended.
- **Multibus Support:** While initially focused on CAN networks, CANoe has evolved to support multiple bus systems such as LIN, FlexRay, MOST, and Ethernet, providing a versatile platform for modern automotive networking needs.
- **Integration with Hardware:** CANoe can interface with various hardware modules, allowing real-time testing and data logging from actual vehicle systems. This integration is crucial for validating the performance of ECUs under real-world conditions.
- **Rich Visualization Tools:** CANoe offers powerful visualization tools to analyze network traffic and data. These tools help engineers to interpret complex data easily and identify issues quickly.
- **Automated Testing:** The tool supports automated test sequences, which enhance testing efficiency and consistency. This automation is particularly beneficial for regression testing during the development cycle.

Overall, CANoe is an essential tool for automotive engineers, providing comprehensive functionalities for the design, development, testing, and validation of vehicle network systems. Its extensive feature set and versatility make it a cornerstone in the development of modern automotive technologies.

CAPL (Communication Access Programming Language)

CAPL (Communication Access Programming Language) is a specialized scripting language developed by Vector Informatik, primarily used within their CANoe and CANalyzer software tools. This language is tailored specifically for automotive applications, offering a robust means to simulate, test, and diagnose automotive network communications, making it a critical tool for engineers in the automotive industry.

The event-driven programming model of CAPL is one of its fundamental characteristics. In contrast to conventional programming languages, which operate according to a sequential execution model, CAPL is made to manage a variety of events that can happen in an automotive network. Timer events, user-defined events, and message transmission and reception across the network are examples of these events. Because CAPL is event-driven, it is ideal for real-time automotive network testing and simulations. This enables engineers to precisely reproduce and examine how vehicle networks behave in various scenarios.

The CANoe and CANalyzer environments are enhanced by the smooth integration of CAPL scripts. With the help of these tools, users may precisely replicate network

behavior and automate intricate testing methods using CAPL. The process of creating and running test cases is streamlined by this integration, which facilitates the identification and correction of problems in automotive networks during the development stage.




Figure 2.6: CAPL Script

Many engineers are familiar with the C programming language, which is similar to the syntax of CAPL. Because of this commonality, those who are already familiar with C can write CAPL scripts more quickly because there is less of a learning curve. Moreover, the construction of test cases and simulations centered on automotive networks is made easier by CAPL's unique commands and capabilities that are designed for automotive applications.

Additionally, CAPL offers large libraries that support intricate and thorough testing scenarios. These libraries include network message, signal, and diagnostic handling functionalities, allowing engineers to write scripts that can communicate with different parts of the car network. For comprehensive testing and validation of the network's dependability and performance, this capability is essential.

In addition to its powerful scripting capabilities, CAPL includes robust debugging and analysis tools. These tools assist engineers in identifying and resolving issues within the scripts, ensuring that the tests are accurate and efficient. The debugging tools allow for step-by-step execution of CAPL scripts, making it easier to pinpoint the exact location and cause of any problems.

Apart from its strong scripting ability, CAPL has comprehensive debugging and analysis tools. By helping engineers find and fix problems with the scripts, these tools guarantee that the tests are precise and effective. The debugging tools facilitate the step-by-step execution of CAPL scripts, hence facilitating the identification of the precise location and root cause of any issues.

All things considered, CAPL is a vital tool for automotive engineers, providing a strong and adaptable scripting language that augments the capacities of CANoe and CANalyzer in terms of modeling, analyzing, and troubleshooting car network systems. Modern automotive technologies rely on it heavily for development and testing because to its event-driven approach, debugging facilities, huge libraries, ease of use, and interaction with Vector's tools.

Chapter 3

Implementation details

3.1 Specifications and final system architecture

In this section we shall discuss the methodology, the concepts used, the algorithm developed and the various other aspects of the proposed system design.

1. **Understanding the Customer Requirements:** The first step in any automotive project is to thoroughly understand the customer requirements. This involves gathering detailed specifications from the customer regarding the functionality, performance, and reliability expected from the vehicle's network systems. Understanding these requirements is crucial for defining the scope of the project, developing relevant test cases, and ensuring that the final product meets the customer's expectations. Effective communication with the customer and stakeholders is essential to capture all necessary details and clarify any ambiguities.
2. **Understanding Different Testing Modules Used in This Project:** Once the customer requirements are understood, the next step is to familiarize oneself with the different testing methods that will be employed in the project. These methods ensure that the vehicle network systems are comprehensively tested to meet all specified requirements. Key testing methods include,
 - **DLB** Through data analysis, we can identify whether accidents resulted from sensor hardware problems or application software errors. Our comprehensive investigation helps improve safety and enhance autonomous vehicle systems.
 - **The MTA (Module Test Adapter)** test assesses how well the F-DASy ECU (Functional ECU) withstands stress caused by other ECUs. It helps ensure optimal performance, minimize data loss and safety.
 - As part of the RQM test plan, continuous flashing tests are conducted based on customer campaigns. These tests help ensure system reliability and performance.
3. **Understanding the Usage of CANoe Tool :** CANoe (Controller Area Network Open Environment) is a versatile tool used for the development, testing, and analysis of automotive networks and ECUs. To effectively use CANoe, it is important to understand its key features and functionalities:
 - **Simulation:** CANoe can simulate entire vehicle networks, allowing for testing without physical hardware.

- Network Analysis: CANoe provides detailed analysis of network traffic, helping engineers to identify and diagnose issues.
 - Diagnostic Testing: The tool supports various diagnostic protocols and can perform comprehensive testing to ensure the health of the network.
 - Visualization Tools: The tool includes powerful visualization features that help in understanding complex data and network behavior.
4. Execution of Test Cases Using CANoe Tool: With a solid understanding of CANoe, the next step is to execute the test cases. This involves:
- Setting Up the Environment: Configuring CANoe to match the vehicle network specifications and the specific requirements of the test cases.
 - Writing and Running Scripts: Using CAPL (Communication Access Programming Language) to write scripts that automate the execution of test cases, simulating network traffic, and triggering events as needed.
 - Monitoring the Execution: Observing the real-time behavior of the network during the test to identify any immediate issues or anomalies.
 - Logging Data: Recording the results and network activity for detailed analysis later.
5. Analysis of the Test Report : The final step in the testing process is to analyze the test report generated by CANoe. This analysis involves:
- Reviewing Test Results: Carefully examining the results to identify any failures or deviations from expected behavior.
 - Diagnosing Issues: Using CANoe's diagnostic tools to trace the root cause of any problems detected during testing.
 - Documenting Findings: Compiling a detailed report that includes the results of the tests, any issues identified, their potential causes, and suggested corrective actions.
 - Communicating with Stakeholders: Sharing the test report with the development team and other stakeholders to ensure that any identified issues are addressed and resolved.

3.2 Flowchart

The algorithm we described in the previous part has a clear flow of stages, which is shown in Figure 3.1 below.




Figure 3.1: Flow of Algorithm

Chapter 4

Results and Analysis

In this chapter, the in general overview of Results are attached. Original results can't be attached as per company guidelines due to confidentiality.

The automobile industry's vehicle electronic control units' (ECUs') diagnostic and programming capabilities have been greatly improved by the adoption of Unified Diagnostic Services (UDS). By ensuring constant communication between diagnostic equipment and ECUs, this standardized protocol—mandated by ISO 14229—simplifies the diagnostic process and boosts accuracy and efficiency. UDS offers comprehensive access to historical and real-time data, facilitating in-depth study and expedited resolution of intricate problems. Because of its versatility and strong security characteristics, it may be applied to a variety of vehicle systems, including body and chassis systems, engine control units, and others. Vehicle maintenance and ECU programming have been made easier by the adoption of UDS, which has enabled software updates and performance enhancements, keeping cars up to speed with emerging technologies. UDS facilitates end-of-line testing in manufacturing and validation, raising the caliber of the product. Furthermore, UDS facilitates remote diagnostics, which is advantageous for telematics and fleet management applications. Overall, UDS has increased customer satisfaction, vehicle performance, and dependability, proving its vital role in the continuous development of automotive programming and diagnostics.

Important components of the Unified Diagnostic Services (UDS) protocol that improve security, functionality, and efficiency in car diagnostics include local authentication, Extended sessions, and soft resets. By confirming credentials like passwords or digital certificates, local authentication makes sure that only authorized diagnostic tools and personnel may access and operate on electronic control units (ECUs), protecting important vehicle data and functionality. Extended sessions, which may require further authentication and require special requests to be sent to the ECU, enable diagnostic tools to access more features than those offered in the usual session, including ECU programming and thorough diagnostics. Usually, these sessions include a time limit to improve security. Conversely, soft resets entail resetting an ECU without disconnecting the vehicle's power source.

which, without affecting the vehicle's general operation, applies modifications made during a diagnostic session or resets the ECU to a known condition. This guarantees that new settings are correctly initialized while preserving the vehicle's operational continuity, and is particularly helpful following software upgrades or configuration changes. When combined, these characteristics give UDS a strong and safe foundation for controlling contemporary car systems.

4.1 Conclusion

Traditional ECUs, as noted in various studies, fall short in managing the complex data requirements of modern ADAS, leading to performance and stability issues. Bosch's DASy addresses these limitations through its advanced preprocessing capabilities and high-precision 360-degree environmental representation, providing vehicles with comprehensive situational awareness.

The significant processing power of DASy, capable of over 3000 DMIPS, allows it to handle the intricate algorithms necessary for autonomous driving efficiently. This capability positions DASy as a key enabler of fully autonomous vehicles, overcoming the constraints faced by older ECU architectures.

In conclusion, DASy represents a pivotal advancement in automotive technology, enhancing the safety, efficiency, and feasibility of autonomous driving. By integrating cutting-edge hardware and sophisticated software, DASy not only meets the current demands of ADAS but also paves the way for future innovations in fully autonomous driving systems. This underscores the importance of continued research and development in this field to achieve the ultimate goal of reliable and efficient automated transportation.

4.2 Future Scope

The future scope of Bosch's Driver Assistance System Domain Controller (DASy) in automated driving systems is expansive and promising. As technology progresses, DASy can integrate more advanced sensors, such as high-resolution cameras, lidar, and radar, enhancing the vehicle's environmental perception even in challenging conditions. Incorporating artificial intelligence and machine learning will further improve DASy's predictive and decision-making abilities. Vehicle-to-Everything (V2X) communication will enable interactions with other vehicles, infrastructure, and pedestrians, facilitating better traffic management and reducing accidents. In urban contexts, DASy can contribute to smart cities by integrating with intelligent transportation systems, optimizing traffic flow, and improving public transportation. Shared mobility services, such as autonomous ride-sharing, will benefit from DASy's capabilities, offering efficient alternatives to private car ownership. Environmentally, DASy can enhance the efficiency of electric and hybrid vehicles, supporting efforts to reduce carbon emissions. Economically, advancements in autonomous driving technologies will create new opportunities in manufacturing, software development, and data analytics, stimulating job creation and growth. Legal and ethical considerations, such as developing regulatory frameworks and increasing public trust, are essential for the safe deployment of autonomous vehicles. International standards and cross-industry collaborations will be crucial for global interoperability and innovation. As research and development continue, DASy will play a pivotal role in shaping the future of transportation, leading to safer, more efficient, and sustainable mobility solutions.

4.2.1 Application in the societal context

The advent of Bosch's Driver Assistance System Domain Controller (DASy) carries significant implications for society, extending far beyond the realm of technological advancement. The deployment of DASy in automated driving systems has the potential to pro-

foundly impact various aspects of daily life, from road safety and traffic efficiency to environmental sustainability and economic growth.

The societal implications of Bosch's DASy extend far beyond technological innovation, promising substantial benefits in road safety, traffic efficiency, environmental sustainability, economic growth, and social inclusion. By addressing the limitations of traditional ECUs and paving the way for fully autonomous driving, DASy not only revolutionizes automotive technology but also contributes to the advancement of society as a whole. As research and development in this field continue to progress, the full potential of DASy's impact on society will become increasingly evident, underscoring the importance of continued investment in automated driving technologies.

Bibliography

- [1] Bosch. (2020). Driver Assistance Systems. Retrieved from Bosch Media Service.
- [2] Robert Warschofsky. Autosar software architecture. Hasso-Plattner- Institute für Softwaresystemtechnik: Potsdam, Germany, pages 1–12, 2009.
- [3] Leohold, J., et al. (2020). Future Automotive Computing Platforms: Opportunities and Challenges. IEEE Micro, 40(2), 18-27.
- [4] Litman, T. (2020). Autonomous vehicle implementation predictions: Implications for transport planning. Victoria Transport Policy Institute.

ORIGINALITY REPORT

7%

SIMILARITY INDEX

7%

INTERNET SOURCES

1%

PUBLICATIONS

%

STUDENT PAPERS

PRIMARY SOURCES

1

docplayer.net

Internet Source

3%

2

www.coursehero.com

Internet Source

1%

3

www.slideshare.net

Internet Source

1%

4

www.embitel.com

Internet Source

1%

5

core.ac.uk

Internet Source

<1%

6

Sakshi Garg, Deepti Mehrotra, Hari Mohan Pandey, Sujata Pandey. "Accessible review of internet of vehicle models for intelligent transportation and research gaps for potential future directions", Peer-to-Peer Networking and Applications, 2021

Publication

<1%

7

drpress.org

Internet Source

<1%

8

www.grin.com

Internet Source

<1 %

9

Haoran Wei, Xuanzhang Liu, Lena Mashayekhy, Keith Decker. "Mixed-Autonomy Traffic Control with Proximal Policy Optimization", 2019 IEEE Vehicular Networking Conference (VNC), 2019

Publication

<1 %

10

Handbook of Driver Assistance Systems, 2016.

Publication

<1 %

11

Md. Motaharul Islam, Ibna Kowsar, Mashfiq Shahriar Zaman, Md. Fahmidur Rahman Sakib, Nazmus Saquib, Syed Md. Shamsul Alam. "A Novel Approach to Enhance Safety on Drowsy Driving in Self-Driving Car", Mobile Networks and Applications, 2022

Publication

<1 %

12

vocal.media

Internet Source

<1 %

13

www.designnews.com

Internet Source

<1 %

14

research.library.mun.ca

Internet Source

<1 %

Exclude quotes On

Exclude bibliography On

Exclude matches < 5 words