

Demonstration of Publication-Grade Three-Line Table in Word

2. Physical and Mechanical Properties of Specimens

The geotechnical and mechanical parameters obtained from comprehensive triaxial and resonant column tests are summarized in **Table 1**. All specimens were consolidated under isotropic conditions prior to shearing, and the critical friction angles were calculated according to the Mohr-Coulomb criterion.

Table 1. Calibrated constitutive parameters and peak mechanical properties of engineered soil-rock mixtures.

Specimen ID	Rock Content (%)	Water Content (%)	Dry Density (g/cm ³)	Cohesion c (kPa)	Friction Angle ϕ (°)	Elastic Modulus E (MPa)
SRM-00	0.0	12.4 ± 0.3	1.78	28.5 ± 1.2	24.2 ± 0.5	45.8 ± 2.1
SRM-20	20.0	11.8 ± 0.2	1.85	34.2 ± 1.5	28.7 ± 0.6	68.4 ± 3.4
SRM-40	40.0	10.5 ± 0.4	1.96	42.8 ± 1.8	33.5 ± 0.8	112.6 ± 5.2
SRM-60	60.0	9.2 ± 0.3	2.08	51.6 ± 2.1	38.9 ± 1.1	185.3 ± 7.8
SRM-80	80.0	8.1 ± 0.2	2.19	46.3 ± 2.4	43.2 ± 1.3	264.0 ± 9.5

Note: Values represent mean ± standard deviation from five repeated triaxial shearing runs under consolidated drained (CD) conditions; c and ϕ denote effective shear parameters.