

Marvin Abisrror Zarate

**On Selecting of
heuristics functions for Domain–Independent
planning.**

Brasil

2015, v-1.9.5

Marvin Abisrror Zarate

**On Selecting of
heuristics functions for Domain–Independent planning.**

Paper presented to the Federal University of Viçosa, as part of the requirements of Graduate program Computer Science, for obtaining the title of Magister Scientiae.

Universidade de Viçosa – UFV

Centro de Ciencias Exactas e Tecnologicas (CCE)

Programa de Pós-Graduação

Supervisor: Levi Henrique Santana de Lelis

Co-supervisor: Santiago Franco

Brasil

2015, v-1.9.5

Marvin Abisrror Zarate

On Selecting of
heuristics functions for Domain–Independent planning./ Marvin Abisrror Zarate. –
Brasil, 2015, v-1.9.5-

61 p. : il. (algumas color.) ; 30 cm.

Supervisor: Levi Henrique Santana de Lelis

Tese (Mestrado) – Universidade de Viçosa – UFV
Centro de Ciencias Exactas e Tecnologicas (CCE)
Programa de Pós-Graduação, 2015, v-1.9.5.

1. Palavra-chave1. 2. Palavra-chave2. 2. Palavra-chave3. I. Orientador. II. Univer-
sidade xxx. III. Faculdade de xxx. IV. Título

Errata sheet

Elemento opcional da [ABNT](#) (2011, 4.2.1.2). Exemplo:

FERRIGNO, C. R. A. **Tratamento de neoplasias ósseas apendiculares com reimplantação de enxerto ósseo autólogo autoclavado associado ao plasma rico em plaquetas**: estudo crítico na cirurgia de preservação de membro em cães. 2011. 128 f. Tese (Livre-Docência) - Faculdade de Medicina Veterinária e Zootecnia, Universidade de São Paulo, São Paulo, 2011.

Folha	Linha	Onde se lê	Leia-se
1	10	auto-conclavo	autoconclavo

Marvin Abisrror Zarate

On Selecting of heuristics functions for Domain–Independent planning.

Paper presented to the Federal University of Viçosa, as part of the requirements of Graduate program Computer Science, for obtaining the title of Magister Scientiae.

Trabalho aprovado. Brasil, 24 de novembro de 2012:

Levi Henrique Santana de Lelis
Orientador

Professor
Convidado 1

Professor
Convidado 2

Brasil
2015, v-1.9.5

This thesis is dedicated to my Mother.

Acknowledgements

I would like to express my sincere gratitude to my advisor PhD. Levi Henrique Santana de Lelis, for the continuous support and guidance during the thesis process. His valuable advice, patience and encouragement have been of great importance for this work.

Besides my advisor, I would like to thank to my co—advisor: PhD. Santiago Franco for his insightful feedback, interest and tough questions.

To the professors of the DTI, particularly the Master Degree program with all its members, played an invaluable role in my graduate education.

Last, but not least, I would like to thank my Mother.

*“Não vos amoldeis às estruturas deste mundo,
mas transformai-vos pela renovação da mente,
a fim de distinguir qual é a vontade de Deus:
o que é bom, o que Lhe é agradável, o que é perfeito.
(Bíblia Sagrada, Romanos 12, 2)*

Abstract

In this dissertation we present a greedy method based on the theory of supermodular optimization for selecting a subset of heuristics functions from a large set of heuristics with the objective of reducing the running time of the search algorithms.

([HOLTE et al., 2006](#)) showed that search can be faster if several smaller pattern databases are used instead of one large pattern database. We introduce a greedy method for selecting a subset of the most promising heuristics from a large set of heuristics functions to guide the A* search algorithm. If the heuristics are consistent, our method selects a subset which is guaranteed to be near optimal with respect to the resulting A* search tree size. In addition to being consistent, if all heuristics have the same evaluation time, our subset is guaranteed to be near optimal with respect to the resulting A* running time. We implemented our method in Fast Downward and showed empirically that it produces heuristics which outperform the state of the art heuristics in the International Planning Competition benchmarks.

Key-words: Heuristics. selection.

List of Figures

Figure 1	– The left tile–puzzle is the initial distribution of tiles and the right tile–puzzle is the goal distribution of tiles. Each one represent a State.	32
Figure 2	– Heuristic Search: I : Initial State, s : Some Sate, G : Goal State	33
Figure 3	– Out of place heuristic	34
Figure 4	– Manhatham distance heuristic	34
Figure 5	– One heuristic of size M	36
Figure 6	– Two heuristics of size $M/2$	36
Figure 7	– N heuristics of size M/N	36

List of Tables

Contents

	Introduction	21
I	PREPARATION OF THE RESEARCH	23
1	ABOUT THE PROBLEM	25
	<i>The purpose of this section is to motivate the problem.</i>	
1.1	Problem Statement and Motivation	25
1.2	Aim and Objectives	26
1.2.1	Aim	26
1.2.2	Objectives	26
1.3	Scope, Limitations, and Delimitations	26
1.4	Justification	27
1.5	Hypothesis	27
1.6	Contribution of the Thesis	27
1.7	Organization of the Thesis	27
II	LITERATURE REVIEW	29
2	BACKGROUND	31
	<i>The purpose of this section is to understand the problem.</i>	
2.1	Similar Selection Systems	31
2.2	Problem definition	31
2.3	Heuristics	32
2.4	Problem Formulation	33
2.4.1	Out of place (O.P)	34
2.4.2	Manhattan Distance (M.D)	34
2.5	Heuristic Generators	35
2.5.1	Pattern Database (PDB)	35
2.5.2	Neural Network	35
2.5.3	Genetic Algorithm	35
2.6	Take advantage of Heuristics	35
2.7	Number of heuristics to create.	35
2.8	Heuristic Subset	36

III	RESULTADOS	37
3	LECTUS LOBORTIS CONDIMENTUM	39
3.1	Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae	39
4	NAM SED TELLUS SIT AMET LECTUS URNA ULLAMCORPER TRISTIQUE INTERDUM ELEMENTUM	41
4.1	Pellentesque sit amet pede ac sem eleifend consectetuer	41
5	CONCLUSÃO	43
	Bibliography	45
	APPENDIX	47
	APPENDIX A – QUISQUE LIBERO JUSTO	49
	APPENDIX B – NULLAM ELEMENTUM URNA VEL IMPERDIET SODALES ELIT IPSUM PHARETRA LIGULA AC PRETIUM ANTE JUSTO A NULLA CURABITUR TRISTIQUE ARCU EU METUS	51
	ANNEX	53
	ANNEX A – MORBI ULTRICES RUTRUM LOREM.	55
	ANNEX B – CRAS NON URNA SED FEUGIAT CUM SOCIIS NA- TOQUE PENATIBUS ET MAGNIS DIS PARTURI- ENT MONTES NASCETUR RIDICULUS MUS	57
	ANNEX C – FUSCE FACILISIS LACINIA DUI	59
	Index	61

Introduction

This thesis is concerned with cost-optimal state-space planning using the A^* algorithm (HART P. E.; NILSSON; RAPHAEL, 1968). We assume that a pool, ζ , of hundreds or even thousands of heuristics is available, and that the final heuristic used to guide A^* , h_{max} , will be defined as the maximum over a subset ζ' of those heuristics ($h_{max}(s, \zeta') = \max_{h \in \zeta'} h(s)$). The choice of the subset ζ' can hugely affect the efficiency of A^* . For a given size N and planning task ∇ , a subset containing N heuristics from ζ is optimal if no other subset containing N heuristics from ζ results in A^* expanding fewer nodes when solving ∇ .

Exists many problems of Artificial Intelligent (AI), such as: Finding the shortest path from one point to another in a game map, 8-tile-puzzle, Rubick's cube, etc. The level of difficulty to solve the problems mentioned are linked with the size of the search space generated.

State-space search algorithms have been used to solve the problems mentioned above. And in this dissertation we study the approach to solve problems in order to reduce the size of the search tree generated and the running time of the search algorithm using the best subset of heuristics selected from a large set of heuristics.

Part I

Preparation of the research

1 About the Problem

The purpose of this section is to motivate the problem.

1.1 Problem Statement and Motivation

Every problem of Artificial Intelligence can be cast as a state space problem. The state space is a set of states where each state represents a possible solution to the problem and each state is linked with other states if there exists a function that goes from one state to another. In the search space there are many solutions that represent the same state, each of these solutions are called nodes. So, many nodes can be represented as one state. To find the solution of the problem is required the use of search algorithms such as: Depth First Search (DFS), which looks for the solution of the problem traversing the search space exploring the nodes in each branch before backtracking up to find the solution. Another search algorithm is Breadth First Search (BFS), which looks for the solution exploring the neighbors nodes first, before moving to the next level of neighbors. The mentioned algorithms have the characteristic that when they do the search, they generate a larger search space. The search space that these algorithms generate are called Brute force search tree (BFST).

There are other types of algorithms called heuristics informed search, which are algorithms that require the use of heuristics. The heuristic is the estimation of the distance for one node in the search tree to get to the near solution. The heuristic informed search generates smaller search tree in comparison to the BFST, because the heuristic guides the search exploring the nodes that are in the solution path and prunes the nodes which are not. Also, the use of heuristics reduces the running time of the search algorithm.

There are different approaches to create heuristics, such as: Pattern Databases (PDBs), Neural Network, and Genetic Algorithm. These systems that create heuristics receive the name of Heuristics Generators. And one of the approaches that have showed most successful results in heuristic generation is the PDBs, which is memory-based heuristic functions obtained by abstracting away certain problem variables, so that the remaining problem ("pattern") is small enough to be solved optimally for every state by blind exhaustive search. The results stored in a table, represent a PDB for the original problem. The abstraction of the search space gives an admissible heuristic function, mapping states to lower bounds.

Exists many ways to take advantage of all the heuristics that can be created, for

example: (HOLTE et al., 2006) showed that search can be faster if several smaller pattern databases are used instead of one large pattern database. In addition (DOMSHLAK; KARPAS; MARKOVITCH, 2010) and (TOLPIN et al., 2013) results showed that evaluating the heuristic lazily, only when they are essential to a decision to be made in the search process is worthy in comparison to take the maximum of the set of heuristics. Then, using all the heuristics do not guarantee to solve the major number of problems in a limit time.

1.2 Aim and Objectives

1.2.1 Aim

The objective of this dissertation is to develop meta-reasoning approaches for selecting heuristics functions from a large set of heuristics with the goal of reducing the running time of the search algorithm employing these functions.

1.2.2 Objectives

- Demonstrate that the problem of finding the optimal subset of ζ of size N for a given problem task is supermodular respect the size of the search tree.
- Develop an approaches to obtain the cardinality of the subsets of heuristics found.
- Develop an approach to find a subset of heuristics from a large pool of heuristics that optimize the number of nodes expanded in the process of search.
- Develop an approach for selecting a subset of heuristic functions based on the minimum evaluation cost of each heuristic.
- Develop an strategy to drop heuristics during the sampling that do not improve the objective function.
- Use Stratified Sampling (SS) algorithm for predicting the search tree size of Iterative-Deepening A* (IDA*). And use SS as our utility function.

1.3 Scope, Limitations, and Delimitations

We implemented our method in Fast Downward (HELMERT, 2006) and the problems we want to solve are the optimal domains benchmarks. Our meta-reasoning described in this thesis are going to try to solve the major number of problems using the most promising heuristics from a large set of heuristics. The exact way to create the large set of heuristics is beyond the scope of this thesis.

1.4 Justification

In the last few decades, Artificial Intelligence has made significant strides in domain-independent planning. The use of heuristics search approach have contributed to problem solving, where the use of an appropriate heuristic often means substantial reduction in the time needed to solve hard problems.

That is why we propose a meta-reasoning that will try to solve the major number of problems without relying on domain knowledge, to guide the A* search algorithm.

1.5 Hypothesis

This thesis will intend to prove the hypotheses listed below:

- **H1:** Probe that our objective function of selection is related with two mathematical properties: Monotonicity and Submodularity.
- **H2:** Reducing the size of the search tree generated helps to solve more problems.

1.6 Contribution of the Thesis

The main contributions of this Thesis are:

- Provide a prediction method to estimate the size of the search tree generated.
- Provide a meta-reasoning approach based on the size of the search tree generated.
- Provide a meta-reasoning approach based on the evaluation cost of each heuristic.

1.7 Organization of the Thesis

The Thesis is organized as follows:

1. In Part 1, the background of the thesis is provided which also includes our motivation and define the scope.
2. In Part 2, we review the State of the Art.
3. In Part 3, we introduce our meta-reasoning approach.
4. In Part 4, we introduce.
5. In Part 5, we .

6. We conclude in Chapter 6 by discussing further improvements and future work.

In the next chapter, the domain 8–tile–puzzle is used to understand the concepts that will be helpful for the other Parts.

Part II

Literature Review

2 Background

The purpose of this section is to understand the problem.

2.1 Similar Selection Systems

An optimization procedure which is similar to ours is presented by (RAYNER; STURTEVANT; BOWLING, 2013), but their procedure maximizes the average heuristic value. By contrast, the meta-reasoning we are proposing minimizes the search tree size.

Our meta-reasoning requires a prediction of the number of nodes expanded by A^* using any given subset. Although there are methods for accurately predicting the number of nodes expanded by Iterative Deepening- A^* (KORF, 1985) (IDA^*). (SS system (LELIS; ZILLES; HOLTE, 2013)), these methods can't be easily adapted to A^* because A^* 's duplicate pruning makes it very difficult to predict how many nodes will occur at depth d of A^* 's search tree (the tree of nodes expanded by A^*). As a part of our proposal, we present SS for predicting the size of the search tree.

The system most similar to ours is **RIDA*** (??). **RIDA*** also selects a subset from a pool of heuristics to guide the A^* search. In **RIDA*** this is done by starting with an empty subset and trying all combination of size one before trying the combination of size two and so on. **RIDA*** stops after evaluating a fixed number of subsets. While **RIDA*** is able to evaluate a set of heuristics with tens of elements, our meta-reasoning is able to evaluate a set of heuristics with thousands of elements.

2.2 Problem definition

A SAS^+ planning task (BÄCKSTRÖM; NEBEL, 1995) is a 4 tuple $\nabla = \{V, O, I, G\}$. V is a set of *state variables*. Each variable $v \in V$ is associated with a finite domain of possible D_v . A state is an assignment of a value to every $v \in V$. The set of possible states, denoted V , is therefore $D_{v_1} \times \dots \times D_{v_2}$. O is a set of operators, where each operator $o \in O$ is triple $\{pre_o, post_o, cost_o\}$ specifying the preconditions, postconditions (effects), and non-negative cost of o . pre_o and $post_o$ are assignments of values to subsets of variables, V_{pre_o} and V_{post_o} , respectively. Operator o is applicable to state s if s and pre_o agree on the assignment of values to variables in V_{pre_o} . The effect of o , when applied to s , is to set the variables in V_{post_o} to the values specified in $post_o$ and to set all other variables to the value they have in s . G is the goal condition, an assignment of values to a subset of variables, V_G . A state is a goal state if it and G agree on the assignment of values to the variable in V_G . I is the initial state, and the planning task, ∇ , is to find an optimal (least-cost)

sequence of operators leading from I to a goal state. We denote the optimal solution cost of ∇ as C^*

The state space problem illustrated in the figure 1 is a game that consists of a frame of numbered square tiles in random order with one tile missing. The puzzle also exists in other sizes, particularly the smaller 8–puzzle. If the size is 3×3 tiles, the puzzle is called the 8–puzzle or 9–puzzle, and if 4×4 tiles, the puzzle is called the 15–puzzle or 16–puzzle named, respectively, for the number of tiles and the number of spaces. The object of the puzzle is to place the tiles in order by making sliding moves that use the empty space.

The legal operators are to slide any tile that is horizontally or vertically adjacent to the blank into the blank position. The problem is to rearrange the tiles from some random initial configuration into a particular desired goal configuration. The 8–puzzle contains 181,440 reachable states, the 15–puzzle contains about 10^{13} reachable states, and the 24–puzzle contains almost 10^{25} states.

Initial			Goal		
4	1	2	1	2	3
8		3	4	5	6
5	7	6	7	8	

Figure 1: The left tile–puzzle is the initial distribution of tiles and the right tile–puzzle is the goal distribution of tiles. Each one represent a State.

Instead of using an algorithm of Brute force search that will analyze all the possible solutions. We can obtain heuristics from the problem of the slide tile puzzle that will help us to solve the problem.

2.3 Heuristics

State–space algorithms, such as A^* (HART P. E.; NILSSON; RAPHAEL, 1968), are important in many AI applications. A^* uses the $f(s) = g(s) + h(s)$ cost function to guide its search. Here, $g(s)$ is the cost of the path from the start state s , and $h(s)$ is the estimated cost–to–go from s to a goal; $h(\cdot)$ is known as the heuristic function. The heuristic is the mathematical concept that represent to the estimate distance from the node s to the nearest goal state.




Figure 2: Heuristic Search: I : Initial State, s : Some Sate, G : Goal State

In the figure 2 the optimal distance from the Initial State I to the state s is 4 and represented by $g(s)$. The $h^*(s)$ represent the optimal distance from s to the Goal State G . And the $h(s)$ is the estimation distance from s to G .

A heuristic function $h(s)$ estimates the cost of a solution path from s to a goal state. A heuristic is admissible if $h(s) \leq h^*(s)$ for all $s \in V$, where $h^*(s)$ is the optimal cost of s . A heuristic is consisten iff $h(s) \leq c(s, t) + h(t)$ for all states s and t , where $c(s, t)$ is the cost of the cheapest path from s to t . For example, the heuristic function provided by a pattern database (PDB) heuristic (CULBERSON; SCHAEFFER, 1998) is admissible and consistent.

Given a set of admissible and consistent heuristics $\zeta = \{h_1, h_2, \dots, h_M\}$, the heuristic $h_{max}(s, \zeta) = \max_{h \in \zeta} h(s)$ is also admissible and consistent. When describing our method we assume all heuristics to be consistent. We define $f_{max}(s, \zeta) = g(s) + h_{max}(s, \zeta)$, where $g(s)$ is the cost of the path expanded from I to s . $g(s)$ is minimal when A* using a consistent heuristic expands s . We call an A* search tree the tree defined by the states expanded by A* using a consistent heuristic while solving a problem ∇ .

2.4 Problem Formulation

When solving ∇ using the consistent heuristic function $h_{max}(\zeta')$ for $\zeta' \subseteq \zeta$, A* expands in the worst case $J(\zeta', \nabla)$ nodes, where

$$J(\zeta', \nabla) = |\{s \in V | f_{max}(s, \zeta') \leq C^*\}| \quad (2.1)$$

$$J(\zeta', \nabla) = |\{s \in V | h_{max}(s, \zeta') \leq C^* - g(s)\}| \quad (2.2)$$

We present a greedy algorithm for approximately solving the following optimization problem,

$$\begin{aligned} &\textbf{minimize}_{\zeta' \in 2^{|\zeta|}} J(\zeta', \nabla) \\ &\textbf{subject to} |\zeta'| = N \end{aligned} \quad (2.3)$$

Where N could be determined by a hard constraint such as the maximum number of PDBs one can store in memory.

The heuristics can be obtained from each state of the problem. For example, for the problem of the 8–tile–puzzle figure 1 we can get two heuristics.

2.4.1 Out of place (O.P)

Counts the number of objects out of place.




Figure 3: Out of place heuristic

The tiles numbered with 4, 1, 2, 3, 6, 7, 5, 8, and 4 are out of place then each object count as 1 and the sum would be 8.

2.4.2 Manhatham Distance (M.D)

Counts the minimum number of operations to get to the goal state.




Figure 4: Manhatham distance heuristic

The tile 4 count 1 to get to the goal position. The tile 1 count 1 to get to the goal position. The tile 2 count 1 to get to the goal position. The tile 3 count 1 to get to the goal position. The tile 6 count 1 to get to the goal position. The tile 7 count 1 to get to the goal position. The tile 5 count 1 to get to the goal position. The tile 8 count 1 to get to the goal position. Then the sum would be 10.

In order to solve the problem, we get the heuristics, which are information from the problem to solve the problem. Exists systems that can create heuristics for each problem. Those systems are called Heuristic Generators.

2.5 Heuristic Generators

Heuristic Generators works by creating abstractions of the original problem spaces. There are different ways to abstract the problem space such as:

2.5.1 Pattern Database (PDB)

It's obtained by abstracting away certain problem variables, so that the remaining problem ("pattern") is small enough to be solved optimally for every state by blind exhaustive search. The results stored in a table, represent a PDB for the original problem. The abstraction of the search space gives an admissible heuristic function, mapping states to lower bounds.

2.5.2 Neural Network

2.5.3 Genetic Algorithm

2.6 Take advantage of Heuristics

The heuristics generators can create hundreds or even thousand of heuristics. In fact, exists different ways to take advantage of those heuristics. For example: If we want to use all the heuristics created by the heuristic generator. It would not be a good idea to use all of them because the main problem involved would be the time to evaluate each heuristic in the search tree, it could take too much time.

One way to take advantage of heuristics would be to take the maximum of the set of heuristics. For example, using three different heuristics $h1$, $h2$ and $\max(h1, h2)$. Heuristic $h1$ and $h2$ are based on domain abstractions and the $\max(h1, h2)$ is the maximum heuristic value of $h1$ and $h2$.

Exists different approaches to take advantage from a large set of heuristics. In this dissertation we use the meta-reasoning based on the minimum evaluation time.

2.7 Number of heuristics to create.

Something here




Figure 5: One heuristic of size M

Figure 6: Two heuristics of size M/2

Figure 7: N heuristics of size M/N

2.8 Heuristic Subset

The heuristics generators systems can create many heuristics. Let's suppose $|\zeta| = 1000$ heuristics were created considering the time and memory available and we want to select the best $N = 100$ heuristics. This would be:

$$\binom{1000}{100} = 10^{138} \text{possibilities}$$

So, try to select heuristics from a large set of heuristics are going to be treated as an optimization problem. In order to select a subset of heuristics, our objective function should guarantee two properties: Monotonicity and Submodularity.

In the next chapter, ...

Part III

Resultados

3 Lectus lobortis condimentum

3.1 Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae

Etiam pede massa, dapibus vitae, rhoncus in, placerat posuere, odio. Vestibulum luctus commodo lacus. Morbi lacus dui, tempor sed, euismod eget, condimentum at, tortor. Phasellus aliquet odio ac lacus tempor faucibus. Praesent sed sem. Praesent iaculis. Cras rhoncus tellus sed justo ullamcorper sagittis. Donec quis orci. Sed ut tortor quis tellus euismod tincidunt. Suspendisse congue nisl eu elit. Aliquam tortor diam, tempus id, tristique eget, sodales vel, nulla. Praesent tellus mi, condimentum sed, viverra at, consectetur quis, lectus. In auctor vehicula orci. Sed pede sapien, euismod in, suscipit in, pharetra placerat, metus. Vivamus commodo dui non odio. Donec et felis.

Etiam suscipit aliquam arcu. Aliquam sit amet est ac purus bibendum congue. Sed in eros. Morbi non orci. Pellentesque mattis lacinia elit. Fusce molestie velit in ligula. Nullam et orci vitae nibh vulputate auctor. Aliquam eget purus. Nulla auctor wisi sed ipsum. Morbi porttitor tellus ac enim. Fusce ornare. Proin ipsum enim, tincidunt in, ornare venenatis, molestie a, augue. Donec vel pede in lacus sagittis porta. Sed hendrerit ipsum quis nisl. Suspendisse quis massa ac nibh pretium cursus. Sed sodales. Nam eu neque quis pede dignissim ornare. Maecenas eu purus ac urna tincidunt congue.

4 Nam sed tellus sit amet lectus urna ullamcorper tristique interdum elementum

4.1 Pellentesque sit amet pede ac sem eleifend consectetuer

Maecenas non massa. Vestibulum pharetra nulla at lorem. Duis quis quam id lacus dapibus interdum. Nulla lorem. Donec ut ante quis dolor bibendum condimentum. Etiam egestas tortor vitae lacus. Praesent cursus. Mauris bibendum pede at elit. Morbi et felis a lectus interdum facilisis. Sed suscipit gravida turpis. Nulla at lectus. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Praesent nonummy luctus nibh. Proin turpis nunc, congue eu, egestas ut, fringilla at, tellus. In hac habitasse platea dictumst.

5 Conclusão

Sed consequat tellus et tortor. Ut tempor laoreet quam. Nullam id wisi a libero tristique semper. Nullam nisl massa, rutrum ut, egestas semper, mollis id, leo. Nulla ac massa eu risus blandit mattis. Mauris ut nunc. In hac habitasse platea dictumst. Aliquam eget tortor. Quisque dapibus pede in erat. Nunc enim. In dui nulla, commodo at, consectetur nec, malesuada nec, elit. Aliquam ornare tellus eu urna. Sed nec metus. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas.

Phasellus id magna. Duis malesuada interdum arcu. Integer metus. Morbi pulvinar pellentesque mi. Suspendisse sed est eu magna molestie egestas. Quisque mi lorem, pulvinar eget, egestas quis, luctus at, ante. Proin auctor vehicula purus. Fusce ac nisl aliquam ante hendrerit pellentesque. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Morbi wisi. Etiam arcu mauris, facilisis sed, eleifend non, nonummy ut, pede. Cras ut lacus tempor metus mollis placerat. Vivamus eu tortor vel metus interdum malesuada.

Sed eleifend, eros sit amet faucibus elementum, urna sapien consectetur mauris, quis egestas leo justo non risus. Morbi non felis ac libero vulputate fringilla. Mauris libero eros, lacinia non, sodales quis, dapibus porttitor, pede. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Morbi dapibus mauris condimentum nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Etiam sit amet erat. Nulla varius. Etiam tincidunt dui vitae turpis. Donec leo. Morbi vulputate convallis est. Integer aliquet. Pellentesque aliquet sodales urna.

Bibliography

ASSOCIAÇÃO BRASILEIRA DE NORMAS TÉCNICAS. *NBR 14724*: Informação e documentação — trabalhos acadêmicos — apresentação. Rio de Janeiro, 2005. 9 p. Citado na página 45.

ASSOCIAÇÃO BRASILEIRA DE NORMAS TÉCNICAS. *NBR 14724*: Informação e documentação — trabalhos acadêmicos — apresentação. Rio de Janeiro, 2011. 15 p. Substitui a Ref. [ABNT \(2005\)](#). Citado na página 3.

BÄCKSTRÖM, C.; NEBEL, B. Complexity results for sas+ planning. *Computational Intelligence*, Wiley Online Library, v. 11, n. 4, p. 625–655, 1995. Citado na página 31.

CULBERSON, J. C.; SCHAEFFER, J. Pattern databases. *Computational Intelligence*, Wiley Online Library, v. 14, n. 3, p. 318–334, 1998. Citado na página 33.

DOMSHLAK, C.; KARPAS, E.; MARKOVITCH, S. To max or not to max: Online learning for speeding up optimal planning. In: *AAAI*. [S.l.: s.n.], 2010. Citado na página 26.

HART P. E.; NILSSON, N. J.; RAPHAEL, B. A formal basis for the heuristic determination of minimum cost paths. *IEEE Transactions on Systems Science and Cybernetics SSC*, IEEE, v. 4, n. 2, p. 100–107, 1968. Citado 2 vezes nas páginas 21 and 32.

HELMERT, M. The fast downward planning system. *J. Artif. Intell. Res.(JAIR)*, v. 26, p. 191–246, 2006. Citado na página 26.

HOLTE, R. C. et al. Maximizing over multiple pattern databases speeds up heuristic search. *Artificial Intelligence*, Elsevier, v. 170, n. 16, p. 1123–1136, 2006. Citado 2 vezes nas páginas 13 and 26.

KORF, R. E. Depth-first iterative-deepening: An optimal admissible tree search. *Artificial Intelligence*, v. 27, p. 97–109, 1985. Citado na página 31.

LELIS, L. H.; ZILLES, S.; HOLTE, R. C. Predicting the size of ida* search tree. *Artificial Intelligence*, Elsevier, v. 196, p. 53–76, 2013. Citado na página 31.

RAYNER, C.; STURTEVANT, N.; BOWLING, M. Subset selection of search heuristics. *Proceedings of the Twenty-Third International Joint Conference on Artificial Intelligence*, p. 637–643, 2013. Citado na página 31.

TOLPIN, D. et al. Towards rational deployment of multiple heuristics in a*. In: *AAAI PRESS. Proceedings of the Twenty-Third international joint conference on Artificial Intelligence*. [S.l.], 2013. p. 674–680. Citado na página 26.

Appendix

APPENDIX A – Quisque libero justo

Quisque facilisis auctor sapien. Pellentesque gravida hendrerit lectus. Mauris rutrum sodales sapien. Fusce hendrerit sem vel lorem. Integer pellentesque massa vel augue. Integer elit tortor, feugiat quis, sagittis et, ornare non, lacus. Vestibulum posuere pellentesque eros. Quisque venenatis ipsum dictum nulla. Aliquam quis quam non metus eleifend interdum. Nam eget sapien ac mauris malesuada adipiscing. Etiam eleifend neque sed quam. Nulla facilisi. Proin a ligula. Sed id dui eu nibh egestas tincidunt. Suspendisse arcu.

APPENDIX B – Nullam elementum urna vel imperdiet sodales elit ipsum pharetra ligula ac pretium ante justo a nulla curabitur tristique arcu eu metus

Nunc velit. Nullam elit sapien, eleifend eu, commodo nec, semper sit amet, elit. Nulla lectus risus, condimentum ut, laoreet eget, viverra nec, odio. Proin lobortis. Curabitur dictum arcu vel wisi. Cras id nulla venenatis tortor congue ultrices. Pellentesque eget pede. Sed eleifend sagittis elit. Nam sed tellus sit amet lectus ullamcorper tristique. Mauris enim sem, tristique eu, accumsan at, scelerisque vulputate, neque. Quisque lacus. Donec et ipsum sit amet elit nonummy aliquet. Sed viverra nisl at sem. Nam diam. Mauris ut dolor. Curabitur ornare tortor cursus velit.

Morbi tincidunt posuere arcu. Cras venenatis est vitae dolor. Vivamus scelerisque semper mi. Donec ipsum arcu, consequat scelerisque, viverra id, dictum at, metus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut pede sem, tempus ut, porttitor bibendum, molestie eu, elit. Suspendisse potenti. Sed id lectus sit amet purus faucibus vehicula. Praesent sed sem non dui pharetra interdum. Nam viverra ultrices magna.

Aenean laoreet aliquam orci. Nunc interdum elementum urna. Quisque erat. Nullam tempor neque. Maecenas velit nibh, scelerisque a, consequat ut, viverra in, enim. Duis magna. Donec odio neque, tristique et, tincidunt eu, rhoncus ac, nunc. Mauris malesuada malesuada elit. Etiam lacus mauris, pretium vel, blandit in, ultricies id, libero. Phasellus bibendum erat ut diam. In congue imperdiet lectus.

Annex

ANNEX A – Morbi ultrices rutrum lorem.

Sed mattis, erat sit amet gravida malesuada, elit augue egestas diam, tempus scelerisque nunc nisl vitae libero. Sed consequat feugiat massa. Nunc porta, eros in eleifend varius, erat leo rutrum dui, non convallis lectus orci ut nibh. Sed lorem massa, nonummy quis, egestas id, condimentum at, nisl. Maecenas at nibh. Aliquam et augue at nunc pellentesque ullamcorper. Duis nisl nibh, laoreet suscipit, convallis ut, rutrum id, enim. Phasellus odio. Nulla nulla elit, molestie non, scelerisque at, vestibulum eu, nulla. Ut odio nisl, facilisis id, mollis et, scelerisque nec, enim. Aenean sem leo, pellentesque sit amet, scelerisque sit amet, vehicula pellentesque, sapien.

ANNEX B – Cras non urna sed feugiat cum sociis natoque penatibus et magnis dis parturient montes nascetur ridiculus mus

Sed consequat tellus et tortor. Ut tempor laoreet quam. Nullam id wisi a libero tristique semper. Nullam nisl massa, rutrum ut, egestas semper, mollis id, leo. Nulla ac massa eu risus blandit mattis. Mauris ut nunc. In hac habitasse platea dictumst. Aliquam eget tortor. Quisque dapibus pede in erat. Nunc enim. In dui nulla, commodo at, consectetur nec, malesuada nec, elit. Aliquam ornare tellus eu urna. Sed nec metus. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas.

ANNEX C – Fusce facilisis lacinia dui

Phasellus id magna. Duis malesuada interdum arcu. Integer metus. Morbi pulvinar pellentesque mi. Suspendisse sed est eu magna molestie egestas. Quisque mi lorem, pulvinar eget, egestas quis, luctus at, ante. Proin auctor vehicula purus. Fusce ac nisl aliquam ante hendrerit pellentesque. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Morbi wisi. Etiam arcu mauris, facilisis sed, eleifend non, nonummy ut, pede. Cras ut lacus tempor metus mollis placerat. Vivamus eu tortor vel metus interdum malesuada.

Index

sinopse de capítulo, [25](#), [31](#)