```
PS C:\dev\projet-e-commerce\shop-api> docker compose exec db mysql -u shopuser -pshoppass
shop_db

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> SHOW TABLES;
+------------------+
| Tables_in_shop_db |
+------------------+
| categories       |
| clients          |
| customer_orders  |
| order_items      |
| products         |
+------------------+
5 rows in set (0.00 sec)

mysql> DESCRIBE products;
+------------+---------------+------+-----+---------+----------------+
| Field      | Type          | Null | Key | Default | Extra          |
+------------+---------------+------+-----+---------+----------------+
| id         | int           | NO   | PRI | NULL    | auto_increment |
| name       | varchar(255)  | NO   |     | NULL    |                |
| price      | decimal(10,2) | NO   |     | NULL    |                |
| stock      | int           | NO   |     | 0       |                |
| categoryId | int           | NO   | MUL | NULL    |                |
+------------+---------------+------+-----+---------+----------------+
5 rows in set (0.00 sec)

mysql> DESCRIBE order_items;
+-----------+---------------+------+-----+---------+----------------+
| Field     | Type          | Null | Key | Default | Extra          |
+-----------+---------------+------+-----+---------+----------------+
| id        | int           | NO   | PRI | NULL    | auto_increment |
```

```
PS C:\dev\projet-e-commerce\shop-api> docker compose exec db mysql -u shopuser -pshoppass
shop_db

mysql> DESCRIBE order_items;
+-----------+---------------+------+-----+---------+----------------+
| Field     | Type          | Null | Key | Default | Extra          |
+-----------+---------------+------+-----+---------+----------------+
| id        | int           | NO   | PRI | NULL    | auto_increment |
| quantity  | int           | NO   |     | NULL    |                |
| unitPrice | decimal(10,2) | NO   |     | NULL    |                |
| orderId   | int           | NO   | MUL | NULL    |                |
| productId | int           | NO   | MUL | NULL    |                |
+-----------+---------------+------+-----+---------+----------------+
5 rows in set (0.00 sec)

mysql> SELECT * FROM categories;
+----+--------------+
| id | name         |
+----+--------------+
|  1 | Informatique |
+----+--------------+
1 row in set (0.00 sec)

mysql> SELECT * FROM products;
+----+------------------+--------+-------+------------+
| id | name             | price  | stock | categoryId |
+----+------------------+--------+-------+------------+
|  1 | Clavier mecanique | 150.00 |    10 |          1 |
|  2 | Clavier mecanique | 150.00 |    12 |          1 |
|  3 | ♦cran            | 180.00 |     8 |          1 |
+----+------------------+--------+-------+------------+
3 rows in set (0.00 sec)

mysql> SELECT * FROM clients;
```

```
PS C:\dev\projet-e-commerce\shop-api> docker compose exec db mysql -u shopuser -pshoppass
shop_db

mysql> SELECT * FROM clients;
+----+---------------+-------------------+
| id | fullName      | email             |
+----+---------------+-------------------+
|  1 | Amira Ben Ali | amira@example.com |
+----+---------------+-------------------+
1 row in set (0.00 sec)

mysql> SELECT * FROM customer_orders;
+----+---------+--------+-------------------------+----------+
| id | status  | total  | createdAt               | clientId |
+----+---------+--------+-------------------------+----------+
|  1 | CREATED | 300.00 | 2026-11-10 09:03:23.137613 |        1 |
+----+---------+--------+-------------------------+----------+
1 row in set (0.00 sec)

mysql> SELECT * FROM order_items;
+----+----------+-----------+---------+-----------+
| id | quantity | unitPrice | orderId | productId |
+----+----------+-----------+---------+-----------+
|  1 |        2 |    150.00 |       1 |         1 |
+----+----------+-----------+---------+-----------+
1 row in set (0.00 sec)

mysql> SELECT o.id, c.fullName, p.name, oi.quantity, oi.unitPrice
    -> FROM customer_orders o
    -> JOIN clients c ON c.id = o.clientId
    -> JOIN order_items oi ON oi.orderId = o.id
    -> JOIN products p ON p.id = oi.productId;
+----+---------------+-------------------+----------+-----------+
| id | fullName      | name              | quantity | unitPrice |
```

```
1 row in set (0.00 sec)

mysql> SELECT o.id, c.fullName, p.name, oi.quantity, oi.unitPrice
    -> FROM customer_orders o
    -> JOIN clients c ON c.id = o.clientId
    -> JOIN order_items oi ON oi.orderId = o.id
    -> JOIN products p ON p.id = oi.productId;
+----+---------------+-------------------+----------+-----------+
| id | fullName      | name              | quantity | unitPrice |
+----+---------------+-------------------+----------+-----------+
|  1 | Amira Ben Ali | Clavier mecanique |        2 |    150.00 |
+----+---------------+-------------------+----------+-----------+
1 row in set (0.00 sec)

mysql>
```