

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 // #define int long long
4 #define M 1000000007
5 #define N 1e6
6 #define INF 1e17
7 #define endl "\n"
8 #define all(v) v.begin(), v.end()
9 #define yes cout << "Yes" << endl
10 #define no cout << "No" << endl
11 #define minus cout << "-1" << endl
12 #define zero cout << "0" << endl
13 #define make_unique(x) \
14     sort(all((x))); \
15     (x).erase(unique(all((x))), (x).end())
16 vector<int> fact(N + 5, 0), ifact(N + 5, 0);
17 const int maxn = 1e3;
18 int ncr[maxn + 1][maxn + 1];
19 void prepascal() {
20     ncr[0][0] = 1;
21     for (int n = 1; n <= maxn; n++) {
22         ncr[n][0] = ncr[n][n] = 1;
23         for (int k = 1; k < n; k++)
24             ncr[n][k] = ncr[n - 1][k - 1] + ncr[n - 1][k];
25     }
26 }
27 int mod(int x, int m = M) { return x % m; }
28 int binexp(int a, int b) {
29     int ans = 1;
30     while (b) {
31         if (b & 1)
32             ans = mod(ans * a);
33         a = mod(a * a), b >>= 1;
34     }
35     return mod(ans);
36 }
37 void pre() {
38     fact[0] = 1;
39     for (int i = 1; i <= N; i++)
40         fact[i] = mod(fact[i - 1] * i);
41     ifact[N] = binexp(fact[N], M - 2);
42     for (int i = N; i > 0; i--)
43         ifact[i - 1] = mod(ifact[i] * i);
44 }
45 int nCr(int n, int r) {
46     return mod(mod(fact[n] * ifact[r]) * ifact[n - r]);
47 }
48 void marwan() {
49 }
50 int32_t main() {
51     ios_base::sync_with_stdio(false), cin.tie(0);
52     pre();
53     int t;
54     cin >> t;
55     while (t--)
56         marwan();
57     return 0;
58 }

```