# Sublime Text – Linux Configuration

## 1. Linux C++17 Build System

Save as `C++17 Linux.sublime-build`:

```
{
    "shell_cmd": "g++ -std=c++17 -O2 -Wall \"${file}\" -o \"${file_path}/${file_base_name}\" && \"${file_path}/${file_base_name}\" < \"${file_path
      }/input.txt\" > \"${file_path}/output.txt\"",
    "working_dir": "${file_path}",
    "selector": "source.cpp"
}
```

## 2. Sublime Text Keybindings

Save as `Default (Linux).sublime-keymap`:

```
[
    // FILES / PROJECT
    { "keys": ["ctrl+o"], "command": "prompt_open_file" },
    { "keys": ["ctrl+k", "ctrl+o"], "command": "prompt_open_folder" },

    // LINES
    { "keys": ["alt+shift+down"], "command": "duplicate_line" },
    { "keys": ["alt+down"], "command": "swap_line_down" },
    { "keys": ["alt+up"], "command": "swap_line_up" },
    { "keys": ["ctrl+shift+k"], "command": "cut" },

    // EDITING
    { "keys": ["ctrl+/"], "command": "toggle_comment" },
    { "keys": ["ctrl+d"], "command": "find_under_expand" },
    { "keys": ["ctrl+shift+l"], "command": "split_selection_into_lines" },

    // NAVIGATION
    { "keys": ["ctrl+p"], "command": "show_overlay",
      "args": {"overlay": "goto", "show_files": true} },
    { "keys": ["ctrl+g"], "command": "goto_line" },
    { "keys": ["ctrl+f"], "command": "show_panel",
      "args": {"panel": "find"} },
    { "keys": ["ctrl+h"], "command": "show_panel",
      "args": {"panel": "replace"} },

    // TABS
    { "keys": ["ctrl+w"], "command": "close_file" },
    { "keys": ["ctrl+shift+t"], "command": "reopen_last_file" },
    { "keys": ["ctrl+tab"], "command": "next_view" },
    { "keys": ["ctrl+shift+tab"], "command": "prev_view" },

    // MULTI-CURSOR
    { "keys": ["ctrl+alt+up"], "command": "select_lines",
      "args": {"forward": false} },
    { "keys": ["ctrl+alt+down"], "command": "select_lines",
      "args": {"forward": true} },

    // CLANG FORMAT
    { "keys": ["shift+alt+f"], "command": "clang_format" }
]
```