

# Enhancement of Footwear Impressions

DIPLOMARBEIT

zur Erlangung des akademischen Grades

**Diplom-Ingenieur**

im Rahmen des Studiums

**Visual Computing**

eingereicht von

**Rebeka Koszticsak, Bsc**

Matrikelnummer 01325492

an der Fakultät für Informatik

der Technischen Universität Wien

Betreuung: Ao.Univ.Prof. Dipl.-Ing. Dr.techn. Robert Sablatnig

Mitwirkung: Proj.-Ass. Dipl.-Ing. Manuel Keglevic

Wien, 4. Jänner 2020

---

Rebeka Koszticsak

---

Robert Sablatnig



# Enhancement of Footwear Impressions

DIPLOMA THESIS

submitted in partial fulfillment of the requirements for the degree of

**Diplom-Ingenieur**

in

**Visual Computing**

by

**Rebeka Koszticsak, Bsc**

Registration Number 01325492

to the Faculty of Informatics

at the TU Wien

Advisor: Ao.Univ.Prof. Dipl.-Ing. Dr.techn. Robert Sablatnig

Assistance: Proj.-Ass. Dipl.-Ing. Manuel Keglevic

Vienna, 4<sup>th</sup> January, 2020

---

Rebeka Koszticsak

---

Robert Sablatnig



# Erklärung zur Verfassung der Arbeit

Rebeka Koszticsak, Bsc  
Address

Hiermit erkläre ich, dass ich diese Arbeit selbständig verfasst habe, dass ich die verwendeten Quellen und Hilfsmittel vollständig angegeben habe und dass ich die Stellen der Arbeit – einschließlich Tabellen, Karten und Abbildungen –, die anderen Werken oder dem Internet im Wortlaut oder dem Sinn nach entnommen sind, auf jeden Fall unter Angabe der Quelle als Entlehnung kenntlich gemacht habe.

Wien, 4. Jänner 2020

---

Rebeka Koszticsak



# Danksagung

---

Ihr Text hier.





# Acknowledgements

Enter your text here.



# Kurzfassung

---

Ihr Text hier.



# Abstract

Shoeprint images are one of the most commonly secured evidences on crimescenes. Even though automatic shoeprint processing is a highly researched topic, the final identification is usually done by human forensic experts. The two main steps of shoeprint identification are enhancement and matching.

In this thesis the possibilities for enhancement of shoeprint samples from a real-life dataset are investigated. The main challenge of this task is to correctly filter the pattern regardless the versatile, possibly heavily structured and cluttered noise on the samples. Two approaches are examined, pattern enhancement and noise suppression. Among fully automated methods, a semi-automated technique is also tested, where user input is required for noise separation.

The main goal of this work is to find a universal approach which is able to filter and enhance the shoeprint data even in the presence of noise and the possible low image quality. Based on the experiences acquired while investigating the possible techniques a new noise-suppression pipeline for shoeprint images is introduced. The noisy pixels are identified based on the Fourier-Mellin features of their multi-sized neighborhood. In the same time a model is built about the average appearance of noise, to eliminate that structure from the foreground as well. Additionally a gradient based line detector is also applied and the edge structures of the shoeprint are clustered to distinguish between pattern and noise edges. The experimental results show that the processed images are clearer, the pattern is sharper whereas the noise is either completely eliminated in the background or suppressed in the foreground. Furthermore based on the results of three different basic image descriptor features, the enhanced shoeprints have higher matching rate to their ground-truth samples than the original images.




# Contents

<b>Kurzfassung</b>	<b>xi</b>
<b>Abstract</b>	<b>xiii</b>
<b>Contents</b>	<b>xv</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Problem Definition . . . . .	2
1.2 Challenges . . . . .	2
1.3 Contribution . . . . .	3
1.4 Structure of the Work . . . . .	4
<b>2 Related Work</b>	<b>7</b>
2.1 Image Enhancement . . . . .	7
2.2 Noise Removal . . . . .	11
2.3 Image Description . . . . .	12
2.4 Classification . . . . .	15
<b>3 Pattern Enhancement</b>	<b>17</b>
<b>4 Fully Automated Noise Supression</b>	<b>19</b>
<b>5 Semi-Automated Noise Supression</b>	<b>21</b>
<b>6 Results and Evaluation</b>	<b>23</b>
<b>7 Future Work</b>	<b>25</b>
<b>8 Conclusion</b>	<b>27</b>
<b>Bibliography</b>	<b>29</b>







# Introduction

Shoeprints found on crimescenes can be important hints or evidences in a criminal investigation [KYZ14]. Event though on one thrid [Ale96] of crimescenes usable shoepatterns can be secured, there is no fully automatized algorithm available yet, which is able to identify and match those prints with the original shoe sole. Because of that human power is needed [WSYZ14] to recognize and analyze the found patterns. The work of forensic experts is not only time consuming and expensive, there is no guarantee about the objectivness of the final outcome[GBCN08], furthermore the stages of the human matching process are unclear and not necessarily reproducible.

There is an excessive amount of research already done [RBCP19] in order to help or replace the work of forensic experst. There is however no algorithm published yet, which can be relaiably used in varying conditions and sample quality. One reason for that are the already mentioned versitile conditions, the features and properties of the pattern on the shoe, like age, material, etc., the characteristics of the ground where the shoeprint is left and enviromental conditions like for example the weather highly influence the overall quality of the acquired sample. Those high amount of factors result in changing appearance of the prints of the same shoe causing high intra class variance while clustering. Additionally there is a lack of universal, wide ranged database [RBCP19] which correctly depicts the common scenarios occuring on real-life crime scenes.

In 2014 a new database, called FID-300 [KAV14] was released which aims to solve the database problem described above. It contains over 1000 reference shoeprint patterns acquired in a laboratory. Moreover the database introduces 300 new shoeprint samples collected by the police providing an insight on images forensic experts are working on the daily basis.

### 1.1 Problem Definition

There are two main stages of automatic shoeprint identification, filtering, where the shoeprint pattern is separated from background and enhanced as well, and matching where the corresponding shoe is determined. Instead of automatizing the entire shoeprint recognition pipeline this work only focuses on the possible ways of increasing the sample quality. Because of the mentioned absence of general, appropriate database it is difficult to compare the already available methods. Furthermore it is also challenging to estimate which one is applicable in a real-life scenario. In this thesis multiple possible enhancing techniques are developed and tested in order to find a method which is able to cope with samples taken from real crime scenes.

For evaluation and testing the FID-300 database is used. The dataset contains both in a laboratory acquired as well as on a crime secured shoeprint patterns. The goal of this work is to define an image processing pipeline which is able to correctly identify and enhance the shoe patterns and eliminate or suppress the noise on the pattern samples regardless the quality of the image. A secondary objective is to gain an overview about the algorithms already published, and make an estimation which methods are applicable in real-life scenarios based on their performance on the FID-300 database.

### 1.2 Challenges

There are two main obstacles in the topic of shoeprint enhancement and in automatic shoeprint matching in general, the versatile image quality and appearance and the lack of universal and wide database. The shoeprint patterns are varying, there are approaches available which build models for given structures of the shoeprint [TSKC10], [AK17], but no detailed, uniform representation for the entire shoeprint is possible. Moreover there is a high inference of noise from multiple sources. The ground where the shoeprint is found is considered as noise expect in the rear case when it is left on a non changing, even surface. The produced print of the same shoe pattern varies on different type of surface. Additionally the roughness and unevenness of a given type of surface also distorts the original pattern. Furthermore other objects on the ground, on or behind the left shoeprint can cover or distort the original pattern, or they can prevent to leave a print on their area completely. Besides that the pattern on the original shoe can also be distorted or modified compared to the new version. Distortions caused by usage are valuable information about the owner, on the other hand they make it more difficult to match the pattern with their unused pairs. Additional objects between the structures of the shoeprint also alter the original appearance. Lastly, there are multiple shoeprint securing methods producing different results for the same print [KS17]. The shoeprint lifting technique used depends on the properties of the ground. Those two factors, the securing method and the floor, also determine if the positive or the negative, the actual pattern or the space between the shoeprint structures, image is captured.

The non-existing universal database causes that two published methods are difficult to

compare based on their results since they are using different testing images. The used dataset is not necessarily published [KS17], [DCC09] making it impossible to reproduce the result in those cases. Additionally the handcrafted databases can be biased, and allow such restrictions and modifications which do not correlate with real-life scenarios [RBCP19]. The used samples are either synthetically generated and computationally distorted [DCFR05], [GBCN08] or exclude low quality and noisy images [DCC09], [TSKC10]. Because of that it is difficult to compare their performance and to estimate which one of the published approaches are applicable on the FID-300 database. Furthermore it is challenging to plan a new algorithm based on the published results because their lack of a uniform baseline.

### 1.3 Contribution

In this thesis the possible ways of enhancing a shoeprint images are discussed. Because of the known issues on database multiple approaches are implemented, discussed and evaluated. The two ways to increase the quality of a given shoeprint sample is to enhance the pattern regardless of the noise and to suppress or eliminate the noise without losing any of pattern information. Along fully-automated methods semi-automated possibilities are also considered. Three different approaches are introduced and examined for their performance on real-life image samples.

Finally a new semi-automated framework is given which is evaluated on the FID-300 database. In the first step user input about the noise is required. The input is separated into tiles, and the subparts are compared based on the Fourier-Mellin features to the region of the user input. In that way the background is separated from the foreground and the average appearance of the image is calculated. Since noise appears on the pattern as well, the distorted parts are corrected based on the calculated noise model. After that gradient based line detection is performed and the results are separated into clusters where pattern and noise classes are defined and candidates of the latter are eliminated. The final image is thresholded to create a binary image, where the shoeprint is clearly visible and recognizable whereas the clutter is suppressed on the pattern and eliminated in the background of the image. Throughout the whole processing pipeline morphological operations and small structure elimination is applied multiple times. First when a mask for background is built, and also in the end of the pipeline to eliminate small inconsistencies on the pattern. Experimental results show, that the enhanced images are clearer, the background is successfully eliminated and the shoeprint pattern is less noisy than on the original images. Figure 1.1 shows an example sample from the FID-300 database 1.1a and the enhanced images 1.1b with the proposed algorithm. Moreover the matching of the sample and the enhanced images with their in a laboratory lifted pair according to basic image features such as SIFT and SURF indicate that the improved images have a better matching rate than its original version.




Figure 1.1: Result of the proposed algorithm

### 1.4 Structure of the Work

To gain an overview about the research already done the following section, Chapter 2, gives a review about the literature. Along papers published in the topic of shoeprint identification, matching and enhancement, research of similar domains is presented as well. Fields of fingerprint processing and tattoo identification is also overviewed for possibilities of using the techniques in the given problem. Furthermore natural image enhancement and denoising techniques are revised as well.

In Chapter 3, 4 and 5 the approaches for enhancement are given and discussed if they are applicable for real-life forensic images. Chapter 3 presents and evaluates a possible way

for pattern enhancement. Chapter 4 and 5 describes an automated and a semi-automated noise suppression pipeline respectively. In Chapter 5 the new algorithm for enhancing real-life crime scene shoeprint impressions is proposed. Details on implementation are revealed as well.

In Chapter 6 experimental results are shown and the proposed algorithm is evaluated. In Chapters 7 and 8 prospective future work is discussed and the final conclusion is given.



## Related Work

In order to find and develop an effective algorithm for shoeprint enhancement an overview about relevant research has to be made first. Along the evident literature of image enhancement other related topics such as discriminative image descriptors and feature classification are also considered, to gain the best insight possible and to be able to develop an algorithm which is optimized for the whole rest of the shoeprint identification pipeline. In this chapter the research on the domain of shoeprint identification is reviewed. Other than that publications from similar domains such as fingerprint and palmprint detection as well as tattoo identification are described. The related domains fingerprint identification and tattoo recognition have been chosen for review because of their similar goal of edge structure and minimal image structure recognition. Moreover an overview of techniques from the field of natural image enhancement and description along with general image denoising is also given. This chapter is separated into four parts, first Image Enhancement techniques are described, after that algorithms developed for Noise Removal specifically are discussed. In the second half of the chapter proposed methods Image Descriptors and lastly for Feature Classifications are reviewed.

### 2.1 Image Enhancement

In this section image enhancement techniques from four specific domains are discussed, these are shoe- and fingerprint identification, tattoo recognition and natural image enhancement.

#### Shoeprint Enhancement

There is an extensive research done in the field of enhancing shoeprint images. However, it has to be noticed that the problem definition and the use-case of the different publications varies. Because of the absence of standard database, the discussed algorithms can be

separated into two groups, techniques tested on synthetic samples and on real-life impressions. Synthetic samples are images scanned in images in a laboratorial enviroment for the purpose of building a dataset for shoeprint identification. The noise derives from scanning artifacts and computationally added distortions and modification. Furthermore many algorithms developed for real crime-scene data make restrictions about the input image and exclude noisy and poor quality images. Figure 2.1 shows example images from a synthetic 2.1a, from a restricted 2.1b and high 2.1c and low quality samples 2.1d from the FID-300 dataset. In the following discussion it is noticed repeatedly, which kind of dataset the proposed approach was tested on.




Figure 2.1: Example images of a synthetic [AK17], of a restricted [LWS14] and of the FID-300 [KAV14] dataset

Morphological Operations, Thresholding and Image Filtering are popular techniques for improve the quality of both kind, realistic and synthetic, of input data. Morphological operations, especially Opening and Closing, is used in many cases [WSYZ14], [KYZ14], [LWS14], [TSKC10], [WWZ19], whereas Wang et al. [WSYZ14] uses a synthetic dataset, and other than Wu et al. [WWZ19] the forensic images are restricted to high quality data. Wang et al. [WSYZ14], Kong et al. [KYZ14] and Li et al. [LWS14] use the Morphological Operations to correct inconsistencies after thresholding. Similar to the previous approaches Wu et al. [WWZ19] applies the same pipeline on a real forensic dataset. Tang et al. [TSKC10] follow the same principle but instead of thresholding,



after Canny edge detection is Opening and Closing used.

To create a binary image and eliminate noise various thresholding techniques are used. Otsu [WWZ19], [AH08], [AK17], [KYZ14] and adaptive thresholding [WSYZ14], [LWS14] are the two most popular algorithms. Algarni et al. [AH08] and Alizedah et al. [AK17] along with Wang et al. [WSYZ14] published their algorithms for synthetic datasets. Kong et al. [KYZ14] and Li et al. [LWS14] tested on restricted, whereas Wu et al. [WWZ19] developed their approach for full real forensic database. Wang et al. [WSYZ14] and Wu et al. [WWZ19] combine thresholding with a grid based approach to calculate exact thresholds for every subarea of the picture.

An other way to eliminate noise is image filtering. Alizadeh et al. [AK17] uses a simple Median filter on a synthetic dataset. Zhang et al. [ZA05] test on synthetic database as well. They take advantage on the partial different equations approach. In this way the edges are preserved while the background is smoothed according to a controlled curvature motion criteria. Katireddy et al. [KS17] uses Successive Mean Quantization Transfrom (SMQT) [Nil13] as an only step to enhance a real-life database. Figure 2.2 shows the output of the SMQT algorithm on an example image.




Figure 2.2: Example image about the enhancement feature of the SMQT algorithm [KS17]

Bandpass operators are also used for noise suppression. The images are converted to the frequency domain where high and low frequencies are eliminated. Gueham et al. [GBC07] and Richetelli et al. [RLL<sup>+</sup>17] utilize this method on a synthetic database. Li et al. [LWS14] work with a restricted real dataset, where only the lower frequencies are eliminated. Another frequency based approach was proposed by Katireddy et al. [KS17] based on Daubechies wavelets. After SMQT enhancement the Daubechies wavelets are used to separate the fore- and background and to remove the noise in the latter.

### Fingerprint Enhnacement

Bandpass and general image filtering is popular in the field of fingerprint enhancement as well. Zhou et al. [ZSL<sup>+</sup>11] uses a low- and a highpass filter to eliminate striking frequencies. Baig et al. [BHK15] apply Directional Hilbert transform of a Butterworth andpass to collect the different phase shifts and eliminate the artifacts created by previous thresholding of the input. Wang et al. [WLWL14] decompose the image into four subbands and process them separately, calculating the noise for every subband respectively. Li et al. [LFLY12] use Fourier transformation combined with Scale Invariant Feature Transform (SIFT) to enhance the fingerrint images. With SIFT the intresting points in the Fourier domain are found and secured, while the image is filtered to suppress noise and other inconsistencies. Jahan et al. [JCI17] apply Fuzzy filtering followed by thinning. Fuzzy filter is a local method to preserve the edge information and fine lines structures and suppress the noisy background of the input.

reference

### Tattoo Enhnacement

For tattoo enhancement an algorithm from Han et al. [HJ13] was proposed which combines Gaussian filtering with Hysteresis thresholding. Hysteresis thresholding is a neighborhood-aware approach where a pixel is labelled when it is above a given low threshold and simultaneously connected to other pixels meeting a higher thresholding criteria. Acton et al. [AR08] propose to use an Active Contour Model to find the boundaries of tattoo images and apply Opening and Closing as well to get rid of small inconsistencies.

reference

reference

### Natural Image Enhnacement

Along Signal, especially Bandpass, general Image Filtering and Thresholding Histogram and Color Operations are also common for natural image enhancement. Maini et al. [MA10] published a review about natural image enhancing algorithms and defined two main groups of algorithms, Frequency and Spatial Domain Methods. First publications utilizing techniques from the first group are discussed, after that the usage of Spatial Domain Methods is reviewed.

Xu et al. [XWYH16] combines Bandpass filtering with adaptive thresholding. Similar to Wang et al. [WLWL14] the image is separated into four subbands, and the threshold is calculated for every image separately. Sugamya et al. [SPV16] applies Subband Decomposition with two staged Histogram Equalization. The histogram of the input is equalized gloablly first, after that it is decomposed into subbands to Equalize the values locally for every four generated subimage.

Median Filters are used for noise suppression no only in the domain of shoeprint enhancement [AK17] but also for natural image processing. Apart from Median Filter Li et al. [LLGF14] utilize Average and Wiener Filter as well to suppress the occuring

noise and to prepare the input for neighborhood based feature extraction. Feng et al. [FJZY11] proposed a Bag-of-Words algorithm based on the Gabor wavelets of the input. For preprocessing the Watershed Transform is used.

Histogram Operations can be combined with not only Bandpass filtering as Suganya et al. [SPV16] do but also with Thresholding as proposed by Yao et al. [YZL<sup>+</sup>16]. Their approach separates the histogram of the input into two parts according to Otsu's method. After that the histogram is equalized of the generated subimages. Figure 2.3 shows the results of algorithm on an example image.




Figure 2.3: Example image [YZL<sup>+</sup>16] about the enhancement feature of the algorithm proposed by Yao et al. [YZL<sup>+</sup>16]

Color processing techniques are widespread in the topic of natural image enhancement. It can be used for image dehazing, so for low contrast images, [SK18] and also for classical noise removal [RLCL18], [ZSP<sup>+</sup>16]. Bhairannawar et al. [BPJH17] switch from RGB to HSV and use Laplace filter to detect regions with intensity changes. During processing the H channel is not modified to prevent color distortion artifacts. Although color processing is a well researched field with many promising solutions, no wider overview is given in this thesis. There are shoeprint impression datasets with colored samples, FID-300 provides grayscale images thus no color processing approach can be used in this specific case.

## 2.2 Noise Removal

Noise Removal methods are based on estimating the original image, and based on that eliminating the deviating features of the data. One way is denoising through gradient histogram preservation [ZZSZ13]. The distribution of gradients is estimated on the

original image, and the noisy image is adjusted to the calculated values. An alternative way is to decompose a single image and based on the clear parts the noisy regions are approximated. Huang et al. [HKWL13] propose a self-learning algorithm, which only considers the high frequency parts of the decomposed image. There were several approaches published, where the images is separated is separated spatially instead of in the frequency domain. [XZZ<sup>+</sup>15], [TM13], [CM11] and [GZZL15] are techniques based on the idea of non-local means, where the image is subsampled into tiles and the pixels are set to the mean of regions belongng to the same cluster. The main difference between the previous algorithms is how they classify the image subregions into different classes. Taleby et al. [TM13] uses an iterative shrinkage strategy. Chatterjee et al. [CM11] groups the geometrically similar regions and estimate the noise for every class separately with a Wiener Filter. Whereas Guo et al. [GZZL15] utilize Block Matching to determine the cluster memberships. Additionally the spatial location is also considered while calculating the mean value in a given class. The members are weighted according to the distance to the current region.

### 2.3 Image Description

Similar to the previous Image Enhancement section 2.1 this part is also subdivided into four domains offering solutions for the same problem in different domains. In this section the published image features are described which are proposed to be the most discriminative for their field. Similar topics are reviewd to gain insight about the most powerful descriptors and consider to port them into the domain of this thesis. Shoeprint descriptors are described first, after that fingerprint features are discussed. Following that an overview about tattoo and natural texture descriptors is given at the end.

#### Shoeprint Descriptors

In the research of Shoeprint Identification and more exactly Shoeprint Description the varying difficulty and quality of the different datasets is a continuous issue, therofore the properties of the database the given approach was tested on is noted repeatedly. Signal or frequency domain based image features are popular in both groups of algorithms using synthetic or real samples for testing. Gabor Transform is used in several applications tested on synthetic [PK09], on restricted [KYZ14], [LWS14] and on real forensic data [WWZ19] as well. Patil et al. [PK09] propose to use the Radon transfrom to determine the dominant direction of structures on the print and process the aligned image with the Gabor Transform. Kong et al. [KYZ14] combined the Gabor Feature of the sample with Zernike Features to describe the shapes in the pattern. Li et al. [LWS14] suggest to use the histogram extracted in the Gabor Transform domain as descriptors. In the approach published by Wu et al. [WWZ19] Gabor Filters are combined with Haar Wavelets and Fourier-Mellin Transform to get an integratet, multi-level descriptor. There are other publications along with Wu et al. [WWZ19] where Fourier-Mellin Transfrom is proposed for feature description. Gueham et al. [GBCN08] use the classical Fourier-Mellin

pipeline to compare samples from a synthetic dataset. As Wang et al. [WSYZ14] state, Fourier-Mellin transform allow multi resolution matching, so they apply it successfully on synthetic data. Richetelli et al. [RLL<sup>+</sup>17] classify synthetic shoeprint impressions by applying Fourier-Mellin transform following the calculation of Phase Only Correlation (POC) to determine the translative difference between two images in the frequency domain. Gueham et al. [GBC07] in an other paper suggest to use the basic Fourier transform before calculating the POC. Unlike the approach of Gueham et al. [GBC07], which were only tested on synthetic images, Kortylewsky et al. [KAV14] propose a Fourier Transformation based method for real forensic images. It is an unsupervised learning approach, where the periodic structure on a shoeprint are compared in the Fourier domain. Richetelli et al. [RNBS17] compares Randomly Acquired Characteristics of shoeprints, e.g. small damages, modifications and stuck objects on or in the shoesole pattern, examining their Fourier descriptor. Other than Fourierlike transformations the use of Power Spectral Density was also proposed for a restricted dataset [DCC09]. It is a descriptor for random, broadband signals based on the frequency and power.

In high quality datasets shape descriptors are a popular choice for feature extraction. Algarni et al. [AH08] suggest to use Hu moments because of its robustness against noise, rotation and resolution. For restricted databases it is proposed to combine the feature descriptors, Kong et al. [KYZ14] incorporate Zernike and Gabor features whereas Tang et al. [TSKC10] define their own fundamental shapes based on common basic structures on a shoesole through Hough Line Transform. The extracted features are then stored in an Attributed Relational Graph to represent the entire shoeprint image.

SIFT and Harris Detector are the two most popular point descriptors for matching shoeprint images. Nibouce et al. [NBC<sup>+</sup>09] propose to use a four-level Harris and combine with SIFT on a synthetic database. Almaadeed et al. [ABCN15] use the same combination and the Hessian Detector additionally for the same purpose on a restricted real-life dataset. Another publication [RLL<sup>+</sup>17] extract the SIFT features from the frequency domain after applying Fourier-Mellin Transformation and POC on the input image.

Kong et al. [KSRF17], [KSRF19] define a new descriptor for real database extracting the mid-level features from a Convolutional Neural Network. Wu et al. [WWNZ19] also use machine learning to calculate opinion scores for given matching pairs from real forensic data. In the learning process manifold ranking is used where the opinions of human experts as well as feature similarities are both incorporated. Kortylewsky et al. [KV16] developed hierarchical composition for Active Basis Models for the same real database, FID-300, as used in this thesis, and also extended for natural image environments [KWW<sup>+</sup>19]. Sparse representation was also proposed [AK17] this method however was only tested on synthetic data and not on real forensic dataset.

## Fingerprint Descriptors

Signal domain representations, because of their robustness against rotation, are attractive not only for shoeprint but also for fingerprint description. Multi-resolution representation through Gabor expansion was proposed by Bolle et al. [BCPR12] to get a localized texture descriptor. Van et al. [VVVL16] use Adaptively Adjusted Modified Finite Radon Transform after Gabor filtering to connect edges and eliminate inconsistencies. Rida et al. [RAMM<sup>+</sup>18] propose an ensemble descriptor consisting of Gabor filter, Local Binary Pattern, Histogram of Oriented Gradient (HOG) and Line detector to represent a palmprint impression. Other than that Li et al. [LFLY12] suggest to use Directional Filter Banks along, where the image is separated into eight directions and every subimage is decomposed into two frequencies via wavelet transform.

Unlike in the domain of shoeprint image representation, in case of fingerprint images several point feature descriptors were proposed. In [ZSL<sup>+</sup>11] SIFT features were fused with Hough Transform and Minutiae Information of the fingerprint. Chen et al. [CHZ13] also use the Hough Transform and extends with hierarchical voting score to get better matching information. Along [RAMM<sup>+</sup>18] Ghandehari et al. [GAS12] recommend to use HOG in a 3-level Gaussian pyramid to estimate the local strength of different kind of edges on the image. Jahan et al. [JCI17] suggest to combine the Minutiae Information with Speeded Up Robust Features and compare them with a neural network to find the matching pairs.

For fingerprint description Local Binary Patterns (LBP) are also suitable. As mentioned previously Rida et al. [RAMM<sup>+</sup>18] published a combined feature vector which LBP is also a part of. Wang et al. [WBZL13] modify the usual LBP pipeline with Pixel to Patch sampling to increase the quality of descriptor without slowing down the calculation. In Pixel to Patch sampling the weighted average of the neighboring pixels in a given radius is calculated instead of interpolation. Additionally the Local Neighboring Intensity Relationships based on gray-scale information are also considered.

Sparse representations are popular also for fingerprint description. Rida et al. [RAMM<sup>+</sup>18] stores the hybrid features in that way, whereas Shao et al. [SWY<sup>+</sup>13] represents predefined fingerprint patches, called dictionary atoms, in a sparse way.

## Tattoo Descriptors

For tattoo description three main methods were introduced, signal domain features, point descriptor especially SIFT and shape features and Kim et al. [KPY<sup>+</sup>15] fuses all three of them. For local descriptor the shape context features are used whereas for global descriptor multi-level SIFT and the Fourier Transform is used. Acton et al. [AR08] build an Active Contour Model which consists of a Haar wavelet an HSV histogram and a Fourier Shape Descriptor,

Other than [KPY<sup>+</sup>15] there are multiple publications available, e.g. [DK13], which take advantage on SIFT features for tattoo image description. It is common to combine them

with other shape descriptor to have a more detailed representation. Han et al. [HJ13] fuse Active Shape Models with SIFT, in [YYXK15] SURF is added and in [KLYD16] SIFT is extended with the Local Self Similarity measure. Duangphasuk et al. [DK13] base their approach mainly on shape description and similar to [KPY<sup>+</sup>15] use shape context features for tattoo representation.

## Natural Texture Descriptors


For natural texture description signal domain features and LBPs are frequently used. Mistry et al. [MII17] mix multiple features, mainly color and texture descriptors. For texture description Gabor wavelet and Binarized Statistical Images [KR12] are used simultanously. Hatipoglu et al. [HMK00] suggest to take advantage on dual tree complex wavelet transform instead of Gabor wavelet. Quevedo et al. [QCAC02] and Xu et al. [XJF09] propose to use Fractal features, because they are invariant to intensity and scale changes. Xu et al. [XJF09] propose to use multifractal spectrum to achive robustness against vievpoint changes and non-rigid deformations additionally. Hayati et al. [HA18] and Ahonen et al. [AMHP09] follow the same principle by incorporating LBP-like features whith the frequency domain representation. Ahonen et al. [AMHP09] calculate the LBP of the Fourier features of the image, whereas Hayati et al. [HA18] se wave inference, where the neighborhood information of multiple different-sized asymetric neighborhoods is added respectively.

## 2.4 Classification





CHAPTER 3



# Pattern Enhancement



CHAPTER 4

# Fully Automated Noise Suppression



CHAPTER 5

# Semi-Automated Noise Supression




# CHAPTER 6

## Results and Evaluation






CHAPTER 7



# Future Work



CHAPTER 8



# Conclusion



# Bibliography

- [ABCN15] Somaya Almaadeed, Ahmed Bouridane, Danny Crookes, and Omar Nibouche. Partial shoeprint retrieval using multiple point-of-interest detectors and sift descriptors. *Integrated Computer-Aided Engineering*, 22(1):41–58, 2015.
- [AH08] Gharsa AlGarni and Madina Hamiane. A novel technique for automatic shoeprint image retrieval. *Forensic science international*, 181(1-3):10–14, 2008.
- [AK17] Sayyad Alizadeh and Cemal Kose. Automatic retrieval of shoeprint images using blocked sparse representation. *Forensic science international*, 277:103–114, 2017.
- [Ale96] Girod Alexandre. Computerized classification of the shoeprints of burglars’ soles. *Forensic Science International*, 82(1):59–65, 1996.
- [AMHP09] Timo Ahonen, Jiří Matas, Chu He, and Matti Pietikäinen. Rotation invariant image description with local binary pattern histogram fourier features. In *Scandinavian conference on image analysis*, pages 61–70. Springer, 2009.
- [AR08] Scott T Acton and Adam Rossi. Matching and retrieval of tattoo images: Active contour cbir and glocal image features. In *2008 IEEE Southwest Symposium on Image Analysis and Interpretation*, pages 21–24. IEEE, 2008.
- [BCPR12] Rudolf Maarten Bolle, Sharat Suresh Chikkerur, Sharathchandra Uma-pathirao Pankanti, and Nalini Kanta Ratha. Fingerprint representation using localized texture feature, May 15 2012. US Patent 8,180,121.
- [BHK15] Abir Raza Baig, Ilyas Huqqani, and Khurram Khurshid. Enhancement of latent fingerprint images with segmentation perspective. In *2015 11th International Conference on Signal-Image Technology & Internet-Based Systems (SITIS)*, pages 132–138. IEEE, 2015.
- [BPJH17] Satish Bhairannawar, Apeksha Patil, Akshay Janmane, and Madhuri Huilgol. Color image enhancement using laplacian filter and contrast limited

- adaptive histogram equalization. In *2017 Innovations in Power and Advanced Computing Technologies (i-PACT)*, pages 1–5. IEEE, 2017.
- [CHZ13] Fanglin Chen, Xiaolin Huang, and Jie Zhou. Hierarchical minutiae matching for fingerprint and palmprint identification. *IEEE Transactions on Image Processing*, 22(12):4964–4971, 2013.
- [CM11] Priyam Chatterjee and Peyman Milanfar. Patch-based near-optimal image denoising. *IEEE Transactions on Image Processing*, 21(4):1635–1649, 2011.
- [DCC09] Francesca Dardi, Federico Cervelli, and Sergio Carrato. A texture based shoe retrieval system for shoe marks of real crime scenes. In *International Conference on Image Analysis and Processing*, pages 384–393. Springer, 2009.
- [DCFR05] Philip De Chazal, John Flynn, and Richard B Reilly. Automated processing of shoeprint images based on the fourier transform for use in forensic science. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, (3):341–350, 2005.
- [DK13] Pruegsa Duangphasuk and Werasak Kurutach. Tattoo skin detection and segmentation using image negative method. In *2013 13th International Symposium on Communications and Information Technologies (ISCIT)*, pages 354–359. IEEE, 2013.
- [FJZY11] Jie Feng, LC Jiao, Xiangrong Zhang, and Dongdong Yang. Bag-of-visual-words based on clonal selection algorithm for sar image classification. *IEEE Geoscience and Remote Sensing Letters*, 8(4):691–695, 2011.
- [GAS12] Azadeh Ghandehari, Mohammad Anvaripour, and Sima Soltanpour. Palm-print verification and identification using pyramidal hog feature and fast tree based matching. In *2012 5th IAPR International Conference on Biometrics (ICB)*, pages 421–426. IEEE, 2012.
- [GBC07] Mourad Gueham, Ahmed Bouridane, and Danny Crookes. Automatic recognition of partial shoeprints based on phase-only correlation. In *2007 IEEE International Conference on Image Processing*, volume 4, pages IV–441. IEEE, 2007.
- [GBCN08] Mourad Gueham, Ahmed Bouridane, Danny Crookes, and Omar Nibouche. Automatic recognition of shoeprints using fourier-mellin transform. In *2008 NASA/ESA Conference on Adaptive Hardware and Systems*, pages 487–491. IEEE, 2008.
- [GZZL15] Qiang Guo, Caiming Zhang, Yunfeng Zhang, and Hui Liu. An efficient svd-based method for image denoising. *IEEE transactions on Circuits and Systems for Video Technology*, 26(5):868–880, 2015.

- [HA18] Saeed Hayati and Mohammad Reza Ahmadzadeh. Wirif: Wave interference-based rotation invariant feature for texture description. *Signal Processing*, 151:160–171, 2018.
- [HJ13] Hu Han and Anil K Jain. Tattoo based identification: Sketch to image matching. In *2013 International Conference on Biometrics (ICB)*, pages 1–8. IEEE, 2013.
- [HKWL13] De-An Huang, Li-Wei Kang, Yu-Chiang Frank Wang, and Chia-Wen Lin. Self-learning based image decomposition with applications to single image denoising. *IEEE Transactions on multimedia*, 16(1):83–93, 2013.
- [HMK00] Serkan Hatipoglu, Sanjit K Mitra, and Nick Kingsbury. Image texture description using complex wavelet transform. In *Proceedings 2000 International Conference on Image Processing (Cat. No. 00CH37101)*, volume 2, pages 530–533. IEEE, 2000.
- [JCI17] Sharmin Jahan, Mozammel Chowdhury, and Rafiqul Islam. Robust fingerprint verification for enhancing security in healthcare system. In *2017 International Conference on Image and Vision Computing New Zealand (IVCNZ)*, pages 1–5. IEEE, 2017.
- [KAV14] Adam Kortylewski, Thomas Albrecht, and Thomas Vetter. Unsupervised footwear impression analysis and retrieval from crime scene data. In *Asian conference on computer vision*, pages 644–658. Springer, 2014.
- [KLYD16] Joonsoo Kim, He Li, Jiaju Yue, and Edward J Delp. Tattoo image retrieval for region of interest. In *2016 IEEE Symposium on Technologies for Homeland Security (HST)*, pages 1–6. IEEE, 2016.
- [KPY<sup>+</sup>15] Joonsoo Kim, Albert Parra, Jiaju Yue, He Li, and Edward J Delp. Robust local and global shape context for tattoo image matching. In *2015 IEEE International Conference on Image Processing (ICIP)*, pages 2194–2198. IEEE, 2015.
- [KR12] Juho Kannala and Esa Rahtu. Bsif: Binarized statistical image features. In *Proceedings of the 21st international conference on pattern recognition (ICPR2012)*, pages 1363–1366. IEEE, 2012.
- [KS17] Harshitha Reddy Katireddy and Sreemanth Sidda. A novel shoeprint enhancement method for forensic evidence using sparse representation method., 2017.
- [KSRF17] Bailey Kong, J Supancic, Deva Ramanan, and Charless Fowlkes. Cross-domain forensic shoeprint matching. In *British Machine Vision Conference (BMVC)*, pages 1–5, 2017.

- [KSRF19] Bailey Kong, James Supancic, Deva Ramanan, and Charless C Fowlkes. Cross-domain image matching with deep feature maps. *International Journal of Computer Vision*, pages 1–13, 2019.
- [KV16] Adam Kortylewski and Thomas Vetter. Probabilistic compositional active basis models for robust pattern recognition. In *BMVC*, 2016.
- [KWW<sup>+</sup>19] Adam Kortylewski, Aleksander Wieczorek, Mario Wieser, Clemens Blumer, Sonali Parbhoo, Andreas Morel-Forster, Volker Roth, and Thomas Vetter. Greedy structure learning of hierarchical compositional models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 11612–11621, 2019.
- [KYZ14] Xiangbin Kong, Chunyu Yang, and Fengde Zheng. A novel method for shoeprint recognition in crime scenes. In *Chinese Conference on Biometric Recognition*, pages 498–505. Springer, 2014.
- [FLY12] Chaorong Li, Bo Fu, Jianping Li, and Xingchun Yang. Texture-based fingerprint recognition combining directional filter banks and wavelet. *International Journal of Pattern Recognition and Artificial Intelligence*, 26(04):1256012, 2012.
- [LLGF14] Chaorong Li, Jianping Li, Dapeng Gao, and Bo Fu. Rapid-transform based rotation invariant descriptor for texture classification under non-ideal conditions. *Pattern Recognition*, 47(1):313–325, 2014.
- [LWS14] Xiangyang Li, Minhua Wu, and Zhiping Shi. The retrieval of shoeprint images based on the integral histogram of the gabor transform domain. In *International Conference on Intelligent Information Processing*, pages 249–258. Springer, 2014.
- [MA10] Raman Maini and Himanshu Aggarwal. A comprehensive review of image enhancement techniques. *arXiv preprint arXiv:1003.4053*, 2010.
- [MII17] Yogita Mistry, DT Ingole, and MD Ingole. Content based image retrieval using hybrid features and various distance metric. *Journal of Electrical Systems and Information Technology*, 2017.
- [NBC<sup>+</sup>09] Omar Nibouche, Ahmed Bouridane, Danny Crookes, Mourad Gueham, and Moussadek Laadjel. Rotation invariant matching of partial shoeprints. In *2009 13th International Machine Vision and Image Processing Conference*, pages 94–98. IEEE, 2009.
- [Nil13] Mikael Nilsson. Smqt-based tone mapping operators for high dynamic range images. In *VISAPP (1)*, pages 61–68, 2013.



- [PK09] Pradeep M Patil and Jayant V Kulkarni. Rotation and intensity invariant shoeprint matching using gabor transform with application to forensic science. *Pattern Recognition*, 42(7):1308–1317, 2009.
- [QCAC02] Roberto Quevedo, López-G Carlos, José M Aguilera, and Laura Cadoche. Description of food surfaces and microstructural changes using fractal image texture analysis. *Journal of food engineering*, 53(4):361–371, 2002.
- [RAMM<sup>+</sup>18] Imad Rida, Somaya Al-Maadeed, Arif Mahmood, Ahmed Bouridane, and Sambit Bakshi. Palmprint identification using an ensemble of sparse representations. *IEEE Access*, 6:3241–3248, 2018.
- [RBCP19] Imad Rida, Sambit Bakshi, Xiaojun Chang, and Hugo Proenca. Forensic shoe-print identification: A brief survey. *arXiv preprint arXiv:1901.01431*, 2019.
- [RLCL18] Xutong Ren, Mading Li, Wen-Huang Cheng, and Jiaying Liu. Joint enhancement and denoising method via sequential decomposition. In *2018 IEEE International Symposium on Circuits and Systems (ISCAS)*, pages 1–5. IEEE, 2018.
- [RLL<sup>+</sup>17] Nicole Richetelli, Mackenzie C Lee, Carleen A Lasky, Madison E Gump, and Jacqueline A Speir. Classification of footwear outsole patterns using fourier transform and local interest points. *Forensic science international*, 275:102–109, 2017.
- [RNBS17] Nicole Richetelli, Madonna Nobel, William J Bodziak, and Jacqueline A Speir. Quantitative assessment of similarity between randomly acquired characteristics on high quality exemplars and crime scene impressions via analysis of feature size and shape. *Forensic science international*, 270:211–222, 2017.
- [SK18] Dilbag Singh and Vijay Kumar. Dehazing of outdoor images using notch based integral guided filter. *Multimedia Tools and Applications*, 77(20):27363–27386, 2018.
- [SPV16] Katta Suganya, Suresh Pabboju, and A VinayaBabu. Image enhancement using singular value decomposition. In *2016 International Conference on Research Advances in Integrated Navigation Systems (RAINS)*, pages 1–5. IEEE, 2016.
- [SWY<sup>+</sup>13] Guangqi Shao, Yanping Wu, A Yong, Xiao Liu, and Tiande Guo. Fingerprint compression based on sparse representation. *IEEE transactions on image processing*, 23(2):489–501, 2013.
- [TM13] Hossein Talebi and Peyman Milanfar. Global image denoising. *IEEE Transactions on Image Processing*, 23(2):755–768, 2013.

- [TSKC10] Yi Tang, Sargur N Srihari, Harish Kasiviswanathan, and Jason J Corso. Footwear print retrieval system for real crime scene marks. In *International workshop on computational forensics*, pages 88–100. Springer, 2010.
- [VVVL16] Hoang Thien Van, Giang Van Vu, and Thai Hoang Le. Fingerprint enhancement for direct grayscale minutiae extraction by combining mfrat and gabor filters. In *Proceedings of the Seventh Symposium on Information and Communication Technology*, pages 360–367. ACM, 2016.
- [WBZL13] Kai Wang, Charles-Edmond Bichot, Chao Zhu, and Bailin Li. Pixel to patch sampling structure and local neighboring intensity relationship patterns for texture classification. *IEEE Signal Processing Letters*, 20(9):853–856, 2013.
- [WLWL14] Jing-Wein Wang, Ngoc Tuyen Le, Chou-Chen Wang, and Jiann-Shu Lee. Enhanced ridge structure for improving fingerprint image quality based on a wavelet domain. *IEEE Signal Processing Letters*, 22(4):390–394, 2014.
- [WSYZ14] Xinnian Wang, Huihui Sun, Qing Yu, and Chi Zhang. Automatic shoeprint retrieval algorithm for real crime scenes. In *Asian Conference on Computer Vision*, pages 399–413. Springer, 2014.
- [WWNZ19] Yanjun Wu, Xinnian Wang, Namusisi Linda Nankabirwa, and Tao Zhang. Logsr: Learned opinion score guided shoeprint retrieval. *IEEE Access*, 7:55073–55089, 2019.
- [WWZ19] Yanjun Wu, Xinnian Wang, and Tao Zhang. Crime scene shoeprint retrieval using hybrid features and neighboring images. *Information*, 10(2):45, 2019.
- [XJF09] Yong Xu, Hui Ji, and Cornelia Fermüller. Viewpoint invariant texture description using fractal analysis. *International Journal of Computer Vision*, 83(1):85–100, 2009.
- [XWYH16] Xiaojun Xu, Youren Wang, Guoshi Yang, and Yanli Hu. Image enhancement method based on fractional wavelet transform. In *2016 IEEE International Conference on Signal and Image Processing (ICSIP)*, pages 194–197. IEEE, 2016.
- [XZZ<sup>+</sup>15] Jun Xu, Lei Zhang, Wangmeng Zuo, David Zhang, and Xiangchu Feng. Patch group based nonlocal self-similarity prior learning for image denoising. In *Proceedings of the IEEE international conference on computer vision*, pages 244–252, 2015.
- [YYXK15] Huang Yi, Peicong Yu, Xingpeng Xu, and Adams Wai Kin Kong. The impact of tattoo segmentation on the performance of tattoo matching. In *2015 IEEE International WIE Conference on Electrical and Computer Engineering (WIECON-ECE)*, pages 43–46. IEEE, 2015.

- [YZL<sup>+</sup>16] Zhijun Yao, Quan Zhou, Zhongyuan Lai, Zhiming Ren, and Liming Liu. Image enhancement based on bi-histogram equalization with non-parametric modified technology. In *2016 IEEE 22nd International Conference on Parallel and Distributed Systems (ICPADS)*, pages 1211–1215. IEEE, 2016.
- [ZA05] Lin Zhang and Nigel Allinson. Automatic shoeprint retrieval system for use in forensic investigations. In *UK workshop on computational intelligence*, volume 99, pages 137–142, 2005.
- [ZSL<sup>+</sup>11] Ru Zhou, SangWoo Sin, Dongju Li, Tsuyoshi Isshiki, and Hiroaki Kunieda. Adaptive sift-based algorithm for specific fingerprint verification. In *2011 International Conference on Hand-Based Biometrics*, pages 1–6. IEEE, 2011.
- [ZSP<sup>+</sup>16] Liang Zhang, Peiyi Shen, Xilu Peng, Guangming Zhu, Juan Song, Wei Wei, and Houbing Song. Simultaneous enhancement and noise reduction of a single low-light image. *IET Image Processing*, 10(11):840–847, 2016.
- [ZZSZ13] Wangmeng Zuo, Lei Zhang, Chunwei Song, and David Zhang. Texture enhanced image denoising via gradient histogram preservation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1203–1210, 2013.