Mac OSX Manual Installation Guide

Overview:

About *Lexos*

Lexos is an integrated workflow of tools to facilitate computational text analysis, presented in a web-based interface. Lexos is written primarily in Python 2.7.11 using the *Flask* microframework, based on Werkzeug and Jinja 2. A heavy dose of Javascript and CSS is included on the front-end. We increasingly incorporate the wiz from *D3.js* in our visualizations and the power in the *scikit-learn* modules for text and statistical processing.

Installing Python and Anaconda

If you do not already have Python v2.7 installed on your computer, we recommend installing it through the free Anaconda distribution.[1] If you already have Python, Anaconda will run alongside your current installation.

1. Visit the Anaconda downloads page on the web: http://continuum.io/downloads. Locate the **Jump to:** on the screen; click on the **OSX** link.
2. Download the **MAC OS X 64-bit Graphical Installer** by clicking on the blue button.

3. Double-click the installer application icon (it will be called something like `Anaconda2-4.1.1-MacOSX-x86_64.pkg`) and follow the instructions on the screen.
4. When the process is complete, select **Finish** to finish the installation of Anaconda.

You should now verify that we have installed it correctly. To this follow the instructions below:

---

[1] Anaconda is a free distribution of the Python programming language for large-scale data processing, predictive analytics, and scientific computing, that aims to simplify package management and deployment. As of June 2016, Anaconda includes 820+ of the most popular Python packages, including most of the packages needed for *Lexos*.

1. Open a terminal window. If you are unfamiliar with how to access a terminal window, search for "terminal" in Spotlight. You should see a window appear with a command-line prompt, typically a `$`.
2. 2. Type `python -V` and hit the `Enter` key.

You should see a response that looks like: `Python 2.7.12 :: Anaconda 4.1.1 (64-bit)`. If you do not see `:: Anaconda 4.1.1` then you did not update your PATH variable during the Anaconda installation. We recommend that you uninstall Anaconda and try to install it again, following the instructions above. To uninstall Anaconda, type `rm -rf ~/anaconda2`, replacing `anaconda2` with the name of the Anaconda directory, if it is different. Hit the `Enter` key.

Installing Additional Python Packages

You must now install three additional Python packages needed to run *Lexos*. 1. Begin my making sure that your package installer (pip) is up to date. Type `pip install -U pip` and hit the `Enter` key. Your terminal window will display some information showing you the update process. Once that is completed, you can now use 'pip' (python package installer) in the next step. 2. Type the following three commands, hitting the `Enter` key after each one. The installation process for each may take some time.

```
pip install gensim
```

```
pip install chardet
```

```
pip install natsort
```

When the last installation is finished, you are ready to download *Lexos*.

Downloading and Extracting *Lexos*

To download *Lexos*, enter https://github.com/WheatonCS/Lexos/archive/master.zip in your browser's address bar. Alternatively, go to the *Lexos* GitHub page: https://github.com/WheatonCS/Lexos. Click the green **Clone or download** button on the right side of the screen; then click the **Download Zip** button.

Once the *Lexos* zip archive has downloaded, right-click on the zip icon, and select **Open With > Archive Utility**. Choose where you would like to install *Lexos*. If you wish, you may change the name of the extracted folder from `Lexos-master` to `Lexos`. In the instructions below, we will assume that you did this and that you extracted the `Lexos` folder to the Desktop.

Starting and Launching *Lexos*

Important: Close your current terminal window and open a new one.

In most cases, the terminal window will open in your computer's user account directory. It will show your location by displaying something like `/users/YOUR_NAME`. If the command prompt

says something else, you may need to navigate to this folder. For help with navigation using the command line, check out this article by *Macworld* http://www.macworld.com/article/2042378/master-the-command-line-navigating-files-and-folders.htm.

Now navigate to the `Lexos` folder by typing `cd Desktop/Lexos` and hit the `Enter` key. If you encounter an error, make sure that you are starting in your user account folder, that the Lexos folder is on the Desktop, and that it is called `Lexos`. The terminal should now display something liken `/users/YOUR_NAME/Desktop`.

Type `python lexos.py` and hit the `Enter` key. This will start *Lexos*. It may take a minute to see a response the first time you run the command because Python has to reconfigure some of the project files for your computer. But shortly after you should see the following:

```
Restarting with stat
Debugger is active!
Debugger pin code: 236-087-009
Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
```

Important: Keep the `python lexos.py` command running while you use *Lexos*. You may minimize the terminal window, but do not close it.

Once you see the message above, you are ready to launch *Lexos*. Go to a web browser and enter `localhost:5000` in the address bar. We recommend using either Firefox or Chrome (other browsers are not supported and may not work with *Lexos*). You will soon see the *Lexos* upload page. For information about using *Lexos*, click the "Gear" icon at the top right of the screen.

Note: Because your computer is acting as both the web server and the user of *Lexos*, you may need to hit the **Reset** button in the top right corner of the **Upload** page to make sure files from any previous sessions are purged.

Note: We've noticed on that some versions of Mac OS X do not have the character encoding set to UTF-8, thus they got an error on this step. Here is a fix that has worked for us:

1. Type `cd` and hit `Enter`.
2. Using an editor of your choice, edit the file `.bash_profile`. For instance, if using "open", type `open .bash_profile`.
3. Add the following lines and then save the file (**Command+s**).

   ```
   export LC_ALL=en_US.UTF-8
   export LANG_=en_US.UTF-8
   ```

4. Return to the `Lexos` directory and restart *Lexos* by entering the following commands.

   ```
   cd
   cd Desktop/Lexos
   python lexos.py
   ```

Quitting *Lexos*

To quit *Lexos* simply close your browser window and close the terminal window running `python lexos.py`.

Last edited: August 20, 2016