

STEM Digital Academy

School of Science & Technology

ID and CLASS Attributes

Web Technologies



Lecture by
Dr Elahe Kani-Zabihi

```
<!doctype html>
<html>
   <head>
     <title>
       Web Technologies
     </title>
     <style>
        р
         color: ■blue;
     </style>
     <script>
     console.log("client-side");
     </script>
   </head>
   <body>
       >
           Welcome!
       </body>
</html>
```



What we will cover

- HTML ID and CLASS attributes
- CSS ID and CLASS selectors
- CSS basic selectors





HTML - ID Attribute

- Uniquely identifies an element
- The value is optional, but the name should be unique and not be repeated



ID Attributes in HTML

```
  Lorem ipsum dolor sit amet, consectetur adipiscing elit.
  Vestibulum neque dolor, efficitur tristique aliquet at,
  consectetur sollicitudin nulla.

<h2 >This is the subheading for the first title</h2>

  In nec egestas sapien. Sed viverra vel ipsum sit amet rho
  malesuada sit amet erat at, interdum finibus mauris. Aene
  egestas suscipit ex euismod. Praesent et tincidunt mauris
```



CSS selector for ID

HTML – ID attribute for


```
  Lorem ipsum dolor sit
  Vestibulum neque dolor
  consectetur sollicitud
```

2. CSS selector for ID

```
p {
    color:green;
    font-style: italic;
}
#initial {
    font-style: normal;
}
```



The Web Page in a Browser







HTML - CLASS Attribute

- All elements can have a CLASS attribute
- The value of a CLASS can be repeated
- Uniquely identifies a group of elements



CLASS Attribute in HTML



CSS Selector for Class

1. HTML – CLASS attribute for and <h1>


```
<h1 class="group_colour">This is my t:


  Lorem ipsum dolor sit amet, consecte
  Vestibulum neque dolor, efficitur to
  consectetur sollicitudin nulla.
```


2. CSS selector for CLASS

```
h1 {color: blue;}
p {color: green;
font-style: italic;}
.group_colour {
  color: brown;
}
```












CSS Selectors

- Type selects the elements in the HTML code
- ID selects the value of ID attributes
- CLASS selects the value of
 CLASS attributes
- Universal selects all HTML elements





CSS Style Rules that Select by Type


```
body {
  background-color: orange;
h1 {
  color: blue;
  color:green;
 font-style: italic;
```




CSS Style Rule that Selects by ID

```
#random {
  font-size: xx-large;
                   <h1>The second page title</h1>
                   >
                       Suspendisse commodo mauris eu lobortis ornare.
                       Fusce varius, massa efficitur scelerisque fring
                       sem risus placerat lacus, at imperdiet quam dui
                       Sed non aliquet elit.
                   <h2 id="random"> The second page heading 2 </h2>
```











CSS Style Rule that selects by Class

```
.focus {
  text-align: center;
   <h2 id="random" class="focus"> The second page heading 2 </h2>
   Suspendisse commodo mauris eu lobortis ornare.
       Fusce varius, massa efficitur scelerisque fringilla,
       sem risus placerat lacus, at imperdiet quam dui nec elit.
       Sed non aliquet elit.
```











CSS Style Rule that Selects All Elements

Universal – selects all HTML elements

```
* {
   text-align: center;
}
```









Try It Yourself

In this activity you can practice how to use

CSS ID and CLASS attribute and selector. So:

- 1. Add the ID attribute to one of your elements for headings or paragraph in your HTML file.
- 2. In your CSS add the ID selector to apply different font-style.
- 3. Save and run the HTML file in your web browser.
- 4. Add the CLASS attributes to a heading and paragraph in your HTML file.
- 5. In your CSS add the CLASS selector to apply a different colour.
- 6. Save and run the HTML file in your web browser.

