

✓ Traditional features construction

Feature extraction from EACH image from the training data using image feature descriptor SIFT (Scale-invariant feature transform) (see https://docs.opencv.org/4.x/da/df5/tutorial_py_sift_intro.html) with 128 dimensions for each keypoint (Note that you should obtain many keypoints from each image). Plot the keypoints on one image from your training dataset (see Fig 1 for one such figure). (0.5 point)

```
import numpy as np
import cv2 as cv
from IPython.display import Image, display

# Read the image
img = cv.imread('/content/drive/MyDrive/TrainingImages/Apple Golden 1/0_100.jpg')

# Convert the image to grayscale
gray = cv.cvtColor(img, cv.COLOR_BGR2GRAY)

# Initialize the SIFT detector with 180 keypoints
sift = cv.SIFT_create(nfeatures=180)

# Detect keypoints
kp = sift.detect(gray, None)

# Draw keypoints on the original image
img_with_keypoints = cv.drawKeypoints(gray, kp, img)

# Save the image with keypoints
cv.imwrite('sift_keypoints.jpg', img_with_keypoints)

# Display the image
display(Image('sift_keypoints.jpg'))
```



Create a new keypoints dataset K that consists of all the keypoints from all the training images.

Perform K-mean clustering such that $K = 100$ on KP .

Use the learned K-mean clusters (see <https://scikit-learn.org/stable/modules/clustering.html>) to construct a 100-D vector for each image.

Example: For Image A, we have 20 keypoints in Cluster 1 and 10 keypoints in cluster 2, and no keypoints in the other clusters, then the vector representing Image A is (20,10,0,0,...,0,0)

Create a new 100-D dataset D consisting of vectors constructed from the training images.

```

from sklearn.cluster import KMeans
import cv2 as cv
import numpy as np
import os

# Initialize an empty list to store keypoints and labels
KP = []
labels = []

# List of directories containing your training images
dir_paths = ['/content/drive/MyDrive/TrainingImages/Apple Golden 1',
             '/content/drive/MyDrive/TrainingImages/Apple Red 1',
             '/content/drive/MyDrive/TrainingImages/Apple Red Delicious',
             '/content/drive/MyDrive/TrainingImages/Avocado',
             '/content/drive/MyDrive/TrainingImages/Ginger Root',
             '/content/drive/MyDrive/TrainingImages/Limes',
             '/content/drive/MyDrive/TrainingImages/Maracuja',
             '/content/drive/MyDrive/TrainingImages/Papaya',
             '/content/drive/MyDrive/TrainingImages/Potato Red',
             '/content/drive/MyDrive/TrainingImages/Rambutan'
             # Add more directory paths as needed
            ]

# Initialize SIFT detector
sift = cv.SIFT_create()

# Initialize a list to store the image vectors
image_vectors = []

# Initialize KMeans with the desired number of clusters
kmeans = KMeans(n_clusters=100)

# Loop through each directory
for label, dir_path in enumerate(dir_paths):
    # Loop through each image file in the directory
    for filename in os.listdir(dir_path):
        # Read the image
        img = cv.imread(os.path.join(dir_path, filename))
        # Convert the image to grayscale
        gray = cv.cvtColor(img, cv.COLOR_BGR2GRAY)
        # Detect keypoints
        kp = sift.detect(gray, None)
        # Append keypoints to list
        KP.append(kp)
        # Append label to the labels list
        labels.append(label)

# Fit KMeans to keypoints
kmeans.fit(np.concatenate([np.array([kp.pt for kp in kp]) for kp in KP]))

# Loop through each directory again to extract features
for label, dir_path in enumerate(dir_paths):
    # Loop through each image file in the directory
    for filename in os.listdir(dir_path):
        # Read the image
        img = cv.imread(os.path.join(dir_path, filename))
        # Convert the image to grayscale
        gray = cv.cvtColor(img, cv.COLOR_BGR2GRAY)
        # Detect keypoints
        kp = sift.detect(gray, None)
        # Get cluster labels for the keypoints of this image
        image_labels = kmeans.predict(np.array([kp.pt for kp in kp]))
        # Count the occurrences of each cluster label
        cluster_counts = np.bincount(image_labels, minlength=100)
        # Append the cluster counts to the list of image vectors
        image_vectors.append(cluster_counts)

# Convert the list of image vectors to a numpy array
image_vectors_array = np.array(image_vectors)

# Ensure each vector follows the specified structure
for i in range(len(image_vectors_array)):
    # Find the indices where the count is nonzero
    nonzero_indices = np.nonzero(image_vectors_array[i])[0]
    # Create a new vector with counts only at those indices
    new_vector = np.zeros_like(image_vectors_array[i])
    new_vector[nonzero_indices] = image_vectors_array[i][nonzero_indices]
    # Replace the original vector with the new one
    image_vectors_array[i] = new_vector

# Convert the list of labels to a numpy array
labels_array = np.array(labels)

```

```
# Print an example vector
example_vector = image_vectors_array[0]
print("Example vector representing Image A:", example_vector)
```

```
# Print the shape of the dataset D
print("Shape of dataset D:", image_vectors_array.shape)
```

```
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 'auto' in 1.4. Set the value of `n_init` explicitly to suppress the warning
  warnings.warn(
Example vector representing Image A: [1 0 0 0 0 0 1 1 0 0 1 2 0 4 0 0 0 1 2 0 0 1 1 1 2 0 0 1 1 2 0 2 2 0 0 0 0
 2 1 0 1 0 0 0 1 0 0 1 0 1 0 2 0 1 0 0 0 0 0 0 2 0 0 4 0 0 0 0 1 0 0 0 1 0
 2 1 0 1 3 1 0 1 1 0 2 0 0 0 1 0 0 0 0 1 0 2 0 2 0 1]
Shape of dataset D: (4665, 100)
```

Dimensionality reduction(using Principal Component Analysis,PCA)(see<https://scikit-learn.org/stable/modules/generated/sklearn.decomposition.PCA.html> for PCA. [https:// scikit-learn.org/stable/auto_examples/decomposition/plot_pca_iris.html](https://scikit-learn.org/stable/auto_examples/decomposition/plot_pca_iris.html) for code example.)

i. Perform Principal Component Analysis (PCA) dimensionality reduction Dataset D to 2 dimensions. (Note: You should not use the class labels)

ii. Plot the 2D points using 10 different colors/symbols for data from the 10 classes (see Figure 2 for an example of the plot without normalization).(1 point)

```

from sklearn.decomposition import PCA
import matplotlib.pyplot as plt
import os

# List of directories containing your training images
train_dir_paths = ['/content/drive/MyDrive/TrainingImages/Apple Golden 1',
                   '/content/drive/MyDrive/TrainingImages/Apple Red 1',
                   '/content/drive/MyDrive/TrainingImages/Apple Red Delicious',
                   '/content/drive/MyDrive/TrainingImages/Avocado',
                   '/content/drive/MyDrive/TrainingImages/Ginger Root',
                   '/content/drive/MyDrive/TrainingImages/Limes',
                   '/content/drive/MyDrive/TrainingImages/Maracuja',
                   '/content/drive/MyDrive/TrainingImages/Papaya',
                   '/content/drive/MyDrive/TrainingImages/Potato Red',
                   '/content/drive/MyDrive/TrainingImages/Rambutan']

# Initialize a list to store the image vectors
train_image_vectors = []
# Initialize a list to store the corresponding class labels
train_labels = []


# Loop through each directory
for label, dir_path in enumerate(train_dir_paths):
    # Loop through each image file in the directory
    for filename in os.listdir(dir_path):
        # Read the image
        img = cv.imread(os.path.join(dir_path, filename))
        # Convert the image to grayscale
        gray = cv.cvtColor(img, cv.COLOR_BGR2GRAY)
        # Detect keypoints
        kp = sift.detect(gray, None)
        # Get cluster labels for the keypoints of this image
        image_labels = kmeans.predict(np.array([kp.pt for kp in kp]))
        # Count the occurrences of each cluster label
        cluster_counts = np.bincount(image_labels, minlength=100)
        # Append the cluster counts to the list of image vectors
        train_image_vectors.append(cluster_counts)
        # Assign class label based on folder name
        train_labels.append(os.path.basename(dir_path))

# Convert the lists to numpy arrays
train_image_vectors_array = np.array(train_image_vectors)
train_labels_array = np.array(train_labels)

# Perform PCA dimensionality reduction to 2 dimensions
pca = PCA(n_components=2)
D_pca = pca.fit_transform(train_image_vectors_array)

# Plot the 2D points with different colors/symbols for each class
plt.figure(figsize=(10, 6))
for label in np.unique(train_labels_array):
    class_indices = np.where(train_labels_array == label)[0]
    plt.scatter(D_pca[class_indices, 0], D_pca[class_indices, 1], label=f'{label}', alpha=0.7)
plt.xlabel('Principal Component 1')
plt.ylabel('Principal Component 2')
plt.title('PCA Dimensionality Reduction of Training Dataset')
plt.legend()
plt.xlim(-10, 10)
plt.ylim(-10, 10)
plt.show()

```



✓ “Traditional” Machine Learning Model - Support Vector Machine (SVM)

(a) We perform model selection to learn a linear SVM (see <https://scikit-learn.org/stable/modules/generated/sklearn.svm.SVC.html>) prediction model (i.e., kernel = 'linear').

(b) Train the SVM model using different C parameters. In particular, you will use the following values: 0.01, 0.1, 1.0, 10, 100.

(c) Plot a graph to show the SVM performance on the training data and test data similar to

(d) Repeat Step (b) and (c) for kernel = 'rbf', 'poly', 'sigmoid'. (2 points - include 0.5 for linear kernel.)

(e) Plot a graph to compare the best performance for SVM using the four kernels on the training data and test data similar to Figure 4 (note that you identify the best results for each kernel from results in Step (d))

✓ First, performing the same steps on testing data to create testing dataset

Combine all the keypoints from all the testing images into a single dataset.

Use the 100 cluster centers obtained from the training data to create a 100D vector for each test image.

Process the test images into the test dataset.

This code will create the test_image_vectors_array with the features obtained using the cluster centers obtained from the training data.

```

# List of directories containing your testing images
test_dir_paths = ['/content/drive/MyDrive/TestingImages/Apple Golden 1',
                  '/content/drive/MyDrive/TestingImages/Apple Red 1',
                  '/content/drive/MyDrive/TestingImages/Apple Red Delicious',
                  '/content/drive/MyDrive/TestingImages/Avocado',
                  '/content/drive/MyDrive/TestingImages/Ginger Root',
                  '/content/drive/MyDrive/TestingImages/Limes',
                  '/content/drive/MyDrive/TestingImages/Maracuja',
                  '/content/drive/MyDrive/TestingImages/Papaya',
                  '/content/drive/MyDrive/TestingImages/Potato Red',
                  '/content/drive/MyDrive/TestingImages/Rambutan',
                  # Add more directory paths as needed
                  ]

# Initialize an empty list to store keypoints for testing data
test_KP = []

# Initialize a list to store the image vectors for testing data
test_image_vectors = []

# Initialize a list to store the labels for testing data
test_labels = []

# Loop through each directory for testing data
for label, dir_path in enumerate(test_dir_paths):
    # Loop through each image file in the directory
    for filename in os.listdir(dir_path):
        # Read the image
        img = cv.imread(os.path.join(dir_path, filename))

        # Convert the image to grayscale
        gray = cv.cvtColor(img, cv.COLOR_BGR2GRAY)

        # Detect keypoints
        kp = sift.detect(gray, None)

        # Append keypoints to the test_KP dataset
        test_KP.extend(kp)

        # Get cluster labels for the keypoints of this image for testing data
        image_labels = kmeans.predict(np.array([kp.pt for kp in kp]))

        # Count the occurrences of each cluster label
        cluster_counts = np.bincount(image_labels, minlength=100)

        # Append the cluster counts to the list of image vectors for testing data
        test_image_vectors.append(cluster_counts)

        # Append label to the test_labels list
        test_labels.append(label)

# Convert the list of keypoints to an array for testing data
test_KP_array = np.array([kp.pt for kp in test_KP])

# Convert the list of image vectors to a numpy array for testing data
test_image_vectors_array = np.array(test_image_vectors)

# Convert the list of labels to a numpy array for testing data
test_labels_array = np.array(test_labels)

# Ensure each vector follows the specified structure for testing data
for i in range(len(test_image_vectors_array)):
    # Find the indices where the count is nonzero
    nonzero_indices = np.nonzero(test_image_vectors_array[i])[0]
    # Create a new vector with counts only at those indices
    new_vector = np.zeros_like(test_image_vectors_array[i])
    new_vector[nonzero_indices] = test_image_vectors_array[i][nonzero_indices]
    # Replace the original vector with the new one for testing data
    test_image_vectors_array[i] = new_vector

# Print an example vector for testing data
example_vector_test = test_image_vectors_array[0] # Assuming the first image is Image A
print("Example vector representing Image A for testing data:", example_vector_test)

# Print the shape of the testing dataset D
print("Shape of testing dataset D:", test_image_vectors_array.shape)

Example vector representing Image A for testing data: [2 0 1 2 0 1 0 0 0 4 2 0 0 1 0 2 0 0 2 0 1 0 1 0 3 2 0 0 1 1 4 0 0 0 0 0 2
0 0 0 0 0 3 0 0 1 0 1 1 0 0 1 0 0 0 0 1 0 2 0 0 0 0 0 0 2 0 0 0 0 0 1 0 2
0 1 1 0 0 1 7 0 0 1 0 0 3 0 0 1 0 2 2 0 1 0 0 0 0 0]
Shape of testing dataset D: (1542, 100)

```

✓ Now, we train the model and test it (using classes from the training images as labels)

The below code uses the default kernel function for the Support Vector Classifier (SVC) in scikit-learn, which is the Radial Basis Function (RBF) kernel.

```
from sklearn.svm import SVC
from sklearn.metrics import accuracy_score
import matplotlib.pyplot as plt

# Define C values
C_values = [0.01, 0.1, 1.0, 10, 100]

# Initialize dictionaries to store results
train_scores = {}
test_scores = {}

# Train SVM models for different C values
for C in C_values:
    # Initialize SVM model
    svm_model = SVC(C=C)

    # Train the model
    svm_model.fit(image_vectors_array, labels_array)

    # Predictions on training data
    train_predictions = svm_model.predict(image_vectors_array)

    # Accuracy on training data
    train_accuracy = accuracy_score(labels_array, train_predictions)
    train_scores[C] = train_accuracy

    # Predictions on testing data
    test_predictions = svm_model.predict(test_image_vectors_array)

    # Accuracy on testing data
    test_accuracy = accuracy_score(test_labels_array, test_predictions)
    test_scores[C] = test_accuracy

# Print the results
for C in C_values:
    print(f"C Value: {C}")
    print(f"Training Accuracy: {train_scores[C]:.4f}")
    print(f"Testing Accuracy: {test_scores[C]:.4f}")
    print()

import matplotlib.pyplot as plt

# Calculate error rates
train_errors = [1 - train_scores[C] for C in C_values]
test_errors = [1 - test_scores[C] for C in C_values]

# Plotting
plt.figure(figsize=(5, 3))
plt.plot(np.log(C_values), train_errors, marker='o', label='Training Error', color='blue')
plt.plot(np.log(C_values), test_errors, marker='o', label='Test Error', color='red')
plt.xlabel('Log of C Values')
plt.ylabel('Error Rate')
plt.title('SVM Performance on Training and Test Data')
plt.grid(True)
plt.legend()
plt.show()
```


C Value: 0.01
Training Accuracy: 0.2114
Testing Accuracy: 0.2122

C Value: 0.1
Training Accuracy: 0.8821
Testing Accuracy: 0.8971

C Value: 1.0
Training Accuracy: 0.9919
Testing Accuracy: 0.9946

C Value: 10
Training Accuracy: 1.0000
Testing Accuracy: 1.0000

C Value: 100
Training Accuracy: 1.0000
Testing Accuracy: 1.0000



In the context of Support Vector Machines (SVM), C values represent the regularization parameter.

Regularization is a technique used to prevent overfitting by adding a penalty term to the loss function. In SVM, the parameter C controls the trade-off between maximizing the margin (decision boundary) and minimizing the classification error.

A small C value allows for a larger margin but may misclassify some points (soft margin). A large C value penalizes misclassifications heavily, potentially resulting in a smaller margin (hard margin).

In essence, C values determine the balance between achieving a low training error and generalizing well to unseen data.

We repeat for kernel = 'linear', 'RBF', 'poly', 'sigmoid'

```
import numpy as np
import matplotlib.pyplot as plt
from sklearn.svm import SVC
from sklearn.metrics import accuracy_score

# Define C values
C_values = [0.01, 0.1, 1.0, 10, 100]

# Define kernel functions
kernel_functions = ['linear', 'rbf', 'poly', 'sigmoid']

# Initialize dictionaries to store results
train_errors = {kernel: [] for kernel in kernel_functions}
test_errors = {kernel: [] for kernel in kernel_functions}
train_accuracies = {kernel: [] for kernel in kernel_functions}
test_accuracies = {kernel: [] for kernel in kernel_functions}
best_test_errors = {kernel: float('inf') for kernel in kernel_functions}
best_train_errors = {kernel: float('inf') for kernel in kernel_functions}
best_C_values = {kernel: None for kernel in kernel_functions}

# Train SVM models for different kernel functions and C values
for kernel in kernel_functions:
    for C in C_values:
        # Initialize SVM model
        svm_model = SVC(kernel=kernel, C=C)
        # Train the model
        svm_model.fit(train_image_vectors_array, train_labels_array)
        # Predictions on training data
        train_predictions = svm_model.predict(train_image_vectors_array)
        # Error rate on training data
        train_error = 1.0 - accuracy_score(train_labels_array, train_predictions)
        # Accuracy on training data
        train_accuracy = accuracy_score(train_labels_array, train_predictions)
```



```

# Predictions on testing data
test_predictions = svm_model.predict(test_image_vectors_array)
# Error rate on testing data
test_error = 1.0 - accuracy_score(test_labels_array, test_predictions)
# Accuracy on testing data
test_accuracy = accuracy_score(test_labels_array, test_predictions)
# Store errors and accuracies
train_errors[kernel].append(train_error)
test_errors[kernel].append(test_error)
train_accuracies[kernel].append(train_accuracy)
test_accuracies[kernel].append(test_accuracy)
# Update best errors and corresponding C value for this kernel
if test_error < best_test_errors[kernel]:
    best_test_errors[kernel] = test_error
    best_train_errors[kernel] = train_error
    best_C_values[kernel] = C

# Print performance of each kernel with each C value
for kernel in kernel_functions:
    print(f"Kernel: {kernel}")
    for i, C in enumerate(C_values):
        print(f"C value: {C}, Training Accuracy: {train_accuracies[kernel][i]}, Testing Accuracy: {test_accuracies[kernel][i]}, Train Error: {train_errors[kernel][i]}, Test Error: {test_errors[kernel][i]}")
    print()

# Plotting
plt.figure(figsize=(15, 5))

# Plot test error rates corresponding to the best C values for each kernel
for i, kernel in enumerate(kernel_functions, start=1):
    plt.subplot(1, len(kernel_functions), i)
    plt.plot(np.log(C_values), test_errors[kernel], marker='o', label='Test Error', color='red')
    plt.plot(np.log(C_values), train_errors[kernel], marker='o', label='Train Error', color='blue')
    plt.xlabel('Log of C Values')
    plt.ylabel('Error Rate')
    plt.title(f'Error Rates with {kernel} Kernel')
    plt.grid(True)
    if i == 1:
        plt.legend()

plt.tight_layout()
plt.show()

# Plotting best test and train errors corresponding to best C values for each kernel
plt.figure(figsize=(10, 5))
for kernel in kernel_functions:
    plt.scatter([kernel], [best_test_errors[kernel]], color='blue', marker='o', label='Best Test Error' if kernel == 'linear' else None, s=100)
    plt.scatter([kernel], [best_train_errors[kernel]], color='red', marker='o', label='Best Train Error' if kernel == 'linear' else None, s=100)
    plt.text(kernel, best_test_errors[kernel], f'C={best_C_values[kernel]}, Test Error={best_test_errors[kernel]}', ha='center', va='bottom')
    plt.text(kernel, best_train_errors[kernel], f'C={best_C_values[kernel]}, Train Error={best_train_errors[kernel]}', ha='center', va='bottom')
plt.xlabel('Kernel')
plt.ylabel('Error Rate')
plt.title('Best Test and Train Error for Each Kernel')
plt.grid(True)
plt.legend()
plt.show()

```

Kernel: linear
 C value: 0.01, Training Accuracy: 0.9343515541264737, Testing Accuracy: 0.9196141479099679, Train Error: 0.06564844587352625, Test Error: 0.08038585209003213
 C value: 0.1, Training Accuracy: 0.9681136120042872, Testing Accuracy: 0.9121114683815649, Train Error: 0.03188638799571275, Test Error: 0.08788853161843513
 C value: 1.0, Training Accuracy: 0.9951768488745981, Testing Accuracy: 0.8981779206859593, Train Error: 0.004823151125401881, Test Error: 0.10182207931404075
 C value: 10, Training Accuracy: 0.9997320471596999, Testing Accuracy: 0.9013933547695605, Train Error: 0.000267952840300123, Test Error: 0.0986066452304395
 C value: 100, Training Accuracy: 1.0, Testing Accuracy: 0.9013933547695605, Train Error: 0.0, Test Error: 0.0986066452304395

Kernel: rbf
 C value: 0.01, Training Accuracy: 0.14817792068595928, Testing Accuracy: 0.13933547695605572, Train Error: 0.8518220793140407, Test Error: 0.8606645230439443
 C value: 0.1, Training Accuracy: 0.8579849946409432, Testing Accuracy: 0.8263665594855305, Train Error: 0.14201500535905676, Test Error: 0.1736334405144695
 C value: 1.0, Training Accuracy: 0.990085744908896, Testing Accuracy: 0.969989281886388, Train Error: 0.009914255091103996, Test Error: 0.030010718113612
 C value: 10, Training Accuracy: 1.0, Testing Accuracy: 0.9742765273311897, Train Error: 0.0, Test Error: 0.025723472668810254
 C value: 100, Training Accuracy: 1.0, Testing Accuracy: 0.9732047159699893, Train Error: 0.0, Test Error: 0.026795284030010746

Kernel: poly
 C value: 0.01, Training Accuracy: 0.2765273311897106, Testing Accuracy: 0.2679528403001072, Train Error: 0.7234726688102894, Test Error: 0.7320471596998928
 C value: 0.1, Training Accuracy: 0.6712218649517685, Testing Accuracy: 0.6216505894962486, Train Error: 0.3287781350482315, Test Error: 0.37834941050375137
 C value: 1.0, Training Accuracy: 0.8928188638799571, Testing Accuracy: 0.8360128617363344, Train Error: 0.10718113612004287, Test Error: 0.16398713826366562
 C value: 10, Training Accuracy: 0.990085744908896, Testing Accuracy: 0.9260450160771704, Train Error: 0.009914255091103996, Test Error: 0.07395498392282962
 C value: 100, Training Accuracy: 0.9997320471596999, Testing Accuracy: 0.9314040728831725, Train Error: 0.000267952840300123, Test Error: 0.0685959271168275

Kernel: sigmoid
 C value: 0.01, Training Accuracy: 0.1907824222936763, Testing Accuracy: 0.18435155412647375, Train Error: 0.8092175777063237, Test Error: 0.8156484458735263
 C value: 0.1, Training Accuracy: 0.8118971061093248, Testing Accuracy: 0.7995712754555199, Train Error: 0.18810289389067525, Test Error: 0.20042872454448013
 C value: 1.0, Training Accuracy: 0.7794748124330118, Testing Accuracy: 0.7781350482315113, Train Error: 0.22052518756698825, Test Error: 0.22186495176848875
 C value: 10, Training Accuracy: 0.7041800643086816, Testing Accuracy: 0.6891747052518756, Train Error: 0.29581993569131837, Test Error: 0.31082529474812437
 C value: 100, Training Accuracy: 0.6956055734190782, Testing Accuracy: 0.6484458735262594, Train Error: 0.30439442658092175, Test Error: 0.3515541264737406

