TSCU test suite: 01

Table of Contents

Initialization	1
Creating a toy example	1
Running TSCU	1

This test runs Time Series Classification Utility (TSCU) in default settings on a small toy example.

- Author: Huseyin Kaya
- Website: http://timewarping.org
- Sources: https://github.com/hkayabilisim/TSCU

Initialization

I prefer to clear and close everything to stay out of any nonsense.

```
clear all
close all
clc
```

Creating a toy example

Let's create 4 time series with two different classes: sine and cosine. We also deviced an artifical change within the same class time series by warping the time axis with $w(t)=t^2$.

tst and trn vectors contain both the time series and their class labels.

```
t = linspace(0,1,29);
a = sin(2*pi*t);
b = sin(2*pi*t.^2);
c = cos(2*pi*t);
d = cos(2*pi*t.^2);
trn = [ 1 a ; 2 c];
tst = [ 1 b ; 2 d];
```

Running TSCU

We run with default settings which means, no alignment is applied. You will see many info messages. The confusion matrix is one of the important output of TSCU. In this example you will see a misclassification resulting an overall classification accuracy of 0.5.

labels of testing objects (True)1labels of testing objects (Estimated)1closest training objects111Overall Accuracy0.500Overall Error0.500

 Producer Accuracy
 : 1.000
 0.000

 User Accuracy
 : 0.500
 NaN

 Kappa
 : 0.000

1]

17

Confusion matrix

tscu(trn,tst);

	1	2	UA	TO
1	1	1	0.500	2
2	0	0	NaN	0
PA	1.000	0.000		
TO	1	1		2

Classification time (sec)...... 0.01
The end of TSCU..... FINISHED

Published with MATLAB® 8.0