

Chapter Three

PART THREE: BOOLEAN VARIABLES AND OPERATORS,
ANALYZING STRINGS, INPUT VALIDATION (SEC3.6-3.9)

Chapter3 Part2 & Part3: Goals & Contents

Goals

Part3:

- To write statements using the Boolean data type
- To develop strategies for testing your programs
- To validate user input

Contents

Part3:

- Problem Solving: Test Cases
- Boolean Variables and Operators
- Analyzing Strings
- Application: Input Validation



Boolean Variables

- Boolean Variables
 - A Boolean variable is often called a flag because it can either be up (true) or down (false)
 - **boolean** is a Python data type
 - failed = True**
 - Boolean variables can either be **True** or **False**
- There are two Boolean Operators: **and**, **or**
 - They are used to combine multiple conditions



Combined Conditions: **and**

- Combining two conditions is often used in range checking
 - Is a value between two other values?
- Both sides of the **and** must be true for the result to be true

```
if temp > 0 and temp < 100 :  
    print("Liquid")
```

Examples

temp = 3

If 3 > 0 **and** 3 < 100 → if True **and** True → True

temp = -7

If -7 > 0 **and** -7 < 100 → if False **and** True → False

A	B	A and B
True	True	True
True	False	False
False	True	False
False	False	False



Combined Conditions: **or**

- We use **or** if only one of two conditions need to be true
- Use a compound conditional with an **or**:

```
if temp <= 0 or temp >= 100  
:  
    print("Not liquid")
```

Examples

temp = -5

If -5 <= 0 **or** -5 >= 100 → if True **or** False → True

temp = 7

If 7 <= 0 **or** 7 >= 100 → if False **or** False → False

A	B	A or B
True	True	True
True	False	True
False	True	True
False	False	False

- If either condition is true
 - The result is true



The *not* operator: **not**

- If you need to invert a boolean variable or comparison, precede it with **not**.

Example: `attending = True, grade = 70`

```
if not attending or grade < 60 :  
    print("Drop?")
```

If **not** (True) **or** 70 < 60
↓
If False **or** False → False

```
if attending and not(grade < 60):  
    print("Stay")
```

If True **and** **not** (70 < 60)
↓
If True **and** True → True

- If you are using **not**, try to use simpler logic:

```
if attending and grade >= 60 :  
    print("Stay")
```

A	not A
True	False
False	True




The *not* operator: inequality !

- A slightly different operator is used for the **not** when checking for inequality rather than negation.
- Example inequality:
 - The password that the user entered is not equal to the password on file.
 - `if userPassword != filePassword :`

Flowchart for “and” Combination

- This is often called ‘range checking’
 - Used to validate that the input is between two values


```
if temp > 0 and temp < 100 :  
    print("Liquid")
```



Flowchart for "or" Combination

- Another form of 'range checking'
 - Checks if value is outside a range

```
if temp <= 0 or temp >= 100 :  
    print("Not Liquid")
```





Comparison Example: Compare2.py

```
1 ##
2 # This program demonstrates comparisons of numbers, using Boolean expressions.
3 #
4
5 x = float(input("Enter a number (such as 3.5 or 4.5): "))
6 y = float(input("Enter a second number: "))
7
8 if x == y :
9     print("They are the same.")
10 else :
11     if x > y :
12         print("The first number is larger")
13     else :
14         print("The first number is smaller")
15
16     if -0.01 < x - y and x - y < 0.01 :
17         print("The numbers are close together")
18
19     if x == y + 1 or x == y - 1 :
20         print("The numbers are one apart")
21
22     if x > 0 and y > 0 or x < 0 and y < 0 :
23         print("The numbers have the same sign")
24     else :
25         print("The numbers have different signs")
26
27
```

- Run the program with several inputs



Boolean Operator Examples

Table 5 Boolean Operator Examples

Expression	Value	Comment
<code>0 < 200 and 200 < 100</code>	False	Only the first condition is true.
<code>0 < 200 or 200 < 100</code>	True	The first condition is true.
<code>0 < 200 or 100 < 200</code>	True	The or is not a test for “either-or”. If both conditions are true, the result is true.
<code>0 < x and x < 100 or x == -1</code>	<code>(0 < x and x < 100) or x == -1</code>	The and operator has a higher precedence than the or operator (see Appendix B).
<code>not (0 < 200)</code>	False	<code>0 < 200</code> is true, therefore its negation is false.
<code>frozen == True</code>	frozen	There is no need to compare a Boolean variable with True.
<code>frozen == False</code>	not frozen	It is clearer to use not than to compare with False.



Common Errors with Boolean Conditions

Confusing **and** and **or** Conditions


- It is a surprisingly common error to confuse **and** and **or** conditions.
- A value lies between 0 and 100 if it is at least 0 **and** at most 100.
- It lies outside that range if it is less than 0 **or** greater than 100.
- There is no golden rule; you just have to think carefully.



Short-circuit Evaluation: **and**

- Combined conditions are evaluated from left to right
 - If the left half of an **and** condition is false, why look further?

```
if temp > 0 and temp < 100 :  
    print("Liquid")
```






Short-circuit evaluation: **or**

- If the left half of the **or** is true, why look further?

```
if temp <= 0 or temp >= 100 :  
    print("Not Liquid")
```





De Morgan's law

- De Morgan's law tells you how to negate **“and”** and **“or”** conditions:
 - `not(A and B)` is the same as `(notA) or (notB)`
 - `not(A or B)` is the same as `(notA) and (notB)`
- Example: Shipping is higher to AK and HI

```
if (country != "USA"  
    and state != "AK"  
    and state != "HI") :  
    shippingCharge = 20.00
```

```
if not(country=="USA"  
        or state=="AK"  
        or state=="HI") :  
    shippingCharge = 20.00
```

- To simplify conditions with negations of **and** or **or** expressions, it's a good idea to apply De Morgan's law to move the negations to the **innermost** level.



Analyzing Strings – The **in** Operator

- Sometimes it's necessary to analyze or ask certain questions about a particular string.
 - Sometimes it is necessary to determine if a string contains a given substring. That is, one string contains an exact match of another string.
 - Given this code segment,
`name = "John Wayne"`
 - the expression
`"Way" in name`
 - yields `True` because the substring "Way" occurs within the string stored in variable `name`.
 - The **not in** operator is the inverse on the `in` operator



Substring: Suffixes

- Suppose you are given the name of a file and need to ensure that it has the correct extension

```
if filename.endswith(".html") :  
    print("This is an HTML file.")
```
- The `endswith()` string method is applied to the string stored in `filename` and returns `True` if the string ends with the substring `".html"` and `False` otherwise.



Operations for Testing Substrings

Table 6 Operations for Testing Substrings

Operation	Description
<i>substring</i> in <i>s</i>	Returns True if the string <i>s</i> contains <i>substring</i> and False otherwise.
<i>s.count(substring)</i>	Returns the number of non-overlapping occurrences of <i>substring</i> in the string <i>s</i> .
<i>s.endswith(substring)</i>	Returns True if the string <i>s</i> ends with the substring and False otherwise.
<i>s.find(substring)</i>	Returns the lowest index in the string <i>s</i> where <i>substring</i> begins, or -1 if <i>substring</i> is not found.
<i>s.startswith(substring)</i>	Returns True if the string <i>s</i> begins with <i>substring</i> and False otherwise.



Methods: Testing String Characteristics (1)

Table 7 Methods for Testing String Characteristics

Method	Description
<code>s.isalnum()</code>	Returns True if string <i>s</i> consists of only letters or digits and it contains at least one character. Otherwise it returns False.
<code>s.isalpha()</code>	Returns True if string <i>s</i> consists of only letters and contains at least one character. Otherwise it returns False.
<code>s.isdigit()</code>	Returns True if string <i>s</i> consists of only digits and contains at least one character. Otherwise, it returns False.

Methods for Testing String Characteristics (2)

Table 7 Methods for Testing String Characteristics

<code>s.islower()</code>	Returns True if string <i>s</i> contains at least one letter and all letters in the string are lowercase. Otherwise, it returns False.
<code>s.isspace()</code>	Returns True if string <i>s</i> consists of only white space characters (blank, newline, tab) and it contains at least one character. Otherwise, it returns False.
<code>s.isupper()</code>	Returns True if string <i>s</i> contains at least one letter and all letters in the string are uppercase. Otherwise, it returns False.



Comparing and Analyzing Strings (1)

Table 8 Comparing and Analyzing Strings

Expression	Value	Comment
"John" == "John"	True	== is also used to test the equality of two strings.
"John" == "john"	False	For two strings to be equal, they must be identical. An uppercase "J" does not equal a lowercase "j".
"john" < "John"	False	Based on lexicographical ordering of strings an uppercase "J" comes before a lowercase "j" so the string "john" follows the string "John". See Special Topic 3.2 on page 101.
"john" in "John Johnson"	False	The substring "john" must match exactly.
name = "John Johnson" "ho" not in name	True	The string does not contain the substring "ho".
name.count("oh")	2	All non-overlapping substrings are included in the count.
name.find("oh")	1	Finds the position or string index where the first substring occurs.
name.find("ho")	-1	The string does not contain the substring ho.
name.startswith("john")	False	The string starts with "John" but an uppercase "J" does not match a lowercase "j".
name.isspace()	False	The string contains non-white space characters.
name.isalnum()	False	The string also contains blank spaces.
"1729".isdigit()	True	The string only contains characters that are digits.
"-1729".isdigit()	False	A negative sign is not a digit.



Comparing and Analyzing Strings (2)

Table 8 Comparing and Analyzing Strings

<code>name.startswith("john")</code>	False	The string starts with "John" but an uppercase "J" does not match a lowercase "j".
<code>name.isspace()</code>	False	The string contains non-white space characters.
<code>name.isalnum()</code>	False	The string also contains blank spaces.
<code>"1729".isdigit()</code>	True	The string only contains characters that are digits.
<code>"-1729".isdigit()</code>	False	A negative sign is not a digit.



Substring Example: Substrings.py

```
1 ##
2 # This program demonstrates the various string methods that test substrings.
3 #
4
5 # Obtain a string and substring from the user.
6 theString = input("Enter a string: ")
7 theSubString = input("Enter a substring: ")
8
9 if theSubString in theString :
10     print("The string does contain the substring.")
11
12     howMany = theString.count(theSubString)
13     print("    It contains", howMany, "instance(s)")
14
15     where = theString.find(theSubString)
16     print("    The first occurrence starts at position", where)
17
18     if theString.startswith(theSubString) :
19         print("    The string starts with the substring.")
20     else :
21         print("    The string does not start with the substring.")
22
23     if theString.endswith(theSubString) :
24         print("    The string ends with the substring.")
25     else :
26         print("    The string does not end with the substring.")
27
28 else :
29     print("The string does not contain the substring.")
30
```

- Run the program and test several strings and substrings



Code Academy

Input Validation

- Accepting user input is dangerous
 - Consider the Elevator program:
 - Assume that the elevator panel has buttons labeled 1 through 20 (but not 13).



Input Validation

- The following are illegal inputs:
 - The number 13

```
if floor == 13 :  
    print("Error: There is no thirteenth floor.")
```

- Zero or a negative number
- A number larger than 20

```
if floor <= 0 or floor > 20 :  
    print("Error: The floor must be between 1 and 20.")
```



Elevatorsim2.py: Validating input data

```
1  ##
2  # This program simulates an elevator panel that skips the 13th floor,
3  # checking for input errors.
4  #
5
6  # Obtain the floor number from the user as an integer.
7  floor = int(input("Floor: "))
8
9  # Make sure the user input is valid.
10 if floor == 13 :
11     print("Error: There is no thirteenth floor.")
12 elif floor <= 0 or floor > 20 :
13     print("Error: The floor must be between 1 and 20.")
14 else :
15     # Now we know that the input is valid.
16     actualFloor = floor
```




Complete Program: elevatorsim2.py

```
1##
2# This program simulates an elevator panel that skips the 13th floor,
3# checking for input errors.
4#
5
6# Obtain the floor number from the user as an integer.
7floor = int(input("Floor: "))
8
9# Make sure the user input is valid.
10if floor == 13 :
11    print("Error: There is no thirteenth floor.")
12elif floor <= 0 or floor > 20 :
13    print("Error: The floor must be between 1 and 20.")
14else :
15    # Now we know that the input is valid
16    actualFloor = floor
17    if floor > 13 :
18        actualFloor = floor - 1
19
20    print("The elevator will travel to the actual floor", actualFloor)
```

- Test the program with a range of inputs including:
 - 12
 - 14
 - 13
 - -1
 - 0
 - 23
 - 19



Python Operator Precedence

Highest precedence at top, lowest at bottom.
Operators in the same box evaluate left to right.

Highest	Operator	Description
	()	Parentheses (grouping)
	f(args...)	Function call
	x[index:index]	Slicing
	x[index]	Subscription
	**	Exponentiation
	+x, -x	Positive, negative
	*, /, %	Multiplication, division, remainder
	+, -	Addition, subtraction
	in, not in, <, <=, >, >=, !=, ==	Comparisons, membership, identity
	not x	Boolean NOT
	and	Boolean AND
	or	Boolean OR
	Lowest	=

For more information, see Python documentation on [operator precedence](#) (Section 5.15)



Terminating a Python Script: exit.py

- In some program, you may need to stop the program when invalid data is entered.
- The **exit()** function defined in the **sys** standard library module immediately aborts the program when executed. The program **exit.py** below demonstrates the use of exit function.

```
1 #exit.py
2 #Program dempnstrates the use of exit() function to terminate a Python script.
3 #This program terminates if the user enters invalid mark
4
5 from sys import exit
6
7 mark = float(input("Enter mark: "))
8 if mark < 0 or mark >100:
9     exit("Error: You must enter a mark between 0 and 100")
10
11 if mark >=90:
12     grade="A"
13 elif mark >=80:
14     grade="B"
15 elif mark >=70:
16     grade="C"
17 elif mark >=60:
18     grade="D"
19 else:
20     grade="F"
21
22 print("Your grade is", grade)
```

If user entered mark value outside range 0-100, this message will be printed on output screen then the program is terminated

Terminating a Python Script: exit.py (2)

First Run

```
runfile('D:/python/src/exit.py', wdir='D:/python/src')
```

Enter mark: 102

C:\Users\pc1\Anaconda3\lib\site-packages\IPython\core\interactiveshell.py:2889:

UserWarning: To exit: use 'exit', 'quit', or Ctrl-D.

warn("To exit: use 'exit', 'quit', or Ctrl-D.", stacklevel=1)

An exception has occurred, use %tb to see the full traceback.

SystemExit: Error: You must enter a mark between 0 and 100

Second Run

```
runfile('D:/python/src/exit.py', wdir='D:/python/src')
```

Enter mark: 92

Your grade is A



Summary: Boolean

- **Boolean**
 - The type **boolean** has two values, **true** and **false**.
 - Python has two Boolean operators that combine conditions: **and** and **or**.
 - To invert a condition, use the **not** operator.
 - When checking for equality use the **!** operator.
 - The **and** and **or** operators are computed lazily:
 - As soon as the truth value is determined, no further conditions are evaluated.
 - De Morgan's law tells you how to negate **and** and **or** conditions.