

Chapter Two

PROGRAMMING WITH NUMBERS AND STRINGS

Sections 2.4
Strings



Code Academy

Lecture Goals

- To learn how to use Python strings

2.4 Strings



Strings

- Definitions:
 - Text consists of **characters**
 - **Characters** are letters, numbers, punctuation marks, spaces,
 - A **string** is a sequence of **characters**
- In Python, string literals are specified by enclosing a sequence of **characters** within a matching pair of either single or double quotes.

```
print("This is a string.", 'So is this.')
```

- By allowing both types of delimiters, Python makes it easy to include an apostrophe or quotation mark within a string.
 - `message = 'He said "Hello"'`
 - Remember to use matching pairs of quotes, single with single, double with double



String Length

- The number of characters in a string is called the length of the string. (For example, the length of **"Harry"** is 5).
- You can compute the length of a string using Python's **len()** function:
- `length = len("World!")` # length is 6
- A string of length 0 is called the empty string. It contains no characters and is written as "" or "".

Examples: What is the length of the string "Python Program"?

14

P	y	t	h	o	n		P	r	o	g	r	a	m
1	2	3	4	5	6	7	8	9	10	11	12	13	14



String Concatenation ("+")

- You can 'add' one String onto the end of another

```
firstName = "Harry"
```

```
lastName = "Morgan"
```

```
name = firstName + lastName # HarryMorgan
```

```
print("my name is:", name)
```

- If you want a space in between the two names then

```
name = firstName + " " + lastName # Harry Morgan
```

- Using "+" to concatenate strings is an example of a concept called *operator overloading*. The "+" operator performs different functions of variables of different types



String repetition ("*")

- You can also produce a string that is the result of repeating a string multiple times.
- Suppose you need to print a dashed line.
 - Instead of specifying a literal string with 50 dashes, you can use the * operator to create a string that is comprised of the string "-" repeated 50 times.

```
dashes = "-" * 50
```

- results in the string:

```
"-----"
```

- The "*" operator is also *overloaded*.



Converting Numbers to Strings

- Use the `str()` function to convert between numbers and strings.

- Example:

```
28 balance = 888.88
29 dollars = 888
30 balanceAsString = str(balance)
31 dollarsAsString = str(dollars)
32 print(balanceAsString)
33 print(dollarsAsString)
```

- To turn a string containing a number into a numerical value, we use the `int()` and `float()` functions:

```
35 id = int("1729")
36 price = float("17.29")
37 print(id)      # 1729
38 print(price)   # 17.29
```

- This conversion is important when the strings come from user input



Strings and Characters

- **strings** are sequences of **characters**
- Python uses **Unicode** characters
 - **Unicode** defines over 100,000 characters
 - **Unicode** was designed to be able to encode text in essentially all written languages
- Characters are stored as integer values
 - See the **ASCII** (*the American Standard Code for Information Interchange*) subset on Unicode chart in Appendix D
 - For example, the letter 'C' has a value of 67

Table 2 The Basic Latin (**ASCII**) Subset of Unicode

Char.	Code	Dec.	Char.	Code	Dec.	Char.	Code	Dec.
			@	"\u0040"	64	`	"\u0060"	96
!	"\u0021"	33	A	"\u0041"	65	a	"\u0061"	97
"	"\u0022"	34	B	"\u0042"	66	b	"\u0062"	98
#	"\u0023"	35	C	"\u0043"	67	c	"\u0063"	99



Copying a character from a String

- Each character inside a String has an **index** number:

0	1	2	3	4	5	6	7	8	9
c	h	a	r	s		h	e	r	e

- The *first character* is in **index** zero (0)
- The `[]` operator returns a character at a given index inside a String:

```
name = "Harry"  
start = name[0]    # "H"  
last  = name[4]    # "y"
```

0	1	2	3	4
H	a	r	r	y



- The **index** value must be within the valid range of character position. If not it will produce an Index error: string index out of range.



String Operations

Table 7 String Operations

Statement	Result	Comment
<code>string = "Py"</code> <code>string = string + "thon"</code>	string is set to "Python"	When applied to strings, + denotes concatenation.
<code>print("Please" + " enter your name: ")</code>	Prints Please enter your name:	Use concatenation to break up strings that don't fit into one line.
<code>team = str(49) + "ers"</code>	team is set to "49ers"	Because 49 is an integer, it must be converted to a string.
<code>greeting = "H & S"</code> <code>n = len(greeting)</code>	n is set to 5	Each space counts as one character.
<code>string = "Sally"</code> <code>ch = string[1]</code>	ch is set to "a"	Note that the initial position is 0.
<code>last = string[len(string) - 1]</code>	last is set to the string containing the last character in string	The last character has position <code>len(string) - 1</code> .



String Escape Sequences

- How would you print a double quote?
 - Preface the " with a "\" inside the double quoted String

```
print("He said \"Hello\"")
```

- OK, then how do you print a backslash?
 - Preface the \ with another \

```
print("C:\\Temp\\Secret.txt")
```

- Special characters inside Strings
 - Output a newline with a '\n'

```
print("*\n**\n***\n")
```

```
*  
**  
***
```



Summary: Strings

- Strings are sequences of characters.
- The `len()` function yields the number of characters in a String.
- Use the `+` operator to concatenate Strings; that is, to put them together to yield a longer String.
- In order to perform a concatenation, the `+` operator requires both arguments to be strings. Numbers must be converted to strings using the `str()` function.
- String index numbers are counted starting with 0.
- Use the `[]` operator to extract the elements of a String.