Given is the following simple Game application:

```
public class Game {
        private int totalPoints = 0;
        private int level = 1;
        public void play() {
                Random random = new Random();
                addPoints(random.nextInt(7));
                System.out.println("points="+totalPoints+" level="+level);
        }
        public int addPoints(int newPoints) {
                if (level == 1) {
                        totalPoints = totalPoints + newPoints;
                        if (totalPoints > 10) { // move to level 2
                                 level = 2;
                                 totalPoints = totalPoints + 1;//add 1 bonus point
                        }
                } else if (level == 2) {
                        totalPoints = totalPoints + 2 * newPoints;
                        if (totalPoints > 20) { // move to level 3
                                 level = 3;
                                 totalPoints = totalPoints + 2; //add 2 bonus points
                        }
                } else if (level == 3) {
                        totalPoints = totalPoints + 3 * newPoints;
                return totalPoints;
        }
}
public class Application {
        public static void main(String[] args) {
                Game game = new Game();
                game.play();
                game.play();
                game.play();
                game.play();
                game.play();
        }
}
```

Whenever we play the game, we get points. We can move up to a higher level of the game when we have a certain amount of points. In our current implementation we start with level 1, and if we have more than 10 points, we go to level 2. If we have more than 20 points in level 2, we move to level 3.

In level 1, our totalpoints is increased with the points we receive in each play. In level 2, our totalpoints is increased with 2 times the points we receive in each play. And in level 3, our totalpoints is increased with 3 times the points we receive in each play.

If you are upgraded to level 2, then you get 1 bonus point.

If you are upgraded to level 3, then you get 2 bonus points.

The problem with the given code is the addPoints() method. If we want to add another level, we have to change this method. If we want to change anything regarding point calculation rules, we always have to change this method. Just imagine how complex this method will be if we have 10 levels and very complex point calculations.

Redesign this application in such a way that

- It will be easier to add new levels
- It will be easier to change the point calculations
- The Game class is independent of the different levels. This means I should be able to add a new level without any change in the Game class.

If you are done, add another level 2\_5 with the following business rules:

- If you are in level 2, and you have more or equal to 15 points, then you go to level 2 5
- In level 2 5 you get 1 bonus point.
- If you are in level 2\_5, and you have more or equal to 20 points, then you go to level 3
- a. Draw the class diagram of your design.
- b. Draw the sequence diagram that shows how your design works. Show in the sequence diagram how you move from level 1 to level 2.
- c. Implement your design in Java.