



JÖNKÖPING UNIVERSITY

*School of Engineering*

---


# ANDROID BLUETOOTH CLASSIC

**Peter Larsson-Green**

Jönköping University

Spring 2020

# BLUETOOTH CLASSIC BASICS



# BLUETOOTH PERMISSIONS

- `android.permission.BLUETOOTH_ADMIN` (**normal**)
  - Enabling discovery & Search and pair with a new device.
- `android.permission.BLUETOOTH` (**normal**)
  - Connect and communicate with a paired device.
- `android.permission.ACCESS_COARSE_LOCATION` (**dangerous**)
  - Because of the first permission...
  - From Android 10 and one, instead use:
    - `android.permission.ACCESS_FINE_LOCATION` (**dangerous**)

# CHECK BLUETOOTH SUPPORT

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
if(bluetoothAdapter == null) {  
    // Bluetooth not supported.  
}
```

# ENABLING BLUETOOTH

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
if(!bluetoothAdapter.isEnabled()){  
    Intent enableBtIntent = new Intent(BluetoothAdapter.ACTION_REQUEST_ENABLE);  
    startActivityForResult(enableBtIntent, 123);  
}
```

```
public void onActivityResult(int requestCode, int resultCode, Intent data){  
    if(requestCode == 123){  
        if(resultCode == Activity.RESULT_OK){  
            // Bluetooth is now enabled 😊  
        }else{  
            // Bluetooth is still disabled 😞  
        }  
    }  
}
```

# ENABLING BLUETOOTH

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
if(!bluetoothAdapter.isEnabled()){  
    Intent enableBtIntent = new Intent(BluetoothAdapter.ACTION_REQUEST_ENABLE);  
    startActivityForResult(enableBtIntent, 123);  
}
```

```
BroadcastReceiver receiver = new BroadcastReceiver{  
    public void onReceive(Context context, Intent intent){  
        int state = intent.getIntExtra(BluetoothAdapter.EXTRA_STATE);  
        if(state == BluetoothAdapter.STATE_ON){ /* 😊 */ }  
        else if(state == BluetoothAdapter.STATE_OFF){ /* 😞 */ }  
    }  
};  
aContext.registerReceiver(receiver,  
    new IntentFilter(BluetoothAdapter.ACTION_STATE_CHANGED));
```

# THE SERVER

Check if the device is discoverable.

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
  
int scanMode = bluetoothAdapter.getScanMode();  
  
boolean isDiscoverable = scanMode == BluetoothAdapter.SCAN_MODE_CONNECTABLE_DISCOVERABLE;
```

Making the device discoverable.

```
Intent intent = new Intent(BluetoothAdapter.ACTION_REQUEST_DISCOVERABLE);  
intent.putExtra(BluetoothAdapter.EXTRA_DISCOVERABLE_DURATION, 60);  
startActivityForResult(  
    public void onActivityResult(int requestCode, int resultCode, Intent data){  
        if(requestCode == 111){  
            if(resultCode == Activity.RESULT_OK){  
                // Device is now discoverable 😊  
            }else{  
                // Device is still not discoverable 😞  
            }  
        }  
    }  
}
```



# THE SERVER

Check if the device is discoverable.

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
  
int scanMode = bluetoothAdapter.getScanMode();  
  
boolean isDiscoverable = scanMode == BluetoothAdapter.SCAN_MODE_CONNECTABLE_DISCOVERABLE;
```

Making the device discoverable.

```
Intent intent = new Intent(BluetoothAdapter.ACTION_REQUEST_DISCOVERABLE);  
intent.putExtra(BluetoothAdapter.EXTRA_DISCOVERABLE_DURATION, 60);  
startActivityForResult(  
    BroadcastReceiver receiver = new BroadcastReceiver()  
    {  
        public void onReceive(Context context, Intent intent){  
            int scanMode = intent.getIntExtra(BluetoothAdapter.EXTRA_SCAN_MODE);  
            if(scanMode == BluetoothAdapter.SCAN_MODE_CONNECTABLE_DISCOVERABLE){ /* 😊 */ }  
            else{ /* 😞 */ }  
        }  
    },  
    aContext.registerReceiver(receiver,  
        new IntentFilter(BluetoothAdapter.ACTION_SCAN_MODE_CHANGED));
```

# THE SERVER

Listening for incoming connections.

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
BluetoothServerSocket server = bluetoothAdapter.listenUsingRfcommWithServiceRecord(  
    "The name",  
    UUID.fromString("6a49c8a8-320c-42c4-afbf-8289c70c246d")  
);  
BluetoothSocket client = server.accept();  
// ...  
server.close();
```

# THE CLIENT

Discover and connect to the server.

```
BluetoothAdapter bluetoothAdapter = BluetoothAdapter.getDefaultAdapter();  
bluetoothAdapter.startDiscovery();  
BroadcastReceiver receiver = new BroadcastReceiver{  
    public void onReceive(Context context, Intent intent){  
        BluetoothDevice device = intent.getParcelableExtra(BluetoothDevice.EXTRA_DEVICE);  
        String name = device.getName();  
        String macAddress = device.getAddress();  
        bluetoothAdapter.cancelDiscovery();  
        UUID service = UUID.fromString("6a49c8a8-320c-42c4-afbf-8289c70c246d");  
        BluetoothSocket server = device.createRfcommSocketToServiceRecord(service);  
        server.connect();  
    }  
};  
aContext.registerReceiver(receiver, new IntentFilter(BluetoothDevice.ACTION_FOUND));
```

# SENDING/RECEIVING DATA

Each device has a `BluetoothSocket` representing the connection to the other device.

## Server

```
BluetoothSocket client = ...;  
String message = "Hello";  
OutputStream outputStream = client.getOutputStream();  
outputStream.write(message.getBytes(StandardCharsets.UTF_8));
```

## Client

```
BluetoothSocket server = ...;  
InputStream inputStream = server.getInputStream();  
byte[] bytes = new byte[512];  
int numberOfBytesRead = inputStream.read(bytes);  
String message = new String(bytes, StandardCharsets.UTF_8)
```