

Based on the provided sources and technical documentation for the ZTE ZXA10 C600, the line card type names and codes are displayed in the **show card** CLI command (or display board in visualization contexts) 1, 2.

While the sources do not provide an exhaustive list of every available card model, they define the structure of the card information table (indexed by Rack/Shelf/Slot) and describe how to identify them via SNMP or CLI 3, 4.

Card Type Strings in "show card" Output

In the ZXA10 C600 (Titan platform), the "Type" string in the command output typically reflects the functional category of the card, while the "Real Type" reflects the specific hardware model 3.

- **10GE Uplink Cards (XGEI):** These cards provide 10-Gigabit Ethernet uplink ports. In the show card output, the functional type string is often listed as **XGEI**.
- **GE Uplink Cards (GEI):** These cards provide Gigabit Ethernet uplink ports. In the output, the functional type string is typically listed as **GEI**.
- **GPON Line Cards:** The most common 16-port GPON line card for the C600 is identified by the type string **GFGH** 5, 6.
- **Combo PON Cards:** Cards that support both GPON and XG-PON/XGS-PON are identified by strings such as **GFXH** (GPON & XG-PON) or **GFXL** (GPON & XGS-PON) 5.

Typical Uplink Slotting and Hierarchy

Uplink cards in the C600 are typically placed in the high-numbered slots (e.g., Slot 19 or 20 in a standard chassis) 7, 8.

- **Slot 19 example:** A 10GE uplink port in slot 19 would follow the C600's **4-tier naming hierarchy**: gei-1/1/19/port or xgei-1/1/19/port 7, 8.
- **SNMP Identification:** These strings can also be retrieved via SNMP using the `zxAnCardActualType` OID (1.3.6.1.4.1.3902.1082.10.1.1.1.4) 9.

Summary of Card Codes

Service/Port Type,"CLI ""Type"" String","Common ""Real Type"" Examples"

10GE Uplink,XGEI,"HUVQ (dedicated), SFUL/SFUM (MPU-based)"

GE Uplink,GEI,"HUVQ (dedicated), SFUL/SFUM (MPU-based)"

16-port GPON,GFGH,GFGH

16-port Combo PON,GFXH / GFXL,"GFXH, GFXL"

(Note: Information regarding specific hardware models like HUVQ or SFUL is based on general industry specifications for the ZTE Titan platform and should be verified against your specific hardware version.)

Would you like to see the specific SNMP OIDs for monitoring the CPU and memory usage of these individual line cards?