

While the ZXA10 C600 series shares many architectural similarities with the C300/C320, there are specific CLI command formats and hierarchical naming differences to note for GPON ONU provisioning.

CLI Command Comparisons

- **Interface Naming:** The C600 transition introduces a **4-tier naming hierarchy** (Rack/Shelf/Slot/Port) compared to the 3-tier system often seen in smaller OLTs like the C320 1.
- **C300/C320 Format:** gpon-olt_1/{slot}/{port}.
- **C600 Format:** interface gpon-olt_{rack}/{shelf}/{slot}/{port}.
- **Example:** For Rack 1, Shelf 1, Slot 3, Port 1, you would enter interface gpon-olt_1/1/3/1 1, 2.
- **ONU Registration Syntax:** The syntax for registering an ONU remains **functionally identical** 2, 3.
- **Syntax:** onu {id} type {type} sn {sn}.
- **C600 Example:** onu 1 Type ZTE-F622 sn ZTEG00000001 2.
- **pon-onu-mng Context:** The format for entering and using the remote management context is the **same**, though it follows the 4-tier interface naming convention to identify the target ONU 4, 5.
- **Context Prompt:** ZXAN(gpon-onu-mng)# 3, 4.
- **Command Example:** Within this context, you still use commands like service internet gemport 1 vlan 100 4, 6.
- **show pon power onu-rx Command:** This command is still used to verify optical levels on the C600 7, 8.
- The C600 visualization table confirms that "Display Signal" (the internal function for this command) is a supported visualization feature 9.
- It is used to analyze the signal levels received by each registered ONU 8.
- **show gpon profile tcont Command:** The profile management syntax is **consistent** between the series 2, 3.
- **Creation:** profile tcont {name} type {1-5} fixed {bw} 2.
- **Verification:** The command show gpon profile tcont remains standard for displaying defined bandwidth profiles 9.
- **terminal length 0 Command:** This command **still works** on the C600 to disable line limits for long command outputs 10.
- The shorthand ter len 0 is validated for ZXA10 software versions typically running on C600 hardware 10.

Summary of Syntax Consistency

Feature	ZXA10 C300/C320 Syntax	ZXA10 C600 Syntax
Interface	gpon-olt_1/slot/port	gpon-olt_rack/shelf/slot/port
Registration	onu {id} type {type} sn {sn}	onu {id} type {type} sn {sn}
ONU Context	(gpon-onu-mng)#	(gpon-onu-mng)#
Power Check	show pon power onu-rx	show pon power onu-rx

T-CONT Profile,profile tcont {name} ...,profile tcont {name} ...

Term Length,terminal length 0,terminal length 0

Would you like the specific CLI steps to configure a GEM port and Service Port for a High-Speed Internet (HIS) service on the C600?