Question 1

```
SELECT count(DISTINCT id) AS
        Total_employees
FROM employees;
```

Total_employees
10

Question 2

```
SELECT sum(salary) AS Totalsalary
FROM employees
WHERE department = "IT";
```

Total_salary
220 000

Question 3

```
SELECT avg(salary) AS average_salary
FROM employees
WHERE department = "HR";
```

average_salary
49 500

Question 4

```
SELECT min(salary) As lowest_salary,
       max(salary) AS highest_salary
FROM employees
```

lowest_salary	highest_salary
43 000	62 000

Question 5

```
SELECT department,
       sum(salary) AS Total_salary
FROM employees
GROUP BY department;
```

department	Total_salary
IT	220 000
HR	99 000
Finance	119 000
Marketing	105 000

Question 6

```
SELECT city,
       count(DISTINCT id) AS Total_count
FROM employees
GROUP BY city;
```

city	Total_count
New York	2
Chicago	3
Los Angeles	2
San Francisco	2
Houston	1

Question 7

```
SELECT department,
       avg(salary) AS Average_salary
FROM employees
GROUP BY department
ORDER BY Average_salary DESC;
```

department	Average_salary
Finance	59 500
IT	55 000
Marketing	52 500
HR	49 500

Question 8

```
SELECT department,
       sum(salary) AS Total_salary
FROM employees
GROUP BY department
HAVING Total_salary > 100 000;
```

department	Total_salary
IT	220 000
Finance	119 000
Marketing	105 000

Question 9

```
SELECT city,
       count(DISTINCT id) AS Total_employees
FROM employees
GROUP BY city
HAVING Total_employees > 1
ORDER BY Total_employees DESC;
```

city	Total_employees
Chicago	3
New York	2
Los Angeles	2
San Francisco	2

Question 10

```
SELECT department,
        avg(salary) AS Average-salary
FROM employees
GROUP BY department
ORDER BY department DESC
LIMIT 1;
```

department	Average-salary
Marketing	52 500