Complete The Task in Manual

Additional Tasks

Consider the Structure of 'restaurants' collection given below:


```
{
 "address": {
    "building": "1007",
    "coord": [ -73.856077, 40.848447 ],
    "street": "Morris Park Ave",
    "zipcode": "10462"
 },
 "borough": "Bronx",
 "cuisine": "Bakery",
 "grades": [
    { "date": { "$date": 1393804800000 }, "grade": "A", "score": 2 },
    { "date": { "$date": 1378857600000 }, "grade": "A", "score": 6 },
    { "date": { "$date": 1358985600000 }, "grade": "A", "score": 10 },
    { "date": { "$date": 1322006400000 }, "grade": "A", "score": 9 },
    { "date": { "$date": 1299715200000 }, "grade": "B", "score": 14 }
 ],
 "name": "Morris Park Bake Shop",
 "restaurant_id": "30075445"
}
```


Tasks

1. Write a MongoDB query to display all the documents in the collection restaurants.
2. Write a MongoDB query to display the fields restaurant_id, name, borough and cuisine for all the documents in the collection restaurant.
3. Write a MongoDB query to display the fields restaurant_id, name, borough and cuisine, but exclude the field _id for all the documents in the collection restaurant.
4. Write a MongoDB query to display the fields restaurant_id, name, borough and zip code, but exclude the field _id for all the documents in the collection restaurant.
5. Write a MongoDB query to display all the restaurant which is in the borough Bronx.
6. Write a MongoDB query to display the first 5 restaurant which is in the borough Bronx.
7. Write a MongoDB query to find the restaurants who achieved a score more than 90.
8. Write a MongoDB query to find the restaurants that achieved a score, more than 80 but less than 100.
9. Write a MongoDB query to find the restaurants which locate in latitude value less than -95.754168.

10. Write a MongoDB query to find the restaurants which belong to the borough Bronx and prepared either American or Chinese dish.