
Table of Contents

loading data	1
defining the parameters	1
showing labels for a specific start point	1
KNN	2
SVM	5
linear	5
gaussian	6
LDA	8
Naive bayes	10

loading data

```
%loading the features we have computed
load features;
%loading data sets
load dataset_BCIcomp1;
```

defining the parameters

```
fs=128;
n_features=10; %number of PCA features
n_trials=size(x_train,3); %140
n_channels=size(x_train,2); %3
n=size(x_train,1); %1152
kernel_size=256; %as mentioned in the essay
s_point=n - kernel_size + 1; %897, which also describes number of
different sets of features we can have
```


showing labels for a specific start point

```
%features when the start point is j and we choose the i'th feature
j=431;%start point
i=2;%number of the feature
sample1=features(i:n_features,:,j);
%finding the datas with 1 lable
leftindex1=find(y_train==1);
%finding the datas with 2 lable
rightindex1=find(y_train==2);
plot3(sample1(1,leftindex1),sample1(2,leftindex1),...
      sample1(3,leftindex1),'.','color','r');
xlabel('channel-1');
ylabel('channel-2');
zlabel('channel-3');
hold on
plot3(sample1(1,rightindex1),sample1(2,rightindex1),...
      sample1(3,rightindex1),'.','color','b');
```

```

legend('left-hand','right-hand');
grid on
grid minor
hold off

```



KNN

```

tp_accuracy=zeros(1,n_trials);
accuracy=zeros(1,s_point);
for k=[1 3 5 7]
    figure;
    for i=1:s_point
        %the dataset with the "i"th start point
        sample=features(:, :, i);
        % dividing data into test and split with the function we
        defined
        [Xs_train,Xs_test,ys_train,ys_test] =
        leave_one_out(sample,y_train);
        for g=1:n_trials
            sampleX_train=Xs_train(:, :, g);
            sampley_train=ys_train(:, g);
            %training the model for KNN with k neighbours


            model=fitcknn(sampleX_train',sampley_train,'NumNeighbors',k);
            %testing the model
            sampleX_test=Xs_test(:, :, g);



```


```

        op=predict(model,sampleX_test');
        %computing the accuracy using leave one out method
        sample_test=ys_test(g,:);
        tp_accuracy(g)=sum(op==sample_test)/length(sample_test)
*100;
    end
    accuracy(i)=sum(tp_accuracy)/length(tp_accuracy);
end
best_point=find(max(accuracy)==accuracy);
plot(accuracy);
hold on
stem(best_point,accuracy(best_point),'*','r');
title(['KNN-k=',num2str(k)]);
xlabel("start-point");
ylabel("accuracy");
grid on;
grid minor;
hold off;
end

```







SVM

linear

```


accuracy=zeros(1,s_point);
for i=1:s_point
    %the dataset with the "i"th start point
    sample=features(:, :, i);
    % dividing data into test and split with the function we defined
    [Xs_train,Xs_test,ys_train,ys_test] =
    leave_one_out(sample,y_train);
    for g=1:n_trials
        sampleX_train=Xs_train(:, :, g);
        sampley_train=ys_train(:, g);
        %training the model for KNN with k neighbours
        model=fitcsvm(sampleX_train',sampley_train,'Standardize',1,...
        'KernelFunction','linear');
        %testing the model
        sampleX_test=Xs_test(:, :, g);
        op=predict(model,sampleX_test');
        %computing the accuracy using leave one out method
        sampley_test=ys_test(g, :);
        tp_accuracy(g)=sum(op==sampley_test)/length(sampley_test)
        *100;
    end
end

```

```

        accuracy(i)=sum(tp_accuracy)/length(tp_accuracy);
    end
    best_point=find(max(accuracy)==accuracy);
    figure;
    plot(accuracy);
    hold on
    stem(best_point,accuracy(best_point),'*','r');
    title('SVM-linear-kernel');
    xlabel("start-point");
    ylabel("accuracy");
    grid on;
    grid minor;
    hold off;

```




gaussian

```

accuracy=zeros(1,s_point);
for i=1:s_point
    %the dataset with the "i"th start point
    sample=features(:, :, i);
    % dividing data into test and split with the function we defined
    [Xs_train,Xs_test,ys_train,ys_test] =
    leave_one_out(sample,y_train);
    for g=1:n_trials
        sampleX_train=Xs_train(:, :, g);
        sampley_train=ys_train(:, g);

```

```
%training the model for KNN with k neighbours
model=fitcsvm(sampleX_train',sampley_train,'Standardize',1,...
'KernelFunction','RBF','KernelScale','auto');
%testing the model
sampleX_test=Xs_test(:, :,g);
op=predict(model,sampleX_test');
%computing the accuracy using leave one out method
sampley_test=ys_test(g,:);
tp_accuracy(g)=sum(op==sampley_test)/length(sampley_test)
*100;
end
accuracy(i)=sum(tp_accuracy)/length(tp_accuracy);
end
best_point=find(max(accuracy)==accuracy);
figure;
plot(accuracy);
hold on
stem(best_point,accuracy(best_point),'*','r');
title('SVM-gaussian-kernel');
xlabel('start-point');
ylabel('accuracy');
grid on;
grid minor;
hold off;
```




LDA

```

accuracy=zeros(1,s_point);
for i=1:s_point
    %the dataset with the "i"th start point
    sample=features(:, :, i);
    % dividing data into test and split with the function we defined
    [Xs_train,Xs_test,ys_train,ys_test] =
    leave_one_out(sample,y_train);
    for g=1:n_trials
        sampleX_train=Xs_train(:, :, g);
        sampley_train=ys_train(:, g);
        %training the model for KNN with k neighbours
        model=fitcdiscr(sampleX_train',sampley_train);
        %testing the model
        sampleX_test=Xs_test(:, :, g);
        op=predict(model,sampleX_test');
        %computing the accuracy using leave one out method
        sampley_test=ys_test(g, :);
        tp_accuracy(g)=sum(op==sampley_test)/length(sampley_test)
    *100;
    end
    accuracy(i)=sum(tp_accuracy)/length(tp_accuracy) ;
end
best_point=find(max(accuracy)==accuracy);

```

```
figure;
plot(accuracy);
hold on
stem(best_point,accuracy(best_point),'*','r');
title('LDA');
xlabel("start-point");
ylabel("accuracy");
grid on;
grid minor;
hold off
```




Naive bayes

```

accuracy=zeros(1,s_point);
for i=1:s_point
    %the dataset with the "i"th start point
    sample=features(:, :, i);
    % dividing data into test and split with the function we defined
    [Xs_train,Xs_test,ys_train,ys_test] =
    leave_one_out(sample,y_train);
    for g=1:n_trials
        sampleX_train=Xs_train(:, :, g);
        sampley_train=ys_train(:, g);
        %training the model for KNN with k neighbours
        model=fitcnb(sampleX_train',sampley_train);
        %testing the model
        sampleX_test=Xs_test(:, :, g);
        op=predict(model,sampleX_test');
        %computing the accuracy using leave one out method
        sampley_test=ys_test(g, :);
        tp_accuracy(g)=sum(op==sampley_test)/length(sampley_test)
    *100;
    end
    accuracy(i)=sum(tp_accuracy)/length(tp_accuracy);
end
best_point=find(max(accuracy)==accuracy);

```

```
figure;
plot(accuracy);
hold on
stem(best_point,accuracy(best_point),'*','r');
title('naive-bayes');
xlabel("start-point");
ylabel("accuracy");
grid on;
grid minor;
hold off
```



Published with MATLAB® R2020a