

LAYER: 4_AppMDM

This file is a merged representation of a subset of the codebase, containing files not matching ignore patterns, combined into a single document by Repomix.

<file_summary>

This section contains a summary of this file.

<purpose>

This file contains a packed representation of a subset of the repository's contents that is considered the most important context.

It is designed to be easily consumable by AI systems for analysis, code review, or other automated processes.

</purpose>

<file_format>

The content is organized as follows:

1. This summary section
2. Repository information
3. Directory structure
4. Repository files (if enabled)
5. Multiple file entries, each consisting of:
 - File path as an attribute
 - Full contents of the file

</file_format>

<usage_guidelines>

- This file should be treated as read-only. Any changes should be made to the original repository files, not this packed version.
- When processing this file, use the file path to distinguish between different files in the repository.
- Be aware that this file may contain sensitive information. Handle it with the same level of security as you would the original repository.

</usage_guidelines>

<notes>

- Some files may have been excluded based on .gitignore rules and Repomix's configuration
- Binary files are not included in this packed representation. Please refer to the Repository Structure section for a complete list of file paths, including binary files
- Files matching these patterns are excluded: `**/obj/**`, `**/bin/**`, `**/*.png`, `**/*.jpg`, `**/node_modules/**`, `**/*.Designer.cs`
- Files matching patterns in .gitignore are excluded
- Files matching default ignore patterns are excluded
- Files are sorted by Git change count (files with more changes are at the bottom)

</notes>

</file_summary>

<directory_structure>

Promatis.Net.Test.MDM.Configuration/Configurator.cs
Promatis.Net.Test.MDM.Configuration/Promatis.Net.Test.MDM.Configuration.csproj
Promatis.Net.Test.MDM.Data/DBContext/MdmApplicationDbContext.cs
Promatis.Net.Test.MDM.Data/Promatis.Net.Test.MDM.Data.csproj
Promatis.Net.Test.MDM.DataInit/Migrations/20260515044539_Init.cs
Promatis.Net.Test.MDM.DataInit/Migrations/20260521060225_TechnologicalParameterCalcMethod.cs
Promatis.Net.Test.MDM.DataInit/Migrations/20260528090200_Add-UnitOfMeasurement.cs
Promatis.Net.Test.MDM.DataInit/Migrations/MdmApplicationDbContextModelSnapshot.cs
Promatis.Net.Test.MDM.DataInit/Promatis.Net.Test.MDM.DataInit.csproj
Promatis.Net.Test.MDM.Domain.Interface/Class1.cs
Promatis.Net.Test.MDM.Domain.Interface/Promatis.Net.Test.MDM.Domain.Interface.csproj
Promatis.Net.Test.MDM.Domain/DepartmentUnit.cs
Promatis.Net.Test.MDM.Domain/DepartmentUnitValidator.cs
Promatis.Net.Test.MDM.Domain/PositionUnit.cs
Promatis.Net.Test.MDM.Domain/PositionUnitValidator.cs
Promatis.Net.Test.MDM.Domain/ProductionUnit.cs
Promatis.Net.Test.MDM.Domain/ProductionUnitValidator.cs
Promatis.Net.Test.MDM.Domain/Promatis.Net.Test.MDM.Domain.csproj
Promatis.Net.Test.MDM.Domain/StorageUnit.cs
Promatis.Net.Test.MDM.Domain/StorageUnitValidator.cs
Promatis.Net.Test.MDM.Domain/TransportUnit.cs
Promatis.Net.Test.MDM.Domain/TransportUnitValidator.cs
Promatis.Net.Test.MDM.Launcher.Web/appsettings.Development.json
Promatis.Net.Test.MDM.Launcher.Web/appsettings.json
Promatis.Net.Test.MDM.Launcher.Web/Bootstrapper.cs
Promatis.Net.Test.MDM.Launcher.Web/Components/_Imports.razor
Promatis.Net.Test.MDM.Launcher.Web/Components/App.razor

```
Promatis.Net.Test.MDM.Launcher.Web/DefaultWebConfig.cs
Promatis.Net.Test.MDM.Launcher.Web/Program.cs
Promatis.Net.Test.MDM.Launcher.Web/Promatis.Net.Test.MDM.Launcher.Web.csproj
Promatis.Net.Test.MDM.Launcher.Web/Properties/launchSettings.json
Promatis.Net.Test.MDM.Launcher.Web/wwwroot/app.css
Promatis.Net.Test.MDM.Service/Promatis.Net.Test.MDM.Service.csproj
Promatis.Net.Test.MDM.Service/Services/TechnologicalOperationService.cs
Promatis.Net.Test.MDM.Service/Services/UnitService.cs
Promatis.Net.Test.MDM.Tests/Promatis.Net.Test.MDM.Tests.csproj
Promatis.Net.Test.MDM.Tests/UnitTest1.cs
Promatis.Net.Test.MDM.UI/_Imports.razor
Promatis.Net.Test.MDM.UI/Promatis.Net.Test.MDM.UI.csproj
Promatis.Net.Test.MDM.UI/UiModule.cs
Promatis.Net.Test.MDM.UI/wwwroot/exampleJsInterop.js
</directory_structure>
```

<files>

This section contains the contents of the repository's files.

```
<file path="Promatis.Net.Test.MDM.Configuration/Configurator.cs">
using Microsoft.AspNetCore.Builder;ð
using Microsoft.EntityFrameworkCore;ð
using Microsoft.Extensions.Configuration;ð
using Microsoft.Extensions.DependencyInjection;ð
using Microsoft.Extensions.Hosting;ð
using Promatis.Net.Configuration.Web;ð
using Promatis.Net.Data;ð
using Promatis.Net.MES.Data;ð
using Promatis.Net.MES.MDM.Data;ð
using Promatis.Net.Test.MDM.Data;ð
ð
namespace Promatis.Net.Test.MDM.Configuration;ð
ð
public class Configurator : IWebAppConfiguratorð
{ð
    public void ConfigureServices(IServiceCollection services, IConfiguration configuration)ð
    {ð
        // 1. B 5C48D BD 0Dd8Dò 5CD8C0AD$2CT=C0>C' @CT0C'LC0>C' DC 1D 8C=8 A ð
        services.AddDbContextFactory<MdmApplicationDbContext>((sp, options) =>ð
        {ð
            string? baseConnString = configuration.GetConnectionString("DefaultConnection");ð
ð
            var builder = new Npgsql.NpgsqlConnectionStringBuilder(baseConnString)ð
            {ð
                Username = "mdm",ð
                Password = "mdm"ð
            };ð
ð
            options.UseNpgsql(builder.ConnectionString, x =>ð
                x.MigrationsAssembly("Promatis.Net.Test.MDM.DataInit"));ð
        });ð
ð
        // 2. A 4C ?D$5D 4C'0 D ;Cä0 MesMDM (IDbContextFactory<MesMdmApplicationDbContext>)ð
        services.AddScoped<IDbContextFactory<MesMdmApplicationDbContext>>(sp =>ð
        {ð
            var factory = sp.GetRequiredService<IDbContextFactory<MdmApplicationDbContext>>();ð
            return new MesMdmDbContextFactoryAdapter(factory);ð
        });ð
ð
        // 3. A A B$ B A' / B Aä/ Mes (IDbContextFactory<MesApplicationDbContext>)ð
        services.AddScoped<IDbContextFactory<MesApplicationDbContext>>(sp =>ð
        {ð
            var factory = sp.GetRequiredService<IDbContextFactory<MdmApplicationDbContext>>();ð
            return new MesDbContextFactoryAdapter(factory);ð
        });ð
ð
        // 4. A 4C ?D$5D 4C'0 D 0CÄ>C4> C 0Ct>C$>C4> D ;Cä0 Core (IDbContextFactory<ApplicationDbContext>)ð
        services.AddScoped<IDbContextFactory<ApplicationDbContext>>(sp =>ð
        {ð
            var factory = sp.GetRequiredService<IDbContextFactory<MdmApplicationDbContext>>();ð
            return new DbContextFactoryAdapter(factory);ð
        });ð
    }ð
ð
    public void ConfigureApp(IHost app) { }ð
ð
}
```

```

    public void ConfigureMiddleware(WebApplication app) { }
}
// --- A A !B + A A B$ B A" 00Y
}
// A 4C ?D$5D 4C'O MesMDM
private class MesMdmDbContextFactoryAdapter(IDbContextFactory<MdmApplicationDbContext> factory)
    : IDbContextFactory<MesMdmApplicationDbContext>
{
    public MesMdmApplicationDbContext CreateDbContext() => factory.CreateDbContext();
}
}
// A 4C ?D$5D 4C'O Mes
private class MesDbContextFactoryAdapter(IDbContextFactory<MdmApplicationDbContext> factory)
    : IDbContextFactory<MesApplicationDbContext>
{
    public MesApplicationDbContext CreateDbContext() => factory.CreateDbContext();
}
}
// A 4C ?D$5D 4C'O Core
private class DbContextFactoryAdapter(IDbContextFactory<MdmApplicationDbContext> factory)
    : IDbContextFactory<ApplicationDbContext>
{
    public ApplicationDbContext CreateDbContext() => factory.CreateDbContext();
}
}
</file>

```

```

<file path="Promatis.Net.Test.MDM.Configuration/Promatis.Net.Test.MDM.Configuration.csproj">
<Project Sdk="Microsoft.NET.Sdk">
}
<PropertyGroup>
    <TargetFramework>net10.0</TargetFramework>
    <ImplicitUsings>enable</ImplicitUsings>
    <Nullable>enable</Nullable>
</PropertyGroup>
}
<ItemGroup>
    <ProjectReference Include="..\..\..\
\Mes\MDM\Promatis.Net.MES.MDM.Configuration\Promatis.Net.MES.MDM.Configuration.csproj" />
    <ProjectReference Include="..\..\..\
\Mes\MDM\Promatis.Net.MES.MDM.UI\Promatis.Net.MES.MDM.UI.csproj" />
    <ProjectReference Include="..\
\Promatis.Net.Test.MDM.DataInit\Promatis.Net.Test.MDM.DataInit.csproj" />
    <ProjectReference Include="..\
\Promatis.Net.Test.MDM.Service\Promatis.Net.Test.MDM.Service.csproj" />
    <ProjectReference Include="..\Promatis.Net.Test.MDM.UI\Promatis.Net.Test.MDM.UI.csproj" />
</ItemGroup>
}
</Project>
</file>

```

```

<file path="Promatis.Net.Test.MDM.Data/DbContext/MdmApplicationDbContext.cs">
using Microsoft.EntityFrameworkCore;
using Microsoft.Extensions.Configuration;
using Promatis.Net.MES.Domain;
using Promatis.Net.MES.MDM.Data;
using Promatis.Net.Test.MDM.Domain;
}
namespace Promatis.Net.Test.MDM.Data;
}
public class MdmApplicationDbContext(
    DbContextOptions options,
    IConfiguration configuration,
    IServiceProvider? serviceProvider = null) // A0@C,,=C<C 5CÂ >C0FC,,>C00C'LC0KC' ?C @C <CTBD
    : MesMdmApplicationDbContext(options, configuration, serviceProvider)
{
}
}
// B4:C 7D'2C 5CÂ ADT5CÄC CD;D0 MD$>C4> C0>C0:D 5D$=Cä3Câ :Cä=D$5C0AD$0D
protected override string Schema => "mdm";
}
public DbSet<UnitBase> Units => Set<UnitBase>();
public DbSet<DepartmentUnit> DepartmentUnits => Set<DepartmentUnit>();
public DbSet<ProductionUnit> ProductionUnits => Set<ProductionUnit>();
public DbSet<TransportUnit> TransportUnits => Set<TransportUnit>();
public DbSet<StorageUnit> StorageUnits => Set<StorageUnit>();
public DbSet<PositionUnit> PositionUnits => Set<PositionUnit>();
}

```

```

}
</file>

<file path="Promatis.Net.Test.MDM.Data/Promatis.Net.Test.MDM.Data.csproj">
<Project Sdk="Microsoft.NET.Sdk">
  <PropertyGroup>
    <TargetFramework>net10.0</TargetFramework>
    <ImplicitUsings>enable</ImplicitUsings>
    <Nullable>enable</Nullable>
  </PropertyGroup>
  <ItemGroup>
    <PackageReference Include="Microsoft.EntityFrameworkCore" Version="10.0.8" />
    <PackageReference Include="Microsoft.EntityFrameworkCore.Relational" Version="10.0.8" />
  </ItemGroup>
  <ItemGroup>
    <ProjectReference Include="..\..\..\Mes\MDM\Promatis.Net.MES.MDM.Data\Promatis.Net.MES.MDM.Data.csproj" />
    <ProjectReference Include="..\Promatis.Net.Test.MDM.Domain\Promatis.Net.Test.MDM.Domain.csproj" />
  </ItemGroup>
</Project>
</file>

<file path="Promatis.Net.Test.MDM.DataInit/Migrations/20260515044539_Init.cs">
using System;
using Microsoft.EntityFrameworkCore.Migrations;
  #nullable disabled
  namespace Promatis.Net.Test.MDM.DataInit.Migrations
  {
    /// <inheritdoc />
    public partial class Init : Migration
    {
      /// <inheritdoc />
      protected override void Up(MigrationBuilder migrationBuilder)
      {
        migrationBuilder.EnsureSchema(
          name: "mdm");

        migrationBuilder.CreateTable(
          name: "AuditLogs",
          schema: "mdm",
          columns: table => new
          {
            Id = table.Column<Guid>(type: "uuid", nullable: false),
            EntityName = table.Column<string>(type: "character varying(100)", maxLength:
100, nullable: false),
            EntityId = table.Column<Guid>(type: "uuid", nullable: false),
            Action = table.Column<string>(type: "character varying(50)", maxLength: 50,
nullable: false),
            ChangedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),
            ChangedBy = table.Column<string>(type: "character varying(100)", maxLength:
100, nullable: true),
            ChangesJson = table.Column<string>(type: "jsonb", maxLength: 255, nullable:
false),
            CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false)
          },
          constraints: table =>
          {
            table.PrimaryKey("PK_AuditLogs", x => x.Id);
          });

        migrationBuilder.CreateTable(
          name: "TechnologicalOperations",
          schema: "mdm",
          columns: table => new
          {
            Id = table.Column<Guid>(type: "uuid", nullable: false),
            CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),

```

```

        Name = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: false),Ø
        Description = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        Code = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: true),Ø
        DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),Ø
        DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        ParentId = table.Column<Guid>(type: "uuid", nullable: true),Ø
        IsLeaf = table.Column<bool>(type: "boolean", nullable: false)Ø
    },Ø
    constraints: table =>Ø
    {Ø
        table.PrimaryKey("PK_TechnologicalOperations", x => x.Id);Ø
        table.ForeignKey(Ø
            name: "FK_TechnologicalOperations_TechnologicalOperations_ParentId",Ø
            column: x => x.ParentId,Ø
            principalSchema: "mdm",Ø
            principalTable: "TechnologicalOperations",Ø
            principalColumn: "Id",Ø
            onDelete: ReferentialAction.Restrict);Ø
    });Ø
Ø
migrationBuilder.CreateTable(Ø
    name: "TechnologicalParameters",Ø
    schema: "mdm",Ø
    columns: table => newØ
    {Ø
        Id = table.Column<Guid>(type: "uuid", nullable: false),Ø
        CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),Ø
        Name = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: false),Ø
        Description = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        Code = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: true),Ø
        DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),Ø
        DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        UnitOfMeasurement = table.Column<string>(type: "character varying(255)",
maxLength: 255, nullable: false),Ø
        DataType = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: false)Ø
    },Ø
    constraints: table =>Ø
    {Ø
        table.PrimaryKey("PK_TechnologicalParameters", x => x.Id);Ø
    });Ø
Ø
migrationBuilder.CreateTable(Ø
    name: "Units",Ø
    schema: "mdm",Ø
    columns: table => newØ
    {Ø
        Id = table.Column<Guid>(type: "uuid", nullable: false),Ø
        Kind = table.Column<int>(type: "integer", nullable: false),Ø
        Type = table.Column<int>(type: "integer", nullable: false),Ø
        CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),Ø
        Name = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: false),Ø
        Description = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        Code = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: true),Ø
        DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),Ø
        DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        ParentId = table.Column<Guid>(type: "uuid", nullable: true)Ø
    },Ø
    constraints: table =>Ø

```

```

        {
            table.PrimaryKey("PK_Units", x => x.Id);
            table.ForeignKey(
                name: "FK_Units_Units_ParentId",
                column: x => x.ParentId,
                principalSchema: "mdm",
                principalTable: "Units",
                principalColumn: "Id",
                onDelete: ReferentialAction.Restrict);
        });

migrationBuilder.CreateTable(
    name: "TechnologicalOperationParameters",
    schema: "mdm",
    columns: table => new
    {
        Id = table.Column<Guid>(type: "uuid", nullable: false),
        CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),
        OperationId = table.Column<Guid>(type: "uuid", nullable: false),
        ParameterId = table.Column<Guid>(type: "uuid", nullable: false),
        IsRequired = table.Column<bool>(type: "boolean", nullable: false),
        DefaultValue = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),
        MinValue = table.Column<double>(type: "double precision", nullable: true),
        MaxValue = table.Column<double>(type: "double precision", nullable: true),
        DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),
        DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true)
    },
    constraints: table =>
    {
        table.PrimaryKey("PK_TechnologicalOperationParameters", x => x.Id);
        table.ForeignKey(
            name: "FK_TechnologicalOperationParameters_TechnologicalOperations_Op-",
            column: x => x.OperationId,
            principalSchema: "mdm",
            principalTable: "TechnologicalOperations",
            principalColumn: "Id",
            onDelete: ReferentialAction.Cascade);
        table.ForeignKey(
            name: "FK_TechnologicalOperationParameters_TechnologicalParameters_Pa~",
            column: x => x.ParameterId,
            principalSchema: "mdm",
            principalTable: "TechnologicalParameters",
            principalColumn: "Id",
            onDelete: ReferentialAction.Cascade);
    });

migrationBuilder.CreateTable(
    name: "DepartmentUnits",
    schema: "mdm",
    columns: table => new
    {
        Id = table.Column<Guid>(type: "uuid", nullable: false)
    },
    constraints: table =>
    {
        table.PrimaryKey("PK_DepartmentUnits", x => x.Id);
        table.ForeignKey(
            name: "FK_DepartmentUnits_Units_Id",
            column: x => x.Id,
            principalSchema: "mdm",
            principalTable: "Units",
            principalColumn: "Id",
            onDelete: ReferentialAction.Cascade);
    });

migrationBuilder.CreateTable(
    name: "PositionUnits",
    schema: "mdm",
    columns: table => new
    {
        Id = table.Column<Guid>(type: "uuid", nullable: false)
    },

```

```

constraints: table => {
  table.PrimaryKey("PK_PositionUnits", x => x.Id);
  table.ForeignKey(
    name: "FK_PositionUnits_Units_Id",
    column: x => x.Id,
    principalSchema: "mdm",
    principalTable: "Units",
    principalColumn: "Id",
    onDelete: ReferentialAction.Cascade);
});

migrationBuilder.CreateTable(
  name: "ProductionUnits",
  schema: "mdm",
  columns: table => new {
    Id = table.Column<Guid>(type: "uuid", nullable: false),
  },
  constraints: table => {
    table.PrimaryKey("PK_ProductionUnits", x => x.Id);
    table.ForeignKey(
      name: "FK_ProductionUnits_Units_Id",
      column: x => x.Id,
      principalSchema: "mdm",
      principalTable: "Units",
      principalColumn: "Id",
      onDelete: ReferentialAction.Cascade);
  });

migrationBuilder.CreateTable(
  name: "StorageUnits",
  schema: "mdm",
  columns: table => new {
    Id = table.Column<Guid>(type: "uuid", nullable: false),
  },
  constraints: table => {
    table.PrimaryKey("PK_StorageUnits", x => x.Id);
    table.ForeignKey(
      name: "FK_StorageUnits_Units_Id",
      column: x => x.Id,
      principalSchema: "mdm",
      principalTable: "Units",
      principalColumn: "Id",
      onDelete: ReferentialAction.Cascade);
  });

migrationBuilder.CreateTable(
  name: "TechnologicalOperationUnits",
  schema: "mdm",
  columns: table => new {
    Id = table.Column<Guid>(type: "uuid", nullable: false),
    CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),
    OperationId = table.Column<Guid>(type: "uuid", nullable: false),
    UnitId = table.Column<Guid>(type: "uuid", nullable: false),
    Priority = table.Column<int>(type: "integer", nullable: false),
    DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),
    DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),
  },
  constraints: table => {
    table.PrimaryKey("PK_TechnologicalOperationUnits", x => x.Id);
    table.ForeignKey(
      name: "FK_TechnologicalOperationUnits_TechnologicalOperations_Operati~",
      column: x => x.OperationId,
      principalSchema: "mdm",
      principalTable: "TechnologicalOperations",
      principalColumn: "Id",
      onDelete: ReferentialAction.Cascade);
  });

```

```

        table.ForeignKey(Ø
            name: "FK_TechnologicalOperationUnits_Units_UnitId",Ø
            column: x => x.UnitId,Ø
            principalSchema: "mdm",Ø
            principalTable: "Units",Ø
            principalColumn: "Id",Ø
            onDelete: ReferentialAction.Cascade);Ø
    });Ø
Ø
migrationBuilder.CreateTable(Ø
    name: "TransportUnits",Ø
    schema: "mdm",Ø
    columns: table => newØ
    {Ø
        Id = table.Column<Guid>(type: "uuid", nullable: false)Ø
    },Ø
    constraints: table =>Ø
    {Ø
        table.PrimaryKey("PK_TransportUnits", x => x.Id);Ø
        table.ForeignKey(Ø
            name: "FK_TransportUnits_Units_Id",Ø
            column: x => x.Id,Ø
            principalSchema: "mdm",Ø
            principalTable: "Units",Ø
            principalColumn: "Id",Ø
            onDelete: ReferentialAction.Cascade);Ø
    });Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperationParameters_DeletedAt",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperationParameters",Ø
    column: "DeletedAt");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperationParameters_OperationId",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperationParameters",Ø
    column: "OperationId");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperationParameters_ParameterId",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperationParameters",Ø
    column: "ParameterId");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperations_DeletedAt",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperations",Ø
    column: "DeletedAt");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperations_ParentId",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperations",Ø
    column: "ParentId");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperationUnits_DeletedAt",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperationUnits",Ø
    column: "DeletedAt");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperationUnits_OperationId",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperationUnits",Ø
    column: "OperationId");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalOperationUnits_UnitId",Ø
    schema: "mdm",Ø
    table: "TechnologicalOperationUnits",Ø
    column: "UnitId");Ø
Ø

```



```

        migrationBuilder.CreateIndex(
            name: "IX_TechnologicalParameters_DeletedAt",
            schema: "mdm",
            table: "TechnologicalParameters",
            column: "DeletedAt");
    }

    migrationBuilder.CreateIndex(
        name: "IX_Units_DeletedAt",
        schema: "mdm",
        table: "Units",
        column: "DeletedAt");
    }

    migrationBuilder.CreateIndex(
        name: "IX_Units_ParentId",
        schema: "mdm",
        table: "Units",
        column: "ParentId");
    }
}

/// <inheritdoc />
protected override void Down(MigrationBuilder migrationBuilder)
{
    migrationBuilder.DropTable(
        name: "AuditLogs",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "DepartmentUnits",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "PositionUnits",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "ProductionUnits",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "StorageUnits",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "TechnologicalOperationParameters",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "TechnologicalOperationUnits",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "TransportUnits",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "TechnologicalParameters",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "TechnologicalOperations",
        schema: "mdm");

    migrationBuilder.DropTable(
        name: "Units",
        schema: "mdm");
    }
}
}
</file>

<file path="Promatis.Net.Test.MDM.DataInit/
Migrations/20260521060225_TechnologicalParameterCalcMethod.cs">
using System;
using Microsoft.EntityFrameworkCore.Migrations;
#nullable disabled

```

```

    namespace Promatis.Net.Test.MDM.DataInit.Migrations
    {
        /// <inheritdoc />
        public partial class TechnologicalParameterCalcMethod : Migration
        {
            /// <inheritdoc />
            protected override void Up(MigrationBuilder migrationBuilder)
            {
                migrationBuilder.RenameIndex(
                    name: "IX_Units_ParentId",
                    schema: "mdm",
                    table: "Units",
                    newName: "IX_UnitBase_ParentId");

                migrationBuilder.RenameIndex(
                    name: "IX_TechnologicalOperations_ParentId",
                    schema: "mdm",
                    table: "TechnologicalOperations",
                    newName: "IX_TechnologicalOperation_ParentId");

                migrationBuilder.CreateTable(
                    name: "TechnologicalParameterCalcMethods",
                    schema: "mdm",
                    columns: table => new
                    {
                        Id = table.Column<Guid>(type: "uuid", nullable: false),
                        CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),
                        UnitId = table.Column<Guid>(type: "uuid", nullable: false),
                        TechnologicalOperationId = table.Column<Guid>(type: "uuid", nullable: false),
                        TechnologicalParameterId = table.Column<Guid>(type: "uuid", nullable: false),
                        CalculationMethod = table.Column<int>(type: "integer", nullable: false),
                        DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),
                        DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true)
                    },
                    constraints: table =>
                    {
                        table.PrimaryKey("PK_TechnologicalParameterCalcMethods", x => x.Id);
                        table.ForeignKey(
                            name: "FK_TechnologicalParameterCalcMethods_TechnologicalOperations_T~",
                            column: x => x.TechnologicalOperationId,
                            principalSchema: "mdm",
                            principalTable: "TechnologicalOperations",
                            principalColumn: "Id",
                            onDelete: ReferentialAction.Cascade);
                        table.ForeignKey(
                            name: "FK_TechnologicalParameterCalcMethods_TechnologicalParameters_T~",
                            column: x => x.TechnologicalParameterId,
                            principalSchema: "mdm",
                            principalTable: "TechnologicalParameters",
                            principalColumn: "Id",
                            onDelete: ReferentialAction.Cascade);
                        table.ForeignKey(
                            name: "FK_TechnologicalParameterCalcMethods_Units_UnitId",
                            column: x => x.UnitId,
                            principalSchema: "mdm",
                            principalTable: "Units",
                            principalColumn: "Id",
                            onDelete: ReferentialAction.Cascade);
                    });

                migrationBuilder.CreateIndex(
                    name: "IX_TechnologicalParameterCalcMethods_DeletedAt",
                    schema: "mdm",
                    table: "TechnologicalParameterCalcMethods",
                    column: "DeletedAt");

                migrationBuilder.CreateIndex(
                    name: "IX_TechnologicalParameterCalcMethods_TechnologicalOperationId",
                    schema: "mdm",
                    table: "TechnologicalParameterCalcMethods",
                    column: "TechnologicalOperationId");
            }
        }
    }

```

```

        migrationBuilder.CreateIndex(
            name: "IX_TechnologicalParameterCalcMethods_TechnologicalParameterId",
            schema: "mdm",
            table: "TechnologicalParameterCalcMethods",
            column: "TechnologicalParameterId");

        migrationBuilder.CreateIndex(
            name: "IX_TechnologicalParameterCalcMethods_UnitId",
            schema: "mdm",
            table: "TechnologicalParameterCalcMethods",
            column: "UnitId");
    }

    /// <inheritdoc />
    protected override void Down(MigrationBuilder migrationBuilder)
    {
        migrationBuilder.DropTable(
            name: "TechnologicalParameterCalcMethods",
            schema: "mdm");

        migrationBuilder.RenameIndex(
            name: "IX_UnitBase_ParentId",
            schema: "mdm",
            table: "Units",
            newName: "IX_Units_ParentId");

        migrationBuilder.RenameIndex(
            name: "IX_TechnologicalOperation_ParentId",
            schema: "mdm",
            table: "TechnologicalOperations",
            newName: "IX_TechnologicalOperations_ParentId");
    }
}
</file>

<file path="Promatis.Net.Test.MDM.DataInit/Migrations/20260528090200_Add-UnitOfMeasurement.cs">
using System;
using Microsoft.EntityFrameworkCore.Migrations;
#nullable disabled
namespace Promatis.Net.Test.MDM.DataInit.Migrations
{
    /// <inheritdoc />
    public partial class AddUnitOfMeasurement : Migration
    {
        /// <inheritdoc />
        protected override void Up(MigrationBuilder migrationBuilder)
        {
            migrationBuilder.DropColumn(
                name: "UnitOfMeasurement",
                schema: "mdm",
                table: "TechnologicalParameters");

            migrationBuilder.AddColumn<int>(
                name: "AllowedMethods",
                schema: "mdm",
                table: "TechnologicalParameters",
                type: "integer",
                nullable: false,
                defaultValue: 0);

            migrationBuilder.AddColumn<Guid>(
                name: "UnitOfMeasurementId",
                schema: "mdm",
                table: "TechnologicalParameters",
                type: "uuid",
                nullable: true);

            migrationBuilder.CreateTable(
                name: "UnitOfMeasurements",
                schema: "mdm",
                columns: table => new
                {
                    Id = table.Column<Guid>(type: "uuid", nullable: false),

```

```

        CreatedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
false),Ø
        Name = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: false),Ø
        Description = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true),Ø
        Code = table.Column<string>(type: "character varying(255)", maxLength: 255,
nullable: true),Ø
        DeletedAt = table.Column<DateTime>(type: "timestamp with time zone", nullable:
true),Ø
        DeletedBy = table.Column<string>(type: "character varying(255)", maxLength:
255, nullable: true)Ø
    },Ø
    constraints: table =>Ø
    {Ø
        table.PrimaryKey("PK_UnitOfMeasurements", x => x.Id);Ø
    });Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_TechnologicalParameters_UnitOfMeasurementId",Ø
    schema: "mdm",Ø
    table: "TechnologicalParameters",Ø
    column: "UnitOfMeasurementId");Ø
Ø
migrationBuilder.CreateIndex(Ø
    name: "IX_UnitOfMeasurements_DeletedAt",Ø
    schema: "mdm",Ø
    table: "UnitOfMeasurements",Ø
    column: "DeletedAt");Ø
Ø
migrationBuilder.AddForeignKey(Ø
    name: "FK_TechnologicalParameters_UnitOfMeasurements_UnitOfMeasuremen~",Ø
    schema: "mdm",Ø
    table: "TechnologicalParameters",Ø
    column: "UnitOfMeasurementId",Ø
    principalSchema: "mdm",Ø
    principalTable: "UnitOfMeasurements",Ø
    principalColumn: "Id");Ø
}Ø
Ø
/// <inheritdoc />Ø
protected override void Down(MigrationBuilder migrationBuilder)Ø
{Ø
    migrationBuilder.DropForeignKey(Ø
        name: "FK_TechnologicalParameters_UnitOfMeasurements_UnitOfMeasuremen~",Ø
        schema: "mdm",Ø
        table: "TechnologicalParameters");Ø
Ø
migrationBuilder.DropTable(Ø
    name: "UnitOfMeasurements",Ø
    schema: "mdm");Ø
Ø
migrationBuilder.DropIndex(Ø
    name: "IX_TechnologicalParameters_UnitOfMeasurementId",Ø
    schema: "mdm",Ø
    table: "TechnologicalParameters");Ø
Ø
migrationBuilder.DropColumn(Ø
    name: "AllowedMethods",Ø
    schema: "mdm",Ø
    table: "TechnologicalParameters");Ø
Ø
migrationBuilder.DropColumn(Ø
    name: "UnitOfMeasurementId",Ø
    schema: "mdm",Ø
    table: "TechnologicalParameters");Ø
Ø
migrationBuilder.AddColumn<string>(Ø
    name: "UnitOfMeasurement",Ø
    schema: "mdm",Ø
    table: "TechnologicalParameters",Ø
    type: "character varying(255)",Ø
    maxLength: 255,Ø
    nullable: false,Ø
    defaultValue: "");Ø
}Ø

```

```

    }
}
</file>

<file path="Promatis.Net.Test.MDM.DataInit/Migrations/MdmApplicationDbContextModelSnapshot.cs">
// <auto-generated />
using System;
using Microsoft.EntityFrameworkCore;
using Microsoft.EntityFrameworkCore.Infrastructure;
using Microsoft.EntityFrameworkCore.Storage.ValueConversion;
using Npgsql.EntityFrameworkCore.PostgreSQL.Metadata;
using Promatis.Net.Test.MDM.Data;

#nullable disabled
namespace Promatis.Net.Test.MDM.DataInit.Migrations
{
    [DbContext(typeof(MdmApplicationDbContext))]
    partial class MdmApplicationDbContextModelSnapshot : ModelSnapshot
    {
        protected override void BuildModel(ModelBuilder modelBuilder)
        {
#pragma warning disable 612, 618
            modelBuilder
                .HasDefaultSchema("mdm")
                .HasAnnotation("ProductVersion", "10.0.8")
                .HasAnnotation("Relational:MaxIdentifierLength", 63);

            NpgsqlModelBuilderExtensions.UseIdentityByDefaultColumns(modelBuilder);

            modelBuilder.Entity("Promatis.Net.Domain.AuditLog", b =>
            {
                b.Property<Guid>("Id")
                    .HasColumnType("uuid");

                b.Property<string>("Action")
                    .IsRequired()
                    .HasMaxLength(50)
                    .HasColumnType("character varying(50)");

                b.Property<DateTime>("ChangedAt")
                    .HasColumnType("timestamp with time zone");

                b.Property<string>("ChangedBy")
                    .HasMaxLength(100)
                    .HasColumnType("character varying(100)");

                b.Property<string>("ChangesJson")
                    .IsRequired()
                    .HasMaxLength(255)
                    .HasColumnType("jsonb");

                b.Property<DateTime>("CreatedAt")
                    .HasColumnType("timestamp with time zone");

                b.Property<Guid>("EntityId")
                    .HasColumnType("uuid");

                b.Property<string>("EntityName")
                    .IsRequired()
                    .HasMaxLength(100)
                    .HasColumnType("character varying(100)");

                b.HasKey("Id");

                b.ToTable("AuditLogs", "mdm");
            });

            modelBuilder.Entity("Promatis.Net.MES.Domain.UnitBase", b =>
            {
                b.Property<Guid>("Id")
                    .HasColumnType("uuid");

                b.Property<string>("Code")
                    .HasMaxLength(255)
                    .HasColumnType("character varying(255)");
            });
        }
    }
}

```

```

        b.Property<DateTime>("CreatedAt")
            .HasColumnType("timestamp with time zone");

        b.Property<DateTime?>("DeletedAt")
            .HasColumnType("timestamp with time zone");

        b.Property<string>("DeletedBy")
            .HasMaxLength(255)
            .HasColumnType("character varying(255)");

        b.Property<string>("Description")
            .HasMaxLength(255)
            .HasColumnType("character varying(255)");

        b.Property<int>("Kind")
            .HasColumnType("integer");

        b.Property<string>("Name")
            .IsRequired()
            .HasMaxLength(255)
            .HasColumnType("character varying(255)");

        b.Property<Guid?>("ParentId")
            .HasColumnType("uuid");

        b.Property<int>("Type")
            .HasColumnType("integer");

        b.HasKey("Id");

        b.HasIndex("DeletedAt");

        b.HasIndex("ParentId")
            .HasDatabaseName("IX_UnitBase_ParentId");

        b.ToTable("Units", "mdm");

        b.UseTptMappingStrategy();
    });

modelBuilder.Entity("Promatis.Net.MES.Domain.UnitOfMeasurement", b =>
{
    b.Property<Guid>("Id")
        .HasColumnType("uuid");

    b.Property<string>("Code")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<DateTime>("CreatedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<DateTime?>("DeletedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DeletedBy")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<string>("Description")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<string>("Name")
        .IsRequired()
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.HasKey("Id");

    b.HasIndex("DeletedAt");

    b.ToTable("UnitOfMeasurements", "mdm");
});

```

```

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperation", b =>
{
    b.Property<Guid>("Id")
        .HasColumnType("uuid");

    b.Property<string>("Code")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<DateTime>("CreatedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<DateTime?>("DeletedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DeletedBy")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<string>("Description")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<bool>("IsLeaf")
        .HasColumnType("boolean");

    b.Property<string>("Name")
        .IsRequired()
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<Guid?>("ParentId")
        .HasColumnType("uuid");

    b.HasKey("Id");

    b.HasIndex("DeletedAt");

    b.HasIndex("ParentId")
        .HasDatabaseName("IX_TechnologicalOperation_ParentId");

    b.ToTable("TechnologicalOperations", "mdm");
});

```

```

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperationParameter", b =>
{
    b.Property<Guid>("Id")
        .HasColumnType("uuid");

    b.Property<DateTime>("CreatedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DefaultValue")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<DateTime?>("DeletedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DeletedBy")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<bool>("IsRequired")
        .HasColumnType("boolean");

    b.Property<double?>("MaxValue")
        .HasColumnType("double precision");

    b.Property<double?>("MinValue")
        .HasColumnType("double precision");

    b.Property<Guid>("OperationId")
        .HasColumnType("uuid");

    b.Property<Guid>("ParameterId")

```

```

        .HasColumnType("uuid");
    }

    b.HasKey("Id");

    b.HasIndex("DeletedAt");

    b.HasIndex("OperationId");

    b.HasIndex("ParameterId");

    b.ToTable("TechnologicalOperationParameters", "mdm");
});

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperationUnit", b =>
{
    b.Property<Guid>("Id")
        .HasColumnType("uuid");

    b.Property<DateTime>("CreatedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<DateTime?>("DeletedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DeletedBy")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<Guid>("OperationId")
        .HasColumnType("uuid");

    b.Property<int>("Priority")
        .HasColumnType("integer");

    b.Property<Guid>("UnitId")
        .HasColumnType("uuid");

    b.HasKey("Id");

    b.HasIndex("DeletedAt");

    b.HasIndex("OperationId");

    b.HasIndex("UnitId");

    b.ToTable("TechnologicalOperationUnits", "mdm");
});

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalParameter", b =>
{
    b.Property<Guid>("Id")
        .HasColumnType("uuid");

    b.Property<int>("AllowedMethods")
        .HasColumnType("integer");

    b.Property<string>("Code")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<DateTime>("CreatedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DataType")
        .IsRequired()
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<DateTime?>("DeletedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DeletedBy")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<string>("Description")

```



```

        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

        b.Property<string>("Name")
            .IsRequired()
            .HasMaxLength(255)
            .HasColumnType("character varying(255)");

        b.Property<Guid?>("UnitOfMeasurementId")
            .HasColumnType("uuid");

        b.HasKey("Id");

        b.HasIndex("DeletedAt");

        b.HasIndex("UnitOfMeasurementId");

        b.ToTable("TechnologicalParameters", "mdm");
    });

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalParameterCalcMethod", b =>
{
    b.Property<Guid>("Id")
        .HasColumnType("uuid");

    b.Property<int>("CalculationMethod")
        .HasColumnType("integer");

    b.Property<DateTime>("CreatedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<DateTime?>("DeletedAt")
        .HasColumnType("timestamp with time zone");

    b.Property<string>("DeletedBy")
        .HasMaxLength(255)
        .HasColumnType("character varying(255)");

    b.Property<Guid>("TechnologicalOperationId")
        .HasColumnType("uuid");

    b.Property<Guid>("TechnologicalParameterId")
        .HasColumnType("uuid");

    b.Property<Guid>("UnitId")
        .HasColumnType("uuid");

    b.HasKey("Id");

    b.HasIndex("DeletedAt");

    b.HasIndex("TechnologicalOperationId");

    b.HasIndex("TechnologicalParameterId");

    b.HasIndex("UnitId");

    b.ToTable("TechnologicalParameterCalcMethods", "mdm");
});

modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.DepartmentUnit", b =>
{
    b.HasBaseType("Promatis.Net.MES.Domain.UnitBase");

    b.ToTable("DepartmentUnits", "mdm");
});

modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.PositionUnit", b =>
{
    b.HasBaseType("Promatis.Net.MES.Domain.UnitBase");

    b.ToTable("PositionUnits", "mdm");
});

modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.ProductionUnit", b =>
{

```

```

        b.HasBaseType("Promatis.Net.MES.Domain.UnitBase");
    }
    b.ToTable("ProductionUnits", "mdm");
});

modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.StorageUnit", b =>
{
    b.HasBaseType("Promatis.Net.MES.Domain.UnitBase");

    b.ToTable("StorageUnits", "mdm");
});

modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.TransportUnit", b =>
{
    b.HasBaseType("Promatis.Net.MES.Domain.UnitBase");

    b.ToTable("TransportUnits", "mdm");
});

modelBuilder.Entity("Promatis.Net.MES.Domain.UnitBase", b =>
{
    b.HasOne("Promatis.Net.MES.Domain.UnitBase", "Parent")
        .WithMany("Children")
        .HasForeignKey("ParentId")
        .OnDelete(DeleteBehavior.Restrict);

    b.Navigation("Parent");
});

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperation", b =>
{
    b.HasOne("Promatis.Net.MES.MDM.Domain.TechnologicalOperation", "Parent")
        .WithMany("Children")
        .HasForeignKey("ParentId")
        .OnDelete(DeleteBehavior.Restrict);

    b.Navigation("Parent");
});

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperationParameter", b =>
{
    b.HasOne("Promatis.Net.MES.MDM.Domain.TechnologicalOperation", "Operation")
        .WithMany("ParameterLinks")
        .HasForeignKey("OperationId")
        .OnDelete(DeleteBehavior.Cascade)
        .IsRequired();

    b.HasOne("Promatis.Net.MES.MDM.Domain.TechnologicalParameter", "Parameter")
        .WithMany()
        .HasForeignKey("ParameterId")
        .OnDelete(DeleteBehavior.Cascade)
        .IsRequired();

    b.Navigation("Operation");
    b.Navigation("Parameter");
});

modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperationUnit", b =>
{
    b.HasOne("Promatis.Net.MES.MDM.Domain.TechnologicalOperation", "Operation")
        .WithMany("UnitLinks")
        .HasForeignKey("OperationId")
        .OnDelete(DeleteBehavior.Cascade)
        .IsRequired();

    b.HasOne("Promatis.Net.MES.Domain.UnitBase", "Unit")
        .WithMany()
        .HasForeignKey("UnitId")
        .OnDelete(DeleteBehavior.Cascade)
        .IsRequired();

    b.Navigation("Operation");
    b.Navigation("Unit");
});

```

```

    modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalParameter", b =>
    {
        b.HasOne("Promatis.Net.MES.Domain.UnitOfMeasurement", "UnitOfMeasurement")
            .WithMany()
            .HasForeignKey("UnitOfMeasurementId");

        b.Navigation("UnitOfMeasurement");
    });

    modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalParameterCalcMethod", b =>
    {
        b.HasOne("Promatis.Net.MES.MDM.Domain.TechnologicalOperation",
"TechnologicalOperation")
            .WithMany()
            .HasForeignKey("TechnologicalOperationId")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();

        b.HasOne("Promatis.Net.MES.MDM.Domain.TechnologicalParameter",
"TechnologicalParameter")
            .WithMany()
            .HasForeignKey("TechnologicalParameterId")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();

        b.HasOne("Promatis.Net.MES.Domain.UnitBase", "Unit")
            .WithMany()
            .HasForeignKey("UnitId")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();

        b.Navigation("TechnologicalOperation");

        b.Navigation("TechnologicalParameter");

        b.Navigation("Unit");
    });

    modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.DepartmentUnit", b =>
    {
        b.HasOne("Promatis.Net.MES.Domain.UnitBase", null)
            .WithOne()
            .HasForeignKey("Promatis.Net.Test.MDM.Domain.DepartmentUnit", "Id")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();
    });

    modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.PositionUnit", b =>
    {
        b.HasOne("Promatis.Net.MES.Domain.UnitBase", null)
            .WithOne()
            .HasForeignKey("Promatis.Net.Test.MDM.Domain.PositionUnit", "Id")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();
    });

    modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.ProductionUnit", b =>
    {
        b.HasOne("Promatis.Net.MES.Domain.UnitBase", null)
            .WithOne()
            .HasForeignKey("Promatis.Net.Test.MDM.Domain.ProductionUnit", "Id")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();
    });

    modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.StorageUnit", b =>
    {
        b.HasOne("Promatis.Net.MES.Domain.UnitBase", null)
            .WithOne()
            .HasForeignKey("Promatis.Net.Test.MDM.Domain.StorageUnit", "Id")
            .OnDelete(DeleteBehavior.Cascade)
            .IsRequired();
    });

    modelBuilder.Entity("Promatis.Net.Test.MDM.Domain.TransportUnit", b =>

```

```

        {
            b.HasOne("Promatis.Net.MES.Domain.UnitBase", null)
                .WithOne()
                .HasForeignKey("Promatis.Net.Test.MDM.Domain.TransportUnit", "Id")
                .OnDelete(DeleteBehavior.Cascade)
                .IsRequired();
        });

        modelBuilder.Entity("Promatis.Net.MES.Domain.UnitBase", b =>
        {
            b.Navigation("Children");
        });

        modelBuilder.Entity("Promatis.Net.MES.MDM.Domain.TechnologicalOperation", b =>
        {
            b.Navigation("Children");

            b.Navigation("ParameterLinks");

            b.Navigation("UnitLinks");
        });
#pragma warning restore 612, 618
    }
}
</file>

<file path="Promatis.Net.Test.MDM.DataInit/Promatis.Net.Test.MDM.DataInit.csproj">
<Project Sdk="Microsoft.NET.Sdk">
    <PropertyGroup>
        <TargetFramework>net10.0</TargetFramework>
        <ImplicitUsings>enable</ImplicitUsings>
        <Nullable>enable</Nullable>
    </PropertyGroup>
    <ItemGroup>
        <PackageReference Include="Microsoft.EntityFrameworkCore.Design" Version="10.0.8">
            <PrivateAssets>all</PrivateAssets>
            <IncludeAssets>runtime; build; native; contentfiles; analyzers; buildtransitive</IncludeAssets>
        </PackageReference>
        <PackageReference Include="Microsoft.EntityFrameworkCore.Relational" Version="10.0.8" />
        <PackageReference Include="Microsoft.EntityFrameworkCore.Tools" Version="10.0.8">
            <PrivateAssets>all</PrivateAssets>
            <IncludeAssets>runtime; build; native; contentfiles; analyzers; buildtransitive</IncludeAssets>
        </PackageReference>
        <PackageReference Include="Microsoft.Extensions.Configuration" Version="10.0.8" />
        <PackageReference Include="Microsoft.Extensions.Configuration.Binder" Version="10.0.8" />
        <PackageReference Include="Microsoft.Extensions.Configuration.Json" Version="10.0.8" />
        <PackageReference Include="Npgsql.EntityFrameworkCore.PostgreSQL" Version="10.0.1" />
    </ItemGroup>
    <ItemGroup>
        <ProjectReference Include="..\Promatis.Net.Test.MDM.Data\Promatis.Net.Test.MDM.Data.csproj" />
    </ItemGroup>
</Project>
</file>

<file path="Promatis.Net.Test.MDM.Domain.Interface/Class1.cs">
namespace Promatis.Net.Test.MDM.Domain.Interface
{
    public class Class1
    {
    }
}
</file>

<file path="Promatis.Net.Test.MDM.Domain.Interface/Promatis.Net.Test.MDM.Domain.Interface.csproj">
<Project Sdk="Microsoft.NET.Sdk">
    <PropertyGroup>
        <TargetFramework>net10.0</TargetFramework>

```

```

        <ImplicitUsings>enable</ImplicitUsings>ð
        <Nullable>enable</Nullable>ð
    </PropertyGroup>ð
ð
    <ItemGroup>ð
        <ProjectReference Include="..\..\..\
\Mes\MDM\Promatis.Net.MES.MDM.Domain.Interface\Promatis.Net.MES.MDM.Domain.Interface.csproj" />ð
    </ItemGroup>ð
ð
</Project>
</file>

<file path="Promatis.Net.Test.MDM.Domain/DepartmentUnit.cs">
using Promatis.Net.MES.MDM.Domain;ð
ð
namespace Promatis.Net.Test.MDM.Domain;ð
ð
/// <summary>ð
/// Að0D$5C4>D 8Dó¢ CT?C @D$0CÄ5CÔB (Bd5DRÂ #Dt0D BCä: Cð0C¢ >D 3-CT4C,,=C,,FC •
/// </summary>ð
public class DepartmentUnit : DepartmentUnitBase { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/DepartmentUnitValidator.cs">
using Promatis.Net.MES.MDM.Domain;ð
ð
namespace Promatis.Net.Test.MDM.Domain;ð
ð
public class DepartmentUnitValidator : DepartmentUnitBaseValidator<DepartmentUnit> { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/PositionUnit.cs">
using Promatis.Net.MES.MDM.Domain;ð
ð
namespace Promatis.Net.Test.MDM.Domain;ð
ð
/// <summary>ð
/// Að0D$5C4>D 8Dó¢ Cä7C,,FC,,O (BôGCT9Cð0, B 0C >Dt0Dò BCäGCð0)ð
/// </summary>ð
public class PositionUnit : PositionUnitBase { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/PositionUnitValidator.cs">
using Promatis.Net.MES.MDM.Domain;ð
ð
namespace Promatis.Net.Test.MDM.Domain;ð
ð
public class PositionUnitValidator : PositionUnitBaseValidator<PositionUnit> { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/ProductionUnit.cs">
using Promatis.Net.MES.MDM.Domain;ð
ð
namespace Promatis.Net.Test.MDM.Domain;ð
ð
/// <summary>ð
/// Að0D$5C4>D 8Dó¢ D >C,,7C$>CDAD$2Cä ,, C,,=C,,O, B BC =Cä:, A$5D AD$0C¢•
/// </summary>ð
public class ProductionUnit : ProductionUnitBase { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/ProductionUnitValidator.cs">
using Promatis.Net.MES.MDM.Domain;ð
ð
namespace Promatis.Net.Test.MDM.Domain;ð
ð
class ProductionUnitValidator : ProductionUnitBaseValidator<ProductionUnit> { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/Promatis.Net.Test.MDM.Domain.csproj">
<Project Sdk="Microsoft.NET.Sdk">ð
ð
    <PropertyGroup>ð
        <TargetFramework>net10.0</TargetFramework>ð
        <ImplicitUsings>enable</ImplicitUsings>ð
        <Nullable>enable</Nullable>ð
    </PropertyGroup>ð

```

```

    </PropertyGroup>
  <ItemGroup>
    <PackageReference Include="Microsoft.EntityFrameworkCore.Relational" Version="10.0.8" />
  </ItemGroup>
  <ItemGroup>
    <ProjectReference Include="..\..\Mes\MDM\Promatis.Net.MES.MDM.Domain\Promatis.Net.MES.MDM.Domain.csproj" />
    <ProjectReference Include="..\Promatis.Net.Test.MDM.Domain.Interface\Promatis.Net.Test.MDM.Domain.Interface.csproj" />
  </ItemGroup>
</Project>
</file>

<file path="Promatis.Net.Test.MDM.Domain\StorageUnit.cs">
using Promatis.Net.MES.MDM.Domain;
namespace Promatis.Net.Test.MDM.Domain;
/// <summary>
/// Að$5C4>D 8Dó¢ !C¢;C 4 (B :C´0CBÂ Că=C Â !D$5C´;C 6)
/// </summary>
public class StorageUnit : StorageUnitBase { }
</file>

<file path="Promatis.Net.Test.MDM.Domain\StorageUnitValidator.cs">
using Promatis.Net.MES.MDM.Domain;
namespace Promatis.Net.Test.MDM.Domain;
public class StorageUnitValidator : StorageUnitBaseValidator<StorageUnit> { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/TransportUnit.cs">
using Promatis.Net.MES.MDM.Domain;
namespace Promatis.Net.Test.MDM.Domain;
/// <summary>
/// Að$5C4>D 8Dó¢ "D 0CÔACô>D B (Aô>C4@D47Dt8C¢Â Că=C$5C"5D •
/// </summary>
public class TransportUnit : TransportUnitBase { }
</file>

<file path="Promatis.Net.Test.MDM.Domain/TransportUnitValidator.cs">
using Promatis.Net.MES.MDM.Domain;
namespace Promatis.Net.Test.MDM.Domain;
public class TransportUnitValidator : TransportUnitBaseValidator<TransportUnit> { }
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/appsettings.Development.json">
{
  "Logging": {
    "LogLevel": {
      "Default": "Information",
      "Microsoft.AspNetCore": "Warning"
    }
  }
}
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/appsettings.json">
{
  "LauncherSettings": {
    "Modules": [
      "Promatis.Net.Test.MDM.Launcher.Web.DefaultWebConfig",
      "Promatis.Net.Test.MDM.Configuration.Configurator"
    ]
  },
  "Logging": {
    "LogLevel": {

```

```

        "Default": "Information",
        "Microsoft.AspNetCore": "Warning"
    },
    "AllowedHosts": "*",
    "ConnectionStrings": {
        "DefaultConnection": "Host=10.10.10.132;Port=5432;Database=TestBase;Username=guest"
    }
}
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/Bootstrapper.cs">
using Promatis.Net.Configuration.Web;
namespace Promatis.Net.Test.MDM.Launcher.Web;
public class Bootstrapper : WebAppBootstrapper<Components.App> { }
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/Components/_Imports.razor">
@using Microsoft.AspNetCore.Components.Web
@using Microsoft.AspNetCore.Components.Routing
@using MudBlazor
@using Promatis.Net.Configuration.Web.Components
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/Components/App.razor">
@using Promatis.Net.Configuration.Web.Components.Layout
<!DOCTYPE html>
<html lang="ru">
<head>
    <meta charset="utf-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <base href="/" />
    <link href="https://googleapis.com" rel="stylesheet" />
    <link href="@Assets["_content/MudBlazor/MudBlazor.min.css"]" rel="stylesheet" />
    <ResourcePreloader />
    <link rel="stylesheet" href="@Assets["_content/Promatis.Net.Ui/app.css"]" />
    <link rel="stylesheet" href="@Assets["Promatis.Net.Web.UI.styles.css"]" />
    <ImportMap />
    <HeadOutlet />
</head>
<body>
    <Routes @rendermode="RenderMode.InteractiveServer" />
    <ReconnectModal />
</body>
</html>
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/DefaultWebConfig.cs">
using Promatis.Net.Configuration.Web;
namespace Promatis.Net.Test.MDM.Launcher.Web;
public class DefaultWebConfig : WebAppConfigurator<Components.App> { }
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/Program.cs">
using Promatis.Net.Test.MDM.Launcher.Web;

```

```

    Ø
    new Bootstrapper().Run(args);
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/Promatis.Net.Test.MDM.Launcher.Web.csproj">
<Project Sdk="Microsoft.NET.Sdk.Web">Ø
    Ø
    <PropertyGroup>Ø
        <TargetFramework>net10.0</TargetFramework>Ø
        <Nullable>enable</Nullable>Ø
        <ImplicitUsings>enable</ImplicitUsings>Ø
        <BlazorDisableThrowNavigationException>true</BlazorDisableThrowNavigationException>Ø
    </PropertyGroup>Ø
    Ø
    <ItemGroup>Ø
        <PackageReference Include="Microsoft.EntityFrameworkCore.Design" Version="10.0.8">Ø
            <PrivateAssets>all</PrivateAssets>Ø
            <IncludeAssets>runtime; build; native; contentfiles; analyzers; buildtransitive</
IncludeAssets>Ø
        </PackageReference>Ø
        <PackageReference Include="Npgsql.EntityFrameworkCore.PostgreSQL" Version="10.0.1" />Ø
    </ItemGroup>Ø
    Ø
    <ItemGroup>Ø
        <ProjectReference Include="..\..\..\
\Core\Configuration.Web\Promatis.Net.Configuration.Web.csproj" />Ø
        <ProjectReference Include="..\
\Promatis.Net.Test.MDM.Configuration\Promatis.Net.Test.MDM.Configuration.csproj" />Ø
    </ItemGroup>Ø
    Ø
</Project>
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/Properties/launchSettings.json">
{Ø
    "$schema": "https://json.schemastore.org/launchsettings.json",Ø
    "profiles": {Ø
        "http": {Ø
            "commandName": "Project",Ø
            "dotnetRunMessages": true,Ø
            "launchBrowser": true,Ø
            "applicationUrl": "http://localhost:5123",Ø
            "environmentVariables": {Ø
                "ASPNETCORE_ENVIRONMENT": "Development"Ø
            }Ø
        },Ø
        "https": {Ø
            "commandName": "Project",Ø
            "dotnetRunMessages": true,Ø
            "launchBrowser": true,Ø
            "applicationUrl": "https://localhost:7285;http://localhost:5123",Ø
            "environmentVariables": {Ø
                "ASPNETCORE_ENVIRONMENT": "Development"Ø
            }Ø
        }Ø
    }Ø
}
</file>

<file path="Promatis.Net.Test.MDM.Launcher.Web/wwwroot/app.css">
h1:focus {Ø
    outline: none;Ø
}Ø
Ø
.valid.modified:not([type=checkbox]) {Ø
    outline: 1px solid #26b050;Ø
}Ø
Ø
.invalid {Ø
    outline: 1px solid #e50000;Ø
}Ø
Ø
.validation-message {Ø
    color: #e50000;Ø
}Ø
Ø

```



```

// AÄ5D$>CB vWD ÆÆ+vVEVæ-G4 7-æ2Â 0 D$0C²6CR Ö÷fT 7-æ2Â vWDgVÆÅG&VT 7-æ2 8 C 0Ct>C$KC' 5%TM
// B4 AR ?Cä;CÔ>D BDÄN D 5C ;C,,7Cä2C =D² 8 D 0C >D$0DäB C00 D4@Cä2C00DR 8C0BCT@DD5C"ACä2 C, 1C 7Cä2D'E C
// A08D 0D$L C,,E Ct4CTADÄ 7C =Cä2Cä AR B4 A0 .D
D
// =====D
// A0 A,, A' AD A / AD ÄÄ A0 A / BD A A,, A "AT%A0 Ä&AT!B A-
// =====D
D
/// <summary>D
/// A 2D$>CÄ0D$8Dt5D :C, 3CT=CT@C,,@D45D" ?D4AD$>C' HC 1C'>C0 BCTEC0>C'>C48Dt5D :Cä9 Cä?CT@C FC,,8 C00 CäAC
/// A0>C'=CäAD$LDä >D 2Cä1Cä6CD0CTB UI-D ;Cä9 CäB D CD$8C0=Cä3Cä 2D'7Cä2C ;D0<C 4C 0DC 1D 8Cfi
/// </summary>D
public override Task<TechnologicalOperation> CreateChildTemplateAsync(TechnologicalOperation
parent)D
{D
// A0> CD>CÄ5C0=D'< C0@C 2C,,;C < C$0D,,5C4> D$5DT?D >Dd5D AC ACä7CD0CT< D0:Ct5CÄ?C'OD :Cä=C²@CTBC0>C
// C0@CT4Ct0C0>C'=D00 CTQ ParentId C,,4CT=D$8DD8C²0D$>D >CÄ 2D'1D 0C0=Cä3Cä @Cä4C,,BCT;DÄAC²>C4> D47C'0
var childOperation = new TechnologicalOperationD
{D
ParentId = parent.Id,D
IsLeaf = true // A0> D4<Cä;Dt0C08Dä =Cä2C 0 Cä?CT@C FC,,0 D02C'0CTBD 0 C'8D BCä< C4@C DC Ä ?Cä:C
};D
D
// At0C0CC'0CT< Dd8C²;C,,GCTAC²CDä AD KC':D2 =C @Cä4C,,BCT;DÄAC²8C' >C JCT:D" 2 C00CÄ0D$8 CD;D0 7C IC,,
childOperation.Parent = null;D
D
return Task.FromResult(childOperation);D
}D
}
</file>

```

```

<file path="Promatis.Net.Test.MDM.Service/Services/UnitService.cs">
using Microsoft.EntityFrameworkCore;D
using Promatis.Net.MES.Domain;D
using Promatis.Net.MES.Domain.Interface;D
using Promatis.Net.MES.Service;D
using Promatis.Net.Test.MDM.Data;D
using Promatis.Net.Test.MDM.Domain;D
D
namespace Promatis.Net.Test.MDM.Service;D
D
/// <summary>D
/// A²>C05Dt=C 0 C0@C,,:C'0CD=C 0 DD0C @C,,:C ?Cä;C,,<Cä@DD8Ct<C í
/// A00D ;CT4D45D" 2D N C4>D$>C$CDä <C BCT<C BC,,:D2 4CT@CT2C !B4 AB 8 D 5C ;C,,7D45D" DC 1D 8C²C C0>C'8CÄ>D D
/// </summary>D
public class UnitService(IDbContextFactory<MdmApplicationDbContext> contextFactory)D
: UnitBaseService<MdmApplicationDbContext>(contextFactory)D
{D
/// <summary>D
/// A²>C05Dt=C 0 C0@C,,:C'0CD=C 0 DD0C @C,,:C ?Cä;C,,<Cä@DD8Ct<C í
/// </summary>D
public override Task<UnitBase> CreateChildTemplateAsync(UnitBase parent)D
{D
UnitKind childKind = parent.Kind switchD
{D
UnitKind.Department => UnitKind.Production,D
UnitKind.Production => UnitKind.Position,D
UnitKind.Storage => UnitKind.Storage,D
UnitKind.Transport => UnitKind.Position,D
_ => UnitKind.PositionD
};D
D
UnitBase childUnit = childKind switchD
{D
UnitKind.Department => new DepartmentUnit { Type = UnitType.Other, ParentId =
parent.Id },D
UnitKind.Production => new ProductionUnit { Type = UnitType.Other, ParentId =
parent.Id },D
UnitKind.Storage => new StorageUnit { Type = UnitType.Other, ParentId = parent.Id },D
UnitKind.Transport => new TransportUnit { Type = UnitType.Other, ParentId = parent.Id },D
UnitKind.Position => new PositionUnit { Type = UnitType.Other, ParentId = parent.Id },D
_ => throw new ArgumentOutOfRangeException(nameof(childKind))D
};D
D
childUnit.Parent = null;D
return Task.FromResult(childUnit);D
}
}

```

```

    }
}
</file>

<file path="Promatis.Net.Test.MDM.Tests/Promatis.Net.Test.MDM.Tests.csproj">
<Project Sdk="Microsoft.NET.Sdk">
    <PropertyGroup>
        <TargetFramework>net10.0</TargetFramework>
        <ImplicitUsings>enable</ImplicitUsings>
        <Nullable>enable</Nullable>
        <IsPackable>false</IsPackable>
    </PropertyGroup>
    <ItemGroup>
        <PackageReference Include="coverlet.collector" Version="10.0.0">
            <PrivateAssets>all</PrivateAssets>
            <IncludeAssets>runtime; build; native; contentfiles; analyzers; buildtransitive</IncludeAssets>
        </PackageReference>
        <PackageReference Include="FluentAssertions" Version="8.10.0" />
        <PackageReference Include="FluentValidation" Version="12.1.1" />
        <PackageReference Include="Microsoft.EntityFrameworkCore.InMemory" Version="10.0.8" />
        <PackageReference Include="Microsoft.NET.Test.Sdk" Version="18.5.1" />
        <PackageReference Include="Moq" Version="4.20.72" />
        <PackageReference Include="xunit.runner.visualstudio" Version="3.1.5">
            <PrivateAssets>all</PrivateAssets>
            <IncludeAssets>runtime; build; native; contentfiles; analyzers; buildtransitive</IncludeAssets>
        </PackageReference>
        <PackageReference Include="xunit.v3" Version="3.2.2" />
    </ItemGroup>
    <ItemGroup>
        <ProjectReference Include="..\Promatis.Net.Test.MDM.Service\Promatis.Net.Test.MDM.Service.csproj" />
    </ItemGroup>
    <ItemGroup>
        <Using Include="Xunit" />
    </ItemGroup>
</Project>
</file>

<file path="Promatis.Net.Test.MDM.Tests/UnitTest1.cs">
namespace Promatis.Net.Test.MDM.Tests
{
    public class UnitTest1
    {
        [Fact]
        public void Test1()
        {
        }
    }
}
</file>

<file path="Promatis.Net.Test.MDM.UI/_Imports.razor">
@using Microsoft.AspNetCore.Components.Forms
@using Microsoft.AspNetCore.Components.Routing
@using Microsoft.AspNetCore.Components.Web
@using MudBlazor
@using Promatis.Net.UI.Components.Workspaces
@using Promatis.Net.UI.Components.Dialogs
@using Promatis.Net.Domain.Interface
</file>

<file path="Promatis.Net.Test.MDM.UI/Promatis.Net.Test.MDM.UI.csproj">
<Project Sdk="Microsoft.NET.Sdk.Razor">
    <PropertyGroup>
        <TargetFramework>net10.0</TargetFramework>
        <Nullable>enable</Nullable>
        <ImplicitUsings>enable</ImplicitUsings>

```

```

    </PropertyGroup>
  
```

```

    <ItemGroup>
      <Compile Remove="Pages\*" />
      <Content Remove="Pages\*" />
      <EmbeddedResource Remove="Pages\*" />
      <None Remove="Pages\*" />
    </ItemGroup>
  
```

```

    <ItemGroup>
      <SupportedPlatform Include="browser" />
    </ItemGroup>
  
```

```

    <ItemGroup>
      <PackageReference Include="Microsoft.AspNetCore.Components.Web" Version="10.0.8" />
      <PackageReference Include="MudBlazor" Version="9.4.0" />
    </ItemGroup>
  
```

```

    <ItemGroup>
      <ProjectReference Include="..\..\..\Core\Configuration.Web\Promatis.Net.Configuration.Web.csproj" />
      <ProjectReference Include="..\..\..\Mes\MDM\Promatis.Net.MES.MDM.UI\Promatis.Net.MES.MDM.UI.csproj" />
      <ProjectReference Include="..\Promatis.Net.Test.MDM.Service\Promatis.Net.Test.MDM.Service.csproj" />
    </ItemGroup>
  
```

```

</Project>
</file>

<file path="Promatis.Net.Test.MDM.UI\UiModule.cs">
using MudBlazor;
using Promatis.Net.UI;
namespace Promatis.Net.Test.MDM.UI;
public class UiModule : IUiModule
{
    public string Name => GetType().Assembly.GetName().Name ?? "Unknown.Module";

    public IEnumerable<(string Title, string Href, string Icon, string? Group)> GetMenuItems()
    {
        return new List<(string Title, string Href, string Icon, string? Group)>
        {
            // A,,=D$5D 0C=BC,,2CÔ>CR 4CT@CT2Câ >D 3D BD CC=BD4@D² 8 Că1Că@D44Că2C =C,,O MESD
            ("B BD CC=BD4@C ?D 5CD?D 8DôBC,,O", "/mdm/units", Icons.Material.Filled.AccountTree, "B ?D 0C$>Dt
        };
    }
}
</file>

<file path="Promatis.Net.Test.MDM.UI/wwwroot/exampleJsInterop.js">
// This is a JavaScript module that is loaded on demand. It can export any number of
// functions, and may import other JavaScript modules if required.
export function showPrompt(message) {
    return prompt(message, 'Type anything here');
}
</file>

</files>

```